

FCC Report

Applicant: Cubix Latin America, LLC

Address of Applicant: 2841 NW 107th Ave, Doral, Florida, United States 33172

Equipment Under Test (EUT)

Product Name: Tablet

Model No.: QD-700ii-BK, QD-700ii-WT

FCC ID: 2ACDE-QD-700II

Applicable standards: FCC CFR Title 47 Part 15 Subpart B:2013

Date of sample receipt: September 01, 2014

Date of Test: September 01-11, 2014

Date of report issue: September 11, 2014

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	September 11, 2014	Original

Prepared By:

Sam. Gao

Date:

September 11, 2014

Project Engineer

Check By:

hank. gao

Date:

September 11, 2014

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	5
5.4 TEST FACILITY.....	6
5.5 TEST LOCATION.....	6
5.6 DESCRIPTION OF SUPPORT UNITS	6
5.7 DEVIATION FROM STANDARDS	6
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA	8
7.1 CONDUCTED EMISSIONS	8
7.2 RADIATED EMISSION	11
8 TEST SETUP PHOTO	17
9 EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	PASS
Radiated Emissions	Part15.109	PASS

PASS: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Cubix Latin America, LLC
Address of Applicant:	2841 NW 107th Ave, Doral, Florida, United States
Manufacturer/Factory:	VIDO DIGITAL ELECTRONICS CO., LTD.
Address of Manufacturer/Factory:	B1 Building, Lianhe Industrial Area, Feng Tang Road, Fuyong, Bao'an District, Shenzhen, China

5.2 General Description of EUT

Product Name:	Tablet
Model No.:	QD-700ii-BK, QD-700ii-WT
Power supply:	Model No.: MX12X8-0502000UX Input: AC 100-240V, 50/60Hz, 0.35A Output: DC 5.0V, 2A DC 3.7V Li-ion Battery

5.3 Test mode

Test mode:	
PC mode	Keep the EUT in exchanging data mode.

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

• **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

5.6 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
HP	Printer	CB495A	05257893	DoC
Lenovo	PC Host	M6900	EA05257893	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC

5.7 Deviation from Standards

Biconical, log.per. antenna and horn antenna were used instead of dipole antenna.

Semi-anechoic Chamber was used as alternation of open air test sites, and all test suites were performed with radiated method in it.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	GTS250	Mar. 28 2014	Mar. 27 2015
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	ESU EMI Test Receiver	R&S	ESU26	GTS203	July 01 2014	June 30 2015
4	BiConiLog Antenna	SCHWARZBECK	VULB9163	GTS214	July 01 2014	June 30 2015
5	Double -ridged waveguide horn	SCHWARZBECK	9120D	GTS208	June 27 2014	June 26 2015
6	RF Amplifier	HP	8347A	GTS204	July 01 2014	June 30 2015
7	Preamplifier	HP	8349B	GTS206	July 01 2014	June 30 2015
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial cable	GTS	N/A	GTS210	Mar. 29 2014	Mar. 28 2015
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 29 2014	Mar. 28 2015


Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	Sep. 07 2013	Sep. 06 2015
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	July 01 2014	June 30 2015
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	July 01 2014	June 30 2015
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	July 01 2014	June 30 2015
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	July 01 2014	June 30 2015
6	Coaxial Cable	GTS	N/A	GTS227	July 01 2014	June 30 2015
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 08 2014	July 07 2015

7 Test Results and Measurement Data

7.1 Conducted Emissions

Test Requirement:	FCC Part15 B Section 15.107																
Test Method:	ANSI C63.4:2003																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	<p>* Decreases with the logarithm of the frequency.</p>																
Test setup:	<p>Reference Plane</p> <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. 																
Test Instruments:	Refer to section 6 for details																
Test mode:	Refer to section 5.3 for details																
Test results:	Pass																

Measurement Data
Line:


Condition : FCC PART15 QP LISN-2013 LINE

Job No. : 1396RF


Test mode : PC mode

Test Engineer: Mike

:

Freq	Read	LISN	Cable	Limit Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB		dBuV	dB	
1	0.165	38.74	0.15	0.12	39.01	65.21	-26.20 QP
2	0.253	34.01	0.12	0.11	34.24	61.64	-27.40 QP
3	0.871	25.65	0.14	0.13	25.92	56.00	-30.08 QP
4	6.352	21.20	0.23	0.16	21.59	60.00	-38.41 QP
5	18.426	21.03	0.53	0.22	21.78	60.00	-38.22 QP
6	26.418	32.30	1.05	0.23	33.58	60.00	-26.42 QP

Neutral:



Condition : FCC PART15 QP LISN-2013 NEUTRAL

Job No. : 1396RF

Test mode : PC mode

Test Engineer: Mike



	Read Freq	LISN Level	Cable Factor	Loss	Line Level	Limit dBuV	Over Line Limit dB	Over Remark
	MHz	dBuV		dB	dB	dBuV	dBuV	
1	0.169	39.16	0.07	0.12	39.35	64.99	-25.64	QP
2	0.256	34.97	0.06	0.11	35.14	61.56	-26.42	QP
3	0.909	27.16	0.07	0.13	27.36	56.00	-28.64	QP
4	6.352	20.60	0.17	0.16	20.93	60.00	-39.07	QP
5	16.398	25.94	0.37	0.22	26.53	60.00	-33.47	QP
6	26.418	34.12	0.96	0.23	35.31	60.00	-24.69	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.2 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																									
Test Method:	ANSI C63.4:2003																									
Test Frequency Range:	30MHz to 6GHz																									
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																									
Receiver setup:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>120kHz</td> <td>300kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>Above 1GHz</td> <td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td></td> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value		Peak	1MHz	10Hz	Average Value	
Frequency	Detector	RBW	VBW	Remark																						
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value																						
Above 1GHz	Peak	1MHz	3MHz	Peak Value																						
	Peak	1MHz	10Hz	Average Value																						
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Limit (dBuV/m @3m)</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td> <td>40.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>88MHz-216MHz</td> <td>43.50</td> <td>Quasi-peak Value</td> </tr> <tr> <td>216MHz-960MHz</td> <td>46.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>960MHz-1GHz</td> <td>54.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>Above 1GHz</td> <td>54.00</td> <td>Average Value</td> </tr> <tr> <td></td> <td>74.00</td> <td>Peak Value</td> </tr> </tbody> </table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.00	Quasi-peak Value	88MHz-216MHz	43.50	Quasi-peak Value	216MHz-960MHz	46.00	Quasi-peak Value	960MHz-1GHz	54.00	Quasi-peak Value	Above 1GHz	54.00	Average Value		74.00	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																								
30MHz-88MHz	40.00	Quasi-peak Value																								
88MHz-216MHz	43.50	Quasi-peak Value																								
216MHz-960MHz	46.00	Quasi-peak Value																								
960MHz-1GHz	54.00	Quasi-peak Value																								
Above 1GHz	54.00	Average Value																								
	74.00	Peak Value																								
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 																									
Test setup:	Below 1GHz																									

	 <p>Above 1GHz</p> 
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1 012mbar
Measurement Record:	Uncertainty: $\pm 4.5\text{dB}$
Test Instruments:	Refer to section 6 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Note:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163-2013M HORIZONTAL
 Job No. : 1396RF
 Test Mode : PC mode
 Test Engineer: Qing

	ReadAntenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	38.481	38.49	15.20	0.65	32.06	22.28	40.00 -17.72 QP
2	78.413	48.16	10.31	1.01	31.78	27.70	40.00 -12.30 QP
3	185.788	56.91	12.16	1.77	32.10	38.74	43.50 -4.76 QP
4	360.448	50.94	16.43	2.67	32.00	38.04	46.00 -7.96 QP
5	480.528	44.37	18.07	3.22	31.62	34.04	46.00 -11.96 QP
6	798.980	35.89	22.06	4.45	31.32	31.08	46.00 -14.92 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163-2013M VERTICAL
 Job No. : 1396RF
 Test Mode : PC mode
 Test Engineer: Qing

Freq	ReadAntenna		Cable		Preamp Loss Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB					
1	60.918	40.48	14.43	0.87	31.93	23.85	40.00	-16.15	QP
2	119.996	58.00	12.48	1.36	31.86	39.98	43.50	-3.52	QP
3	180.017	48.70	11.68	1.74	32.08	30.04	43.50	-13.46	QP
4	300.367	46.30	15.06	2.36	32.17	31.55	46.00	-14.45	QP
5	360.448	45.62	16.43	2.67	32.00	32.72	46.00	-13.28	QP
6	645.120	35.88	20.61	3.89	31.11	29.27	46.00	-16.73	QP

Above 1GHz

Horizontal:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120D ANT(>1GHZ) HORIZONTAL

Job No. : 1396RF
 Test Mode : PC mode
 Test Engineer: Qing

	Read	Antenna	Cable	Preamp	Limit	Over		
	Freq	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1200.000	28.03	25.34	4.47	33.10	24.74	54.00	-29.26 Average
2	1200.000	38.06	25.34	4.47	33.10	34.77	74.00	-39.23 Peak
3	2075.000	28.31	26.71	5.05	34.38	25.69	54.00	-28.31 Average
4	2075.000	38.15	26.71	5.05	34.38	35.53	74.00	-38.47 Peak
5	2530.000	27.66	27.58	5.52	33.86	26.90	54.00	-27.10 Average
6	2530.000	37.87	27.58	5.52	33.86	37.11	74.00	-36.89 Peak
7	3235.000	27.36	28.62	6.43	33.06	29.35	54.00	-24.65 Average
8	3235.000	37.30	28.62	6.43	33.06	39.29	74.00	-34.71 Peak
9	4085.000	25.43	29.86	7.95	32.09	31.15	54.00	-22.85 Average
10	4085.000	35.51	29.86	7.95	32.09	41.23	74.00	-32.77 Peak
11	4985.000	23.04	31.95	8.75	32.17	31.57	54.00	-22.43 Average
12	4985.000	33.17	31.95	8.75	32.17	41.70	74.00	-32.30 Peak

Vertical:



Site : 3m chamber

Condition : FCC PART 15 (PK) 3m BBHA9120D ANT(>1GHZ) VERTICAL

Job No. : 1396RF


Test Mode : PC mode

Test Engineer: Qing

Freq	ReadAntenna	Cable	Preamp	Limit		Over	Remark
	Freq	Level	Factor	Loss	Factor		
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1170.000	28.65	25.17	4.44	33.04	25.22	54.00 -28.78 Average
2	1170.000	38.70	25.17	4.44	33.04	35.27	74.00 -38.73 Peak
3	2525.000	28.61	27.58	5.51	33.86	27.84	54.00 -26.16 Average
4	2525.000	38.23	27.58	5.51	33.86	37.46	74.00 -36.54 Peak
5	3395.000	28.76	28.60	6.76	32.87	31.25	54.00 -22.75 Average
6	3395.000	38.85	28.60	6.76	32.87	41.34	74.00 -32.66 Peak
7	4360.000	25.06	30.97	8.21	31.87	32.37	54.00 -21.63 Average
8	4360.000	35.04	30.97	8.21	31.87	42.35	74.00 -31.65 Peak
9	4815.000	23.50	31.79	8.61	32.09	31.81	54.00 -22.19 Average
10	4815.000	33.63	31.79	8.61	32.09	41.94	74.00 -32.06 Peak
11	5720.000	21.13	32.53	9.81	32.29	31.18	54.00 -22.82 Average
12	5720.000	31.32	32.53	9.81	32.29	41.37	74.00 -32.63 Peak

8 Test Setup Photo

Radiated Emission



Conducted Emission



9 EUT Constructional Details

Reference to the test report No. GTSE14080139601

----- End -----