



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM140400170004
Page: 1 of 29

FCC REPORT

Application No: SZEM1507004061CR
Applicant: CANARY CONNECT INC.
Manufacturer: CANARY CONNECT INC.
Factory: SKY LIGHT Electronic (ShenZhen) Limited
Product Name: Canary
Model No.(EUT): CAN100
Add Model No.: CANXXYY--XX-region(A-Z),YY-color(A-Z)
Trade Mark: Canary
FCC ID: 2ACDL-C100
Standards: 47 CFR Part 15, Subpart C (2014) (only for Conducted Emission, Conducted Peak Output Power, Spurious RF Transmit Conducted Emissions, Radiated Transmit Spurious Emissions)
Date of Receipt: 2015-07-09
Date of Test: 2015-07-13 to 2015-07-23
Date of Issue: 2015-07-28

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Jack Zhang
EMC Laboratory Manager
The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-07-28		Original

Authorized for issue by:			
Tested By	 (Eric Fu) /Project Engineer	2015-07-23	Date
Prepared By	 (Jade Chen) /Clerk	2015-07-28	Date
Checked By	 (Owen Zhou) /Reviewer	2015-07-28	Date

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2009	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

Remark:

Model No.: CAN100, CANXXYY---XX-region(A-Z), YY-color(A-Z).

Only the model CAN100 was tested, since the electrical circuit design, PCB layout, components used and internal wiring were identical for the above models, only different on region and color.

This test report (Ref. No.: SZEM140400170004) is only valid with the original test report (Ref. No.: SZEM140400170001).

Review this report and original report, this report just added an adaptor and updated the standard.

Considering to the change, pre-scan were performed on the sample in this report to find the items which can be influential to the result in the original test report for fully retest.

Therefore in this report Conducted Emission, Conducted Peak Output Power, Spurious RF Transmit Conducted Emissions and Radiated Transmit Spurious Emissions were fully retested on CAN100 and shown the data in this report, other tests please refer to original report SZEM140400170001.

Additionally, Updated the below standards:

47 CFR Part 15, Subpart C (2013) 47 CFR Part 15, Subpart C (2014)

4 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
REMARK:	3
4 CONTENTS	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST LOCATION	7
5.6 TEST FACILITY	8
5.7 DEVIATION FROM STANDARDS	8
5.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
5.10 EQUIPMENT LIST	9
6 TEST RESULTS AND MEASUREMENT DATA	12
6.1 ANTENNA REQUIREMENT	12
6.2 CONDUCTED EMISSIONS	13
6.3 CONDUCTED PEAK OUTPUT POWER	17
6.4 RADIATED SPURIOUS EMISSION	20
6.4.1 Spurious Emissions	20
7 PHOTOGRAPHS - EUT TEST SETUP	27
7.1 CONDUCTED EMISSION	27
7.2 RADIATED EMISSION	27
7.3 RADIATED SPURIOUS EMISSION	28
8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	29

5 General Information

5.1 Client Information

Applicant:	CANARY CONNECT INC.
Address of Applicant:	101 Avenue of the Americas - 18th floor, New York, NY10013, USA
Manufacturer:	CANARY CONNECT INC.
Address of Manufacturer:	101 Avenue of the Americas - 18th floor, New York, NY10013, USA
Factory:	SKYLIGHT Electronic(Shenzhen) Limited
Address of Factory:	No. 5&6 Building, JinBi Industiral Area, HuangTian, BaoAn, Shenzhen, China

5.2 General Description of EUT

Product Name:	Canary	
Model No.:	CAN100	
Trade Mark:	Canary	
Operation Frequency:	2402MHz~2480MHz	
Bluetooth Version:	4.0	
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)	
Modulation Type:	GFSK	
Number of Channel:	40	
Hopping Channel Type:	Adaptive Frequency Hopping systems	
Sample Type:	Fixed production	
Antenna Type:	Integral	
Antenna Gain:	0dBi	
Power Supply:	Supply by adapter through USB port	
EUT Cables & Ports:	USB cable: 200cm, unshielded AUX cable: 100cm, unshielded	
AC Adapter:	New:	Model: CAN100USA Input voltage: AC 100-240V 50/60Hz 0.3A Output voltage: DC5V 2A Test voltage: AC120V 60Hz
	Original:	Model: PA03-050200U-U INPUT: 100-240V~50/60Hz 0.3A OUTPUT: 5V == 2A



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
4	2408MHz	14	2428MHz	24	2448MHz	34	2468MHz
5	2410MHz	15	2430MHz	25	2450MHz	35	2470MHz
6	2412MHz	16	2432MHz	26	2452MHz	36	2472MHz
7	2414MHz	17	2434MHz	27	2454MHz	37	2474MHz
8	2416MHz	18	2436MHz	28	2456MHz	38	2476MHz
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2440MHz
The Highest channel	2480MHz

5.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1005mbar

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

5.10 Equipment List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2016-05-13
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-24
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2016-05-13
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	SEL0162	2015-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	SEL0163	2015-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	SEL0164	2015-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2016-05-13
8	Coaxial Cable	SGS	N/A	SEL0025	2016-05-13
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
10	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
11	Barometer	Chang Chun	DYM3	SEL0088	2016-05-13



RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2016-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2016-05-13
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2016-05-13
10	Coaxial cable	SGS	N/A	SEL0189	2016-05-13
11	Coaxial cable	SGS	N/A	SEL0121	2016-05-13
12	Coaxial cable	SGS	N/A	SEL0178	2016-05-13
13	Band filter	Amindeon	82346	SEL0094	2016-05-13
14	Barometer	Chang Chun	DYM3	SEL0088	2016-05-13
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2016-05-13
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2016-05-13

RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2016-05-13
5	Coaxial cable	SGS	N/A	SEL0179	2016-05-13
6	Barometer	ChangChun	DYM3	SEL0088	2016-05-13
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2016-04-25
8	Band filter	amideon	82346	SEL0094	2016-05-13
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2016-04-25
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

Note: The calibration interval is one year, all the instruments are valid.

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(b) (4) requirement:	The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:	

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.

6.2 Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
5-30		60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none">1) The mains terminal disturbance voltage test was conducted in a shielded room.2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.		

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live line:



Site : Shielding Room
Condition : 47 CFR PART 15 B AV CE LINE
Job No. : 4061CR
Test mode : a

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level			
1	0.15160	0.02	9.82	39.07	48.91	55.91	-7.00 Peak
2	0.19242	0.02	9.83	39.02	48.87	53.93	-5.06 Peak
3	0.28178	0.01	9.84	35.21	45.07	50.76	-5.70 Peak
4	0.40187	0.01	9.85	32.35	42.22	47.81	-5.60 Peak
5	0.83932	0.02	9.89	32.63	42.53	46.00	-3.47 Peak
6	19.635	0.02	10.29	26.97	37.28	50.00	-12.72 Peak

Neutral line:




Site : Shielding Room
Condition : 47 CFR PART 15 B AV CE NEUTRAL
Job No. : 4061CR
Test mode : a

	Freq	Cable	LISN	Read	Limit		Over	Remark
		Loss	Factor	Level	Level	Line	Limit	
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15816	0.02	9.79	35.71	45.52	55.56	-10.04	Peak
2	0.18152	0.02	9.83	36.54	46.39	54.42	-8.03	Peak
3	0.20833	0.02	9.85	35.51	45.38	53.27	-7.89	Peak
4	0.26724	0.01	9.86	36.39	46.27	51.20	-4.94	Peak
5	0.44679	0.01	9.88	32.62	42.50	46.93	-4.43	Peak
6	0.84826	0.02	9.99	30.94	40.95	46.00	-5.05	Peak

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10 2009
Test Setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Limit:	30dBm
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Measurement Data

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-1.04	30.00	Pass
Middle	0.21	30.00	Pass
Highest	1.57	30.00	Pass




Test plot as follows:


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



6.4 Radiated Spurious Emission

6.4.1 Spurious Emissions					
Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				
Test Setup:					




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz)
- Repeat above procedures until all frequencies measured was complete.

Exploratory Test

Non-hopping transmitting mode with all kind of modulation and all kind of




**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM140400170004
Page: 22 of 29

Mode:	data type Transmitting mode.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Radiated Emission below 1GHz		
30MHz~1GHz (QP)		
Test mode:	Transmitting	Vertical




Condition: 47 CFR PART 15B 3m VERTICAL

Job No. : 4061CR

Test Mode: a

Freq	Cable		Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	38.89	0.77	13.72	25.75	41.80	30.54	40.00	-9.46
2	47.66	0.91	9.73	25.69	45.31	30.26	40.00	-9.74
3	125.01	1.61	8.00	25.62	54.03	38.02	43.50	-5.48
4	175.04	2.01	9.70	25.21	46.76	33.26	43.50	-10.24
5	383.93	3.18	16.08	25.08	42.69	36.87	46.00	-9.13
6	750.11	4.85	21.60	26.39	40.50	40.56	46.00	-5.44

Test mode:	Transmitting	Horizontal
------------	--------------	------------



Condition: 47 CFR PART 15B 3m HORIZONTAL

Job No. : 4061CR

Test Mode: a

Freq	Cable		Antenna	Preamp	Read	Limit	Over
	Loss	Factor	Factor	Level	Level		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 125.01	1.61	8.00	25.62	40.42	24.41	43.50	-19.09
2 175.04	2.01	9.70	25.21	44.53	31.03	43.50	-12.47
3 273.23	2.58	12.66	24.31	40.12	31.05	46.00	-14.95
4 438.66	3.38	16.63	26.04	41.82	35.79	46.00	-10.21
5 750.11	4.85	21.60	26.39	41.33	41.39	46.00	-4.61
6 875.25	5.16	22.80	25.80	35.15	37.31	46.00	-8.69

Transmitter Emission above 1GHz									
Test mode:		GFSK		Test channel:		Lowest		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
1750.702	2.83	29.89	38.40	45.49	39.81	74.00	-34.19	Vertical	
3616.451	4.15	33.01	38.79	45.73	44.10	74.00	-29.90	Vertical	
4804.000	4.29	34.70	39.24	44.04	43.79	74.00	-30.21	Vertical	
7206.000	5.30	35.63	39.07	45.05	46.91	74.00	-27.09	Vertical	
9608.000	6.52	37.33	37.93	42.48	48.40	74.00	-25.60	Vertical	
11457.210	7.74	38.19	38.45	43.16	50.64	74.00	-23.36	Vertical	
1814.218	2.89	30.22	38.41	46.60	41.30	74.00	-32.70	Horizontal	
3472.118	3.89	32.86	38.73	46.95	44.97	74.00	-29.03	Horizontal	
4804.000	4.29	34.70	39.24	44.99	44.74	74.00	-29.26	Horizontal	
7206.000	5.30	35.63	39.07	44.97	46.83	74.00	-27.17	Horizontal	
9608.000	6.52	37.33	37.93	42.84	48.76	74.00	-25.24	Horizontal	
11283.550	7.60	38.13	38.36	43.52	50.89	74.00	-23.11	Horizontal	

Test mode:		GFSK		Test channel:		Middle		Remark:	Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit (dB)	Polarization	
1750.702	2.83	29.89	38.40	47.13	41.45	74.00	-32.55	Vertical	
3653.463	4.12	33.04	38.81	46.76	45.11	74.00	-28.89	Vertical	
4880.000	4.36	34.78	39.26	45.48	45.36	74.00	-28.64	Vertical	
7320.000	5.21	35.51	39.06	45.25	46.91	74.00	-27.09	Vertical	
9760.000	6.49	37.80	37.84	41.52	47.97	74.00	-26.03	Vertical	
11399.030	7.86	38.15	38.42	44.33	51.92	74.00	-22.08	Vertical	
1724.166	2.81	29.77	38.40	46.70	40.88	74.00	-33.12	Horizontal	
3653.463	4.12	33.04	38.81	46.76	45.11	74.00	-28.89	Horizontal	
4880.000	4.36	34.78	39.26	44.62	44.50	74.00	-29.50	Horizontal	
7320.000	5.21	35.51	39.06	45.25	46.91	74.00	-27.09	Horizontal	
9760.000	6.49	37.80	37.84	42.86	49.31	74.00	-24.69	Horizontal	
11515.680	7.62	38.24	38.47	43.96	51.35	74.00	-22.65	Horizontal	



Test mode:		GFSK		Test channel:		Highest		Remark:		Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit (dB)		Polarization	
1933.424	2.97	31.19	38.42	45.96	41.70	74.00	-32.30		Vertical	
3728.625	4.05	33.10	38.84	46.83	45.14	74.00	-28.86		Vertical	
4960.000	4.43	34.86	39.29	45.42	45.42	74.00	-28.58		Vertical	
7440.000	5.15	35.43	39.05	42.26	43.79	74.00	-30.21		Vertical	
9920.000	6.83	38.27	37.75	41.60	48.95	74.00	-25.05		Vertical	
11933.470	7.25	38.63	38.67	44.20	51.41	74.00	-22.59		Vertical	
1880.038	2.93	30.76	38.41	45.19	40.47	74.00	-33.53		Horizontal	
3719.146	4.06	33.09	38.84	45.15	43.46	74.00	-30.54		Horizontal	
4960.000	4.43	34.86	39.29	43.74	43.74	74.00	-30.26		Horizontal	
7440.000	5.15	35.43	39.05	43.12	44.65	74.00	-29.35		Horizontal	
9920.000	6.83	38.27	37.75	39.88	47.23	74.00	-26.77		Horizontal	
12556.750	6.82	39.24	39.17	44.50	51.39	74.00	-22.61		Horizontal	

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.


7 Photographs - EUT Test Setup

Test Model No.: CAN100

7.1 Conducted Emission




7.2 Radiated Emission



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

7.3 Radiated Spurious Emission





8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1507004061CR.