



1 Cover Page

RF Exposure Evaluation Report

Application No.:	SHEM1803001946CR
Applicant:	Hangzhou Gubei Electronics Technoloy Co.,Ltd
FCC ID:	2ACDZ-BL3335-P
IC	21239-BL3335P
Equipment Under Test (EUT): NOTE: The following sample(s) submitted was/were identified on behalf of the client as	
Product Name:	Wifi Module
Model No.:	BL3335-P
Standards:	FCC Rules 47 CFR §2.1091 KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt:	2018-03-16
Date of Test:	2018-03-16 to 2018-03-21
Date of Issue:	2018-04-04
Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards specified above.



Parlam Zhan
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2018-04-04	/

Authorized for issue by:			
		 <hr/> Vincent Zhu /Project Engineer	
		 <hr/> Parlam Zhan /Reviewer	

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF E.U.T.....	4
3.3 TEST LOCATION	5
3.4 TEST FACILITY	5
4 TEST STANDARDS AND LIMITS	6
4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5 MEASUREMENT AND CALCULATION	6
5.1 MAXIMUM TRANSMIT POWER	6
5.2 MPE CALCULATION.....	7

3 General Information

3.1 Client Information

Applicant:	Hangzhou Gubei Electronics Technoloy Co.,Ltd
Address of Applicant:	Room106,No.1 Building,No.611 Jianghong Road Binjiang,Hangzhou
Manufacturer:	Hangzhou Gubei Electronics Technoloy Co.,Ltd
Address of Manufacturer:	Room106,No.1 Building,No.611 Jianghong Road Binjiang,Hangzhou
Factory:	Hangzhou Gubei Electronics Technoloy Co.,Ltd
Address of Factory:	Room106,No.1 Building,No.611 Jianghong Road Binjiang,Hangzhou

3.2 General Description of E.U.T.

Power supply:	DC 3.3V
Antenna Gain	0dBi
Antenna Type	PCB Antenna
Channel Spacing	5MHz
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n(HT20 and HT40):
Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). Certificate No. 201034-0.

- **FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868,C-4336,T-12221,G-10830 respectively.

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM180300194602

Test Mode	Test Channel	Ant	Level [dBm]	10log(1/x) Factor[dB]	Power [dBm]	Power [mW]
11B	2412	Ant1	18.32	0.13	18.45	69.98
11B	2437	Ant1	18.23	0.13	18.36	68.55
11B	2462	Ant1	17.83	0.13	17.97	62.66
11G	2412	Ant1	14.87	0.25	15.12	32.51
11G	2437	Ant1	14.79	0.25	15.03	31.84
11G	2462	Ant1	14.33	0.25	14.57	28.64
11N20SISO	2412	Ant1	14.49	0.30	14.79	30.13
11N20SISO	2437	Ant1	14.39	0.30	14.69	29.44
11N20SISO	2462	Ant1	13.92	0.26	14.19	26.24
11N40SISO	2422	Ant1	12.88	0.52	13.40	21.88
11N40SISO	2437	Ant1	12.36	0.52	12.87	19.36
11N40SISO	2452	Ant1	12.32	0.52	12.84	19.23

5.2 MPE Calculation

The Max Conducted Peak Output Power is 69.98mW;

The best case gain of the antenna is 0dBi. 0dB logarithmic terms convert to numeric result is nearly 1

For FCC:

According to the formula $S = \frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note:

- 1) P (Watts)
- 2) G (Antenna gain in numeric)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{PG}{4R^2\pi} = \frac{69.98 \times 1}{4 \times 400 \times 3.14} = 0.014 \text{ mW/cm}^2 < 1 \text{ mW/cm}^2$$

So the device is exclusion from SAR test.

--End of the Report--