

FCC Part 15C

Measurement and Test Report

For

Hangzhou Gubei Electronics Technology Co., Ltd.

**Room 106, Building 1, No. 611 Jianghong Road, Binjiang, Hangzhou,
Zhejiang 310052, China**

FCC ID: 2ACDZ-BL3351-P

FCC Rule(s): FCC Part 15.247

Product Description: WiFi Module

Tested Model: BL3351-P

Report No.: STR18098252I

Sample Receipt Date: 2018-09-21

Tested Date: 2018-09-21 to 2018-10-31

Issued Date: 2018-10-31

Tested By: Ray Yang/ Engineer



Reviewed By: Silin Chen / EMC Manager



Approved & Authorized By: Jandy So / PSQ Manager



Prepared By:

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permission by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND TEST MODE	5
1.6 MEASUREMENT UNCERTAINTY	6
1.7 TEST EQUIPMENT LIST AND DETAILS	7
2. SUMMARY OF TEST RESULTS	8
3. RF EXPOSURE	9
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
4. ANTENNA REQUIREMENT	10
4.1 STANDARD APPLICABLE.....	10
4.2 EVALUATION INFORMATION	10
5. POWER SPECTRAL DENSITY	11
5.1 STANDARD APPLICABLE.....	11
5.2 TEST PROCEDURE.....	11
5.3 SUMMARY OF TEST RESULTS/PLOTS	11
6. DTS BANDWIDTH.....	16
6.1 STANDARD APPLICABLE.....	16
6.2 TEST PROCEDURE.....	16
6.3 SUMMARY OF TEST RESULTS/PLOTS	16
7. RF OUTPUT POWER	21
7.1 STANDARD APPLICABLE.....	21
7.2 TEST PROCEDURE.....	21
7.3 SUMMARY OF TEST RESULTS/PLOTS	21
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	27
8.1 STANDARD APPLICABLE.....	27
8.2 TEST PROCEDURE.....	27
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	28
8.4 SUMMARY OF TEST RESULTS/PLOTS	28
9. OUT OF BAND EMISSIONS.....	36
9.1 STANDARD APPLICABLE.....	36
9.2 TEST PROCEDURE.....	36
9.3 SUMMARY OF TEST RESULTS/PLOTS	37
10. CONDUCTED EMISSIONS	58
10.1 TEST PROCEDURE.....	58
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	58
10.3 TEST RECEIVER SETUP	58
10.4 SUMMARY OF TEST RESULTS/PLOTS	58

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Hangzhou Gubei Electronics Technology Co., Ltd.
Address of applicant: Room 106, Building 1, No. 611 Jianghong Road, Binjiang,
Hangzhou, Zhejiang 310052, China

Manufacturer: Hangzhou Gubei Electronics Technology Co., Ltd.
Address of manufacturer: Room 106, Building 1, No. 611 Jianghong Road, Binjiang,
Hangzhou, Zhejiang 310052, China

General Description of EUT	
Product Name:	WiFi Module
Trade Name:	BroadLink
Model No.:	BL3351-P
Adding Model(s):	/
Rated Voltage:	DC 3.3V
Power Adapter:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20 2422-2452MHz for 802.11n-HT40
RF Output Power:	15.19dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20 7 for 802.11n-HT40
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	0dBi
Lowest Internal Frequency of EUT:	26MHz

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

Test Conditions		
Temperature:		22~25 °C
Relative humidity		50~56 %.
ATM Pressure:		1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	1.5	Unshielded	Without Core

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Router	TP-Link	TL-WR886N	/
Power adapter	Shenzhen Jihongda Power Co.,Ltd	JHD-AP006E-05100BB-B Input:AC100/240V 50/60Hz 0.2A Output:DC5V/1A	/
Test board	BroadLink	3339-P TEST 1V1	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	± 0.42dB
Occupied Bandwidth	Conducted	± 1.5%
Power Spectral Density	Conducted	± 1.8dB
Conducted Spurious Emission	Conducted	± 2.17dB
Conducted Emissions	Conducted	9-150kHz ± 3.74dB
		0.15-30MHz ± 3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ± 4.52dB
		0.2-1GHz ± 5.56dB
		1-6GHz ± 3.84dB
		6-18GHz ± 3.92dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	DTS Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a PCB antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure


According to the KDB 558074 D01 v05 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).


5.3 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_11Mbps	2412	-15.99	8
	2437	-16.42	8
	2462	-16.80	8
802.11g_54Mbps	2412	-18.88	8
	2437	-19.71	8
	2462	-20.37	8
802.11n-HT20_MCS7	2412	-20.17	8
	2437	-20.44	8
	2462	-20.79	8
802.11n-HT40_MCS7	2422	-23.90	8
	2437	-24.49	8
	2452	-24.82	8

Please refer to the following test plots:









6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure


According to the KDB 558074 D01 v05 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:


- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


6.3 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_11Mbps	2412	9.647	≥ 500
	2437	9.602	≥ 500
	2462	9.994	≥ 500
802.11g_54Mbps	2412	16.338	≥ 500
	2437	16.398	≥ 500
	2462	16.384	≥ 500
802.11n-HT20_MCS7	2412	17.544	≥ 500
	2437	17.355	≥ 500
	2462	17.365	≥ 500
802.11n-HT40_MCS7	2422	35.390	≥ 500
	2437	34.686	≥ 500
	2452	35.737	≥ 500

Please refer to the following test plots:









7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure


According to the KDB-558074 D01 v05 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth


- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98 \%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.


7.3 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	15.15	32.734	1000
	2437	15.19	33.037	1000
	2462	14.77	29.992	1000
802.11g_54Mbps	2412	14.16	26.062	1000
	2437	13.72	23.550	1000
	2462	13.16	20.701	1000
802.11n HT20_MCS7	2412	13.56	22.699	1000
	2437	13.65	23.174	1000
	2462	12.77	18.923	1000
802.11n HT40_MCS7	2422	12.45	17.579	1000
	2437	12.14	16.368	1000
	2452	12.27	16.866	1000

Please refer to the following test plots:









8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=360KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


8.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.


➤ Spurious Emissions Below 1GHz

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	53.1313	28.62	-11.75	16.87	40.00	-23.13	97	100	peak
2	90.5374	27.31	-13.51	13.80	43.50	-29.70	152	100	peak
3	124.5690	26.54	-16.51	10.03	43.50	-33.47	104	100	peak
4	230.9068	27.44	-12.24	15.20	46.00	-30.80	143	100	peak
5	434.0651	28.05	-8.07	19.98	46.00	-26.02	228	100	peak
6	763.3757	28.07	-2.36	25.71	46.00	-20.29	244	100	peak

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	57.7962	28.62	-13.07	15.55	40.00	-24.45	150	100	peak
2	91.4949	27.15	-13.70	13.45	43.50	-30.05	122	100	peak
3	225.3080	26.84	-12.77	14.07	46.00	-31.93	97	100	peak
4	425.0280	27.56	-8.19	19.37	46.00	-26.63	125	100	peak
5	570.6100	28.06	-6.21	21.85	46.00	-24.15	112	100	peak
6	755.3873	27.19	-2.64	24.55	46.00	-21.45	279	100	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	52.7600	27.13	-11.69	15.44	40.00	-24.56	324	100	peak
2	93.7685	28.83	-14.15	14.68	43.50	-28.82	100	100	peak
3	202.1005	28.45	-13.22	15.23	43.50	-28.27	226	100	peak
4	437.1199	28.13	-8.08	20.05	46.00	-25.95	101	100	peak
5	833.3171	27.22	-0.28	26.94	46.00	-19.06	259	100	peak
6	972.3374	27.88	1.94	29.82	54.00	-24.18	217	100	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	53.3179	27.89	-11.78	16.11	40.00	-23.89	332	100	peak
2	112.1305	27.87	-14.28	13.59	43.50	-29.91	125	100	peak
3	297.2241	26.24	-10.16	16.08	46.00	-29.92	101	100	peak
4	435.5898	27.34	-8.08	19.26	46.00	-26.74	104	100	peak
5	709.1823	27.54	-3.64	23.90	46.00	-22.10	344	100	peak
6	952.0937	27.51	1.58	29.09	46.00	-16.91	108	100	peak


802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree	Height (cm)	Remark
1	52.0251	27.69	-11.59	16.10	40.00	-23.90	236	100	peak
2	106.0126	27.74	-13.48	14.26	43.50	-29.24	153	100	peak
3	271.3246	26.83	-11.06	15.77	46.00	-30.23	73	100	peak
4	352.9434	26.98	-8.96	18.02	46.00	-27.98	264	100	peak
5	467.2349	28.67	-8.09	20.58	46.00	-25.42	88	100	peak
6	614.2142	29.84	-5.14	24.70	46.00	-21.30	115	100	peak

802.11b_11Mbps

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	57.7962	27.09	-13.07	14.02	40.00	-25.98	237	100	peak
2	106.0126	27.17	-13.48	13.69	43.50	-29.81	95	100	peak
3	204.2377	26.62	-13.24	13.38	43.50	-30.12	75	100	peak
4	414.7223	28.66	-8.41	20.25	46.00	-25.75	113	100	peak
5	737.0714	27.67	-3.22	24.45	46.00	-21.55	357	100	peak
6	912.8620	27.59	1.37	28.96	46.00	-17.04	266	100	peak

- Spurious Emissions Below 1GHz
- *Test Mode: 802.11b_11Mbps (worst case)*

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.00	62.04	-3.87	58.17	74.00	-15.83	H	PK
4824.00	46.54	-3.87	42.67	54.00	-11.33	H	AV
7236.00	56.51	1.14	57.65	74.00	-16.35	H	PK
7236.00	34.97	1.19	36.16	54.00	-17.84	H	AV
4824.00	68.11	-3.86	64.25	74.00	-9.75	V	PK
4824.00	41.64	-3.86	37.78	54.00	-16.22	V	AV
7236.00	63.69	1.10	64.79	74.00	-9.21	V	PK
7236.00	35.60	1.10	36.70	54.00	-17.30	V	AV
Middle Channel-2437MHz							
4874.00	61.20	-3.74	57.46	74.00	-16.54	H	PK
4874.00	47.95	-3.74	44.21	54.00	-9.79	H	AV
7311.00	58.31	1.47	59.78	74.00	-14.22	H	PK
7311.00	44.10	1.47	45.57	54.00	-8.43	H	AV
4874.00	61.53	-3.74	57.79	74.00	-16.21	V	PK
4874.00	47.86	-3.74	44.12	54.00	-9.88	V	AV
7311.00	56.79	1.47	58.26	74.00	-15.74	V	PK
7311.00	43.21	1.47	44.68	54.00	-9.32	V	AV
High Channel-2462MHz							
4924.00	61.39	-3.59	57.80	74.00	-16.20	H	PK
4924.00	48.34	-3.59	44.75	54.00	-9.25	H	AV
7386.00	54.88	1.79	56.67	74.00	-17.33	H	PK
7386.00	43.25	1.79	45.04	54.00	-8.96	H	AV
4924.00	61.39	-3.59	57.80	74.00	-16.20	V	PK
4924.00	47.49	-3.59	43.90	54.00	-10.10	V	AV
7386.00	55.87	1.79	57.66	74.00	-16.34	V	PK
7440.00	43.49	1.79	45.28	54.00	-8.72	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v05 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Summary of Test Results/Plots


➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.76	-7.78	34.98	54.00	-19.02	Average Detector
	2310.000	60.99	-7.78	53.21	74.00	-20.79	Peak Detector
2	2390.000	50.36	-7.32	43.04	54.00	-10.96	Average Detector
	2390.000	73.63	-7.32	66.31	74.00	-7.69	Peak Detector
3	2412.588	108.10	-7.18	100.92	/	/	Average Detector
	2413.076	112.86	-7.18	105.68	/	/	Peak Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.112	105.40	-6.90	98.50	/	/	Average Detector
	2460.914	110.16	-6.90	103.26	/	/	Peak Detector
2	2483.500	48.42	-6.77	41.65	54.00	-12.35	Average Detector
	2483.500	67.88	-6.77	61.11	74.00	-12.89	Peak Detector
3	2500.000	42.03	-6.67	35.36	54.00	-18.64	Average Detector
	2500.000	57.16	-6.67	50.49	74.00	-23.51	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.25	-7.78	36.47	54.00	-17.53	Average Detector
	2310.000	66.00	-7.78	58.22	74.00	-15.78	Peak Detector
2	2390.000	58.57	-7.32	51.25	54.00	-2.75	Average Detector
	2390.000	75.56	-7.32	68.24	74.00	-5.76	Peak Detector
3	2408.925	96.27	-7.21	89.06	/	/	Average Detector
	2411.610	110.96	-7.19	103.77	/	/	Peak Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2465.243	101.51	-6.87	94.64	/	/	Average Detector
	2459.422	112.36	-6.90	105.46	/	/	Peak Detector
2	2483.500	59.03	-6.77	52.26	54.00	-1.74	Average Detector
	2483.500	74.54	-6.77	67.77	74.00	-6.23	Peak Detector
3	2500.000	46.23	-6.67	39.56	54.00	-14.44	Average Detector
	2500.000	65.30	-6.67	58.63	74.00	-15.37	Peak Detector


802.11n-HT20_MCS7

Test Channel

Low

Polarity:


Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	45.10	-7.78	37.32	54.00	-16.68	Average Detector
	2310.000	66.12	-7.78	58.34	74.00	-15.66	Peak Detector
2	2390.000	57.29	-7.32	49.97	54.00	-4.03	Average Detector
	2390.000	77.42	-7.32	70.10	74.00	-3.90	Peak Detector
3	2407.827	95.45	-7.21	88.24	/	/	Average Detector
	2406.364	109.52	-7.22	102.30	/	/	Peak Detector

802.11n-HT20_MCS7

Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2458.131	94.62	-6.92	87.70	/	/	Average Detector
	2458.777	107.25	-6.91	100.34	/	/	Peak Detector
2	2483.500	55.65	-6.77	48.88	54.00	-5.12	Average Detector
	2483.500	77.01	-6.77	70.24	74.00	-3.76	Peak Detector
3	2500.000	42.82	-6.67	36.15	54.00	-17.85	Average Detector
	2500.000	66.66	-6.67	59.99	74.00	-14.01	Peak Detector


802.11n-HT40_MCS7

Test Channel

Low

Polarity:


Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.37	-7.78	36.59	54.00	-17.41	Average Detector
	2310.000	63.89	-7.78	56.11	74.00	-17.89	Peak Detector
2	2390.000	58.60	-7.32	51.28	54.00	-2.72	Average Detector
	2390.000	74.40	-7.32	67.08	74.00	-6.92	Peak Detector
3	2406.140	90.52	-7.22	83.30	/	/	Average Detector
	2411.952	102.29	-7.19	95.10	/	/	Peak Detector

802.11n-HT40_MCS7


Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2454.832	88.68	-6.94	81.74	/	/	Average Detector
	2455.878	105.45	-6.92	98.53	/	/	Peak Detector
2	2483.500	58.02	-6.77	51.25	54.00	-2.75	Average Detector
	2483.500	75.08	-6.77	68.31	74.00	-5.69	Peak Detector
3	2500.000	47.20	-6.67	40.53	54.00	-13.47	Average Detector
	2500.000	73.37	-6.67	66.70	74.00	-7.30	Peak Detector

➤ Conducted test


802.11b_11Mbps




802.11b_11Mbps




802.11b_11Mbps




High




802.11g_54Mbps




802.11g_54Mbps




802.11g_54Mbps




High




802.11n-HT20_MCS7




802.11n-HT20_MCS7



802.11n-HT20_MCS7





High




802.11n-HT40_MCS7


Low




802.11n-HT40_MCS7



802.11n-HT40_MCS7



High




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	23.63	10.10	33.73	55.57	-21.84	AVG
2	0.1660	44.77	10.11	54.88	65.16	-10.28	QP
3*	0.6340	29.72	10.36	40.08	46.00	-5.92	AVG
4	0.6380	37.99	10.36	48.35	56.00	-7.65	QP
5	2.6540	15.17	10.65	25.82	46.00	-20.18	AVG
6	2.7020	25.58	10.65	36.23	56.00	-19.77	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1540	45.21	10.10	55.31	65.78	-10.47	QP
2	0.1620	24.03	10.10	34.13	55.36	-21.23	AVG
3	0.6380	36.84	10.36	47.20	56.00	-8.80	QP
4*	0.6380	31.13	10.36	41.49	46.00	-4.51	AVG
5	4.7060	15.05	10.75	25.80	46.00	-20.20	AVG
6	5.2220	21.99	10.77	32.76	60.00	-27.24	QP

***** END OF REPORT *****