



RF EXPOSURE REPORT

REPORT NO.: SA140527E05

MODEL NO.: QLivebox

FCC ID: 2ACFN-QLIVEBOX

RECEIVED: May 27, 2014

TESTED: June 19, 2014

ISSUED: Nov. 17, 2014

APPLICANT: QNAP Systems, Inc.

ADDRESS: 2F., No. 22, Zhongxing Rd., Xizhi Dist., New Taipei City, 221 Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION.....	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	7



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140527E05	Original release	Nov. 17, 2014



1. CERTIFICATION

PRODUCT: QLivebox
BRAND NAME: QNAP
MODEL NO.: QLivebox
TEST SAMPLE: MASS-PRODUCTION
APPLICANT: QNAP Systems, Inc.
TESTED DATE: June 19, 2014
STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D03
IEEE C95.1

The above equipment (Model: QLivebox) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared By :  , **Date:** Nov. 17, 2014
(Lori Chung, Specialist)

Approved By :  , **Date:** Nov. 17, 2014
(May Chen, Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

For WLAN							
Ant. No.	Transmitter Circuit	Brand	Model	Antenna Type	Antenna Gain (dBi)	Connector type	Frequency range (GHz to GHz)
1	CHAIN (0)	Unictron	AA077	CHIP	1.4	NA	2.4~2.5
	CHAIN (1)						
2	CHAIN (0)				2.3		5.15~5.85
	CHAIN (1)						
For Zigbee							
Ant. No.	Brand	Model	Antenna Type	Antenna Gain (dBi)	Connector type	Frequency range (GHz to GHz)	
3	Unictron	AA055	CHIP	2.5	NA	2.4~2.5	

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For WLAN (2.4GHz)

802.11b

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 - 2462	132.05	4.41	20	0.07252	1.00

NOTE: Directional gain = 1.4dBi + 10log(2) = 4.41dBi.

802.11g

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 - 2462	496.964	4.41	20	0.27293	1.00

NOTE: Directional gain = 1.4dBi + 10log(2) = 4.41dBi.

802.11n (HT20)

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 - 2462	462.538	4.41	20	0.25403	1.00

NOTE: Directional gain = 1.4dBi + 10log(2) = 4.41dBi.

802.11n (HT40)

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2422-2452	150.356	4.41	20	0.08258	1.00

NOTE: Directional gain = 1.4dBi + 10log(2) = 4.41dBi.

For WLAN (5GHz)

802.11a

FREQUENCY BAND (MHz)	MAX POWER AVG. (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 - 5240	44.486	5.31	20	0.03006	1.00

NOTE: Directional gain = 2.3dBi + 10log(2) = 5.31dBi.

802.11n (HT20)

FREQUENCY BAND (MHz)	MAX POWER AVG. (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 - 5240	44.674	5.31	20	0.03018	1.00

NOTE: Directional gain = 2.3dBi + 10log(2) = 5.31dBi.

802.11n (HT40)

FREQUENCY BAND (MHz)	MAX POWER AVG. (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5190-5230	42.125	5.31	20	0.02846	1.00

NOTE: Directional gain = 2.3dBi + 10log(2) = 5.31dBi.

For Zigbee

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2425 - 2475	0.6109	2.5	20	0.00022	1.00

CONCLUSION:

Both of the WLAN and Zigbee can transmit simultaneously, the formula of calculated the MPE is:

$$CPD_1 / LPD_1 + CPD_2 / LPD_2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.27293 / 1 + 0.00022 / 1 = 0.273$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---