



731 Enterprise Drive  
Lexington, KY 40510

Telephone: 859-226-1000  
Facsimile: 859-226-1040  
www.intertek-etlsemko.com

# TEST REPORT

**Report Number:** 101617363LEX-001  
**Project Number:** G101617363

**Report Issue Date:** 6/17/2014


**Product Name:** TDWLB Wireless Pressure Sensor  
**Model Number:** TDWLB  
**FCCID:** 2ACGE -TDWLB  
**ICID:** 12056A-TDWLB

**Standards:** Title 47 CFR Part 15 Subpart C and RSS-210 Issue 8

**Radios Under Test:** Low Energy Bluetooth (BTLE)

**Tested by:**  
Intertek Testing Services NA, Inc.  
731 Enterprise Drive  
Lexington, KY 40510

**Client:**  
Transducers Direct / ACAM  
264 Center Street, PO Box 162  
Miami, OH 45147

Report prepared by  
  
Bryan Taylor, Team Leader

Report reviewed by  
  
Jason Centers, Senior Project Engineer



*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.*

**TABLE OF CONTENTS**

**1 Introduction and Conclusion..... 3**

**2 Test Summary ..... 3**

**3 Description of Equipment Under Test ..... 4**

**4 Peak Conducted Power ..... 6**

**5 Occupied Bandwidth ..... 9**

**6 Conducted Spurious Emissions..... 12**

**7 Power Spectral Density..... 14**

**8 Radiated Spurious Emissions (Transmitter)..... 17**

**9 Radiated Spurious Emissions (Receiver)..... 21**

**10 Antenna Requirement per FCC Part 15.203..... 24**

**11 Measurement Uncertainty..... 25**

**12 Revision History ..... 26**

## 1 Introduction and Conclusion

The tests indicated in section 2 were performed on the product constructed as described in section 3. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test method, a list of the actual test equipment used, documentation photos, results and raw data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested complied with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

The INTERTEK-Lexington is located at 731 Enterprise Drive, Lexington Kentucky, 40510. The radiated emission test site is a 10-meter semi-anechoic chamber. The chamber meets the characteristics of CISPR 16-1 and ANSI C63.4. For measurements, a remotely controlled flush-mount metal-top turntable is used to rotate the EUT a full 360 degrees. A remote controlled non-conductive antenna mast is used to scan the antenna height from one to four meters. The test site is listed with the FCC under registration number 485103. The test site is listed with Industry Canada under site number IC 2042M-1.

## 2 Test Summary

Page	Test full name	FCC Reference	IC Reference	Result
6	Peak Conducted Power	§ 15.247(b)(3)(4)	RSS-210 (A8.4)	Pass
9	Occupied Bandwidth	§ 15.247(a)(2)	RSS-210 (A8.2), RSS-GEN (4.6.1)	Pass
12	Conducted Spurious Emissions	§ 15.247(d)	RSS-210 (A8.5)	Pass
14	Power Spectral Density	§ 15.247(e)	RSS-210 (A8.2b)	Pass
17	Radiated Spurious Emissions (Transmitter)	§ 15.247(d), § 15.209, and § 15.205	RSS-210 (2.2) (A8.5)	Pass
21	Radiated Spurious Emissions (Receiver)	§ 15.109	RSS-Gen (6.1)	Pass
---	Conducted Voltage Emissions on the AC Mains Terminals	§ 15.107, § 15.207	RSS-Gen (7.2.4)	NA <sup>1</sup>
24	Antenna Requirement per FCC Part 15.203	§ 15.203	RSS-Gen (7.1.2)	Pass

<sup>1</sup> This product was battery powered and had no connections to the AC mains.

**3 Description of Equipment Under Test**

<b>Equipment Under Test</b>	
<b>Manufacturer</b>	Transducers Direct / ACAM
<b>Model Number</b>	TDWLB
<b>Serial Number</b>	Test Sample 1
<b>FCC Identifier</b>	2ACGE -TDWLB
<b>IC Identifier</b>	12056A-TDWLB
<b>Receive Date</b>	5/15/2014
<b>Test Start Date</b>	5/15/2014
<b>Test End Date</b>	5/27/2014
<b>Device Received Condition</b>	Good
<b>Test Sample Type</b>	Production
<b>Frequency Band</b>	2402MHz – 2480MHz
<b>Mode(s) of Operation</b>	BTLE
<b>Modulation Type</b>	GFSK
<b>Number of Hopping Channels</b>	40
<b>Transmission Control</b>	Test Commands
<b>Test Channels</b>	0, 19, 39 (2402, 2440, 2480 MHz)
<b>Antenna Type (15.203)</b>	Internal
<b>Power Supply</b>	Battery Powered

**Description of Equipment Under Test**


The TDWLB is a pressure transducer outfitted with a BTLE radio.

**Operating modes of the EUT:**

No.	Descriptions of EUT Exercising
1	Transmitting BTLE Signal on low mid or high channels
2	Receive / idle mode

**3.1 System setup including cable interconnection details, support equipment and simplified block diagram**

**3.2 EUT Block Diagram:**



**3.3 Cables:**

No cables were used during the radiated measurements. A coaxial cable was used during the conducted measurements at the antenna terminals

**3.4 Support Equipment:**

No support equipment was used during this evaluation.

## 4 Peak Conducted Power

### 4.1 Test Limits

§ 15.247(b)(3): For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

§ 15.247(b)(4): The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 4.2 Test Procedure

ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247). The peak output power was measured using the channel power function of the spectrum analyzer.


### 4.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3720	Rohde&Schwarz	FSEK30	9/10/2013	9/10/2014


### 4.4 Results:

The peak output power measurements were all below the 30dBm limit.


Mode	Channel Number	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Result
BTLE	0	2402	0.171	30	Pass
BTLE	19	2440	-0.664	30	Pass
BTLE	39	2480	-1.627	30	Pass



Peak Output Power, Low Channel



Peak Output Power, Mid Channel



Peak Output Power, High Channel



## 5 Occupied Bandwidth

### 5.1 Test Limits

§ 15.247(a)(2): For digital modulation systems, the minimum 6dB bandwidth shall be at least 500kHz.

### 5.2 Test Procedure


ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)

### 5.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3720	Rohde&Schwarz	FSEK30	9/10/2013	9/10/2014


### 5.4 Results:

Mode	Channel Number	Frequency (MHz)	6dB Bandwidth	99% Power Bandwidth	Result
BTLE	0	2402	717.4kHz	---	Pass
BTLE	19	2440	721.4kHz	1.05MHz	Pass
BTLE	39	2480	717.4kHz	---	Pass




Date: 15.MAY.2014 14:21:03

6dB Bandwidth, Low Channel




Date: 15.MAY.2014 14:22:20

6dB Bandwidth, Middle Channel



99% Bandwidth, Middle Channel



6dB Bandwidth, High Channel

## 6 Conducted Spurious Emissions

### 6.1 Test Limits

**§ 15.247(d):** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 6.2 Test Procedure


ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)

### 6.3 Test Equipment Used:


Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3720	Rohde&Schwarz	FSEK30	9/10/2013	9/10/2014

### 6.4 Results:

The following plots show that there are no conducted spurious emissions exceeding the 20dB down criteria.



Low / High Band Edge Plot



Conducted Spurious Emissions, Low, Mid, and High Channel

## 7 Power Spectral Density

### 7.1 Test Limits

§ 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 7.2 Test Procedure

ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)


### 7.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3720	Rohde&Schwarz	FSEK30	9/10/2013	9/10/2014


### 7.4 Results:

\*PSD Option 1 Method


Mode	Channel Number	Frequency (MHz)	PSD in 3kHz BW (dBm)	Limit (dBm)	Result
BTLE	0	2402	-12.574	8.0	Pass
BTLE	19	2440	-13.271	8.0	Pass
BTLE	39	2480	-14.838	8.0	Pass



PSD Low Channel



PSD Middle Channel



PSD, High Channel



## 8 Radiated Spurious Emissions (Transmitter)

### 8.1 Test Limits

**§ 15.247(d):** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### Part 15.205(a): Restricted Bands of Operations

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

#### Part 15.209(a): Field Strength Limits for Restricted Bands of Operation

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2,400 / F (kHz)	300
0.490 - 1.705	24,000 / F (kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

## 8.2 Test Procedure

ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)

### 8.3 Example of Field Strength Calculation Method:

The measured field strength was calculated by summing the readings taken from the spectrum analyzer with the appropriate correction factors associated with the antenna losses and cable losses. The calculation formula and sample calculations are listed below:

Formula:

$$FS = RA + AF + CF$$

FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude in dB $\mu$ V

AF = Antenna Factor in dB

CF = Cable Attenuation Factor in dB (Including preamplifier and filter attenuation)

Example Calculation:

$$RA = 19.48 \text{ dB}\mu\text{V}$$

$$AF = 18.52 \text{ dB}$$

$$CF = 0.78 \text{ dB}$$

$$FS = 19.48 + 18.52 + 0.78 = 38.78 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(38.78 \text{ dB}\mu\text{V/m})/20] = 86.89 \mu\text{V/m}$$

### 8.4 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	1302.6005.40	Rohde & Schwarz	ESU40	9/11/2013	9/11/2014
Bilog Antenna	00051864	ETS	3142C	12/17/2013	12/17/2014
Horn Antenna	00154521	ETS	3117	10/10/2013	10/10/2014
Horn Antenna (18 – 26.5GHz)	LM8621	ETS	3160-09	10/9/2013	10/9/2014
Preamplifier	122005	Rohde&Schwarz	TS-PR18	9/19/2013	9/19/2014
Preamplifier	100050	Rohde&Schwarz	TS-PR26	9/19/2013	9/19/2014
System Controller	3957	Sunol Sciences	SC110V	Time of Use	Time of Use

**8.5 Results:**

The radiated spurious testing was conducted up to 10 times the fundamental frequency. All spurious emissions were attenuated by at least 20dB below the level of the fundamental as required by Part 15.247(d). Additionally, all emissions falling within restricted bands of operation and at the band edges were found to be below the limit specified in Part 15.209(a). The spurious emissions listed in the following tables are the worst case emissions. Emissions not reported were at or below the measurement noise floor. The test sample was evaluated on three orthogonal axes since it could be used in any orientation.

Radiated Emissions											
<b>Test Engineer:</b> Bryan Taylor		<b>Start Date:</b> 5/16/2014		<b>End Date:</b> 5/19/2014							
<b>Temperature:</b> 23.5C		<b>Humidity:</b> 46.70%		<b>Pressure:</b> 988.7mBar							
<b>Specification:</b> FCC Part 15B		<b>Test Limit:</b> 15.247									
<b>Notes:</b> Bluetooth Low Energy, GFSK, Low Channel											
A	B	C	D	E	F	G	H	I	J	K	
Frequency	Polarity (H/V)	Raw Reading (dBuV)	Cab. (dB)	Ant. (dB)	Corr. Reading. (dBuV/m)	Limit (dBuV/m)	Delta (dB)	RBW / Detector	Test Distance	Results	
4.8041 GHz	V	57.74	-29.623	34.7	62.817	74	-11.183	1MHz / Pk	3m	Compliant	
4.8041 GHz	V	42.65	-29.623	34.7	47.727	54	-6.273	1MHz / Av	3m	Compliant	
4.804 GHz	H	43.82	-29.623	34.7	48.897	74	-25.103	1MHz / Pk	3m	Compliant	
4.804 GHz	H	40.33	-29.623	34.7	45.407	54	-8.593	1MHz / Av	3m	Compliant	
Band Edge Measurements											
2.39 GHz	V	22.88	4.673	32.944	60.497	74	-13.503	1MHz / Pk	3m	Compliant	
2.39 GHz	V	13.04	4.673	32.944	50.657	54	-3.343	1MHz / Av	3m	Compliant	
2.39 GHz	H	22.74	4.673	32.944	60.357	74	-13.643	1MHz / Pk	3m	Compliant	
2.39 GHz	H	13.05	4.673	32.944	50.667	54	-3.333	1MHz / Av	3m	Compliant	
<b>Calculations:</b>		F = C + D + E					H = F - G				

**Worst Case Spurious Emissions (BTLE, Low Channel)**

Radiated Emissions											
<b>Test Engineer:</b> Bryan Taylor		<b>Start Date:</b> 5/16/2014		<b>End Date:</b> 5/19/2014							
<b>Temperature:</b> 23.5C		<b>Humidity:</b> 46.70%		<b>Pressure:</b> 988.7mBar							
<b>Specification:</b> FCC Part 15B		<b>Test Limit:</b> 15.247									
<b>Notes:</b> Bluetooth Low Energy, GFSK, Mid Channel											
A	B	C	D	E	F	G	H	I	J	K	
Frequency	Polarity (H/V)	Raw Reading (dBuV)	Cab. (dB)	Ant. (dB)	Corr. Reading. (dBuV/m)	Limit (dBuV/m)	Delta (dB)	RBW / Detector	Test Distance	Results	
4.88 GHz	V	50.52	-29.512	34.7	55.708	74	-18.292	1MHz / Pk	3m	Compliant	
4.88 GHz	V	41.09	-29.512	34.7	46.278	54	-7.722	1MHz / Av	3m	Compliant	
4.88 GHz	H	46.69	-29.512	34.7	51.878	74	-22.122	1MHz / Pk	3m	Compliant	
4.88 GHz	H	37.26	-29.512	34.7	42.448	54	-11.552	1MHz / Av	3m	Compliant	
<b>Calculations:</b>		F = C + D + E					H = F - G				

**Worst Case Spurious Emissions (BTLE, Middle Channel)**

Radiated Emissions										
<b>Test Engineer:</b> Bryan Taylor		<b>Start Date:</b> 5/16/2014		<b>End Date:</b> 5/19/2014						
<b>Temperature:</b> 23.5C		<b>Humidity:</b> 46.70%		<b>Pressure:</b> 988.7mBar						
<b>Specification:</b> FCC Part 15B		<b>Test Limit:</b> 15.247								
<b>Notes:</b> Bluetooth Low Energy, GFSK, High Channel										
A	B	C	D	E	F	G	H	I	J	K
Frequency	Polarity (H/V)	Raw Reading (dBuV)	Cab. (dB)	Ant. (dB)	Corr. Reading. (dBuV/m)	Limit (dBuV/m)	Delta (dB)	RBW / Detector	Test Distance	Results
4.96 GHz	V	43.24	-29.396	34.7	48.544	74	-25.456	1MHz / Pk	3m	Compliant
4.96 GHz	V	42.34	-29.396	34.7	47.644	54	-6.356	1MHz / Av	3m	Compliant
4.9601 GHz	H	54.14	-29.396	34.7	59.444	74	-14.556	1MHz / Pk	3m	Compliant
4.9601 GHz	H	43.74	-29.396	34.7	49.044	54	-4.956	1MHz / Av	3m	Compliant
Band Edge Measurements										
2.4835 GHz	V	22.98	4.773	32.907	60.66	74	-13.34	1MHz / Pk	3m	Compliant
2.4835 GHz	V	13.71	4.773	32.907	51.39	54	-2.61	1MHz / Av	3m	Compliant
2.4835 GHz	H	23.44	4.773	32.907	61.12	74	-12.88	1MHz / Pk	3m	Compliant
2.4835 GHz	H	13.71	4.773	32.907	51.39	54	-2.61	1MHz / Av	3m	Compliant
Calculations:				F = C + D + E			H = F - G			

**Worst Case Spurious Emissions (BTLE, High Channel)**

## 9 Radiated Spurious Emissions (Receiver)

### 9.1 Test Limits

§ 15.109: Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of emission (MHz)	Field strength (microvolts/meter)	Field strength (dBuV/m)
30–88	100	40
88–216	150	43.5
216–960	200	46
Above 960	500	54

These limits are identical to those in RSS-GEN

### 9.2 Test Procedure

ANSI C63.4: 2009

### 9.3 Example of Field Strength Calculation Method:

The measured field strength was calculated by summing the readings taken from the spectrum analyzer with the appropriate correction factors associated with the antenna losses and cable losses. The calculation formula and sample calculations are listed below:

Formula:

$$FS = RA + AF + CF$$

FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude in dB $\mu$ V

AF = Antenna Factor in dB

CF = Cable Attenuation Factor in dB (Including preamplifier and filter attenuation)

Example Calculation:

$$RA = 19.48 \text{ dB}\mu\text{V}$$

$$AF = 18.52 \text{ dB}$$

$$CF = 0.78 \text{ dB}$$

$$FS = 19.48 + 18.52 + 0.78 = 38.78 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(38.78 \text{ dB}\mu\text{V/m})/20] = 86.89 \mu\text{V/m}$$

### 9.4 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	1302.6005.40	Rohde & Schwarz	ESU40	9/11/2013	9/11/2014
Bilog Antenna	00051864	ETS	3142C	12/17/2013	12/17/2014
Horn Antenna	00154521	ETS	3117	10/10/2013	10/10/2014
Preamplifier	122005	Rohde&Schwarz	TS-PR18	9/19/2013	9/19/2014
System Controller	3957	Sunol Sciences	SC110V	Time of Use	Time of Use


**9.5 Results:**

All spurious emissions with the test sample in receive mode were below the limits specified in Part 15.109 for a class B digital device and RSS-GEN Section 6.1.

**9.6 Test Data (Bilog):**

Radiated Emissions										
<b>Test Engineer:</b> Toby Carrier		<b>Start Date:</b> 5/16/2014		<b>End Date:</b> 5/16/2014						
<b>Temperature:</b> 24.5°C		<b>Humidity:</b> 35.80%		<b>Pressure:</b> 982.8 mbar						
<b>Specification:</b> FCC Part 15B		<b>Test Limit:</b> Class B								
<b>Notes:</b> Receive Mode										
A	B	C	D	E	F	G	H	I	J	K
Frequency	Polarity (H/V)	Raw Reading (dBuV)	Cab. (dB)	Ant. (dB)	Corr. Reading (dBuV/m)	Limit (dBuV/m)	Delta (dB)	RBW / Detector	Test Distance	Results
224.01 MHz	H	13.41	2.3	11.46	27.17	46	-18.83	120kHz/QP	3m	Compliant
48.534 MHz	V	12.6	1.01	9.69	23.3	40	-16.7	120kHz/QP	3m	Compliant
80.877 MHz	V	13.12	1.5	6.7	21.32	40	-18.68	120kHz/QP	3m	Compliant
97.053 MHz	V	13.82	1.41	8.6	23.83	43.52	-19.69	120kHz/QP	3m	Compliant
114.55 MHz	V	16.26	1.7	8	25.96	43.52	-17.56	120kHz/QP	3m	Compliant
223.99 MHz	V	12.66	2.3	11.46	26.42	46	-19.58	120kHz/QP	3m	Compliant
<b>Calculations:</b>					F = C + D + E		H = F - G			

Deviations, Additions, or Exclusions: None




Bilog Prescan

**9.7 Test Data (Horn):**

Radiated Emissions										
Test Engineer: Toby Carrier		Start Date: 5/16/2014		End Date: 5/16/2014						
Temperature: 24.5°C		Humidity: 35.80%		Pressure: 982.8 mbar						
Specification: FCC Part 15		Test Limit: Class B								
Notes: Receive Mode										
A	B	C	D	E	F	G	H	I	J	K
Frequency	Polarity (H/V)	Raw Reading (dBuV)	Cab. (dB)	Ant. (dB)	Corr. Reading. (dBuV/m)	Limit (dBuV/m)	Delta (dB)	RBW / Detector	Test Distance	Results
6.329 GHz	H	24.73	-22.77	36.17	38.12	54	-15.88	1MHz/AVG	3m	Compliant
17.891 GHz	H	17.38	-16.26	41.57	42.68	54	-11.32	1MHz/AVG	3m	Compliant
1.2029 GHz	V	35.14	-27.38	29.02	36.77	54	-17.23	1MHz/AVG	3m	Compliant
17.897 GHz	V	17.35	-16.2	41.58	42.73	54	-11.27	1MHz/AVG	3m	Compliant
Calculations:		F = C + D + E				H = F - G				

Deviations, Additions, or Exclusions: None



Horn Prescan

**10 Antenna Requirement per FCC Part 15.203****10.1 Test Limits**

**§ 15.203:** An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

**10.2 Results:**

The sample tested met the antenna requirement. The antenna was permanently attached to the PCB.



## 11 Measurement Uncertainty

The measured value related to the corresponding limit will be used to decide whether the equipment meets the requirements.

The measurement uncertainty figures were calculated and correspond to a coverage factor of  $k = 2$ , providing a confidence level of respectively 95.45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian).

Measurement uncertainty Table

Parameter	Uncertainty	Notes
Radiated emissions, 30 to 1000 MHz	+3.9dB	
Radiated emissions, 1 to 18 GHz	+4.2dB	
Radiated emissions, 18 to 40 GHz	+4.3dB	
Power Port Conducted emissions, 150kHz to 30 MHz	+2.8dB	

**12 Revision History**

Revision Level	Date	Report Number	Notes
0	6/17/2014	101617363LEX-001	Original Issue