

# EMC Test Report

regarding

**USA: CFR Title 47, Part 15.231** (Emissions)  
**Canada: ISSED RSS-210v10/GENv5** (Emissions)

for



**047**

**Category: Keyless Entry Transmitter**

Judgments:

**Compliant 15.231/RSS-210v10 Transmitter**

Testing Completed: June 16, 2022



Prepared for:

**Alps Alpine North America, Inc.**

1500 Atlantic Boulevard, Auburn Hills Michigan 48326 USA

Phone: +1 (248) 830-5302, Fax:

Contact: John Cabigao, john.cabigao@alpsalpine.com

Data Recorded by:

Dr. Joseph Brunett, EMC-002790-NE

Reviewed by:

Dr. Joseph Brunett, EMC-002790-NE

Prepared by:

John Nantz

Date of Issue: June 17, 2022

## Revision History

Rev. No.	Date	Details	Revised By
r0	June 17, 2022	Initial Release.	J. Brunett

## Contents

<b>Revision History</b>	<b>2</b>
<b>Table of Contents</b>	<b>2</b>
<b>1 Test Report Scope and Limitations</b>	<b>4</b>
1.1 Laboratory Authorization . . . . .	4
1.2 Report Retention . . . . .	4
1.3 Subcontracted Testing . . . . .	4
1.4 Test Data . . . . .	4
1.5 Limitation of Results . . . . .	4
1.6 Copyright . . . . .	4
1.7 Endorsements . . . . .	4
1.8 Test Location . . . . .	5
1.9 Traceability and Equipment Used . . . . .	5
<b>2 Test Specifications and Procedures</b>	<b>6</b>
2.1 Test Specification and General Procedures . . . . .	6
<b>3 Configuration and Identification of the Equipment Under Test</b>	<b>7</b>
3.1 Description and Declarations . . . . .	7
3.1.1 EUT Configuration . . . . .	8
3.1.2 Modes of Operation . . . . .	8
3.1.3 Variants . . . . .	8
3.1.4 Test Samples . . . . .	8
3.1.5 Functional Exerciser . . . . .	8
3.1.6 Modifications Made . . . . .	8
3.1.7 Production Intent . . . . .	8
3.1.8 Declared Exemptions and Additional Product Notes . . . . .	8
<b>4 Emissions</b>	<b>9</b>
4.1 General Test Procedures . . . . .	9
4.1.1 Radiated Test Setup and Procedures . . . . .	9
4.1.2 Conducted Emissions Test Setup and Procedures . . . . .	11
4.1.3 Power Supply Variation . . . . .	11
4.2 Intentional Emissions . . . . .	12
4.2.1 Fundamental Emission Pulsed Operation . . . . .	12
4.2.2 Fundamental Emission Bandwidth . . . . .	14
4.2.3 Fundamental Emission Field Strength . . . . .	16
4.3 Unintentional Emissions . . . . .	17
4.3.1 Transmit Chain Spurious Emissions . . . . .	17
4.3.2 Radiated Digital Spurious . . . . .	18
<b>5 Measurement Uncertainty and Accreditation Documents</b>	<b>19</b>

List of Tables

1	Test Site List. . . . .	5
2	Equipment List. . . . .	5
3	EUT Declarations. . . . .	7
4	Fundamental Emission Pulsed Operation. . . . .	12
5	Fundamental Emission Bandwidth. . . . .	14
6	Fundamental Emission Field Strength. . . . .	16
7	Transmit Chain Spurious Emissions. . . . .	17
8	Measurement Uncertainty. . . . .	19

List of Figures

1	Photos of EUT. . . . .	7
2	EUT Test Configuration Diagram. . . . .	8
3	Radiated Emissions Diagram of the EUT. . . . .	9
4	Radiated Emissions Test Setup Photograph(s). . . . .	10
5	Fundamental Emission Pulsed Operation. . . . .	13
6	Fundamental Emission Bandwidth. . . . .	15
7	Accreditation Documents . . . . .	19

## **1 Test Report Scope and Limitations**

### **1.1 Laboratory Authorization**

Test Facility description and attenuation characteristics are on file with the FCC Laboratory, Columbia, Maryland (FCC Reg. No: US5348 and US5356) and with ISED Canada, Ottawa, ON (File Ref. No: 3161A and 24249). Amber Helm Development L.C. holds accreditation under NVLAP Lab Code 200129-0.

### **1.2 Report Retention**

For equipment verified to comply with the regulations herein, the manufacturer is obliged to retain this report with the product records for the life of the product, and no less than ten years. A copy of this Report will remain on file with this laboratory until July 2032.

### **1.3 Subcontracted Testing**

This report does not contain data produced under subcontract.

### **1.4 Test Data**

This test report contains data included within the laboratory's scope of accreditation. Any data in this report that is not covered under the laboratory's scope is clearly identified.

### **1.5 Limitation of Results**

The test results contained in this report relate only to the item(s) tested. Any electrical or mechanical modification made to the test item subsequent to the test date shall invalidate the data presented in this report. Any electrical or mechanical modification made to the test item subsequent to this test date shall require reevaluation.

### **1.6 Copyright**

This report shall not be reproduced, except in full, without the written approval of Amber Helm Development L.C.

### **1.7 Endorsements**

This report shall not be used to claim product endorsement by any accrediting, regulatory, or governmental agency.

## 1.8 Test Location

The EUT was fully tested by **Amber Helm Development L.C.**, headquartered at 92723 Michigan Hwy-152, Sister Lakes, Michigan 49047 USA. Table 1 lists all sites employed herein. Specific test sites utilized are also listed in the test results sections of this report where needed.

Table 1: Test Site List.

Description	Location	Quality Num.
OATS (3 meter)	3615 E Grand River Rd., Williamston, Michigan 48895	OATSC

## 1.9 Traceability and Equipment Used

Pertinent test equipment used for measurements at this facility is listed in Table 2. The quality system employed at Amber Helm Development L.C. has been established to ensure all equipment has a clearly identifiable classification, calibration expiry date, and that all calibrations are traceable to the SI through NIST, other recognized national laboratories, accepted fundamental or natural physical constants, ratio type of calibration, or by comparison to consensus standards.

Table 2: Equipment List.

Description	Manufacturer/Model	SN	Quality Num.	Cal/Ver By / Date Due
Biconical	EMCO / 93110B	9802-3039	BICEMCO01	Keysight / Aug-2023
Log Periodic Antenna	EMCO / 3146	9305-3614	LOGEMCO01	Keysight / Aug-2023
BNC-BNC Coax	WRTL / RG58/U	001	CAB001-BLACK	AHD / Sept-2022
3.5-3.5MM Coax	PhaseFlex / PhaseFlex	001	CAB015-PURP	AHD / Jul-2022
Spectrum Analyzer	R & S / FSV30	101660	RSFSV30001	RS / Apr-2023
Quad Ridge Horn	Singer / A6100	C35200	HQR1TO18S01	Keysight / Aug-2022

## 2 Test Specifications and Procedures

### 2.1 Test Specification and General Procedures

The goal of Alps Alpine North America, Inc. is to demonstrate that the Equipment Under Test (EUT) complies with the Rules and/or Directives below. Detailed in this report are the results of testing the Alps Alpine North America, Inc. 047 for compliance to:

Country/Region	Rules or Directive	Referenced Section(s)
United States	Code of Federal Regulations	CFR Title 47, Part 15.231
Canada	ISED Canada	ISED RSS-210v10/GENv5

It has been determined that the equipment under test is subject to the rules and directives above at the date of this testing. In conjunction with these rules and directives, the following specifications and procedures are followed herein to demonstrate compliance (in whole or in part) with these regulations.

ANSI C63.4:2014	"Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz"
ANSI C63.10:2013	"American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices"
TP0102RA	"AHD Internal Document TP0102 - Radiated Emissions Test Procedure"
ISED Canada	"The Measurement of Occupied Bandwidth"
ICES-003; Issue 7 (2020)	"Information Technology Equipment (ITE) - Limits and methods of measurement"

### 3 Configuration and Identification of the Equipment Under Test

#### 3.1 Description and Declarations

The equipment under test is a remote entry UHF transmitter. The EUT is approximately 5 x 4 x 1 cm in dimension, and is depicted in Figure 1. It is powered by 3 VDC Lithium coin cell battery. In use, this device is a hand held UHF transmitter. Table 3 outlines provider declared EUT specifications.



Figure 1: Photos of EUT.

Table 3: EUT Declarations.

<b>General Declarations</b>	
<b>Equipment Type:</b>	Keyless Entry Transmitter
<b>Country of Origin:</b>	Not Declared
<b>Nominal Supply:</b>	3 VDC
<b>Oper. Temp Range:</b>	Not Declared
<b>Frequency Range:</b>	433.589 MHz and 434.251 MHz
<b>Antenna Dimension:</b>	Not Declared
<b>Antenna Type:</b>	PCB Trace
<b>Antenna Gain:</b>	Not Declared
<b>Number of Channels:</b>	1
<b>Channel Spacing:</b>	N/A
<b>Alignment Range:</b>	Not Declared
<b>Type of Modulation:</b>	FSK
<b>United States</b>	
<b>FCC ID Number:</b>	2ACH3WB1G0608
<b>Classification:</b>	DSC
<b>Canada</b>	
<b>IC Number:</b>	1788A-FWB1G0608
<b>Classification:</b>	Remote Control Device

### 3.1.1 EUT Configuration

The EUT is configured for testing as depicted in Figure 2.




Figure 2: EUT Test Configuration Diagram.

### 3.1.2 Modes of Operation

This EUT is capable of transmitting only in a manual activated mode (normal button press).

### 3.1.3 Variants

There is only a single variant of the EUT, as tested.

### 3.1.4 Test Samples

One sample of the EUT was provided, including custom software to enable both normal operating as well as continuous modulation (CM) transmission.

### 3.1.5 Functional Exerciser

Normal operating EUT functionality was verified by observation of transmitted signal.

### 3.1.6 Modifications Made

There were no modifications made to the EUT by this laboratory.

### 3.1.7 Production Intent

The EUT appears to be a production ready sample.

### 3.1.8 Declared Exemptions and Additional Product Notes

No emissions other than fundamental and harmonic spurious were observed within 20 dB of the regulatory limits.



## 4 Emissions

### 4.1 General Test Procedures

#### 4.1.1 Radiated Test Setup and Procedures

Radiated electromagnetic emissions from the EUT are first pre-scanned in our screen room. Spectrum and modulation characteristics of all emissions are recorded. Instrumentation, including spectrum analyzers and other test equipment as detailed in Section 1.8 are employed. After pre-scan, emission measurements are made on the test site of record. If the EUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in relevant test standards are followed. Alternatively, a layout closest to normal use (as declared by the provider) is employed if the resulting emissions appear to be worst-case in such a configuration. See Figure 3. All intentionally radiating elements that are not fixed-mounted in use are placed on the test table lying flat, on their side, and on their end (3-axes) and the resulting worst case emissions are recorded. If the EUT is fixed-mounted in use, measurements are made with the device oriented in the manner consistent with installation and then emissions are recorded. If the EUT exhibits spurious emissions due to internal receiver circuitry, such emissions are measured with an appropriate carrier signal applied.




Figure 3: Radiated Emissions Diagram of the EUT.

For devices with intentional emissions below 30 MHz, a shielded loop antenna and/or E-field and H-Field broadband probes are used depending on the regulation. Shielded loops are placed at a 1 meter receive height at the desired measurement distance. For exposure in this band, 10cm diameter single-axis broadband probes meeting the requirements of ISSED SPR-002 section 5.2 are employed. Measurements are repeated and summed over three axes, and the entire frequency range is measured with and without the EUT transmitting.

Emissions between 30 MHz and 1 GHz are measured using calibrated broadband antennas. For both horizontal and vertical polarizations, the test antenna is raised and lowered from 1 to 4 m in height until a maximum emission level is detected. The EUT is then rotated through 360° in azimuth until the highest emission is detected. The test antenna is then raised and lowered one last time from 1 to 4 m and the worst case value is recorded. Emissions above 1 GHz are characterized using standard gain or broadband ridge-horn antennas on our OATS with a 4 × 5 m rectangle of ECCOSORB absorber covering the OATS ground screen and a 1.5m table height. Care is taken to ensure that test receiver resolution and video bandwidths meet the regulatory requirements, and that the emission bandwidth of the EUT is not reduced. Photographs of the test setup employed are depicted in Figure 4.

Where regulations allow for direct measurement of field strength, power values (dBm) measured on the test receiver / analyzer are converted to dBμV/m at the regulatory distance, using

$$E_{dist} = 107 + P_R + K_A - K_G + K_E - C_F$$

where  $P_R$  is the power recorded on spectrum analyzer, in dBm,  $K_A$  is the test antenna factor in dB/m,  $K_G$  is the combined pre-amplifier gain and cable loss in dB,  $K_E$  is duty correction factor (when applicable) in dB, and  $C_F$  is a distance conversion (employed only if limits are specified at alternate distance) in dB. This field strength value is then compared with the regulatory limit. If effective isotropic radiated power (EIRP) is computed, it is computed as

$$EIRP(dBm) = E_{3m}(dB\mu V/m) - 95.2.$$

When presenting data at each frequency, the highest measured emission under all possible EUT orientations (3-axes) is reported.




Figure 4: Radiated Emissions Test Setup Photograph(s).

#### **4.1.2 Conducted Emissions Test Setup and Procedures**

The EUT is not subject to measurement of power line conducted emissions as it is powered solely by its internal battery.

#### **4.1.3 Power Supply Variation**

Tests at extreme supply voltages are made if required by the procedures specified in the test standard, and results of this testing are detailed in this report.

In the case the EUT is designed for operation from a battery power source, the extreme test voltages are evaluated over the range specified in the test standard; no less than  $\pm 10\%$  of the nominal battery voltage declared by the manufacturer. For all battery operated equipment, worst case intentional and spurious emissions are re-checked employing a new (fully charged) battery.

## 4.2 Intentional Emissions

### 4.2.1 Fundamental Emission Pulsed Operation

**Test Setup & Procedure** The test equipment and facilities were setup in accordance with the standards and procedures listed in Section 2.1. Environmental conditions were set at the appropriate temperature and thermal balance was checked with a thermocouple based probe. Duty cycle is reported for all relevant modes of operation. The test equipment employed includes RSFSV30001, LOGEMCO01.

**Measurement Results** The details and results of testing the EUT are summarized in Table 4. Plots showing the measurements made to obtain these values are provided in Figure 5.

Table 4: Fundamental Emission Pulsed Operation.

<b>Detector</b>	<b>Span</b>	<b>IF Bandwidth</b>	<b>Video Bandwidth</b>	<b>Test Date:</b>	16-Jun-22
Pk	0	1 MHz	3 MHz	<b>Test Engineer:</b>	J. Brunett
				<b>EUT:</b>	Alps DUT2
				<b>EUT Mode:</b>	Normal Operating
				<b>Meas. Distance:</b>	10 cm

FCC/IC										
R0	Test Freq. (MHz)	EUT Test Mode*	Overall Transmission			Internal Frame Characteristics			Computed Duty Cycle	
			Min. Repetition Rate (sec)	Max. No. of Frames	Total Transmission Length (sec)	Max. Frame Length (ms)	Min. Frame Period (ms)	Frame Encoding	(%)	(dB)
R1	433.92	Manual Activated, FSK	single	3	0.505	100.50	201.0	In the worse case, the EUT transmits 100ms FSK data frames. Thus, no duty cycle is applicable.	100.5	0.0
R2										
#	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10

Example Calculation: 100 ms / 100 ms = 100 % on-time.




Figure 5: Fundamental Emission Pulsed Operation.

#### 4.2.2 Fundamental Emission Bandwidth

**Test Setup & Procedure** The test equipment and facilities were setup in accordance with the standards and procedures listed in Section 2.1. Environmental conditions were set at the appropriate temperature and thermal balance was checked with a thermocouple based probe. Emission bandwidth (EBW) of the EUT is measured with the device placed in the test mode(s) with the shortest available frame length and minimum frame spacing. The 20 dB EBW is measured as the max-held peak-detected signal when the IF bandwidth is greater than or equal to 1% of the receiver span. For complex modulations other than ASK and FSK, the 99% emission bandwidth per IC test procedures has a different result, and is also reported. The test equipment employed includes RSFSV30001, LOGEMCO01.

**Measurement Results** The details and results of testing the EUT are summarized in Table 5. Plots showing the measurements made to obtain these values are provided in Figure 6.

Table 5: Fundamental Emission Bandwidth.

<b>Detector</b>		<b>IF Bandwidth</b>	<b>Video Bandwidth</b>	<b>Test Date:</b> 16-Jun-22		
Pk		10 kHz	100 kHz	<b>Test Engineer:</b> J. Brunett		
				<b>EUT:</b> Alps DUT2		
				<b>EUT Mode:</b> Normal Operating		
				<b>Meas. Distance:</b> 10 cm		
						FCC/IC
R0	Mode	Center Frequency (MHz)	20 dB EBW (MHz)	EBW Limit (MHz)	99% OBW (MHz)	Pass/Fail
R1	Norm	433.92	0.067	1.085	0.112	Pass
R2						
R3						
#	C1	C2	C3	C4	C5	C6

(ROW) (COLUMN) NOTE:

R0 C0




Figure 6: Fundamental Emission Bandwidth.

### 4.2.3 Fundamental Emission Field Strength

**Test Setup & Procedure** The test equipment and facilities were setup in accordance with the standards and procedures listed in Section 2.1. Environmental conditions were set at the appropriate temperature and thermal balance was checked with a thermocouple based probe. Fundamental emissions are measured at the regulatory distance on our OATS. The test equipment employed includes RSFSV30001, LOGEMCO01.

**Measurement Results** The details and results of testing the EUT are summarized in Table 6.

Table 6: Fundamental Emission Field Strength.

		EUT Modes:										a1	CM - 3-BTN				a5																	
		Test Date(s):										06/16/22	a2					a6																
		Test Engineer:										J. Brunett	a3					a7																
													a4					a8																
R0	Frequency		Site						EUT			Test Antenna				Cable	Receiver				Field Strength @ DR						EIRP		Details					
	Start	Stop	Temp.	Table	MR	DR	N/F	CF	Mode	Volt.	Dim	Pol.	Ant.	Dim.	Ka	Kg	Rx Power	Bandwidth	Meas.	Pk	Limit	Qpk / Avg	Pk	Limit	Calc.	Limit	Calc.							
			( C )	Angle					see				Height				Pk	Avg										RBW		VBW	USA	CAN	USA	CAN
	MHz	MHz	Hum.	deg					table	(V)	cm	H/V	m	cm	dB/m	dB	dBm	dBm										MHz		dBuV/m	dBm			
R1	SETUP		OATSC						ALPS DUT2			EMCOLOG01				CAB001	RSFSV30001				NOTES: H-POL - FLAT, V-POL END Worst Case Orient													
R2	433.9	433.9	36 / 40	180.0	3.0	3.0		0.0	a1	3.3	7.5	H	1.0	100.0	16.3	-0.1			0.12	0.30	74.0	100.8	100.8	74.0	80.8	80.8	-21.1		6.8					
R3	433.9	433.9	36 / 40	0.0	3.0	3.0		0.0	a1	3.3	7.5	V	1.3	100.0	16.3	-0.1			0.12	0.30	75.5	100.8	100.8	75.5	80.8	80.8	-19.6		5.3					
R4																																		
R5																																		
R6																																		
#	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16	C17	C18	C19	C20	C21	C22	C23	C24	C25	C26	C27	C28	C29					
(ROW)	(COLUMN)																																	
R0	NOTE:																																	
R0	C5 MR is Measurement Range, which is reduced from DR to achieve necessary SNR.																																	
R0	C6 DR is the regulatory Desired Range measurement distance.																																	
R0	C7 N/F is Near-Field / Far-Field distance computed for max of EUT Antenna Dimension (C10) computed above 1 GHz.																																	
R0	C8 CF is computed using a 20 dB/decade Decay Rate.																																	
R0	C17/18 When E-field or EIRP is reported directly from Spectrum Analyzer, Antenna Factors and Cable losses are included directly in SA settings and Pr is not reported.																																	



### 4.3 Unintentional Emissions

#### 4.3.1 Transmit Chain Spurious Emissions

The results for the measurement of transmit chain spurious emissions at the nominal voltage and temperature are provided in Table 7.

Table 7: Transmit Chain Spurious Emissions.

		EUT Modes: a1 CM - 3-BTN														a5	
		a2														a6	
Test Date(s):		06/16/22														a7	
Test Engineer:		J. Brunett														a8	

R0	Frequency		Temp. ( C ) Hum. %	Table Angle deg	Site			EUT			Test Antenna			Cable	Receiver			Field Strength @ DR						EIRP		Details			
	Start	Stop			MR	DR	N/F	CF	Mode	Volt.	Dim	Pol.	Ant.	Dim.	Ka	Rx Power	Bandwidth	Meas.	Pk		Qpk / Avg		Limit		Calc.		Limit		
	MHz	MHz							see	(V)	cm	H/V	m	cm	dB/m	dB	dBm		dBm	USA/CAN	dBuV/m	USA/CAN	dBm	dBm					
									table								MHz												
R1	SETUP				OATSC				ALPS DUT2			EMCOLOG01			CAB001	RSFSV30001			NOTES: H-POL - FLAT, V-POL END Worst Case Orient										
R2	867.8	867.8	36 /40	220.0	3.0	3.0		0.0	a1	3.0	8.0	H	1.0	100.0	15.3	-0.2		0.12	0.30	39.7	80.8	80.8	39.7	60.8	60.8	-55.5		21.1	
R3	867.8	867.8	36 /40	0.0	3.0	3.0		0.0	a1	3.0	8.0	V	1.0	100.0	15.3	-0.2		0.12	0.30	36.8	80.8	80.8	36.8	60.8	60.8	-58.4		24.0	
R4	SETUP				OATSC				ALPS DUT2			HRNSINGQR			CAB015	RSFSV30001			NOTES: max all orientations of EUT										
R5	1301.8	1301.8	36 /40	all	3.0	3.0	0.2	0.0	a1	3.0	8.0	H/V	all	15.0	22.0	-2.9		1.00	3.00	51.2	74.0	74.0	51.2	54.0	54.0	-44.0		2.8	
R6	1735.3	1736.0	36 /40	all	3.0	3.0	0.3	0.0	a1	3.0	8.0	H/V	all	15.0	26.7	-3.4		1.00	3.00	44.7	80.8	80.8	44.7	60.8	60.8	-50.5		16.1	
R7	2168.9	2170.3	36 /40	all	3.0	3.0	0.3	0.0	a1	3.0	8.0	H/V	all	15.0	29.6	-3.9		1.00	3.00	52.6	80.8	80.8	52.6	60.8	60.8	-42.6		8.2	
R8	2602.5	2604.5	36 /40	all	3.0	3.0	0.4	0.0	a1	3.0	8.0	H/V	all	15.0	31.1	-4.4		1.00	3.00	50.9	80.8	80.8	50.9	60.8	60.8	-44.3		9.9	
R9	3036.1	3038.8	36 /40	all	3.0	3.0	0.5	0.0	a1	3.0	8.0	H/V	all	15.0	31.8	-4.9		1.00	3.00	50.4	80.8	80.8	50.4	60.8	60.8	-44.8		10.4	
R10	3469.7	3473.0	36 /40	all	3.0	3.0	0.5	0.0	a1	3.0	8.0	H/V	all	15.0	31.9	-5.4		1.00	3.00	51.3	80.8	80.8	51.3	60.8	60.8	-43.9		9.5	
R11	3903.3	3907.3	36 /40	all	3.0	3.0	0.6	0.0	a1	3.0	8.0	H/V	all	15.0	32.0	-5.9		1.00	3.00	44.6	74.0	74.0	44.6	54.0	54.0	-50.6		9.4	
R12	4336.9	4341.5	36 /40	all	3.0	3.0	0.7	0.0	a1	4.0	8.0	H/V	all	15.0	32.3	-6.3		1.00	3.00	49.3	74.0	74.0	49.3	54.0	54.0	-45.9		4.7	
R13																													
#	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16	C17	C18	C19	C20	C21	C22	C23	C24	C25	C26	C27	C28	C29

(ROW)	(COLUMN)	NOTE:
R0	C5	MR is Measurement Range, which is reduced from DR to achieve necessary SNR.
R0	C6	DR is the regulatory Desired Range measurement distance.
R0	C7	N/F is Near-Field / Far-Field distance computed for max of EUT Antenna Dimension (C10) computed above 1 GHz.
R0	C8	CF is computed using a 20 dB/decade Decay Rate.
R0	C17/18	When E-field or EIRP is reported directly from Spectrum Analyzer, Antenna Factors and Cable losses are included directly in SA settings and Pr is not reported.
R3/R16	C21	Measured signal was background noise.

#### **4.3.2 Radiated Digital Spurious**

The results for the measurement of digital spurious emissions are not reported herein as all digital emissions were greater than 20 dB below the regulatory limit. Radiation from digital components was measured to 1 GHz, or to five times the maximum digital component operating frequency, whichever is greater.

## 5 Measurement Uncertainty and Accreditation Documents

The maximum values of measurement uncertainty for the laboratory test equipment and facilities associated with each test are given in the table below. This uncertainty is computed for a 95.45% confidence level based on a coverage factor of  $k = 2$ .

Table 8: Measurement Uncertainty.

Measured Parameter	Measurement Uncertainty <sup>†</sup>
Radio Frequency	$\pm(f_{Mkr}/10^7 + RBW/10 + (SPN/(PTS - 1))/2 + 1 \text{ Hz})$
Conducted Emm. Amplitude	$\pm 1.9 \text{ dB}$
Radiated Emm. Amplitude ( $f < 30 \text{ MHz}$ )	$\pm 3.1 \text{ dB}$
Radiated Emm. Amplitude (30 – 200 MHz)	$\pm 4.0 \text{ dB}$
Radiated Emm. Amplitude (200 – 1000 MHz)	$\pm 5.2 \text{ dB}$
Radiated Emm. Amplitude ( $f > 1000 \text{ MHz}$ )	$\pm 3.7 \text{ dB}$

<sup>†</sup>Ref: CISPR 16-4-2:2011+A1:2014



Figure 7: Accreditation Documents