ONE WORLD • OUR APPROVAL



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at device output terminal:	17.80 dBm
Cable and Jumper loss:	0.0 dB
Maximum peak output power at antenna input terminal:	17.80 dBm
	60.25595861 mW
Single Antenna gain (typical):	-2 dBi
Number of Antennae:	1
Total Antenna gain (typical):	-2 dBi
	0.630957344 (numeric)
Prediction distance:	20 cm
Prediction frequency:	916 MHz
MPE limit for uncontrolled exposure at prediction frequency:	0.610666667 mW/cm ²
Power density at prediction frequency:	0.007564 mW/cm ²
rower density at prediction frequency.	0.075000 W/m ²
TOU	0.075636 W/III
Ix On time:	1.000000 ms
Ix period time:	1.000000 ms
Average Factor:	100.000000 %
Average Power density at prediction frequency:	0.075636 W/m ²
Maximum allowable antenna gain:	17.0707407 dBi
Margin of Compliance:	19 0707407 dB