



## FCC REPORT

**Applicant:** Atoms Labs LLC

**Address of Applicant:** 2670 Firewheel Dr. Suite D Flower Mound TX 75028  
United States

**Equipment Under Test (EUT)**

Product Name: Control hub

Model No.: AHS-6R

**FCC ID:** 2ACMYAHS6R

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.249:2014

**Date of sample receipt:** May 28, 2015

**Date of Test:** May 28- June 24, 2015

**Date of report issued:** June 24, 2015

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	June 24, 2015	Original

Prepared By:

*Edward Pan*

Date:

June 24, 2015

Project Engineer

Check By:

*Hank Yan*

Date:

June 24, 2015

Reviewer

## 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
4.1 MEASUREMENT UNCERTAINTY .....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF EUT .....	5
5.3 TEST MODE .....	6
5.4 DESCRIPTION OF SUPPORT UNITS .....	6
5.5 TEST FACILITY.....	6
5.6 TEST LOCATION .....	6
5.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
6 TEST INSTRUMENTS LIST .....	7
7 TEST RESULTS AND MEASUREMENT DATA.....	8
7.1 ANTENNA REQUIREMENT.....	8
7.2 CONDUCTED EMISSIONS .....	9
7.3 RADIATED EMISSION METHOD.....	12
7.3.1 <i>Field Strength of The Fundamental Signal</i> .....	14
7.3.2 <i>Spurious emissions</i> .....	14
7.3.3 <i>Bandedge emissions</i> .....	17
7.4 20dB OCCUPY BANDWIDTH .....	18
8 TEST SETUP PHOTO .....	19
9 EUT CONSTRUCTIONAL DETAILS .....	21

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

*Remark: Test according to ANSI C63.4:2014*

### 4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 Client Information

Applicant:	Atoms Labs LLC
Address of Applicant:	2670 Firewheel Dr. Suite D Flower Mound TX 75028 United States

### 5.2 General Description of EUT

Product Name:	Control hub
Model No.:	AHS-6R
Operation Frequency:	916.8MHz
Modulation type:	GFSK
Antenna Type:	Integral antenna
Antenna gain:	2dBi (declare by Applicant)
Power supply:	AC/DC Adapter 1 Model No.:KSAS0121200100HU Input: 100-240V~50/60Hz 0.4A Output: 12V $\overline{\text{---}}$ 1.0A AC/DC Adapter 2 Model No.:CS12F120100FUF Input: 100-240V~50/60Hz 500mA Output: 12.0V $\overline{\text{---}}$ 1.0A
Remark:	Two adapters were tested, and the adapter 2 is worse. So only the data of adapter 1 is reported.

### 5.3 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: The test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

#### Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	77.26	78.63	76.22

#### Final Test Mode:

The EUT was tested in GFSK modulation is the worst case.

According to ANSI C63.4 standards, the test results are both the "worst case" and "worst setup":

Y axis (see the test setup photo)

### 5.4 Description of Support Units

None

### 5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

### 5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Room 301-309, 3th Floor, Block A, Huafeng Jinyuan Business Building, No. 300 Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

### 5.7 Other Information Requested by the Customer

None.

## 6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 28 2015	Mar. 27 2016
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	Jul. 01 2014	Jun 30 2015
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 01 2014	Jun 30 2015
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Jul. 01 2014	Jun 30 2015
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 27 2014	June 26 2015
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 27 2015	Mar. 26 2016
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	Mar. 28 2015	Mar. 27 2016
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 28 2015	Mar. 27 2016
11	Coaxial cable	GTS	N/A	GTS210	Mar. 28 2015	Mar. 27 2016
12	Coaxial Cable	GTS	N/A	GTS212	Mar. 28 2015	Mar. 27 2016
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 01 2014	Jun. 30, 2015
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 01 2014	Jun. 30, 2015
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 27 2014	June 26 2015
16	Band filter	Amindeon	82346	GTS219	Mar. 28 2015	Mar. 27 2016

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	July 01 2014	June 30 2015
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	July 01 2014	June 30 2015
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	July 01 2014	June 30 2015
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	July 01 2014	June 30 2015
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	July 01 2014	June 30 2015
6	Coaxial Cable	GTS	N/A	GTS227	July 01 2014	June 30 2015
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 08 2014	July 07 2015

## 7 Test results and Measurement Data

### 7.1 Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203
<b>15.203 requirement:</b>	
<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
<b>EUT Antenna:</b>	
<p><i>The antenna is integral antenna, the best case gain of the antenna is 2dBi</i></p>	
	




## 7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.4:2014														
Test Frequency Range:	150KHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test setup:	<p><i>Remark</i>  E.U.T: Equipment Under Test  LISN: Line Impedance Stabilization Network  Test table height=0.8m</p>														
Test procedure:	<ol style="list-style-type: none"> <li>1. The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.</li> </ol>														
Test Instruments:	Refer to section 6.0 for details														
Test mode:	Refer to section 5.3 for details														
Test results:	Pass														

**Measurement data**


Line:



Site : Shielded room  
 Condition : FCC PART15 CLASSB QP LISN-2013 LINE  
 Job No. : 1054RF  
 Test mode : Transmitting mode  
 Test Engineer: Song

	Read Freq	Cable Level	Loss	LISN Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.172	43.48	0.12	0.15	43.75	64.86	-21.11	QP
2	0.371	31.97	0.10	0.11	32.18	58.47	-26.29	QP
3	0.708	22.97	0.13	0.14	23.24	56.00	-32.76	QP
4	1.324	23.91	0.13	0.12	24.16	56.00	-31.84	QP
5	2.044	21.88	0.15	0.12	22.15	56.00	-33.85	QP
6	7.606	27.81	0.18	0.27	28.26	60.00	-31.74	QP

Neutral:



Site : Shielded room  
 Condition : FCC PART15 CLASSB QP LISN-2013 NEUTRAL  
 Job No. : 1054RF  
 Test mode : Transmitting mode  
 Test Engineer: Song


	Freq	Read Level	Cable Loss	LISN Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.182	42.68	0.13	0.07	42.88	64.42	-21.54	QP
2	0.371	33.36	0.10	0.06	33.52	58.47	-24.95	QP
3	0.839	23.90	0.13	0.07	24.10	56.00	-31.90	QP
4	1.449	24.49	0.13	0.09	24.71	56.00	-31.29	QP
5	2.012	22.97	0.15	0.09	23.21	56.00	-32.79	QP
6	3.642	23.02	0.15	0.14	23.31	56.00	-32.69	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

## 7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209			
Test Method:	ANSI C63.4:2014			
Test Frequency Range:	30MHz to 10GHz			
Test site:	Measurement Distance: 3m			
Receiver setup:	Frequency	Detector	RBW	VBW
	30MHz-1GHz	Quasi-peak	120KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Peak		1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark
	902MHz ~ 928MHz	94.00		Quasi-peak Value
Limit: (Spurious Emissions)	Frequency	Limit (dBuV/m @3m)		Remark
	30MHz-88MHz	40.00		Quasi-peak Value
	88MHz-216MHz	43.50		Quasi-peak Value
	216MHz-960MHz	46.00		Quasi-peak Value
	960MHz-1GHz	54.00		Quasi-peak Value
	Above 1GHz	54.00		Average Value
74.00		Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.			
Test setup:	<p>Below 1GHz</p> <p>Above 1GHz</p>			

	 <p>The diagram illustrates the test setup. An EUT (Equipment Under Test) is placed on a turn table that is 0.8m high from the ground. The turn table is positioned 3m away from a horn antenna. The horn antenna is mounted on an antenna tower. The antenna height is varied from 1m to 4m above the ground. The test receiver system includes an amplifier and a spectrum analyzer.</p>
<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8m meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Pass</p>

**Measurement data:**

### 7.3.1 Field Strength of The Fundamental Signal

**Quasi-peak Value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
916.80	68.81	23.21	4.91	29.10	67.83	94.00	-26.17	Vertical
916.80	79.61	23.21	4.91	29.10	78.63	94.00	-15.37	Horizontal

### 7.3.2 Spurious emissions

■ Below 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
31.40	45.65	14.32	0.57	30.09	30.45	40.00	-9.55	Vertical
94.43	36.57	14.75	1.15	29.72	22.75	43.50	-20.75	Vertical
203.52	41.61	12.67	1.86	29.23	26.91	43.50	-16.59	Vertical
480.53	32.63	18.07	3.22	29.34	24.58	46.00	-21.42	Vertical
721.73	32.64	21.10	4.17	29.20	28.71	46.00	-17.29	Vertical
962.16	32.98	23.49	5.09	29.10	32.46	54.00	-21.54	Vertical
31.62	32.39	14.32	0.57	30.09	17.19	40.00	-22.81	Horizontal
201.39	44.06	12.60	1.85	29.21	29.30	43.50	-14.20	Horizontal
360.45	37.83	16.43	2.67	29.69	27.24	46.00	-18.76	Horizontal
480.53	37.63	18.07	3.22	29.34	29.58	46.00	-16.42	Horizontal
721.73	37.39	21.10	4.17	29.20	33.46	46.00	-12.54	Horizontal
842.13	35.47	22.51	4.63	29.16	33.45	46.00	-12.55	Horizontal

■ Above 1GHz

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1833.60	40.08	25.45	4.88	34.17	36.24	74.00	-37.76	Vertical
2750.40	38.06	28.26	5.71	33.61	38.42	74.00	-35.58	Vertical
3667.20	36.71	29.20	7.28	32.56	40.63	74.00	-33.37	Vertical
4584.00	33.88	31.49	8.41	31.98	41.80	74.00	-32.20	Vertical
5500.80	32.84	31.98	9.51	32.43	41.90	74.00	-32.10	Vertical
6417.60	31.94	33.49	10.78	32.12	44.09	74.00	-29.91	Vertical
7334.40	30.83	36.41	11.72	31.88	47.08	74.00	-26.92	Vertical
8251.20	28.88	36.76	12.51	31.77	46.38	74.00	-27.62	Vertical
9168.00	29.56	37.31	13.80	32.13	48.54	74.00	-25.46	Vertical
1833.60	40.31	25.45	4.88	34.17	36.47	74.00	-37.53	Horizontal
2750.40	38.82	28.26	5.71	33.61	39.18	74.00	-34.82	Horizontal
3667.20	37.77	29.20	7.28	32.56	41.69	74.00	-32.31	Horizontal
4584.00	34.53	31.49	8.41	31.98	42.45	74.00	-31.55	Horizontal
5500.80	32.77	31.98	9.51	32.43	41.83	74.00	-32.17	Horizontal
6417.60	32.31	33.49	10.78	32.12	44.46	74.00	-29.54	Horizontal
7334.40	31.04	36.41	11.72	31.88	47.29	74.00	-26.71	Horizontal
8251.20	30.46	36.76	12.51	31.77	47.96	74.00	-26.04	Horizontal
9168.00	29.71	37.31	13.80	32.13	48.69	74.00	-25.31	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1833.60	30.55	25.45	4.88	34.17	26.71	54.00	-27.29	Vertical
2750.40	28.86	28.26	5.71	33.61	29.22	54.00	-24.78	Vertical
3667.20	26.95	29.20	7.28	32.56	30.87	54.00	-23.13	Vertical
4584.00	23.99	31.49	8.41	31.98	31.91	54.00	-22.09	Vertical
5500.80	22.88	31.98	9.51	32.43	31.94	54.00	-22.06	Vertical
6417.60	22.00	33.49	10.78	32.12	34.15	54.00	-19.85	Vertical
7334.40	20.86	36.41	11.72	31.88	37.11	54.00	-16.89	Vertical
8251.20	18.70	36.76	12.51	31.77	36.20	54.00	-17.80	Vertical
9168.00	19.67	37.31	13.80	32.13	38.65	54.00	-15.35	Vertical
1833.6	30.98	25.45	4.88	34.17	27.14	54.00	-26.86	Horizontal
2750.40	28.95	28.26	5.71	33.61	29.31	54.00	-24.69	Horizontal
3667.20	27.86	29.20	7.28	32.56	31.78	54.00	-22.22	Horizontal
4584.00	24.87	31.49	8.41	31.98	32.79	54.00	-21.21	Horizontal
5500.80	22.49	31.98	9.51	32.43	31.55	54.00	-22.45	Horizontal
6417.60	22.37	33.49	10.78	32.12	34.52	54.00	-19.48	Horizontal
7334.40	21.90	36.41	11.72	31.88	38.15	54.00	-15.85	Horizontal
8251.20	20.88	36.76	12.51	31.77	38.38	54.00	-15.62	Horizontal
9168.00	19.69	37.31	13.80	32.13	38.67	54.00	-15.33	Horizontal

*Remark:*

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *“\*” , means this data is the too weak instrument of signal is unable to test.*




### 7.3.3 Bandedge emissions

*All of the restriction bands were tested, and only the data of worst case was exhibited.*

Test channel:					916.8MHz channel			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	QP Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
902.00	27.91	23.12	4.87	29.10	26.80	46.00	-19.20	Vertical
928.00	26.02	23.28	4.96	29.10	25.16	46.00	-20.84	Vertical
902.00	27.28	23.12	4.87	29.10	26.17	46.00	-19.83	Horizontal
928.00	25.35	23.28	4.96	29.10	24.49	46.00	-21.51	Horizontal


## 7.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.4:2014
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

### Measurement Data


20dB bandwidth(MHz)	Result
0.229	Pass

Test plot as follows:



## 8 Test Setup Photo


Radiated Emission




## Conducted Emission





## 9 EUT Constructional Details






























Adapter 1:



Adapter 2:



-----End-----