

# **FCC Test Report**

Report No.: AGC01040220803FE09

FCC ID : 2ACN7RC905

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION**: Group Training Data Hub

**BRAND NAME** : N/A

MODEL NAME RC905, RC906, RC907, RC908, RC5, RC6, RC7, RC8, RC9,

RC905G

**APPLICANT**: ShenZhen Fitcare Electronics Co., Ltd.

**DATE OF ISSUE** : Sep. 22, 2022

**STANDARD(S)** : FCC Part 15.407 **TEST PROCEDURE(S)** : KDB 905462 D02

**REPORT VERSION**: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd






Page 2 of 14

## **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 22, 2022	Valid	Initial Release





## **TABLE OF CONTENTS**

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
3. DESCRIPTION OF TEST MODES	6
4. SUMMARY OF TEST RESULTS	7
5. TEST FACILITY	7
6. DYNAMIC FREQUENCY SELECTION (DFS)	8
6.1. APPLICABILITY OF DFS REQUIREMENTS	8
6.2. TEST SET-UP	9
6.3. LIMITS	
6.4. RADAR TEST WAVEFORMS	11
6.5. TEST PROCEDURE	11
6.6. TEST RESULT	11
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	14
APPENDIX B: PHOTOGRAPHS OF EUT	14





#### 1. VERIFICATION OF CONFORMITY

Applicant	ShenZhen Fitcare Electronics Co., Ltd.	
Address 6th Floor(south), Building A, Dingxin Science Park, Honglang North 2nd Bao'an, Shenzhen, China		
Manufacturer	ShenZhen Fitcare Electronics Co., Ltd.	
Address	6th Floor(south), Building A, Dingxin Science Park, Honglang North 2nd Road, Bao'an, Shenzhen, China	
Factory	ShenZhen Fitcare Electronics Co., Ltd.	
Address	6th Floor(south), Building A, Dingxin Science Park, Honglang North 2nd Road, Bao'an, Shenzhen, China	
Product Designation Group Training Data Hub		
Brand Name	N/A	
Test Model	RC905	
Series Model	RC906, RC907, RC908, RC5, RC6, RC7, RC8, RC9, RC905G	
Declaration of Difference	All the same except for the model name	
<b>Date of test</b> Aug. 17,2022 to Sep. 22,2022		
Deviation	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result Pass		
Report Template	AGCRT-US-BGN/RF	

#### We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in KDB 905462 D02.

Alan Duan
(Project Engineer)

Reviewed By

Calvin Liu
(Reviewer)

Approved By

Max Zhang
(Authorized Officer)

Sep. 22, 2022

Sep. 22, 2022



Page 5 of 14

#### 2. GENERAL INFORMATION

The EUT is designed as "Group Training Data Hub". It is designed by way of utilizing the OFDM technology to achieve the system operation.

Equipment Type	☐ Outdoor access points ☐ Indoor access points			
Equipment Type	☐ Fixed P2P access points ☐ Client devices			
Operation Frequency	□ U-NII 1:5150MHz~5250MHz     □ U-NII 2A: 5250MHz~5350MHz			
Operation Frequency	☐ U-NII 2C:5470MHz~5725MHz ☐ U-NII 3: 5725MHz~5850MHz			
DFS Design Type	☐ Master ☐ Slave with radar detection ☐ Slave without radar detection			
TPC Function	☐ Yes ☒ No			
Took Fraguency Dange	For 802.11a/n-HT20: 5180~5240MHz, 5260~5320MHz			
Test Frequency Range	For 802.11n-HT40: 5190~5230MHz, 5270~5310MHz			
Output Dower	IEEE 802.11a: 11.19dBm; IEEE 802.11n-HT20: 10.70dBm;			
Output Power	IEEE 802.11n-HT40: 10.50dBm;			
Modulation	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM)			
Modulation	802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM,128QAM)			
Data Rate	802.11a: 6/9/12/18/24/36/48/54Mbps			
Data Kate	802.11n: up to 300Mbps			
Number of channels	6 channels of U-NII-1 Band			
Number of Chamiles	6 channels of U-NII-2A Band			
Hardware Version	V1.3.1			
Software Version	V1.5.9			
Antenna Designation	FPC antenna (Comply with requirements of the FCC part 15.203)			
Antenna Gain	U-NII 1:4.95dBi			
Antenna Gam	U- NII-2A:4.95dBi			
Power Supply	DC 5V from type-C port or DC 12V from adapter			

#### Note:

- 1. This device does not support radar monitoring.
- 2. The signal loading method between the client device and the Master device is TCP technology.
- 3. Distribution of start-up time of Master device and client device:



Page 6 of 14

Equipment	Boot time(s)
Passive device(client)	10s
Active device(master)	40s

#### 3. DESCRIPTION OF TEST MODES

The tests in this section are run sequentially and the UUT must pass all tests successfully.

If the UUT fails any one of the tests it will count as a failure of compliance.

To show compliance, all tests must be performed with waveforms randomly generated as specified with test results meeting the required percentage of successful detection criteria.

One frequency will be chosen from the operating Channels of the UUT within the 5250-5350 MHz or 5470-5725 MHz bands.



Page 7 of 14

## 4. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.407(h)(2)	Dynamic Frequency Selection Channel Move Time and Channel Closing Transmission Time	Compliant

#### 5. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd	
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China	
Designation Number CN1259		
FCC Test Firm Registration Number	975832	
A2LA Cert. No.	5054.02	
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA	

Description	Manufacturer	Model No.	S/N	Calibration Due.	Calibration Due.
MXG X-Series Vector Signal Generator	Agilent	N5182B	MY53050647	Aug. 03, 2022	Aug. 02, 2023
EXA Signal Analyzer	Agilent	N9020A	MY49100060	Aug. 04, 2022	Aug. 03, 2023
Attenuator	ZHINAN	E-002	N/A	Sep. 03, 2020	Sep. 02, 2022
Attenuator	ZHINAN	E-002	N/A	Sep. 02, 2022	Sep. 01, 2024
Power spliter	Mini-Circuits	ZFRSC-183-s	3122	N/A	N/A
RF Cable	Harbour	SHWCB-3000-N	N/A	May 13, 2022	May 12, 2023
DFS waveform Generator software	Keysight	N7607C V2.0.0.0	N/A	N/A	N/A
DFS data Analyzer software	Tonscend	JS1120-2	N/A	N/A	N/A
AP(Master)	ZTE	ZXHN F670	N/A	N/A	N/A

FCC ID of AP(Master): Q78-ZXHNF670E



Page 8 of 14

## 6. DYNAMIC FREQUENCY SELECTION (DFS)

#### **6.1. APPLICABILITY OF DFS REQUIREMENTS**

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

	Operational Mode			
Requirement	Master	⊠Client Without Radar	☐Client With Radar	
	□iviastei	Detection	Detection	
Non-Occupancy Period	Yes	Not required	Yes	
DFS Detection Threshold	Yes	Not required	Yes	
Channel Availability Check Time	Yes	Not required	Not required	
U-NII Detection Bandwidth	Yes	Not required	Yes	

Table 2: Applicability of DFS requirements during normal operation


	Operational Mode			
Requirement	☐ Master Device or Client with	⊠Client Without Radar		
	Radar Detection	Detection		
DFS Detection Threshold	Yes	Not required		
Channel Closing Transmission Time	Yes	Yes		
Channel Move Time	Yes	Yes		
U-NII Detection Bandwidth	Yes	Not required		

	Additional requirements for devices	☐Master Device or Client with	⊠Client Without Radar
with multiple bandwidth modes		Radar Detection	Detection
U-NII Detection Bandwidth and		All BW modes must be tested	Not required
	Statistical Performance Check		
Channel Move Time and Channel		Test using widest BW mode	Test using the widest BW mode
	Closing Transmission Time	available	available for the link
	All other tests	Any single BW mode	Not required
	All other tests	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.



#### 6.2. TEST SET-UP



#### 6.3. LIMITS

Table 3: DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)	
EIRP ≥ 200 milliwatt	-64 dBm	
EIRP < 200 milliwatt and	CO JD	
power spectral density < 10 dBm/MHz	-62 dBm	
EIRP < 200 milliwatt that do not meet the power	-64 dBm	
spectral density requirement		

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.



Page 10 of 14

Table 4: DFS Response Requirement Values

Parameter	Value	
Non-occupancy period	Minimum 30 minutes	
Channel Availability Check Time	60 seconds	
Changel Mayo Time	10 seconds	
Channel Move Time	See Note 1.	
	200 milliseconds + an	
Channel Closing Transmission Time	aggregate of 60	
	milliseconds over remaining	
	10 second period.	
	See Notes 1 and 2.	
	Minimum 100% of the U-	
U-NII Detection Bandwidth	NII 99% transmission power bandwidth.	
	See Note 3.	

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.



Page 11 of 14

#### 6.4. RADAR TEST WAVEFORMS

Radar Type	Pulse Width (µsec)	PRI (µsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1

#### **6.5. TEST PROCEDURE**

- 1. When a Client Device without Radar Detection is the UUT, the Master Device is the Radar Detection Device.
- 2. A spectrum analyzer is used to establish the test signal level for each radar type.
- 3. During this process, there are no transmissions by either the Master Device or Client Device.
- 4. The spectrum analyzer is switched to the zero span (time domain) mode at the frequency of the Radar Waveform generator. The peak detector function of the spectrum analyzer is utilized. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) are set to at least 3 MHz.
- 5. The measured channels are 5530MHz in 80MHz Bandwidth and 5290MHz in 80MHz Bandwidth. The Radar signal was the same as transmitted channels, and injected into the antenna port of AP(master) ,measured the DFS parameters. The master transmitted the test data to client, the transmitted duty cycle is 30.8%.


#### **6.6. TEST RESULT**

#### 6.6.1 DFS DETECTION THRESHOLD

#### Calibration:


For a detection threshold level of -64dBm and the antenna gain is 5dBi, required detection threshold is -62dBm (= -64+2).

Note: Maximum Transmit Power is greater than 200 milliwatt in this report, so detection threshold level is -64dBm .










#### **6.6.2TEST RESULT**

## Channel Move Time and Channel Closing Transmission Time


Test Frequency	Requirement	Measurement Level	Limit
5260MHz	Channel Closing Transmission Time	0.041	≤0.26s
	Channel Move Time	1.311	≤10s
5500MHz	Channel Closing Transmission Time	0.009	≤0.26s
	Channel Move Time	1.069	≤10s
5290MHz	Channel Closing Transmission Time	0.008	≤0.26s
	Channel Move Time	1.028	≤10s
5530MHz	Channel Closing Transmission Time	0.020	≤0.26s
	Channel Move Time	1.190	≤10s



## Radar Type 0(20MHz/5260MHz)



## Non-occupancy Period-Elapse time 30minutes



**RESULT: PASS** 



Page 14 of 14

#### **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

Refer to the Report No.: AGC01040220803AP01

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC01040220803AP02

----END OF REPORT----



## Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.