

# TEST REPORT

**FCC ID: 2ACOE-WG217**

**Product: WIFI module**

**Model No.: WG217**

**Additional Model No.: WG217\_ES, WG217\_E6, WG217\_E4, WG217\_PS,  
WG217\_P6, WG217\_P4**

**Trade Mark: N/A**

**Report No.: TCT1890321E014**

**Issued Date: Apr. 02, 2019**

Issued for:

**Skylab M&C Technology Co., Ltd.**

**6/F, Building 9, Lijincheng park, Gongye East Rd, Longhua St, Longhua  
District, Shenzhen 518109, China**

Issued By:

**Shenzhen Tongce Testing Lab.**

**1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,  
Shenzhen, Guangdong, China**

**TEL: +86-755-27673339**

**FAX: +86-755-27673332**

**Note:** This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

**TABLE OF CONTENTS**

<b>1. Test Certification.....</b>	<b>3</b>
<b>2. Test Result Summary .....</b>	<b>4</b>
<b>3. EUT Description .....</b>	<b>5</b>
<b>4. General Information.....</b>	<b>7</b>
4.1. Test environment and mode.....	7
4.2. Description of Support Units.....	8
<b>5. Facilities and Accreditations .....</b>	<b>9</b>
5.1. Facilities .....	9
5.2. Location .....	9
5.3. Measurement Uncertainty.....	9
<b>6. Test Results and Measurement Data .....</b>	<b>10</b>
6.1. Antenna requirement .....	10
6.2. Conducted Emission.....	11
6.3. Maximum Conducted (Average) Output Power .....	15
6.4. Emission Bandwidth .....	16
6.5. Power Spectral Density.....	17
6.6. Conducted Band Edge and Spurious Emission Measurement .....	18
6.7. Radiated Spurious Emission Measurement.....	20
<b>Appendix A: Test Result of Conducted Test</b>	
<b>Appendix B: Photographs of Test Setup</b>	
<b>Appendix C: Photographs of EUT</b>	

## 1. Test Certification

<b>Product:</b>	WIFI module
<b>Model No.:</b>	WG217
<b>Additional Model:</b>	WG217_ES, WG217_E6, WG217_E4, WG217_PS, WG217_P6, WG217_P4
<b>Trade Mark:</b>	N/A
<b>Applicant:</b>	Skylab M&C Technology Co., Ltd.
<b>Address:</b>	6/F, Building 9, Lijincheng park, Gongye East Rd, Longhua St, Longhua District, Shenzhen 518109, China
<b>Manufacturer:</b>	Skylab M&C Technology Co., Ltd.
<b>Address:</b>	6/F, Building 9, Lijincheng park, Gongye East Rd, Longhua St, Longhua District, Shenzhen 518109, China
<b>Date of Test:</b>	Mar. 22, 2019 – Apr. 01, 2019
<b>Applicable Standards:</b>	FCC CFR Title 47 Part 15 Subpart C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r01

*The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.*

**Tested By:** Jerry Xie

**Date:** Apr. 01, 2019

Jerry Xie

**Reviewed By:** Beryl Zhao

**Date:** Apr. 02, 2019

Beryl Zhao

**Approved By:** Tomsin

**Date:** Apr. 02, 2019

Tomsin

## 2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. EUT Description

<b>Product:</b>	WIFI module
<b>Model No.:</b>	WG217
<b>Additional Model:</b>	WG217_ES, WG217_E6, WG217_E4, WG217_PS, WG217_P6, WG217_P4
<b>Trade Mark:</b>	N/A
<b>Hardware Version:</b>	WG211_EVB
<b>Software Version:</b>	V1.05
<b>Operation Frequency:</b>	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
<b>Channel Separation:</b>	5MHz
<b>Number of Channel:</b>	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
<b>Modulation Technology: (IEEE 802.11b)</b>	Direct Sequence Spread Spectrum (DSSS)
<b>Modulation Technology: (IEEE 802.11g/802.11n)</b>	Orthogonal Frequency Division Multiplexing(OFDM)
<b>Data speed (IEEE 802.11b):</b>	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
<b>Data speed (IEEE 802.11g):</b>	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
<b>Data speed (IEEE 802.11n):</b>	Up to 150Mbps
<b>Antenna Type:</b>	PCB Antenna / External antenna
<b>Antenna Gain:</b>	PCB Antenna: 1.5dBi External antenna: 2 dBi
<b>Power Supply:</b>	DC 5.0V From PC
<b>Remark:</b>	1. There are two antenna types for the product, and the worst test data is reflected in the report. 2. All models above are identical in interior structure, electrical circuits and components, and just antennas and connectors are different for the marketing requirement.

**Operation Frequency each of channel For 802.11b/g/n(HT20)**

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

**Operation Frequency each of channel For 802.11n (HT40)**

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

**Note:**

*In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:*

**802.11b/802.11g/802.11n (HT20)**

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

**802.11n (HT40)**

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

## 4. General Information

### 4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%)
<p>The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. For the full battery state and The output power to the maximum state.</p>	

<p>We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:</p>	
<p><b>Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.</b></p>	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps
Final Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation
<p>1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.</p> <p>2. According to ANSI C63.10 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20), 13.5Mbps for 802.11(H40). Duty cycle setting during the transmission is 98.5% with maximum power setting for all modulations.</p>	

## 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



## 5. Facilities and Accreditations

### 5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

### 5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339



### 5.3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$

## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
<b>E.U.T Antenna:</b>	
<p>The WIFI antenna is PCB antenna which permanently attached, and the best case gain of the antenna is 1.5dBi.</p>	
	
<p>The WIFI antenna is External antenna which is a broken antenna can be replaced by the user, and the best case gain of the antenna is 2dBi.</p>	
	

## 6.2. Conducted Emission

### 6.2.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.207														
<b>Test Method:</b>	ANSI C63.10:2013														
<b>Frequency Range:</b>	150 kHz to 30 MHz														
<b>Receiver setup:</b>	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
<b>Limits:</b>	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
<b>Test Setup:</b>	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
<b>Test Mode:</b>	Charging + transmitting with modulation														
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol>														
<b>Test Result:</b>	PASS														

6.2.2. Test Instruments


Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	R&S	ESPI	101402	Jul. 17, 2019
LISN	Schwarzbeck	NSLK 8126	8126453	Sep. 20, 2019
Coax cable (9KHz-30MHz)	TCT	CE-05	N/A	Sep. 16, 2019
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)




Site: Phase: **L1** Temperature: 25  
Limit: FCC Part 15C Conduction(QP) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1860	37.82	10.12	47.94	64.21	-16.27	peak	
2	*	0.5325	33.07	10.13	43.20	56.00	-12.80	peak	
3		2.0670	30.30	10.12	40.42	56.00	-15.58	peak	
4		2.8275	30.49	10.12	40.61	56.00	-15.39	peak	
5		5.4375	27.24	10.13	37.37	60.00	-22.63	peak	
6		15.5625	26.32	10.18	36.50	60.00	-23.50	peak	

**Note:**

- Freq. = Emission frequency in MHz
- Reading level (dBuV) = Receiver reading
- Corr. Factor (dB) = LISN factor + Cable loss
- Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)
- Limit (dBuV) = Limit stated in standard
- Margin (dB) = Measurement (dBuV) – Limits (dBuV)
- Q.P. =Quasi-Peak
- AVG =average
- \*Any value more than 10dB below limit have not been specifically reported.
- \* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

**Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)**



Site: Phase: **N** Temperature: 25  
Limit: FCC Part 15C Conduction(QP) Power: Humidity: 55 %


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1815	38.71	10.12	48.83	64.42	-15.59	peak	
2	*	0.5280	33.26	10.13	43.39	56.00	-12.61	peak	
3		0.8340	32.95	10.12	43.07	56.00	-12.93	peak	
4		1.3740	29.57	10.12	39.69	56.00	-16.31	peak	
5		1.8870	31.01	10.12	41.13	56.00	-14.87	peak	
6		5.2440	29.03	10.13	39.16	60.00	-20.84	peak	

**Note:**

- Freq. = Emission frequency in MHz
- Reading level (dBuV) = Receiver reading
- Corr. Factor (dB) = LISN factor + Cable loss
- Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)
- Limit (dBuV) = Limit stated in standard
- Margin (dB) = Measurement (dBuV) – Limits (dBuV)
- Q.P. =Quasi-Peak
- AVG =average
- \*Any value more than 10dB below limit have not been specifically reported.
- \* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

### 6.3. Maximum Conducted (Average) Output Power

#### 6.3.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (b)(3)
<b>Test Method:</b>	KDB 558074
<b>Limit:</b>	30dBm
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r01.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Measure the conducted output power and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS


#### 6.3.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 20, 2019
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-01	N/A	Sep. 20, 2019

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 6.4. Emission Bandwidth

### 6.4.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (a)(2)
<b>Test Method:</b>	KDB 558074
<b>Limit:</b>	>500kHz
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r01.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.</li> <li>4. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS

### 6.4.2. Test Instruments


RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 20, 2019
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-01	N/A	Sep. 20, 2019

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



## 6.5. Power Spectral Density

### 6.5.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (e)
<b>Test Method:</b>	KDB 558074
<b>Limit:</b>	The average power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r01.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>. Video bandwidth <math>\text{VBW} \geq 3 \times \text{RBW}</math>. Set the span to at least 1.5 times the OBW.</li> <li>5. Detector = RMS, Sweep time = auto couple.</li> <li>6. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.</li> <li>6. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS


### 6.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 20, 2019
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-01	N/A	Sep. 20, 2019

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 6.6. Conducted Band Edge and Spurious Emission Measurement

### 6.6.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (d)
<b>Test Method:</b>	KDB558074
<b>Limit:</b>	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r01.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).</li> <li>5. Measure and record the results in the test report.</li> <li>6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</li> </ol>
<b>Test Result:</b>	PASS

**6.6.2. Test Instruments**


RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 20, 2019
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-01	N/A	Sep. 20, 2019

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).


## 6.7. Radiated Spurious Emission Measurement

### 6.7.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.209					
<b>Test Method:</b>	ANSI C63.10: 2013					
<b>Frequency Range:</b>	9 kHz to 25 GHz					
<b>Measurement Distance:</b>	3 m					
<b>Antenna Polarization:</b>	Horizontal & Vertical					
<b>Operation mode:</b>	Transmitting mode with modulation					
<b>Receiver Setup:</b>	Frequency	Detector	RBW	VBW	Remark	
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		Peak	1MHz	10Hz	Average Value	
<b>Limit:</b>	Frequency		Field Strength (microvolts/meter)	Measurement Distance (meters)		
	0.009-0.490		2400/F(KHz)	300		
	0.490-1.705		24000/F(KHz)	30		
	1.705-30		30	30		
	30-88		100	3		
	88-216		150	3		
	216-960		200	3		
	Above 960		500	3		
	Frequency		Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	
	Above 1GHz		500	3	Average	
			5000	3	Peak	
	<b>Test setup:</b>	For radiated emissions below 30MHz				
		<p>The diagram shows a test setup for radiated emissions below 30MHz. An Equipment Under Test (EUT) is placed on a turn table at a height of 0.8m. The turn table is on a ground plane. An antenna is positioned at a distance of 3m from the EUT. The antenna is connected to a Pre-Amplifier, which is connected to a Receiver, which is connected to a Computer.</p>				
	30MHz to 1GHz					



Above 1GHz



**Test Procedure:**

1. For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for

	<p>receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <p>(1) Span shall wide enough to fully capture the emission being measured;</p> <p>(2) Set RBW=100 kHz for <math>f &lt; 1</math> GHz; <math>VBW \geq RBW</math>; Sweep = auto; Detector function = peak; Trace = max hold;</p> <p>(3) Set RBW = 1 MHz, <math>VBW = 3</math> MHz for <math>f \geq 1</math> GHz for peak measurement.</p> <p>For average measurement: <math>VBW = 10</math> Hz, when duty cycle is no less than 98 percent. <math>VBW \geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
<b>Test results:</b>	PASS

6.7.2. Test Instruments


Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	ROHDE&SCHW ARZ	ESIB7	100197	Jul. 17, 2019
Spectrum Analyzer	ROHDE&SCHW ARZ	FSQ40	200061	Sep. 20, 2019
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep. 16, 2019
Pre-amplifier	HP	8447D	2727A05017	Sep. 16, 2019
Loop antenna	ZHINAN	ZN30900A	12024	Oct. 20, 2019
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 02, 2019
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Oct. 20, 2019
Horn Antenna	A-INFO	LB-180400-KF	J211020657	Sep. 16, 2019
Antenna Mast	Keleto	RE-AM	N/A	N/A
Coax cable (9KHz-1GHz)	TCT	RE-low-01	N/A	Sep. 16, 2019
Coax cable (9KHz-40GHz)	TCT	RE-high-02	N/A	Sep. 16, 2019
Coax cable (9KHz-1GHz)	TCT	RE-low-03	N/A	Sep. 16, 2019
Coax cable (9KHz-40GHz)	TCT	RE-high-04	N/A	Sep. 16, 2019
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

**6.7.3. Test Data**

Please refer to following diagram for individual  
Below 1GHz

Horizontal:




Site: Polarization: **Horizontal** Temperature: 25  
Limit: FCC Part 15C 3M Radiation Power: DC 3.7V Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		166.6385	50.66	-15.50	35.16	43.50	-8.34	QP		
2	!	266.8395	52.49	-12.01	40.48	46.00	-5.52	QP		
3	!	280.2936	52.09	-11.57	40.52	46.00	-5.48	QP		
4	*	300.6988	53.24	-10.90	42.34	46.00	-3.66	QP		
5		624.4897	41.91	-5.69	36.22	46.00	-9.78	QP		
6		798.6205	40.70	-4.67	36.03	46.00	-9.97	QP		



Vertical:



Site: Polarization: **Vertical** Temperature: 25  
 Limit: FCC Part 15C 3M Radiation Power: DC 3.7V Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		140.7767	44.71	-16.10	28.61	43.50	-14.89	QP		
2	*	280.2936	43.24	-11.57	31.67	46.00	-14.33	QP		
3		401.1050	38.95	-8.94	30.01	46.00	-15.99	QP		
4		448.8361	39.16	-8.34	30.82	46.00	-15.18	QP		
5		665.2610	36.43	-5.55	30.88	46.00	-15.12	QP		
6		804.2523	35.73	-4.60	31.13	46.00	-14.87	QP		

**Note:** 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported


2. Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40) ), and the worst case Mode (Highest channel and 802.11b) was submitted only.

**Test Result of Radiated Spurious at Band edges**

Modulation Type: 802.11b

Low channel: 2412 MHz


Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2310	H	45.63	-4.20	40.71	74.00	54.00
2377.38	H	48.18	-4.10	50.64	74.00	54.00
2390	H	53.39	-3.94	51.26	74.00	54.00
2310	V	44.91	-4.20	41.43	74.00	54.00
2377.38	V	54.74	-4.10	44.08	74.00	54.00
2390	V	55.20	-3.94	49.45	74.00	54.00



Modulation Type: 802.11b

High channel: 2462 MHz



Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2483.5	H	50.46	-3.60	46.86	74.00	54.00
2487.09	H	47.02	-3.50	43.52	74.00	54.00
2500	H	45.85	-3.34	42.51	74.00	54.00
2483.5	V	54.57	-3.60	50.97	74.00	54.00
2487.09	V	47.48	-3.50	43.98	74.00	54.00
2500	V	42.93	-3.34	39.59	74.00	54.00



Modulation Type: 802.11g

Low channel: 2412 MHz



Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2310	H	42.05	-4.20	41.70	74.00	54.00
2388.96	H	50.27	-4.12	44.50	74.00	54.00
2390	H	53.53	-3.94	50.52	74.00	54.00
2310	V	45.90	-4.20	37.85	74.00	54.00
2388.96	V	48.62	-4.12	46.15	74.00	54.00
2390	V	54.46	-3.94	49.59	74.00	54.00



Modulation Type: 802.11g

High channel: 2462 MHz


Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2483.5	H	53.05	-3.60	49.45	74.00	54.00
2487.59	H	50.71	-3.52	47.19	74.00	54.00
2500	H	46.84	-3.34	43.50	74.00	54.00
2483.5	V	51.18	-3.60	47.58	74.00	54.00
2487.59	V	47.39	-3.52	43.87	74.00	54.00
2500	V	46.63	-3.34	43.29	74.00	54.00



Modulation Type: 802.11n(20MHz)

Low channel: 2412 MHz


Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2310	H	45.28	-4.20	41.08	74.00	54.00
2388.01	H	54.42	-4.10	50.32	74.00	54.00
2390	H	53.09	-3.94	49.15	74.00	54.00
2310	V	48.51	-4.20	44.31	74.00	54.00
2388.01	V	54.36	-4.10	50.26	74.00	54.00
2390	V	55.80	-3.94	51.86	74.00	54.00



Modulation Type: 802.11n(20MHz)

High channel: 2462 MHz


Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2483.5	H	52.76	-3.60	48.56	74.00	54.00
2392.55	H	51.82	-3.50	47.72	74.00	54.00
2500	H	47.37	-3.34	43.43	74.00	54.00
2483.5	V	53.94	-3.60	49.74	74.00	54.00
2392.55	V	50.60	-3.50	46.50	74.00	54.00
2500	V	48.17	-3.34	44.23	74.00	54.00




Modulation Type: 802.11n(40MHz)

Low channel: 2422 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2310	H	50.42	-4.20	46.22	74.00	54.00
2387.85	H	55.07	-4.10	50.97	74.00	54.00
2390	H	52.43	-3.94	48.49	74.00	54.00
2310	V	51.82	-4.20	47.62	74.00	54.00
2389.98	V	50.65	-4.10	46.55	74.00	54.00
2390	V	49.07	-3.94	45.13	74.00	54.00



Site Limit: FCC part 15.247 bandedge(peak) Polarization: Horizontal Temperature: 25 (C) Humidity: 55 % Power:




Site Limit: FCC part 15.247 bandedge(peak) Polarization: Vertical Temperature: 25 (C) Humidity: 55 % Power:


Modulation Type: 802.11n(40MHz)

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level (dBμV/m)	Peak limit (dBμV/m)	AV limit (dBμV/m)
2483.5	H	52.49	-3.60	48.89	74.00	54.00
2493.51	H	54.26	-3.50	50.76	74.00	54.00
2500	H	49.63	-3.34	46.29	74.00	54.00
2493.51	V	54.95	-3.60	51.35	74.00	54.00
2489.36	V	52.71	-3.46	49.21	74.00	54.00
2500	V	50.38	-3.34	47.04	74.00	54.00



Site Limit: FCC part 15.247 bandedge(peak) Polarization: Horizontal Temperature: 25 (C) Humidity: 55 % Power:



Site Limit: FCC part 15.247 bandedge(peak) Polarization: Vertical Temperature: 25 (C) Humidity: 55 % Power:

**Note:**

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

### Above 1GHz

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	49.05	---	0.75	49.80	---	74	54	-4.20
7236	H	40.81	---	9.87	50.68	---	74	54	-3.32
---	H	---	---	---	---	---	---	---	---
4824	V	47.37	---	0.75	48.12	---	74	54	-5.88
7236	V	40.62	---	9.87	50.49	---	74	54	-3.51
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	49.58	---	0.97	50.55	---	74	54	-3.45
7311	H	41.16	---	9.83	50.99	---	74	54	-3.01
---	H	---	---	---	---	---	---	---	---
4874	V	49.40	---	0.97	50.37	---	74	54	-3.63
7311	V	40.73	---	9.83	50.56	---	74	54	-3.44
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	47.94	---	1.18	49.12	---	74	54	-4.88
7386	H	39.29	---	10.07	49.36	---	74	54	-4.64
---	H	---	---	---	---	---	---	---	---
4924	V	46.64	---	1.18	47.82	---	74	54	-6.18
7386	V	40.18	---	10.07	50.25	---	74	54	-3.75
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	49.74	---	0.75	50.49	---	74	54	-3.51
7236	H	40.29	---	9.87	50.16	---	74	54	-3.84
---	H	---	---	---	---	---	---	---	---
4824	V	47.80	---	0.75	48.55	---	74	54	-5.45
7236	V	40.57	---	9.87	50.44	---	74	54	-3.56
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	48.18	---	0.97	49.15	---	74	54	-4.85
7311	H	40.42	---	9.83	50.25	---	74	54	-3.75
---	H	---	---	---	---	---	---	---	---
4874	V	47.93	---	0.97	48.90	---	74	54	-5.10
7311	V	40.05	---	9.83	49.88	---	74	54	-4.12
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	47.36	---	1.18	48.54	---	74	54	-5.46
7386	H	39.61	---	10.07	49.68	---	74	54	-4.32
---	H	---	---	---	---	---	---	---	---
4924	V	47.28	---	1.18	48.46	---	74	54	-5.54
7386	V	39.30	---	10.07	49.37	---	74	54	-4.63
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	49.70	---	0.75	50.45	---	74	54	-3.55
7236	H	40.48	---	9.87	50.35	---	74	54	-3.65
---	H	---	---	---	---	---	---	---	---
4824	V	47.06	---	0.75	47.81	---	74	54	-6.19
7236	V	40.53	---	9.87	50.40	---	74	54	-3.60
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	48.61	---	0.97	49.58	---	74	54	-4.42
7311	H	40.39	---	9.83	50.22	---	74	54	-3.78
---	H	---	---	---	---	---	---	---	---
4874	V	47.14	---	0.97	48.11	---	74	54	-5.89
7311	V	40.92	---	9.83	50.75	---	74	54	-3.25
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	48.27	---	1.18	49.45	---	74	54	-4.55
7386	H	40.85	---	10.07	50.92	---	74	54	-3.08
---	H	---	---	---	---	---	---	---	---
4924	V	46.03	---	1.18	47.21	---	74	54	-6.79
7386	V	40.56	---	10.07	50.63	---	74	54	-3.37
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.



Modulation Type: 802.11n (HT40)

Low channel: 2422 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4844	H	45.84	---	0.66	46.50	---	74	54	-7.50
7266	H	38.50	---	9.50	48.00	---	74	54	-6.00
---	H	---	---	---	---	---	---	---	---
4824	V	44.29	---	0.66	44.95	---	74	54	-9.05
7236	V	35.72	---	9.50	45.22	---	74	54	-8.78
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	42.48	---	0.99	43.47	---	74	54	-10.53
7311	H	34.06	---	9.85	43.91	---	74	54	-10.09
---	H	---	---	---	---	---	---	---	---
4874	V	43.93	---	0.99	44.92	---	74	54	-9.08
7311	V	37.17	---	9.85	47.02	---	74	54	-6.98
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4904	H	45.65	---	1.33	46.98	---	74	54	-7.02
7356	H	36.31	---	10.22	46.53	---	74	54	-7.47
---	H	---	---	---	---	---	---	---	---
4904	V	43.73	---	1.33	45.06	---	74	54	-8.94
7356	V	36.16	---	10.22	46.38	---	74	54	-7.62
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "---" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.


## Appendix A: Test Result of Conducted Test


### Conducted Average Output Power




#### Result Table

Mode	Channel	Meas.Level [dBm]	Verdict
11B	LCH	15.42	PASS
11B	MCH	16.01	PASS
11B	HCH	15.41	PASS
11G	LCH	13.1	PASS
11G	MCH	16.23	PASS
11G	HCH	12.93	PASS
11N20SISO	LCH	13.23	PASS
11N20SISO	MCH	13.05	PASS
11N20SISO	HCH	12.8	PASS
11N40SISO	LCH	13.4	PASS
11N40SISO	MCH	13.33	PASS
11N40SISO	HCH	13.18	PASS



#### Test Graph



11B/MCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Radio Std: None          Trig: Free Run Avg/Hold: 10/10          #FGain: Low #Atten: 40 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Center 2.437 GHz Span 25.62 MHz          #Res BW 1 MHz #VBW 3 MHz #Sweep 100 ms</p> <p>Channel Power Power Spectral Density          16.01 dBm / 12.81 MHz -55.07 dBm / Hz</p> <p>Frequency: Center Freq 2.437000000 GHz          CF Step 2.561800 MHz          Freq Offset 0 Hz</p>
11B/HCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Radio Std: None          Trig: Free Run Avg/Hold: 10/10          #FGain: Low #Atten: 40 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Center 2.462 GHz Span 25.58 MHz          #Res BW 1 MHz #VBW 3 MHz #Sweep 100 ms</p> <p>Channel Power Power Spectral Density          15.41 dBm / 12.79 MHz -55.66 dBm / Hz</p> <p>Frequency: Center Freq 2.462000000 GHz          CF Step 2.568400 MHz          Freq Offset 0 Hz</p>
11G/LCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.412000000 GHz Center Freq: 2.412000000 GHz Radio Std: None          Trig: Free Run Avg/Hold: 10/10          #FGain: Low #Atten: 40 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Center 2.412 GHz Span 32.86 MHz          #Res BW 1 MHz #VBW 3 MHz #Sweep 100 ms</p> <p>Channel Power Power Spectral Density          13.10 dBm / 16.43 MHz -59.06 dBm / Hz</p> <p>Frequency: Center Freq 2.412000000 GHz          CF Step 3.286200 MHz          Freq Offset 0 Hz</p>

11G/MCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.46200000 GHz</p> <p>Channel Power: 13.23 dBm / 16.46 MHz</p> <p>Power Spectral Density: -55.94 dBm / Hz</p>
11G/HCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.46200000 GHz</p> <p>Channel Power: 12.93 dBm / 16.4 MHz</p> <p>Power Spectral Density: -59.22 dBm / Hz</p>
11N20SISO/LCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.41200000 GHz</p> <p>Channel Power: 13.23 dBm / 17.59 MHz</p> <p>Power Spectral Density: -59.22 dBm / Hz</p>

<p>11N20SISO/MCH</p>	<p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Radio Std: None</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Channel Power: 13.05 dBm / 17.58 MHz</p> <p>Power Spectral Density: -59.41 dBm / Hz</p>
<p>11N20SISO/HCH</p>	<p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Radio Std: None</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Channel Power: 12.80 dBm / 17.59 MHz</p> <p>Power Spectral Density: -59.65 dBm / Hz</p>
<p>11N40SISO/LCH</p>	<p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.422000000 GHz Center Freq: 2.422000000 GHz Radio Std: None</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Channel Power: 13.40 dBm / 35.96 MHz</p> <p>Power Spectral Density: -62.15 dBm / Hz</p>


<p>11N40SISO/MCH</p>	
<p>11N40SISO/HCH</p>	

### 6dB Occupied Bandwidth


#### Result Table

Mode	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict
11B	LCH	9.036	12.797	PASS
11B	MCH	9.043	12.809	PASS
11B	HCH	9.028	12.792	PASS
11G	LCH	16.55	16.431	PASS
11G	MCH	16.47	16.47	PASS
11G	HCH	16.53	16.397	PASS
11N20SISO	LCH	17.67	17.589	PASS
11N20SISO	MCH	17.64	17.584	PASS
11N20SISO	HCH	17.62	17.587	PASS
11N40SISO	LCH	36.41	35.956	PASS
11N40SISO	MCH	36.40	35.964	PASS
11N40SISO	HCH	36.41	35.963	PASS


#### Test Graph




11B/MCH



11B/HCH




11G/LCH







11G/MCH



11G/HCH



11N20SISO/LCH



<p>11N20SISO/MCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Radio Std: None          Trig: Free Run Avg/Hold: &gt;10/10          #FGain: Low #Atten: 40 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Center 2.437 GHz Span 40 MHz          #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms</p> <p>Occupied Bandwidth 17.584 MHz Total Power 18.8 dBm</p> <p>Transmit Freq Error -9.650 kHz OBW Power 99.00 %          x dB Bandwidth 17.64 MHz x dB -6.00 dB</p>
<p>11N20SISO/HCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Radio Std: None          Trig: Free Run Avg/Hold: &gt;10/10          #FGain: Low #Atten: 40 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Center 2.462 GHz Span 40 MHz          #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms</p> <p>Occupied Bandwidth 17.587 MHz Total Power 18.6 dBm</p> <p>Transmit Freq Error -8.950 kHz OBW Power 99.00 %          x dB Bandwidth 17.64 MHz x dB -6.00 dB</p>
<p>11N40SISO/LCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.422000000 GHz Center Freq: 2.422000000 GHz Radio Std: None          Trig: Free Run Avg/Hold: &gt;10/10          #FGain: Low #Atten: 40 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 23.90 dBm</p> <p>Center 2.422 GHz Span 80 MHz          #Res BW 100 kHz #VBW 300 kHz Sweep 8 ms</p> <p>Occupied Bandwidth 35.956 MHz Total Power 19.2 dBm</p> <p>Transmit Freq Error -7.797 kHz OBW Power 99.00 %          x dB Bandwidth 36.41 MHz x dB -6.00 dB</p>


<p>11N40SISO/MCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.43700000 GHz</p> <p>Center Freq: 2.43700000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 10/10</p> <p>Radio Std: None</p> <p>#FGain: Low</p> <p>#Atten: 40 dB</p> <p>Radio Device: BTS</p> <p>Ref Offset 0.9 dB</p> <p>Ref 23.90 dBm</p> <p>Center 2.437 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 80 MHz</p> <p>Sweep 8 ms</p> <p>Occupied Bandwidth <b>35.964 MHz</b></p> <p>Total Power 19.1 dBm</p> <p>Transmit Freq Error -474 Hz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 36.40 MHz</p> <p>x dB -6.00 dB</p> <p>Center Freq 2.43700000 GHz</p> <p>CF Step 8.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11N40SISO/HCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.45200000 GHz</p> <p>Center Freq: 2.45200000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 10/10</p> <p>Radio Std: None</p> <p>#FGain: Low</p> <p>#Atten: 40 dB</p> <p>Radio Device: BTS</p> <p>Ref Offset 0.9 dB</p> <p>Ref 23.90 dBm</p> <p>Center 2.452 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 80 MHz</p> <p>Sweep 8 ms</p> <p>Occupied Bandwidth <b>35.963 MHz</b></p> <p>Total Power 19.0 dBm</p> <p>Transmit Freq Error -9.904 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 36.41 MHz</p> <p>x dB -6.00 dB</p> <p>Center Freq 2.45200000 GHz</p> <p>CF Step 8.000000 MHz</p> <p>Freq Offset 0 Hz</p>

## Band-edge for RF Conducted Emissions


### Result Table

Mode	Channel	Carrier Power [dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	6.097	-48.490	-23.9	PASS
11B	HCH	6.134	-48.881	-23.87	PASS
11G	LCH	-0.987	-47.633	-30.99	PASS
11G	HCH	-1.286	-47.748	-31.29	PASS
11N20SISO	LCH	-0.805	-47.586	-30.81	PASS
11N20SISO	HCH	-0.792	-47.703	-30.79	PASS
11N40SISO	LCH	-4.119	-46.171	-34.12	PASS
11N40SISO	HCH	-4.413	-47.298	-34.41	PASS


### Test Graph




11G/LCH






11G/HCH



11N20SISO/LCH




<p>11N20SISO/HCH</p>	 <table border="1" data-bbox="598 526 1157 683"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.486 612 5 GHz</td> <td>-0.792 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.483 500 0 GHz</td> <td>-49.373 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>f</td> <td>2.480 000 0 GHz</td> <td>-49.350 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.493 600 0 GHz</td> <td>-47.703 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.486 612 5 GHz	-0.792 dBm				2	N	1	f	2.483 500 0 GHz	-49.373 dBm				3	N	1	f	2.480 000 0 GHz	-49.350 dBm				4	N	1	f	2.493 600 0 GHz	-47.703 dBm			
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.486 612 5 GHz	-0.792 dBm																																									
2	N	1	f	2.483 500 0 GHz	-49.373 dBm																																									
3	N	1	f	2.480 000 0 GHz	-49.350 dBm																																									
4	N	1	f	2.493 600 0 GHz	-47.703 dBm																																									
<p>11N40SISO/LCH</p>	 <table border="1" data-bbox="598 1014 1157 1171"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.418 500 0 GHz</td> <td>-4.119 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.400 000 0 GHz</td> <td>-40.408 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>f</td> <td>2.390 000 0 GHz</td> <td>-60.273 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.377 600 0 GHz</td> <td>-46.171 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.418 500 0 GHz	-4.119 dBm				2	N	1	f	2.400 000 0 GHz	-40.408 dBm				3	N	1	f	2.390 000 0 GHz	-60.273 dBm				4	N	1	f	2.377 600 0 GHz	-46.171 dBm			
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.418 500 0 GHz	-4.119 dBm																																									
2	N	1	f	2.400 000 0 GHz	-40.408 dBm																																									
3	N	1	f	2.390 000 0 GHz	-60.273 dBm																																									
4	N	1	f	2.377 600 0 GHz	-46.171 dBm																																									
<p>11N40SISO/HCH</p>	 <table border="1" data-bbox="598 1507 1157 1664"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.448 612 5 GHz</td> <td>-4.413 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.483 500 0 GHz</td> <td>-60.607 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>f</td> <td>2.500 000 0 GHz</td> <td>-60.127 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.489 762 5 GHz</td> <td>-47.298 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.448 612 5 GHz	-4.413 dBm				2	N	1	f	2.483 500 0 GHz	-60.607 dBm				3	N	1	f	2.500 000 0 GHz	-60.127 dBm				4	N	1	f	2.489 762 5 GHz	-47.298 dBm			
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.448 612 5 GHz	-4.413 dBm																																									
2	N	1	f	2.483 500 0 GHz	-60.607 dBm																																									
3	N	1	f	2.500 000 0 GHz	-60.127 dBm																																									
4	N	1	f	2.489 762 5 GHz	-47.298 dBm																																									

## RF Conducted Spurious Emissions




Result Table

Mode	Channel	Pref [dBm]	Puw [dBm]	Verdict
11B	LCH	6.031	<Limit	PASS
11B	MCH	6.663	<Limit	PASS
11B	HCH	5.992	<Limit	PASS
11G	LCH	-1.016	<Limit	PASS
11G	MCH	-1.048	<Limit	PASS
11G	HCH	-1.337	<Limit	PASS
11N20SISO	LCH	-0.862	<Limit	PASS
11N20SISO	MCH	-0.518	<Limit	PASS
11N20SISO	HCH	-1.039	<Limit	PASS
11N40SISO	LCH	-4.226	<Limit	PASS
11N40SISO	MCH	-3.795	<Limit	PASS
11N40SISO	HCH	-4.125	<Limit	PASS



Test Graph



Puw/11B/LCH











Puw/11B/MCH







Puw/11B/HCH





Puw/11G/LCH







Puw/11G/MCH









Puw/11G/HCH





/11N20SISO/  
CH

