

Report No.: SHEM190801676302 Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.:	SHEM1908016763CR
FCC ID:	2ACOE-WG217
Applicant:	Skylab M&C Technology Co., Ltd.
Address of Applicant:	6/F,Building 9,Lijincheng park,Gongye East Rd,Longhua St,Longhua District,Shenzhen 518109,China
Manufacturer:	Skylab M&C Technology Co., Ltd.
Address of Manufacturer:	6/F,Building 9,Lijincheng park,Gongye East Rd,Longhua St,Longhua District,Shenzhen 518109,China
Equipment Under Test (EU	Т):
EUT Name:	WiFi Module
Model No.:	WG217
Standard(s) :	FCC Rules 47 CFR §2.1091
	KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt:	2019-08-30
Date of Test:	2019-09-03 to 2019-09-07
Date of Issue:	2019-09-09
Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards specified above.

parlan share

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Member of the SGS Group (SGS SA)



Report No.: SHEM190801676302 Page: 2 of 7

Revision Record					
Version	Remark				
00	Original	2019-09-09	/		

Authorized for issue by:	
	Bril Wu
	Bill Wu / Project Engineer
	Parlam zhan
	Parlam Zhan /Reviewer



Report No.: SHEM190801676302 Page: 3 of 7

2 Contents

	COVER PAGE
	CONTENTS
	GENERAL INFORMATION
	3.1 GENERAL DESCRIPTION OF E.U.T.
5	3.2 TEST LOCATION
	3.3 TEST FACILITY
	TEST STANDARDS AND LIMITS
	4.1 FCC RADIOFREQUENCY RADIATION EXE
	MEASUREMENT AND CALCULATION
	5.1 MAXIMUM TRANSMIT POWER



Report No.: SHEM190801676302 Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

Power supply:DC 5V from PCTest voltage:DC 5V

Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	Band 1	802.11a/n(HT20)/ac(HT20)	5180-5240	4
		802.11n(HT40)/ac(HT40)	5190-5230	2
		802.11ac(HT80)	5210	1
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)			
	802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)			
	802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)			
Channel Spacing:	802.11a/n(HT20)/ac(HT20): 20MHz			
	802.11n(HT40)/ac(HT40): 40MHz			
	802.11ac(HT80): 80MHz			
Antenna Gain	3.5dBi			
Antenna Type	PCB Antenna			

NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM190801676302 Page: 5 of 7

3.2 Test Location

All tests were performed at: SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch 588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China. Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

• FCC – Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB Identifier: CN0020.

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM190801676302 Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to§1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report TCT1890321E019

Configuration Band 1 (5150 - 5250 MHz)					
Mode Test channe		Maximum Conducted (Average) Output Power (dBm)	FCC Limit (dBm)	Result	
11a	CH36	11.78	24	PASS	
11a	CH40	11.74	24	PASS	
11a	CH48	10.60	24	PASS	
11n(HT20)	CH36	9.72	24	PASS	
11n(HT20)	CH40	10.56	24	PASS	
11n(HT20)	CH48	8.34	24	PASS	
11n(HT40)	CH38	10.19	24	PASS	
11n(HT40)	CH46	8.49	24	PASS	
11ac(HT20)	CH36	9.77	24	PASS	
11ac(HT20)	CH40	10.05	24	PASS	
11ac(HT20)	CH48	8.45	24	PASS	
11ac(HT40)	CH38	10.05	24	PASS	
11ac(HT40)	CH46	8.63	24	PASS	
11ac(HT80)	CH42	6.53	24	PASS	



Report No.: SHEM190801676302 Page: 7 of 7

5.2 MPE Calculation

For FCC:

According to the formula S=P/4 π R², we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm²

The max. antenna gain is 3.5

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
11.78	2.239	20	0.00525	1	Pass

So the device is exclusion from SAR test.

--End of the Report--

dBi