

TEST REPORT

FCC ID: 2ACOE-WG225

Product: WIFI Module

Model No.: WG225

Additional Model No.: N/A

Trade Mark: SKYLAB

Report No.: TCT200907E065

Issued Date: Oct. 28, 2020

Issued for:

**Skylab M&C Technology Co., Ltd.
6/F, Building 9, Lijincheng park, Gongye East Rd, Longhua St, Longhua
District, Shenzhen 518109, China**

Issued By:

**Shenzhen Tongce Testing Lab.
1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,
Shenzhen, Guangdong, China
TEL: +86-755-27673339
FAX: +86-755-27673332**

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. Test Certification 3

2. Test Result Summary 4

3. EUT Description..... 5

4. General Information..... 7

 4.1. Test environment and mode..... 7

 4.2. Description of Support Units..... 8

5. Facilities and Accreditations 9

 5.1. Facilities 9

 5.2. Location 9

 5.3. Measurement Uncertainty..... 9

6. Test Results and Measurement Data 10

 6.1. Antenna requirement 10

 6.2. Conducted Emission..... 11

 6.3. Maximum Conducted Output Power 15

 6.4. 6dB Emission Bandwidth..... 19

 6.5. 26dB Bandwidth and 99% Occupied Bandwidth 26

 6.6. Power Spectral Density..... 38

 6.7. Band edge 51

 6.8. Spurious Emission 62

 6.9. Frequency Stability Measurement 77

Appendix A: Test Result of Conducted Test

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

1. Test Certification

Product:	WIFI Module
Model No.:	WG225
Additional Model No.:	N/A
Trade Mark:	SKYLAB
Applicant:	Skylab M&C Technology Co., Ltd.
Address:	6/F, Building 9, Lijincheng park, Gongye East Rd, Longhua St, Longhua District, Shenzhen 518109, China
Manufacturer:	Skylab M&C Technology Co., Ltd.
Address:	6/F, Building 9, Lijincheng park, Gongye East Rd, Longhua St, Longhua District, Shenzhen 518109, China
Date of Test:	Sep. 08, 2020 – Oct. 28, 2020
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart E Section 15.407: 2016 KDB662911 D01 Multiple Transmitter Output v02r01r01 KDB789033 D02 General U-NII Test Procedures New Rules v02r01r01

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Rleo

Date:

Oct. 28, 2020

Reviewed By:



Beryl Zhao

Date:

Oct. 28, 2020

Approved By:



Tomsin

Date:

Oct. 28, 2020

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth & 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(a)	PASS
Radiated Emission	§15.407(a)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. NA: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product:	WIFI Module
Model No.:	WG225
Additional Model No.:	N/A
Trade Mark:	SKYLAB
Operation Frequency:	Band 1: 5180 MHz -5240 MHz Band 3: 5745 MHz -5825 MHz
Channel Bandwidth:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz
Modulation Technology:	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type:	External Antenna
Antenna Gain:	4dBi
Power Supply:	DC 3.3V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

Test Frequency each of channel

Band 1

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180	38	5190	42	5210
40	5200	46	5230		
48	5240				

Band 3

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745	151	5755	155	5775
157	5785	159	5795		
165	5825				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below.

4. General Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 100%)
<p>The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	6.5 Mbps
802.11n(HT40)	13.5 Mbps
802.11ac(VHT20)	6.5 Mbps
802.11ac(VHT40)	13.5 Mbps
802.11ac(VHT80)	29.3 Mbps

Final Test Mode:

Operation mode:	Keep the EUT in continuous transmitting with modulation
-----------------	---

Remark: All the antennas were tested, only the worst(white antenna) was showed in the report.

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
PC	Inspiron 3668	CN-04T4P2-C13 32-26C-0013	/	Dell
Monitor	SE1918HV	CN-0YVJCX-FC C00-75D-AUAB- A00	/	Dell
Mouse	MS116p	CN-009NK2-738 26-74M-0QI9	/	Dell
Keyboard	KB216t	CN-0RKR0N-71 616-75I-0CYQ-A 03	/	Dell
WG221/WG2 25 EVB	/	1828	/	SKYLAB

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:


FCC Part15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

E.U.T Antenna:

The WIFI antenna is external antenna which permanently attached, and the best case gain of the antenna is 4dBi.



6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Tx Mode														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Result:	PASS														


6.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	R&S	ESCI3	100898	Jul. 27, 2021
LISN-2	Schwarzbeck	NSLK 8126	8126453	Sep. 11, 2021
Line-5	TCT	CE-05	N/A	Sep. 02, 2021
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual
Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)




Site: Phase: **L1** Temperature: 25 (C)
Limit: FCC Part 15C Conduction(QP) Power: DC3.3V Humidity: 55 %RH

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1740	33.91	10.22	44.13	54.77	-10.64	AVG	
2		0.1749	34.58	10.22	44.80	64.72	-19.92	QP	
3		0.2300	32.61	10.23	42.84	62.45	-19.61	QP	
4		0.2300	26.55	10.23	36.78	52.45	-15.67	AVG	
5		0.3460	24.99	10.23	35.22	49.06	-13.84	AVG	
6		0.3580	30.08	10.22	40.30	58.77	-18.47	QP	
7		0.5740	28.97	10.23	39.20	56.00	-16.80	QP	
8		0.5740	19.17	10.23	29.40	46.00	-16.60	AVG	
9		0.6860	26.34	10.23	36.57	56.00	-19.43	QP	
10		0.6860	20.14	10.23	30.37	46.00	-15.63	AVG	
11		1.2460	25.32	10.38	35.70	56.00	-20.30	QP	
12		1.2579	10.44	10.38	20.82	46.00	-25.18	AVG	

Note:

- Freq. = Emission frequency in MHz
- Reading level (dBuV) = Receiver reading
- Corr. Factor (dB) = LISN factor + Cable loss
- Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)
- Limit (dBuV) = Limit stated in standard
- Margin (dB) = Measurement (dBuV) – Limits (dBuV)
- Q.P. =Quasi-Peak
- AVG =average
- * is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **N** Temperature: 25 (C)
Limit: FCC Part 15C Conduction(QP) Power: DC3.3V Humidity: 55 %RH


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1740	33.58	10.22	43.80	64.77	-20.97	QP	
2	*	0.1740	31.84	10.22	42.06	54.77	-12.71	AVG	
3		0.2300	32.37	10.23	42.60	62.45	-19.85	QP	
4		0.2300	24.48	10.23	34.71	52.45	-17.74	AVG	
5		0.3420	28.27	10.23	38.50	59.15	-20.65	QP	
6		0.3420	18.71	10.23	28.94	49.15	-20.21	AVG	
7		0.5700	29.17	10.23	39.40	56.00	-16.60	QP	
8		0.5700	18.97	10.23	29.20	46.00	-16.80	AVG	
9		0.8020	22.33	10.27	32.60	56.00	-23.40	QP	
10		0.8020	13.28	10.27	23.55	46.00	-22.45	AVG	
11		1.2460	23.82	10.38	34.20	56.00	-21.80	QP	
12		1.2460	8.85	10.38	19.23	46.00	-26.77	AVG	

Note:

Freq. = Emission frequency in MHz
 Reading level (dBuV) = Receiver reading
 Corr. Factor (dB) = LISN factor + Cable loss
 Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)
 Limit (dBuV) = Limit stated in standard
 Margin (dB) = Measurement (dBuV) – Limits (dBuV)
 Q.P. =Quasi-Peak
 AVG =average
 * is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

6.3. Maximum Conducted Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046										
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E										
Limit:	<table border="1"> <thead> <tr> <th>Frequency Band (MHz)</th> <th>Limit</th> </tr> </thead> <tbody> <tr> <td>5180 - 5240</td> <td>24dBm(250mW) for client device</td> </tr> <tr> <td>5260 - 5320</td> <td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td> </tr> <tr> <td>5470 - 5725</td> <td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td> </tr> <tr> <td>5745 - 5825</td> <td>30dBm(1W)</td> </tr> </tbody> </table>	Frequency Band (MHz)	Limit	5180 - 5240	24dBm(250mW) for client device	5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5745 - 5825	30dBm(1W)
Frequency Band (MHz)	Limit										
5180 - 5240	24dBm(250mW) for client device										
5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5745 - 5825	30dBm(1W)										
Test Setup:	 <p style="text-align: center;"> Power meter EUT </p>										
Test Mode:	Transmitting mode with modulation										
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 5. Measure the conducted output power and record the results in the test report. 										
Test Result:	PASS										
Remark:	<p>Conducted output power= measurement power +10log(1/x) X is duty cycle=1, so 10log(1/1)=0</p> <p>Conducted output power= measurement power</p>										

6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 11, 2021
Power Meter	Agilent	E4418B	GB43312526	Sep. 11, 2021
Power Sensor	Agilent	E9301A	MY41497725	Sep. 11, 2021
4 Ch. Simultaneous Sampling 14 Bits 2 MS/s	Agilent	U2531A	N/A	Sep. 11, 2021
Combiner Box	Ascentest	AT890-RFB	N/A	Sep. 11, 2021

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3.3. Test Data


Configuration Band 1 (5180 - 5240 MHz)				
Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)	Limit (dBm)	Result
11a	CH36	7.79	24	PASS
11a	CH40	8.09	24	PASS
11a	CH48	7.63	24	PASS
11n(HT20)	CH36	8.02	24	PASS
11n(HT20)	CH40	8.45	24	PASS
11n(HT20)	CH48	7.84	24	PASS
11n(HT40)	CH38	8.45	24	PASS
11n(HT40)	CH46	7.94	24	PASS
11ac(VHT20)	CH36	8.01	24	PASS
11ac(VHT20)	CH40	8.48	24	PASS
11ac(VHT20)	CH48	7.66	24	PASS
11ac(VHT40)	CH38	8.35	24	PASS
11ac(VHT40)	CH46	7.90	24	PASS
11ac(VHT80)	CH42	8.08	24	PASS

Configuration Band 3 (5745 - 5825 MHz)

Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)	Limit (dBm)	Result
11a	CH149	8.98	30	PASS
11a	CH157	9.47	30	PASS
11a	CH165	9.46	30	PASS
11n(HT20)	CH149	9.20	30	PASS
11n(HT20)	CH157	9.74	30	PASS
11n(HT20)	CH165	9.46	30	PASS
11n(HT40)	CH151	9.42	30	PASS
11n(HT40)	CH159	9.78	30	PASS
11ac(VHT20)	CH149	9.18	30	PASS
11ac(VHT20)	CH157	9.67	30	PASS
11ac(VHT20)	CH165	9.65	30	PASS
11ac(VHT40)	CH151	9.56	30	PASS
11ac(VHT40)	CH159	9.82	30	PASS
11ac(VHT80)	CH155	9.52	30	PASS

6.4. 6dB Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 11, 2021
4 Ch. Simultaneous Sampling 14 Bits 2 MS/s	Agilent	U2531A	N/A	Sep. 11, 2021
Combiner Box	Ascentest	AT890-RFB	N/A	Sep. 11, 2021

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).


6.4.3. Test data

Band 3 (5745 - 5825 MHz)					
Mode	Test channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
11a	CH149	5745	16.42	0.5	PASS
11a	CH157	5785	16.42	0.5	PASS
11a	CH165	5825	16.42	0.5	PASS
11n(HT20)	CH149	5745	17.62	0.5	PASS
11n(HT20)	CH157	5785	17.59	0.5	PASS
11n(HT20)	CH165	5825	17.60	0.5	PASS
11n(HT40)	CH151	5755	36.11	0.5	PASS
11n(HT40)	CH159	5795	36.12	0.5	PASS
11ac(VHT20)	CH149	5745	17.61	0.5	PASS
11ac(VHT20)	CH157	5785	17.61	0.5	PASS
11ac(VHT20)	CH165	5825	17.61	0.5	PASS
11ac(VHT40)	CH151	5755	36.19	0.5	PASS
11ac(VHT40)	CH159	5795	36.09	0.5	PASS
11ac(VHT80)	CH155	5775	75.14	0.5	PASS


Band 3 (5745 – 5825 MHz)

11a


CH149



CH157




CH165




11n(HT20)


CH149



CH157




CH165




11n(HT40)

CH151




CH159




11ac(VHT20)


CH149



CH157




CH165




11ac(VHT40)

CH151




CH159



11ac(VHT80)

CH155



Band 1

Mode	Test channel	Frequency (MHz)	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	CH36	5180	19.19	16.374
11a	CH40	5200	19.14	16.371
11a	CH48	5240	19.16	16.366
11n(HT20)	CH36	5180	19.78	17.571
11n(HT20)	CH40	5200	19.66	17.566
11n(HT20)	CH48	5240	19.72	17.567
11n(HT40)	CH38	5190	39.62	36.165
11n(HT40)	CH46	5230	39.58	36.183
11ac(VHT20)	CH36	5180	19.73	17.568
11ac(VHT20)	CH40	5200	19.65	17.568
11ac(VHT20)	CH48	5240	19.73	17.567
11ac(VHT40)	CH38	5190	39.61	36.158
11ac(VHT40)	CH46	5230	39.51	36.192
11ac(VHT80)	CH42	5210	79.02	75.257


Band 3

Mode	Test channel	Frequency (MHz)	99% Bandwidth (MHz)
11a	CH149	5745	16.523
11a	CH157	5785	16.508
11a	CH165	5825	16.505
11n(HT20)	CH149	5745	17.655
11n(HT20)	CH157	5785	17.673
11n(HT20)	CH165	5825	17.676
11n(HT40)	CH151	5755	36.171
11n(HT40)	CH159	5795	36.181
11ac(VHT20)	CH149	5745	17.680
11ac(VHT20)	CH157	5785	17.666
11ac(VHT20)	CH165	5825	17.658
11ac(VHT40)	CH151	5755	36.177
11ac(VHT40)	CH159	5795	36.161
11ac(VHT80)	CH155	5775	75.286


Test plots as follows:
Band 1 (5180-5240 MHz)

11a


CH36



CH40




CH48




11n(HT20)


CH36



CH40




CH48




11n(HT40)

CH38




CH46




11ac(VHT20)


CH36



CH40




CH48




11ac(VHT40)

CH38




CH46



11ac(VHT80)


CH42




Band 3(5745-5825MHz)

11a


CH149



CH157




CH165




11n(HT20)


CH149



CH157




CH165




11n(HT40)

CH151




CH159




11ac(VHT20)


CH149



CH157




CH165




11ac(VHT40)

CH151




CH159




11ac(VHT80)

CH155



6.6. Power Spectral Density

6.6.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device) ≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725 ≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz The e.i,r,p spectral density for Band 1 5150MHz – 5250 MHz should not exceed 10dBm/MHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS

6.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 11, 2021
4 Ch. Simultaneous Sampling 14 Bits 2 MS/s	Agilent	U2531A	N/A	Sep. 11, 2021
Combiner Box	Ascentest	AT890-RFB	N/A	Sep. 11, 2021

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

Configuration Band 1 (5180 - 5240 MHz)

Mode	Test channel	Power Spectral Density	Limit (dBm)	Result
11a	CH36	-2.66	11	PASS
11a	CH40	-2.03	11	PASS
11a	CH48	-3.01	11	PASS
11n(HT20)	CH36	-2.82	11	PASS
11n(HT20)	CH40	-2.70	11	PASS
11n(HT20)	CH48	-3.26	11	PASS
11n(HT40)	CH38	-5.63	11	PASS
11n(HT40)	CH46	-5.65	11	PASS
11ac(VHT20)	CH36	-2.91	11	PASS
11ac(VHT20)	CH40	-2.90	11	PASS
11ac(VHT20)	CH48	-3.74	11	PASS
11ac(VHT40)	CH38	-5.54	11	PASS
11ac(VHT40)	CH46	-5.32	11	PASS
11ac(VHT80)	CH42	-7.76	11	PASS

Configuration Band 3 (5745 - 5825 MHz)

Mode	Test channel	Power Spectral Density	Limit (dBm/500kHz)	Result
11a	CH149	-3.83	30	PASS
11a	CH157	-3.02	30	PASS
11a	CH165	-3.40	30	PASS
11n(HT20)	CH149	-3.56	30	PASS
11n(HT20)	CH157	-3.54	30	PASS
11n(HT20)	CH165	-3.58	30	PASS
11n(HT40)	CH151	-6.32	30	PASS
11n(HT40)	CH159	-6.32	30	PASS
11ac(VHT20)	CH149	-3.27	30	PASS
11ac(VHT20)	CH157	-4.01	30	PASS
11ac(VHT20)	CH165	-3.59	30	PASS
11ac(VHT40)	CH151	-6.10	30	PASS
11ac(VHT40)	CH159	-5.84	30	PASS
11ac(VHT80)	CH155	-8.22	30	PASS