

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	Bluetooth Earbud
Model Name	BT979, BT970, BT989, BT969, 30095696, BT979W, BT979B, BT989W, BT989B, BT968, BT971, BT976, BT977
FCC ID	2ACP4BT979

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

$$P_t = -3.85 \text{ dBm} = 0.41 \text{ mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.41 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.48(\text{GHz})}] = 0.13 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.