

TEST REPORT

Reference No. : WTS16S1166496E
FCC ID..... : 2ACQ5SGW001
Applicant : Revogi Innovation Co., Ltd.
Address : 2018, Anhui Building, No.6007, Shennan Boulevard, Shenzhen,
Guangdong, China
Manufacturer : SkyRC Technology Co., Ltd.
Address : 4/F, Building No. 6, Meitai Industry Park, Guanguang South Road,
Guihua, Guanlan, 518110, Baoan District, Shenzhen, China
Product Name : Smart Sensor Gateway
Model No. : SGW001
Brand Name : revogi
Standards : FCC CFR47 Part 15 Section 15.249: 2016
Date of Receipt sample.... : Nov. 25, 2016
Date of Test..... : Nov. 26 – Dec. 10, 2016
Date of Issue..... : Jan. 07, 2017
Test Result : Pass
Note..... : This report is for Sub-G function

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Tel :+86-755-83551033


Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF E.U.T.....	4
4.2 DETAILS OF E.U.T.....	4
4.3 CHANNEL LIST	4
4.4 STANDARDS APPLICABLE FOR TESTING	4
4.5 TEST FACILITY	5
4.6 SUB-G TEST MODE	5
5 EQUIPMENT USED DURING TEST	6
5.1 EQUIPMENTS LIST	6
5.2 MEASUREMENT UNCERTAINTY.....	7
5.3 TEST EQUIPMENT CALIBRATION.....	7
6 TEST SUMMARY	8
7 CONDUCTED EMISSION	9
7.1 E.U.T. OPERATION.....	9
7.2 EUT SETUP	9
7.3 MEASUREMENT DESCRIPTION	9
7.4 TEST RESULT	10
8 RADIATION EMISSION TEST	12
8.1 EUT OPERATION.....	12
8.2 TEST SETUP	13
8.3 SPECTRUM ANALYZER SETUP.....	14
8.4 TEST PROCEDURE.....	15
8.5 FREQUENCY RANGE OF RADIATED MEASUREMENTS.....	16
8.6 TEST RESULT	17
9 PERIODIC OPERATION	19
10 BAND EDGE	20
10.1 TEST PROCEDURE.....	20
10.2 TEST RESULT	20
11 BANDWIDTH MEASUREMENT	21
11.1 TEST PROCEDURE.....	21
11.2 TEST RESULT	21
12 ANTENNA REQUIREMENT	22
13 PHOTOGRAPHS- MODEL SGW001 TEST SETUP PHOTOS.....	23
13.1 PHOTOGRAPH – RADIATION EMISSION	23
13.2 PHOTOGRAPH – CONDUCTED EMISSION TEST SETUP AT TEST SITE 1#.....	26
14 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	27
14.1 MODEL SGW001-EXTERNAL PHOTOS.....	27
14.2 MODEL SGW001-INTERNAL PHOTOS	32

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS16S1166496E	Nov. 25, 2016	Nov. 26 – Dec. 10, 2016	Dec. 12, 2016	original	-	replaced
WTS16S1166496E	Nov. 25, 2016	Nov. 26 – Dec. 10, 2016	Jan. 07, 2017	revision1	Adding the usage description of this product for Sub-G and Wi-Fi	valid

4 General Information

4.1 General Description of E.U.T.

Product Name:	Smart Sensor Gateway
Model No.:	SGW001
Model Difference:	N/A
Operation Frequency:	802.11b/g/n HT20: 2412MHz ~ 2462MHz, 802.11n HT40: 2422MHz~2452MHz, Sub-G: 915MHz
The Lowest Oscillator:	26MHz
Antenna Gain:	2.8dBi for Wi-Fi 0dBi for Sub-G
Type of modulation:	IEEE 802.11b (CCK/QPSK/BPSK, 11Mbps max.) IEEE 802.11g (BPSK/QPSK/16QAM/64QAM, 54Mbps max.) IEEE 802.11n (BPSK/QPSK/16QAM/64QAM, HT20: 72Mbps max., HT40: 150Mbps max.) Sub-G: FSK
The usage description for Sub-G and Wi-Fi:	The Sub-G is the communication between the sensing host (Smart Sensor Gateway) and the slave device (e.g. Smoke Detector); and the Wi-Fi is used to communicate between the sensing host (Smart Sensor Gateway) and the computer or mobile device. First, use Sub-G for Smart Sense kit to set up the internal network, and then use Wi-Fi to achieve communication between the sensing host and the computer or mobile device. For this product, Wi-Fi and Sub-G will not simultaneous operation.

4.2 Details of E.U.T.

Technical Data:	DC 5V, 1.0A by AC ADAPTER (AC ADAPTER Input: 100-240V~, 0.18A, 50/60Hz, Output: DC 5V $\overline{=}$ 1.0A, Model: XY05B-0501000Q-U) XING YUAN ELECTRONICS CO.,LTD.
-----------------	---

4.3 Channel List

Sub-G Mode	
Channel No.	Frequency (MHz)
0	915MHz

4.4 Standards Applicable for Testing

The tests were performed according to following standards:

FCC CFR47 Part 15 Section 15.249: 2016	Telecommunication-RADIO FREQUENCY DEVICES-Intentional Radiators-Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.
--	---

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **IC – Registration No.:7760A-1**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A-1, October 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014

4.6 Sub-G Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests.

And according to Part 15.31(m).

Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle.
1 to 10 MHz	2	1 near top and 1 near bottom.
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

The frequency range of this product over 915MHz to 915MHz is less than 1MHz, so only one channel 915MHz was recorded and reported.

Test mode	Upper channel
Transmitting	915MHz

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	Sep.12, 2016	Sep.11, 2017
2.	LISN	R&S	ENV216	101215	Sep.12, 2016	Sep.11, 2017
3.	Cable	Top	TYPE16(3.5M)	-	Sep.12, 2016	Sep.11, 2017
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Sep.12, 2016	Sep.11, 2017
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Sep.12, 2016	Sep.11, 2017
3.	Limitter	York	MTS-IMP-136	261115-001-0024	Sep.12, 2016	Sep.11, 2017
4.	Cable	LARGE	RF300	-	Sep.12, 2016	Sep.11, 2017
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	Apr.29, 2016	Apr.28, 2017
2	Amplifier	Agilent	8447D	2944A10178	Jan.13, 2016	Jan.12, 2017
3	Active Loop Antenna	Beijing Dazhi	ZN30900A	0703	Oct.17, 2016	Oct.16, 2017
4	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	33 6	Apr.09, 2016	Apr.08, 2017
5	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.12, 2016	Sep.11, 2017
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.09, 2016	Apr.08, 2017
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Apr.13, 2016	Apr.12, 2017
8	Coaxial Cable (above 1GHz)	Top	1GHz-18GHz	EW02014-7	Apr.13, 2016	Apr.12, 2017
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Apr.13, 2016	Apr.12, 2017
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Apr.09, 2016	Apr.08, 2017
3	Amplifier	ANRITSU	MH648A	M43381	Apr.13, 2016	Apr.12, 2017
4	Cable	HUBER+SUHNER	CBL2	525178	Apr.13, 2016	Apr.12, 2017

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.12, 2016	Sep.11, 2017
2.	Spectrum Analyzer (9k~6GHz)	R&S	FSL6	100959	Sep.12, 2016	Sep.11, 2017
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Sep.12, 2016	Sep.11, 2017

5.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207	C
Radiated Emission	15.249(a) 15.209 15.205(a)	C
Periodic Operation	15.35(c)	C
Band Edge	15.249 15.205 15.209	C
Bandwidth	15:215(c)	C
Antenna Requirement	15.203	C
Note: C=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.		

7 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013;ANSI C63.4:2014
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)
Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> not applicable (Remark)

7.1 E.U.T. Operation

Operating Environment :


Temperature:	25.5 °C
Humidity:	51 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in Sub-G Transmitting mode, the test data were shown in the report.

7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013




7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


7.4 Test Result

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.4339	39.31	10.05	49.36	57.18	-7.82	QP	
2	0.4339	32.53	10.05	42.58	47.18	-4.60	AVG	
3	0.5540	30.85	10.07	40.92	56.00	-15.08	QP	
4	0.5540	22.91	10.07	32.98	46.00	-13.02	AVG	
5	0.7299	33.53	10.11	43.64	56.00	-12.36	QP	
6	0.7299	25.82	10.11	35.93	46.00	-10.07	AVG	
7	1.4179	29.88	10.12	40.00	56.00	-16.00	QP	
8	1.4179	22.28	10.12	32.40	46.00	-13.60	AVG	
9	3.0299	28.26	10.24	38.50	56.00	-17.50	QP	
10	3.0299	21.16	10.24	31.40	46.00	-14.60	AVG	
11	3.3260	28.80	10.25	39.05	56.00	-16.95	QP	
12	3.3260	20.68	10.25	30.93	46.00	-15.07	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1660	31.69	9.64	41.33	65.15	-23.82	QP	
2	0.1660	16.38	9.64	26.02	55.15	-29.13	AVG	
3	0.2220	26.80	9.63	36.43	62.74	-26.31	QP	
4	0.2220	13.02	9.63	22.65	52.74	-30.09	AVG	
5	0.4660	21.78	9.65	31.43	56.58	-25.15	QP	
6	0.4660	14.60	9.65	24.25	46.58	-22.33	AVG	
7	0.5100	23.88	9.66	33.54	56.00	-22.46	QP	
8	0.5100	17.45	9.66	27.11	46.00	-18.89	AVG	
9	0.9020	19.97	9.79	29.76	56.00	-26.24	QP	
10	0.9020	11.03	9.79	20.82	46.00	-25.18	AVG	
11	2.5180	17.37	9.94	27.31	56.00	-28.69	QP	
12	2.5180	7.91	9.94	17.85	46.00	-28.15	AVG	

8 Radiation Emission Test

Test Requirement: FCC Part15 Paragraph 15.249&15.209&15.205

Test Method: ANSI 63.10: 2013;ANSI C63.4:2014

Measurement Distance: 3m

Test Result: Pass Fail

15.249(a) Limit:

Fundamental frequency	Field strength of fundamental		Field strength of harmonics	
	mV/m	dBuV/m	uV/m	dBuV/m
902-928 MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25 GHz	250	108	2500	68

15.209 Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log ^{(2400/F(kHz))} + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log ^{(24000/F(kHz))} + 40
1.705 ~ 30	30	30	100 * 30	20log ⁽³⁰⁾ + 40(29.54+40)
30 ~ 88	100	3	100	20log ⁽¹⁰⁰⁾ =(40)
88 ~ 216	150	3	150	20log ⁽¹⁵⁰⁾ =(43.5)
216 ~ 960	200	3	200	20log ⁽²⁰⁰⁾ =(46)
Above 960	500	3	500	20log ⁽⁵⁰⁰⁾ =(54)

Note: RF Voltage(dBuV)=20 log₁₀ RF Voltage(uV)

8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in Sub-G Transmitting mode, the test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10: 2013.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth 10kHz
 Resolution Bandwidth 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth 10Hz

Video Bandwidth 10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane; For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X, Y, Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), after pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

8.5 Frequency range of radiated measurements.

According to FCC 47 CFR Section 15.33:

(a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:

(1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

(2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.

(3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.

(4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1) through (a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this section, whichever is the higher frequency range of investigation.

Result: So the Frequency range of radiated form: 26MHz to 10GHz.

8.6 Test Result

Test Frequency: 26MHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 10GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.249/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP)	Degree	(m)	(H/V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)
424.79	47.43	QP	201	1.4	H	-6.84	40.59	46.00	-5.41
915.00	87.77	PK	129	0.9	H	0.93	88.70	114.00	-25.30
915.00	87.20	PK	76	1.1	V	0.93	88.13	114.00	-25.87
1830.00	64.76	PK	142	1.5	H	-15.22	49.54	74.00	-24.46
1830.00	58.83	PK	351	1.8	V	-15.22	43.61	74.00	-30.39
2745.00	62.67	PK	351	1.3	H	-14.19	48.48	74.00	-25.52
2745.00	65.02	PK	92	1.9	V	-14.19	50.83	74.00	-23.17
4575.00	54.88	PK	13	1.5	H	-4.24	50.64	74.00	-23.36
4575.00	47.45	PK	356	1.1	V	-4.24	43.21	74.00	-30.79

AV = Peak +20Log10 (duty cycle) =PK+ (0) [refer to section 9 for more detail]

Frequency	PK	RX Antenna Polar	Duty cycle Factor	AV	FCC Part 15.249/209/205	
					Limit	Margin
(MHz)	(dB μ V/m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
915.00	88.70	H	0	88.70	94	-5.3
915.00	88.13	V	0	88.13	94	-5.87
1830.00	49.54	H	0	49.54	54	-4.46
1830.00	43.61	V	0	43.61	54	-10.39
2745.00	48.48	H	0	48.48	54	-5.52
2745.00	50.83	V	0	50.83	54	-3.17
4575.00	50.64	H	0	50.64	54	-3.36
4575.00	43.21	V	0	43.21	54	-10.79

9 Periodic Operation

The duty cycle was determined by the following equation:


To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

$$\text{Duty Cycle(\%)} = \text{Total On interval in a complete pulse train} / \text{Length of a complete pulse train} * \%$$

$$\text{Duty Cycle Correction Factor(dB)} = 20 * \text{Log}_{10}(\text{Duty Cycle})$$

Total transmission time(ms)	100
Length of a complete transmission period(ms)	100
Duty Cycle(%)	100
Duty Cycle Correction Factor(dB)	0

Refer to the duty cycle plot (as below)




10 Band Edge

Test Requirement:	15.249(d):Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.
Test Method:	ANSI C63.10:2013
Test Mode:	Transmitting

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100 kHz, VBW = 300 kHz, Sweep = auto
Detector function = peak, Trace = max hold

10.2 Test Result



11 Bandwidth Measurement


Test Requirement: FCC CFR47 Part 15 Section 15.215(c)
 Test Method: ANSI C63.10:2013
 Test Mode: Transmitting

11.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyser: RBW = 10 KHz, VBW = 30 KHz

11.2 Test Result

Frequency (MHz)	20dB Bandwidth Emission (kHz)	99% Bandwidth Emission (kHz)
915.00	323.40	275.45




12 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:


The EUT has one PCB Printed Antenna for Sub-G, the gain is 0dBi. meets the requirements of FCC 15.203.




13 Photographs- Model SGW001 Test Setup Photos


13.1 Photograph – Radiation Emission

Test frequency from 26MHz to 30MHz at test site 2#




Test frequency from 30MHz to 1GHz at test site 2#





Test frequency from 1GHz to 10GHz at test site 1#





13.2 Photograph – Conducted Emission Test Setup at Test Site 1#



14 Photographs - Constructional Details

14.1 Model SGW001-External Photos




















14.2 Model SGW001-Internal Photos






















====End of Report====