



TEST REPORT

Report Reference No..... : **TRE1404007602** R/C.....: 66283

FCC ID..... : **2ACRAHX-DU1006D**

Applicant's name..... : **HARXON CORPORATION**

Address..... : 6/F, Block B, D3 Building, TCL International E City, No. 1001
Zhongshanyuan Road, Nanshan District, Shenzhen, 518055, PRC

Manufacturer..... : **HARXON CORPORATION**

Address..... : 6/F, Block B, D3 Building, TCL International E City, No. 1001
Zhongshanyuan Road, Nanshan District, Shenzhen, 518055, PRC

Test item description : **Wireless data transceiver module**

Trade Mark : Harxon

Model/Type reference..... : HX-DU1006D

Listed Model(s) : HX-DU1006T,HX-DU1006R,HX-DU1080D to HX-DU1098D,
HX-DU1080T to HX-DU1098T,HX-DU1080R to HX-DU1098R.

Standard : **FCC Per 47 CFR 2.1091(b)**
KDB447498 v05r01

Date of receipt of test sample..... : Apr 21, 2014

Date of testing..... : Apr 21, 2014- Jun 24, 2014

Date of issue..... : Jun 24, 2014

Result..... : **PASS**

Compiled by
(position+printed name+signature)...: File administrators Vivi Zhou

Supervised by
(position+printed name+signature)...: Project Engineer Eric Wang

Approved by
(position+printed name+signature)...: RF Manager Hans Hu

Vivi Zhou

Eric Wang

Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd**

Address..... : Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Contents

| | | |
|-----------|--|----------|
| 1. | <u>SUMMARY</u> | 3 |
| 1.1. | Client Information | 3 |
| 1.2. | Product Description | 3 |
| 1.3. | EUT operation mode | 4 |
| 1.4. | EUT configuration | 4 |
| 1.5. | Modifications | 4 |
| 2. | <u>TEST ENVIRONMENT</u> | 5 |
| 2.1. | Address of the test laboratory | 5 |
| 2.2. | Environmental conditions | 5 |
| 2.3. | Statement of the measurement uncertainty | 5 |
| 3. | <u>METHOD OF MEASUREMENT</u> | 5 |
| 3.1. | Applicable Standard | 5 |
| 3.2. | Limit | 6 |
| 3.3. | MPE Calculation Method | 6 |
| 4. | <u>CONCLUSION</u> | 7 |

1. Summary

1.1. Client Information

| | |
|---------------|---|
| Applicant: | HARXON CORPORATION |
| Address: | 6/F, Block B, D3 Building, TCL International E City, No. 1001 Zhongshanyuan Road, Nanshan District, Shenzhen, 518055, PRC |
| Manufacturer: | HARXON CORPORATION |
| Address: | 6/F, Block B, D3 Building, TCL International E City, No. 1001 Zhongshanyuan Road, Nanshan District, Shenzhen, 518055, PRC |

1.2. Product Description

| | |
|------------------------|--|
| Name of EUT: | Wireless data transceiver module |
| Trade Mark: | Harxon |
| Model/Type reference : | HX-DU1006D |
| Listed Model(s): | HX-DU1006T,HX-DU1006R,HX-DU1080D to HX-DU1098D, HX-DU1080T to HX-DU1098T,HX-DU1080R to HX-DU1098R |
| Operation frequency: | From 410 MHz to 470 MHz |
| Rated Output Power | maximum rated power : 1 Watts minimum rated power : 0.5 Watts |
| Channel separation: | 12.5KHz |
| Modulation: | 4FSK&GMSK |
| Power supply: | DC 3.3V |

1.3. EUT operation mode

The EUT has been tested under typical operating condition and The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

| EUT operation mode no. | Description of operation mode | Additional information |
|------------------------|-------------------------------|--|
| Op 1 | 4FSK+BW12.5KHz+TX | The equipment is set with 4FSK modulation and 12.5KHz bandwidth at maximum rated power for TX Mode,powered by DC 3.30V |
| Op2 | 4FSK+BW12.5KHz+TX | The equipment is set with 4FSK modulation and 12.5KHz bandwidth at minimum rated power for TX Mode,powered by DC 3.30V |
| Op 3 | GMSK+BW12.5KHz+TX | The equipment is set with GMSK modulation and 12.5KHz bandwidth at maximum rated power for TX Mode,powered by DC 3.30V |
| Op 4 | GMSK+BW12.5KHz+TX | The equipment is set with GMSK modulation and 12.5KHz bandwidth at minimum rated power for TX Mode,powered by DC 3.30V |
| Op 5 | 4FSK+BW12.5KHz+TX | The equipment is set with 4FSK modulation and 12.5KHz bandwidth for RX Mode,powered by DC 3.30V |
| Op 6 | GMSK+BW12.5KHz+TX | The equipment is set with GMSK modulation and 12.5KHz bandwidth for RX Mode,powered by DC 3.30 |

1.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

| | | | |
|-----------------------|-------------|----------------|---|
| <input type="radio"/> | Power Cable | Length (m) : | / |
| | | Shield : | / |
| | | Detachable : | / |
| <input type="radio"/> | Multimeter | Manufacturer : | / |
| | | Model No. : | / |

1.5. Modifications

No modifications were implemented to meet testing criteria.

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|-----------------------|---------------------|
| Temperature: | <u>15-35 ° C</u> |
| Humidity: | <u>30-60 %</u> |
| Atmospheric pressure: | <u>950-1050mbar</u> |

2.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

| Test Items | Measurement Uncertainty | Notes |
|-----------------------------|--------------------------------|--------------|
| Transmitter power conducted | 0.57 dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 v05r01:Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | (100) * | 6 |
| 3.0 – 30 | 1842/f | 4.89/f | (900/f ²)* | 6 |
| 30 – 300 | 61.4 | 0.163 | 1.0 | 6 |
| 300 – 1500 | / | / | f/300 | 6 |
| 1500 – 100,000 | / | / | 5 | 6 |

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | (100) * | 30 |
| 3.0 – 30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30 – 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 – 1500 | / | / | f/1500 | 30 |
| 1500 – 100,000 | / | / | 1.0 | 30 |

F=frequency in MHz

*=Plane-wave equivalent power density

3.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum soure-baed Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 60 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, r =60cm, as well as the gain of the used antenna is 3.50dBi, the RF power density can be obtained.

TEST RESULTS

For Op 1

| Test Frequency (MHz) | Minimum Separation Distance (cm) | Output Power (dBm) | Output Power (mW) | Antenna Gain (Numeric) | Power Density At 60 cm (mW/cm ²) | Power Density Limit FCC (mW/cm ²) | Test Results |
|----------------------|----------------------------------|--------------------|-------------------|------------------------|--|---|--------------|
| 410.000 | 60.00 | 30.65 | 1161.4486 | 2.2387 | 0.0575 | 1.3667 | PASS |
| 440.000 | 60.00 | 30.41 | 1099.0058 | 2.2387 | 0.0544 | 1.4667 | PASS |
| 470.000 | 60.00 | 30.24 | 1056.8175 | 2.2387 | 0.0523 | 1.5667 | PASS |

For Op 3

| Test Frequency (MHz) | Minimum Separation Distance (cm) | Output Power (dBm) | Output Power (mW) | Antenna Gain (Numeric) | Power Density At 60 cm (mW/cm ²) | Power Density Limit FCC (mW/cm ²) | Test Results |
|----------------------|----------------------------------|--------------------|-------------------|------------------------|--|---|--------------|
| 410.000 | 60.00 | 30.70 | 1174.8976 | 2.2387 | 0.0581 | 1.3667 | PASS |
| 440.000 | 60.00 | 30.01 | 1002.3052 | 2.2387 | 0.0496 | 1.4667 | PASS |
| 470.000 | 60.00 | 30.25 | 1059.2537 | 2.2387 | 0.0524 | 1.5667 | PASS |

4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the controlled RF Exposure.

.....**End of Report**.....