

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
ZEGO ELECTRONIC COMPANY LIMITED

Sonic Jet
Model No.: 22231

FCC ID: 2ACS622TX

Prepared for : ZEGO ELECTRONIC COMPANY LIMITED
Address : ROOM 703, KOWLOON BUILDING, 555 NATHAN
ROAD, KOWLOON, Hong Kong

Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Chan Yuan New Material Port, Keyuan
Rd. Science & Industry Park, Nan Shan, Shenzhen,
Guangdong P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20170426
Date of Test : April 10-12, 2017
Date of Report : April 14, 2017

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT)	4
1.2. Special Accessory and Auxiliary Equipment	4
1.3. Description of Test Facility	5
1.4. Measurement Uncertainty	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. OPERATION OF EUT DURING TESTING	7
3.1. Operating Mode	7
3.2. Configuration and peripherals	7
4. TEST PROCEDURES AND RESULTS	8
5. 20DB BANDWIDTH MEASUREMENT	9
5.1. Block Diagram of Test Setup	9
5.2. The Requirement For Section 15.215(c)	9
5.3. Operating Condition of EUT	9
5.4. Test Procedure	9
5.5. Test Result	10
6. BAND EDGE COMPLIANCE TEST	12
6.1. Block Diagram of Test Setup	12
6.2. The Requirement For Section 15.249	12
6.3. EUT Configuration on Measurement	12
6.4. Operating Condition of EUT	13
6.5. Test Procedure	13
6.6. Test Result	13
7. RADIATED SPURIOUS EMISSION TEST	18
7.1. Block Diagram of Test Setup	18
7.2. The Limit For Section 15.249	19
7.3. Restricted bands of operation	20
7.4. Configuration of EUT on Measurement	20
7.5. Operating Condition of EUT	21
7.6. Test Procedure	21
7.7. The Field Strength of Radiation Emission Measurement Results	22
8. ANTENNA REQUIREMENT	35
8.1. The Requirement	35
8.2. Antenna Construction	35

Test Report Certification

Applicant : ZEGO ELECTRONIC COMPANY LIMITED
Address : ROOM 703, KOWLOON BUILDING, 555 NATHAN ROAD,
KOWLOON, Hong Kong
Manufacturer : Shenzhen Yangri Electronic Company Limited
Address : The Third Industrial Area, Luotian community, Songgang town,
Shenzhen City, China.
Product : Sonic Jet
Model No. : 22231

Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.10: 2013


The EUT was tested according to FCC 47CFR 15.249 for compliance to FCC 47CFR 15.249 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : April 10-12, 2017
Date of Report : April 14, 2017

Prepared by : 
(Bob Wang, Engineer)

Approved & Authorized Signer : 
(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Sonic Jet
Model Number	:	22231
Power Supply	:	DC 9V
Operate Frequency	:	2410-2470MHz
Modulation mode	:	GFSK
Antenna Gain	:	1dBi
Antenna type	:	Integral Antenna
Applicant	:	ZEGO ELECTRONIC COMPANY LIMITED
Address	:	ROOM 703, KOWLOON BUILDING, 555 NATHAN ROAD, KOWLOON, Hong Kong
Manufacturer	:	Shenzhen Yangri Electronic Company Limited
Address	:	The Third Industrial Area, Luotian community, Songgang town, Shenzhen City, China.
Date of sample received	:	April 10, 2017
Date of Test	:	April 10-12, 2017

1.2. Special Accessory and Auxiliary Equipment

N/A

1.3. Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen
		Listed by FCC
		The Registration Number is 752051
		Listed by Industry Canada
		The Registration Number is 5077A-2
		Accredited by China National Accreditation Committee for Laboratories
		The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 07, 2017	One Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 07, 2017	One Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 07, 2017	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 07, 2017	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 13, 2017	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 13, 2017	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 13, 2017	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 13, 2017	One Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 07, 2017	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 07, 2017	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 07, 2017	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 07, 2017	One Year

3. OPERATION OF EUT DURING TESTING

3.1. Operating Mode


The mode is used: **Transmitting mode**

Low Channel: 2410MHz

Middle Channel: 2440MHz

High Channel: 2470MHz

3.2. Configuration and peripherals




4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.215(c)	20dB Bandwidth	Compliant
Section 15.249(d)	Band Edge Compliance Test	Compliant
Section 15.205(a), Section 15.209(a), Section 15.249, Section 15.35	Radiated Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	N/A
Section 15.203	Antenna Requirement	Compliant

Note: The power supply mode of the EUT is DC 9V, According to the FCC standard requirements, conducted emission is not applicable.

5. 20DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.215(c)

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near-term distribution of frequencies appears random, with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long-term distribution appears evenly distributed.

5.3. Operating Condition of EUT

5.3.1. Setup the EUT and simulator as shown as Section 5.1.

5.3.2. Turn on the power of all equipment.

5.3.3. Let the EUT work in TX modes measure it. The transmit frequency are 2410, 2440, 2470MHz.

5.4. Test Procedure

5.4.1. Place the EUT on the table and set it in transmitting mode.

5.4.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

5.4.3. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz, Detector function=peak, Trace=max hold, Sweep=auto.

5.4.4. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.

5.5. Test Result

Channel	Frequency(MHz)	20 dB Bandwidth(MHz)
Low	2410	4.064
Middle	2440	5.184
High	2470	5.216


The spectrum analyzer plots are attached as below.

Low channel



Comment A:
Date: 12.APR.2017 12:09:08

Middle channel



Comment A:
 Date: 12.APR.2017 11:57:56


High channel



Comment A:
 Date: 12.APR.2017 12:01:04

6. BAND EDGE COMPLIANCE TEST

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

6.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2410, 2470MHz.

6.5. Test Procedure

Radiate Band Edge:

6.5.1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.

6.5.2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

6.5.3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

6.5.4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

6.5.5. The band edges was measured and recorded.

6.6. Test Result



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ding #1053
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Sonic Jet
Mode: TX 2410MHz
Model: 22231
Manufacturer: YANGRI

Polarization: Horizontal
Power Source: DC 9V
Date: 17/04/11/
Time: 9/51/01
Engineer Signature: Ding
Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2392.160	40.09	6.75	46.84	74.00	-27.16	peak			
2	2392.160	30.59	6.75	37.34	54.00	-16.66	AVG			
3	2400.000	41.12	6.78	47.90	74.00	-26.10	peak			
4	2400.000	31.67	6.78	38.45	54.00	-15.55	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ding #1054

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2410MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Vertical

Power Source: DC 9V


Date: 17/04/11/

Time: 9/52/21

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2361.220	40.28	6.62	46.90	74.00	-27.10	peak			
2	2361.220	30.57	6.62	37.19	54.00	-16.81	AVG			
3	2400.000	45.45	6.78	52.23	74.00	-21.77	peak			
4	2400.000	35.67	6.78	42.45	54.00	-11.55	AVG			

Job No.: ding #1055

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2470MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Vertical

Power Source: DC 9V


Date: 17/04/11/

Time: 9/55/32

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	42.09	7.13	49.22	74.00	-24.78	peak			
2	2483.500	32.73	7.13	39.86	54.00	-14.14	AVG			
3	2500.960	49.72	7.20	46.92	74.00	-27.08	peak			
4	2500.960	29.85	7.20	37.05	54.00	-16.95	AVG			

Job No.: ding #1056

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2470MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Horizontal

Power Source: DC 9V


Date: 17/04/11/

Time: 9/58/02

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	38.35	7.13	45.48	74.00	-28.52	peak			
2	2483.500	28.77	7.13	35.90	54.00	-18.10	AVG			
3	2498.400	39.09	7.20	46.29	74.00	-27.71	peak			
4	2498.400	29.21	7.20	36.41	54.00	-17.59	AVG			

Note:


1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$
3. Display the measurement of peak values.
4. The average measurement was not performed when peak measured data under the limit of average detection.

7. RADIATED SPURIOUS EMISSION TEST


7.1. Block Diagram of Test Setup

7.1.1. Block diagram of connection between the EUT and peripherals




7.1.2. Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30-1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



7.2. The Limit For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

7.3. Restricted bands of operation

7.3.1. FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

7.4. Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.5. Operating Condition of EUT

7.5.1. Setup the EUT and simulator as shown as Section 7.1.

7.5.2. Turn on the power of all equipment.

7.5.3. Let the EUT work in TX modes and measure it. The transmit frequency are 2410, 2440, 2470MHz.

7.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter (Below 1GHz) and 1.5m (above 1GHz) high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 9 kHz in below 30MHz. and set at 120 kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The frequency range from 9 kHz to 25GHz is checked.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

Peak detector above 1GHz

RBW (1 MHz), VBW (3MHz) for Peak measurement

RBW (1 MHz), VBW (10Hz) for AV measurement

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

7.7. The Field Strength of Radiation Emission Measurement Results

PASS.

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

3. The EUT is tested radiation emission in three axes. The worst emissions are reported in all channels.

4. The radiation emissions from 9KHz-30MHz and 18GHz-25GHz are not reported, because the test values lower than the limits of 20dB.

5. The average measurement was not performed when peak measured data under the limit of average detection.

Below 1GHz



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: ding #1041
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Sonic Jet
Mode: TX 2410MHz
Model: 22231
Manufacturer: YANGRI

Polarization: Horizontal
Power Source: DC 9V
Date: 17/04/10/
Time: 10/14/59
Engineer Signature: Ding
Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.2924	27.89	-10.16	17.73	40.00	-22.27	QP			
2	52.5752	27.31	-12.77	14.54	40.00	-25.46	QP			
3	100.5806	24.95	-13.14	11.81	43.50	-31.69	QP			
4	265.6757	26.94	-10.15	16.79	46.00	-29.21	QP			
5	465.5994	28.45	-5.12	23.33	46.00	-22.67	QP			
6	699.3046	27.97	-1.08	26.89	46.00	-19.11	QP			

Job No.: ding #1042

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2410MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Vertical

Power Source: DC 9V


Date: 17/04/10/

Time: 10/15/12

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	33.0949	28.26	-10.24	18.02	40.00	-21.98	QP			
2	49.8813	27.42	-12.58	14.84	40.00	-25.16	QP			
3	129.9225	27.13	-13.76	13.37	43.50	-30.13	QP			
4	349.2500	27.65	-7.44	20.21	46.00	-25.79	QP			
5	590.9737	29.24	-2.46	26.78	46.00	-19.22	QP			
6	903.3093	28.14	2.20	30.34	46.00	-15.66	QP			




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: ding #1043	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 9V
Test item: Radiation Test	Date: 17/04/10/
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 10/15/16
EUT: Sonic Jet	Engineer Signature: Ding
Mode: TX 2440MHz	Distance: 3m
Model: 22231	
Manufacturer: YANGRI	

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.2924	27.89	-10.16	17.73	40.00	-22.27	QP			
2	49.8813	27.42	-12.58	14.84	40.00	-25.16	QP			
3	119.4360	26.04	-13.06	12.98	43.50	-30.52	QP			
4	222.9501	27.74	-11.35	16.39	46.00	-29.61	QP			
5	349.2500	27.65	-7.44	20.21	46.00	-25.79	QP			
6	590.9737	29.24	-2.46	26.78	46.00	-19.22	QP			

Job No.: ding #1044

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2440MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Horizontal

Power Source: DC 9V


Date: 17/04/10/

Time: 10/15/29

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	30.1053	28.37	-9.94	18.43	40.00	-21.57	QP			
2	60.2800	30.06	-14.01	16.05	40.00	-23.95	QP			
3	129.9225	29.13	-13.76	15.37	43.50	-28.13	QP			
4	281.0074	27.29	-9.55	17.74	46.00	-28.26	QP			
5	383.9318	29.86	-6.94	22.92	46.00	-23.08	QP			
6	590.9737	29.24	-2.46	26.78	46.00	-19.22	QP			

Job No.: ding #1045

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2470MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Horizontal

Power Source: DC 9V


Date: 17/04/10/

Time: 10/15/31

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	36.6375	27.63	-10.77	16.86	40.00	-23.14	QP			
2	83.2297	26.11	-15.73	10.38	40.00	-29.62	QP			
3	175.6516	27.37	-13.47	13.90	43.50	-29.60	QP			
4	321.0607	27.73	-8.40	19.33	46.00	-26.67	QP			
5	511.8351	27.68	-4.03	23.65	46.00	-22.35	QP			
6	779.6068	27.57	0.36	27.93	46.00	-18.07	QP			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: ding #1046
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Sonic Jet
Mode: TX 2470MHz
Model: 22231
Manufacturer: YANGRI

Polarization: Vertical
Power Source: DC 9V
Date: 17/04/10/
Time: 10/15/33
Engineer Signature: Ding
Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	30.1053	28.37	-9.94	18.43	40.00	-21.57	QP			
2	43.0504	27.81	-12.20	15.61	40.00	-24.39	QP			
3	192.4185	27.52	-12.39	15.13	43.50	-28.37	QP			
4	265.6757	28.94	-10.15	18.79	46.00	-27.21	QP			
5	381.2485	29.02	-6.96	22.06	46.00	-23.94	QP			
6	537.5891	29.15	-3.38	25.77	46.00	-20.23	QP			

Above 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING #1047	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 9V
Test item: Radiation Test	Date: 17/04/10/
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 20/15/58
EUT: Sonic Jet	Engineer Signature: Ding
Mode: TX 2410MHz	Distance: 3m
Model: 22231	
Manufacturer: YANGRI	

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2410.000	80.53	6.81	87.34	114.00	-26.66	peak			
2	2410.000	70.42	6.81	77.23	94.00	-16.77	AVG			
3	4820.000	47.86	2.05	49.91	74.00	-24.09	peak			
4	4820.000	35.03	2.05	37.08	54.00	-16.92	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING #1048

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2410MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Horizontal

Power Source: DC 9V


Date: 17/04/10/

Time: 20/17/41

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2410.000	75.27	6.81	82.08	114.00	-31.92	peak			
2	2410.000	66.42	6.81	73.23	94.00	-20.77	AVG			
3	4820.000	46.89	2.05	48.94	74.00	-25.06	peak			
4	4820.000	36.26	2.05	38.31	54.00	-15.69	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING #1049

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2440MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Horizontal

Power Source: DC 9V


Date: 17/04/10/

Time: 20/22/00

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.00	76.72	6.93	83.65	114.00	-30.35	peak			
2	2440.000	66.15	6.93	73.08	94.00	-20.92	AVG			
3	4880.000	47.13	2.23	49.36	74.00	-24.64	peak			
4	4880.000	37.11	2.23	39.34	54.00	-14.66	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING #1050

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Sonic Jet

Mode: TX 2440MHz

Model: 22231

Manufacturer: YANGRI

Polarization: Vertical

Power Source: DC 9V


Date: 17/04/10/

Time: 20/24/09

Engineer Signature: Ding

Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.000	80.30	6.96	87.26	114.00	-26.74	peak			
2	2440.000	70.79	6.96	77.75	94.00	-16.25	AVG			
3	4880.000	49.33	2.23	51.56	74.00	-22.44	peak			
4	4880.000	39.17	2.23	41.40	54.00	-12.60	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING #1051
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Sonic Jet
Mode: TX 2470MHz
Model: 22231
Manufacturer: YANGRI

Polarization: Vertical
Power Source: DC 9V
Date: 17/04/10/
Time: 20/27/56
Engineer Signature: Ding
Distance: 3m

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2470.000	80.44	7.07	87.51	114.00	-26.49	peak			
2	2470.000	70.57	7.07	77.64	94.00	-16.36	AVG			
3	4940.000	49.32	2.35	51.67	74.00	-22.33	peak			
4	4940.000	39.41	2.35	41.76	54.00	-12.24	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING #1052	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 9V
Test item: Radiation Test	Date: 17/04/10/
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 20/29/01
EUT: Sonic Jet	Engineer Signature: Ding
Mode: TX 2470MHz	Distance: 3m
Model: 22231	
Manufacturer: YANGRI	

Note: Report NO.:ATE20170426



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2470.000	76.22	7.07	83.29	114.00	-30.71	peak			
2	2470.000	66.02	7.07	73.09	94.00	-20.91	AVG			
3	4940.000	48.02	2.47	50.49	74.00	-23.51	peak			
4	4940.000	38.75	2.47	41.22	54.00	-12.78	AVG			

