



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.407

TEST REPORT

For

High-Flying Electronics Technology Co., Ltd.

Room 1002, Building 1, No.3000, Longdong Avenue, Pudong New Area, Shanghai, 201203 China

FCC ID: 2ACSVHF-LPD100

Report Type: Original Report	Product Type: WiFi Module
Test Engineer:	Stone Zhang <i>Stone Zhang</i>
Report Number:	RSHD191217004-00B
Report Date:	2020-02-24
Reviewed By:	Oscar Ye <i>Oscar Ye</i> EMC Manager
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)4

 OBJECTIVE4

 RELATED SUBMITTAL(S)/GRANT(S).....4

 TEST METHODOLOGY4

 MEASUREMENT UNCERTAINTY.....5

 TEST FACILITY5

SYSTEM TEST CONFIGURATION.....6

 DESCRIPTION OF TEST CONFIGURATION6

 EUT EXERCISE SOFTWARE7

 EQUIPMENT MODIFICATIONS11

 SUPPORT EQUIPMENT LIST AND DETAILS11

 EXTERNAL I/O CABLE.....11

 BLOCK DIAGRAM OF TEST SETUP12

SUMMARY OF TEST RESULTS14

TEST EQUIPMENT LIST15

FCC§1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....16

 APPLICABLE STANDARD16

 CALCULATED FORMULARY:.....16

 CALCULATED DATA:.....17

FCC §15.203 – ANTENNA REQUIREMENT18

 APPLICABLE STANDARD18

 ANTENNA CONNECTOR CONSTRUCTION18

FCC §15.407 (b) (6) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS19

 APPLICABLE STANDARD19

 EUT SETUP19

 EMI TEST RECEIVER SETUP.....19

 TEST PROCEDURE20

 FACTOR & OVER LIMIT CALCULATION.....20

 TEST RESULTS SUMMARY20

 TEST DATA20

§15.205 & §15.209 & §15.407(B)(1)(4) (6)(7) – UNDESIRABLE EMISSION & RESTRICTED BANDS25

 APPLICABLE STANDARD25

 EUT SETUP25

 EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP26

 TEST PROCEDURE26

 CORRECTED AMPLITUDE & MARGIN CALCULATION27

 TEST DATA27

FCC §15.407(a) & §15.407(e)–EMISSION BANDWIDTH.....51

 APPLICABLE STANDARD51

 TEST PROCEDURE51

 TEST DATA52

FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER69

 APPLICABLE STANDARD69

 TEST PROCEDURE69

 TEST DATA69

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY	71
APPLICABLE STANDARD	71
TEST PROCEDURE	71
TEST DATA	71

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	High-Flying Electronics Technology Co., Ltd.
Test Model	HF-LPD100
Product Type:	WiFi Module
Power Supply:	DC 2.1~3.46V
RF Function:	5G Wi-Fi
Operating Band/Frequency:	5G Wi-Fi B1: 5180-5240MHz, B4: 5745-5825MHz
Channel Number:	5G Wi-Fi B1: 6, B4: 7
Channel Separation:	5G Wi-Fi: a/n-HT20: 20 MHz, n-HT40: 40 MHz
Modulation Type:	5GWi-Fi: DSSS,OFDM
Antenna Type:	PCB Antenna
Maximum Antenna Gain:	0.0dBi

**All measurement and test data in this report was gathered from production sample serial number: 20191217004. (Assigned by the BACL). The EUT supplied by the applicant was received on 2019-12-17.*

Objective

This type approval report is prepared on behalf of *High-Flying Electronics Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions' rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: 2ACSVHF-LPD100

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan).

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

In **5150~5250 MHz** band, test channel list is as below,

802.11a/n20 mode Channel 36, 40, 48 were tested.

802.11n40 mode Channel 38, 46 were tested.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240

For **5725~5850 MHz** band,

802.11a /n20 mode Channel 149, 157, 165 were tested.

802.11n40 mode Channel 151, 159 were tested.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	159	5795
151	5755	161	5805
153	5765	165	5825
157	5785	/	/

EUT Exercise Software


RF test tool: Secure CRT

The worst case was performed under:


Mode	Data rate	Power level	
		5150-5250 Band	5725-5850 Band
802.11a	6 Mbps	1	1
802.11n-HT20	MCS0	1	1
802.11n-HT40	MCS0	1	1

Duty Cycle:
5150MHz-5250MHz Band:


802.11a mode



802.11n-HT20 mode




802.11n-HT40 mode




5725MHz-5850MHz Band:


802.11a mode



802.11n-HT20 mode



802.11n-HT40 mode



Mode	Frequency Range (MHz)	Duty Cycle (%)	T (ms)	1/T (kHz)	10log(1/x)
802.11a	5150-5250	100	/	/	0
802.11n-HT20		100	/	/	0
802.11n-HT40		100	/	/	0
802.11a	5725-5850	100	/	/	0
802.11n-HT20		100	/	/	0
802.11n-HT40		100	/	/	0

Note: “x” means duty cycle.

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263
High-Flying	Base plate	HF-LPD100 EVK	/

External I/O Cable


Cable Description	Length (m)	From Port	To
USB cable	1.0	Base plate	Notebook
Power cable	1.3	Notebook	Adapter
Power cable	1.0	Adapter	AC Source

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 & §15.407(b) (6)	AC Power Line Conducted Emissions	Compliant
§ 15.205 & §15.209 & §15.407(b) (1) (4)(6)(7)	Undesirable Emission & Restricted Bands	Compliant
§15.407(a)(1) (5) & §15.407 (e)	Emission Bandwidth	Compliant
§15.407(a) (1) (3)	Conducted Transmitter Output Power	Compliant
§15.407(a) (1) (3)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-11-30	2020-11-29
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2019-12-26	2022-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-08-27	2020-08-26
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
A.H.Systems, inc	Amplifier	2641-1	491	2019-02-20	2020-02-19
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2019-05-20	2020-05-19
SELECTOR	Amplifier	EM18G40G	060726	2019-03-22	2020-03-21
MICRO-TRONICS	Band Reject Filter	BRC50703	G094	2019-08-05	2020-08-04
MICRO-TRONICS	Band Reject Filter	BRC50705	G085	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-11-30	2020-11-29
Agilent	Power Meter	N1912A	MY5000492	2019-11-18	2020-11-17
Agilent	Power Sensor	N1921A	MY54210024	2019-11-18	2020-11-17
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
High-Flying	RF Cable	High-Flying C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03- 101746-zn	2019-07-11	2020-07-10
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Audix	Test Software	e3	V9	--	--
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2019-08-10	2020-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

S = PG/4πR² = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412~2462	0.0	1.00	21.00	125.89	20	0.0250	1.0
802.11g		0.0	1.00	22.00	158.49	20	0.0315	1.0
802.11n-HT20		0.0	1.00	21.00	125.89	20	0.0250	1.0
802.11n-HT40	2422~2452	0.0	1.00	21.50	141.25	20	0.0281	1.0
802.11a	5150~5250	0.0	1.00	15.00	31.62	20	0.0063	1.0
	5725~5850	0.0	1.00	15.00	31.62	20	0.0063	1.0
802.11n-HT20	5150~5250	0.0	1.00	15.50	35.48	20	0.0071	1.0
	5725~5850	0.0	1.00	15.50	35.48	20	0.0071	1.0
802.11n-HT40	5150~5250	0.0	1.00	16.00	39.81	20	0.0079	1.0
	5725~5850	0.0	1.00	15.50	35.48	20	0.0071	1.0

Note:

- (1) The tune-up output power was declared by the manufacturer.
- (2) 2.4GWi-Fi and 5G Wi-Fi cannot transmit simultaneously.

Conclusion: The EUT meets exemption requirement - RF exposure evaluation greater than 20cm distance specified in § 2.1091. If the device built into a host as a portable usage, the additional RF exposure evaluation may be required as specified by § 2.1093.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407, if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connector Construction

The EUT has a PCB antenna for 5G Wi-Fi and antenna gain is 0.0dBi which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.407 (b) (6) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a), §15.407(b) (6)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 30 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of 7dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	24.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa

The testing was performed by Stone Zhang on 2020-01-17.

EUT operation mode: Transmitting in 802.11n-HT40 mode high channel of 5150~5250MHz (worst case).


AC 120V/60 Hz, Line



	Read	Limit	Over				
Freq	Level	Factor	Level	Line			
MHz	dBuV	dB	dBuV	dBuV			
1	0.150	22.30	19.82	42.12	56.00	-13.88	Average
2	0.150	40.00	19.82	59.82	66.00	-6.18	QP
3	0.174	16.40	19.83	36.23	54.77	-18.54	Average
4	0.174	36.80	19.83	56.63	64.77	-8.14	QP
5	0.224	13.70	19.82	33.52	52.66	-19.14	Average
6	0.224	28.00	19.82	47.82	62.66	-14.84	QP
7	0.486	23.80	19.76	43.56	46.23	-2.67	Average
8	0.486	25.70	19.76	45.46	56.23	-10.77	QP
9	0.720	18.40	19.74	38.14	46.00	-7.86	Average
10	0.720	22.00	19.74	41.74	56.00	-14.26	QP
11	2.012	15.30	19.82	35.12	46.00	-10.88	Average
12	2.012	20.10	19.82	39.92	56.00	-16.08	QP

AC 120V/60 Hz, Neutral

Date: 2020-01-17



		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	22.10	19.82	41.92	56.00	-14.08	Average
2	0.150	40.50	19.82	60.32	66.00	-5.68	QP
3	0.162	23.20	19.83	43.03	55.34	-12.31	Average
4	0.162	41.10	19.83	60.93	65.34	-4.41	QP
5	0.232	15.00	19.82	34.82	52.39	-17.57	Average
6	0.232	29.10	19.82	48.92	62.39	-13.47	QP
7	0.486	23.70	19.76	43.46	46.23	-2.77	Average
8	0.486	26.20	19.76	45.96	56.23	-10.27	QP
9	0.716	17.60	19.74	37.34	46.00	-8.66	Average
10	0.716	23.00	19.74	42.74	56.00	-13.26	QP
11	1.698	20.30	19.84	40.14	46.00	-5.86	Average
12	1.698	23.40	19.84	43.24	56.00	-12.76	QP


Note:

1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

EUT operation mode: Transmitting in 802.11n-HT20 mode high channel of 5725~5850MHz (worst case).


AC 120V/60 Hz, Line



		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.156	23.30	19.82	43.12	55.65	-12.53	Average
2	0.156	41.40	19.82	61.22	65.65	-4.43	QP
3	0.185	14.01	19.82	33.83	54.24	-20.41	Average
4	0.185	34.11	19.82	53.93	64.24	-10.31	QP
5	0.489	23.80	19.76	43.56	46.19	-2.63	Average
6	0.489	26.30	19.76	46.06	56.19	-10.13	QP
7	0.720	18.80	19.74	38.54	46.00	-7.46	Average
8	0.720	23.50	19.74	43.24	56.00	-12.76	QP
9	1.310	17.40	19.82	37.22	46.00	-8.78	Average
10	1.310	22.10	19.82	41.92	56.00	-14.08	QP
11	2.487	16.40	19.48	35.88	46.00	-10.12	Average
12	2.487	21.60	19.48	41.08	56.00	-14.92	QP

AC 120V/60 Hz, Neutral

Date: 2020-01-17



	Read Freq	Read Level	Factor	Limit Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.151	23.50	19.82	43.32	55.96	-12.64	Average
2	0.151	41.70	19.82	61.52	65.96	-4.44	QP
3	0.181	13.70	19.83	33.53	54.46	-20.93	Average
4	0.181	35.70	19.83	55.53	64.46	-8.93	QP
5	0.226	16.30	19.82	36.12	52.61	-16.49	Average
6	0.226	29.40	19.82	49.22	62.61	-13.39	QP
7	0.494	23.60	19.76	43.36	46.10	-2.74	Average
8	0.494	27.40	19.76	47.16	56.10	-8.94	QP
9	0.716	18.60	19.74	38.34	46.00	-7.66	Average
10	0.716	25.90	19.74	45.64	56.00	-10.36	QP
11	1.456	15.90	19.84	35.74	46.00	-10.26	Average
12	1.456	20.80	19.84	40.64	56.00	-15.36	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

§15.205 & §15.209 & §15.407(B)(1)(4) (6)(7) – UNDESIRABLE EMISSION & RESTRICTED BANDS

Applicable Standard

FCC §15.407 (b)(1)(4) (6) (7); §15.209; §15.205;

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27dBm/MHz

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of –27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000MHz shall be performed using a minimum resolution bandwidth of 1MHz.


According to 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP [dBm] + 95.2$, for $d = 3$ meters.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions

Temperature:	20.2-22.3 °C
Relative Humidity:	49-51 %
ATM Pressure:	101.3-101.6 kPa


The testing was performed by Stone Zhang from 2019-12-31 to 2020-01-19.

Test Mode: Transmitting

Spurious Emission Test

30MHz-1GHz(5150-5250MHz Band):


Pre-scan with 802.11a, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11 n-HT40 mode in X-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
33.572250	21.51	200.0	H	268.0	-6.4	40.00	18.49
75.942550	17.84	100.0	V	125.0	-17.6	40.00	22.16
87.342050	17.27	100.0	V	120.0	-17.6	40.00	22.73
117.272050	11.00	100.0	V	197.0	-11.7	43.50	32.50
159.511350	22.20	200.0	H	59.0	-12.7	43.50	21.30
202.601700	14.66	100.0	V	268.0	-12.3	43.50	28.84

30MHz-1GHz(5725-5850MHz Band):

Pre-scan with 802.11a , 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11n-HT20 mode in channel 5825 in X-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
33.304050	22.21	100.0	V	319.0	-6.2	40.00	17.79
71.864650	15.86	100.0	V	95.0	-17.4	40.00	24.14
78.014950	19.55	100.0	V	177.0	-17.7	40.00	20.45
87.936350	19.30	100.0	V	80.0	-17.5	40.00	20.70
123.295600	10.83	200.0	H	144.0	-11.3	43.50	32.67
160.818700	21.75	200.0	H	61.0	-12.8	43.50	21.75

1GHz-18GHz(5150-5250MHz Band):

802.11a Mode:


(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1593.30	40.86	---	200	V	247	-9.6	74.00	33.14
1593.30	---	32.86	200	V	247	-9.6	54.00	21.14
2130.50	41.48	---	150	V	252	-7.9	68.20	26.72
4116.10	42.76	---	150	V	130	-1.7	74.00	31.24
4116.10	---	33.77	150	V	130	-1.7	54.00	20.23
7621.50	---	41.2	200	V	29	6.4	54.00	12.80
7621.50	50.08	---	200	V	29	6.4	74.00	23.92
10361.90	56.32	---	150	V	351	8.8	68.20	11.88
17830.00	---	47.91	200	V	321	13.8	54.00	6.09
17830.00	56.12	---	200	V	321	13.8	74.00	17.88

Middle Channel: 5200MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1555.90	---	29.24	150	V	240	-9.7	54.00	24.76
1555.90	41.76	---	150	V	240	-9.7	74.00	32.24
2127.10	40.57	---	150	V	258	-7.9	68.20	27.63
4347.30	43.75	---	150	V	73	-1.2	74.00	30.25
4347.30	---	33.53	150	V	73	-1.2	54.00	20.47
6933.00	49.36	---	200	H	328	5.2	68.20	18.84
10401.00	54.37	---	200	V	357	8.8	68.20	13.83
17588.60	56.83	---	150	V	311	14.1	68.20	11.37

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1503.20	---	29.93	200	V	243	-9.9	54.00	24.07
1503.20	42.16	---	200	V	243	-9.9	74.00	31.84
2123.70	38.99	---	150	V	78	-7.9	68.20	29.21
4520.70	43.49	---	150	V	287	-1	74.00	30.51
4520.70	---	33.16	150	V	287	-1	54.00	20.84
6820.80	48.63	---	150	V	169	5.0	68.20	19.57
10477.50	56.15	---	150	V	358	8.9	68.20	12.05
17678.70	56.90	---	150	V	44	14.0	68.20	11.30

802.11n-HT20 Mode:


Pre-scan with X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1438.60	---	28.39	200	H	170	-10.3	54.00	25.61
1438.60	42.24	---	200	H	170	-10.3	74.00	31.76
2127.10	40.87	---	150	V	71	-7.9	68.20	27.33
3500.70	41.87	---	200	V	179	-3.5	68.20	26.33
7964.90	50.9	---	200	V	99	7.0	68.20	17.30
10355.10	55.05	---	150	V	342	8.8	68.20	13.15
17588.60	56.69	---	150	V	255	14.1	68.20	11.51

Middle Channel: 5200MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1491.30	---	30.56	200	V	259	-10.0	54.00	23.44
1491.30	41.25	---	200	V	259	-10.0	74.00	32.75
2123.70	40.07	---	200	V	254	-7.9	68.20	28.13
2657.50	42.46	---	150	H	316	-6.1	68.20	25.74
6735.80	49.4	---	150	V	78	4.8	68.20	18.80
10397.60	54.04	---	200	V	296	8.8	68.20	14.16
17595.40	57.74	---	200	H	305	14.1	68.20	10.46

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1511.70	---	29.29	150	V	223	-9.9	54.00	24.71
1511.70	44.31	---	150	V	223	-9.9	74.00	29.69
2127.10	40	---	150	V	252	-7.9	68.20	28.20
2655.80	47.15	---	200	V	259	-6.1	68.20	21.05
8065.20	---	41.39	150	V	344	7.0	54.00	12.61
8065.20	50.04	---	150	V	344	7.0	74.00	23.96
10477.50	54.25	---	200	V	338	8.9	68.20	13.95
17586.90	56.9	---	200	H	232	14.1	68.20	11.30

802.11n-HT40 Mode:


Pre-scan with X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5190MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1530.40	---	33.79	150	V	215	-9.8	54.00	20.21
1530.40	49.43	---	150	V	215	-9.8	74.00	24.57
2130.50	38.63	---	150	V	82	-7.9	68.20	29.57
2660.90	40.62	---	200	V	172	-6.1	68.20	27.58
6797.00	48.85	---	200	H	3	5.0	68.20	19.35
12962.90	55.48	---	200	V	16	11.9	68.20	12.72
17583.50	56.97	---	150	V	158	14.1	68.20	11.23

High Channel: 5230MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.20	41.00	---	200	V	276	-12.3	74.00	33.00
1061.20	---	28.47	200	V	276	-12.3	54.00	25.53
1511.70	44.21	---	200	V	224	-9.9	74.00	29.79
1511.70	---	32.45	200	V	224	-9.9	54.00	21.55
2123.70	39.84	---	150	V	273	-7.9	68.20	28.36
9828.10	54.73	---	150	H	296	8.0	68.20	13.47
10458.80	53.30	---	150	V	192	8.9	68.20	14.90
17847.00	---	46.53	150	V	158	13.7	54.00	7.47
17847.00	56.64	---	200	V	99	13.7	74.00	17.36

1GHz-18GHz(5725-5850MHz Band):

802.11a Mode:


(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5745MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1340.00	---	26.52	150	V	244	-10.8	54.00	27.48
1340.00	37.12	---	150	V	244	-10.8	74.00	36.88
1591.60	---	28.37	150	V	244	-9.6	54.00	25.63
1591.60	38.68	---	150	V	244	-9.6	74.00	35.32
2130.50	38.88	---	150	V	273	-7.9	68.20	29.32
7660.60	---	39.6	150	H	326	6.4	54.00	14.40
7660.60	49.36	---	150	H	326	6.4	74.00	24.64
13362.40	---	44.81	150	V	96	12.0	54.00	9.19
13362.40	54.47	---	150	V	96	12.0	74.00	19.53
17649.80	56.24	---	150	V	222	14.0	68.20	11.96

Middle Channel: 5785MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1596.70	37.64	---	150	V	253	-9.6	74.00	36.36
1596.70	---	30.37	150	V	253	-9.6	54.00	23.63
2128.80	38.49	---	150	V	106	-7.9	68.20	29.71
3890.00	42.19	---	150	H	131	-2.2	74.00	31.81
3890.00	---	32.11	150	H	131	-2.2	54.00	21.89
7713.30	50.22	---	150	H	0	6.5	74.00	23.78
7713.30	---	42.46	150	H	0	6.5	54.00	11.54
13872.40	54.04	---	150	V	106	12.4	68.20	14.16
17490.00	56.24	---	150	V	36	14.2	68.20	11.96

High Channel: 5825MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1596.70	---	31.70	150	V	273	-9.6	54.00	22.30
1596.70	38.66	---	150	V	273	-9.6	74.00	35.34
2123.70	38.6	---	150	V	273	-7.9	68.20	29.60
6300.60	46.68	---	150	H	117	3.6	68.20	21.52
10780.10	---	41.47	150	H	160	9.4	54.00	12.53
10780.10	51.69	---	150	H	160	9.4	74.00	22.31
14236.20	55.13	---	150	H	244	12.6	68.20	13.07
17544.40	55.92	---	150	H	138	14.2	68.20	12.28

802.11n-HT20 Mode:


Pre-scan with X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5745MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1595.00	---	28.55	150	V	254	-9.6	54.00	25.45
1595.00	38.06	---	150	V	254	-9.6	74.00	35.94
2130.50	38.31	---	150	V	81	-7.9	68.20	29.89
3538.10	41.68	---	150	H	213	-3.4	68.20	26.52
7723.50	---	40.98	150	V	22	6.5	54.00	13.02
7723.50	49.73	---	150	V	22	6.5	74.00	24.27
12673.90	---	43.84	150	V	81	10.9	54.00	10.16
12673.90	53.52	---	150	V	81	10.9	74.00	20.48
17772.20	---	47.58	150	V	313	13.8	54.00	6.42
17772.20	55.81	---	150	V	313	13.8	74.00	18.19

Middle Channel: 5785MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1341.70	---	26.02	150	V	209	-10.8	54.00	27.98
1341.70	36.16	---	150	V	209	-10.8	74.00	37.84
1595.00	---	26.54	150	H	264	-9.6	54.00	27.46
1595.00	37.01	---	150	H	264	-9.6	74.00	36.99
2130.50	37.73	---	150	V	273	-7.9	68.20	30.47
4964.40	---	33.21	150	V	351	-0.3	54.00	20.79
4964.40	44.82	---	150	V	351	-0.3	74.00	29.18
9998.10	51.02	---	150	V	19	8.2	68.20	17.18
17595.40	55.77	---	150	V	8	14.1	68.20	12.43

High Channel: 5825MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1504.90	---	29.82	150	V	229	-9.9	54.00	24.18
1504.90	43.67	---	150	V	229	-9.9	74.00	30.33
2660.90	47.3	---	150	H	318	-6.1	68.20	20.90
6608.30	48.09	---	150	H	0	4.6	68.20	20.11
10565.90	51.1	---	150	V	229	9.1	68.20	17.10
13374.30	---	43.65	150	V	144	12.0	54.00	10.35
13374.30	54.02	---	150	H	49	12.0	74.00	19.98
17729.70	---	47.02	150	H	318	13.9	54.00	6.98
17729.70	56.38	---	150	H	318	13.9	74.00	17.62

802.11n-HT40 Mode:


Pre-scan with X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5755MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1435.20	41.12	---	200	V	248	-10.3	74.00	32.88
1435.20	---	28.82	200	V	248	-10.3	54.00	25.18
1593.30	---	33.15	200	V	231	-9.6	54.00	20.85
1593.30	40.28	---	200	V	231	-9.6	74.00	33.72
2127.10	39.63	---	150	V	270	-7.9	68.20	28.57
7698.00	---	40.16	200	V	305	6.5	54.00	13.84
7698.00	50.73	---	150	V	124	6.5	74.00	23.27
10559.10	51.09	---	200	V	168	9.1	68.20	17.11
17770.50	---	49.34	150	V	101	13.8	54.00	4.66
17770.50	57.15	---	150	V	101	13.8	74.00	16.85

High Channel: 5795MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1593.30	---	33.93	150	V	231	-9.6	54.00	20.07
1593.30	41.13	---	150	V	231	-9.6	74.00	32.87
2123.70	42.01	---	150	V	253	-7.9	68.20	26.19
3888.30	---	32.13	150	V	148	-2.2	54.00	21.87
3888.30	41.63	---	150	V	148	-2.2	74.00	32.37
11591.00	---	42.70	150	H	213	9.8	54.00	11.30
11591.00	50.56	---	150	H	213	9.8	74.00	23.44
17396.50	56.49	---	150	V	0	13.7	68.20	11.71

18GHz-40GHz(5150-5250MHz Band):


Pre-scan with 802.11a, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11 n-HT40 mode high channel in X-axis of orientation was recorded

Horizontal



Date: 15.JAN.2020 12:42:07

Vertical




Date: 15.JAN.2020 12:57:28

18GHz-40GHz(5725-5850MHz Band):


Pre-scan with 802.11a, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11 n-HT20 mode high channel in X-axis of orientation was recorded

Horizontal



Date: 15.JAN.2020 13:45:38

Vertical



Date: 15.JAN.2020 13:59:56

Restricted Bands Emissions Test (5150-5250MHz Band):

Note:

1. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
2. Corrected Amplitude = Corrected Factor + Reading
3. Margin = Limit - Corrected. Amplitude

802.11a Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in X-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5150.00	---	48.94	150	H	351	10.20	54.00	5.06
5150.00	58.70	---	150	H	351	10.20	74.00	15.30
High Channel: 5240MHz								
5350.00	53.16	---	100	V	308	10.60	74.00	20.84
5350.00	---	44.29	100	V	308	10.60	54.00	9.71

802.11n-HT20 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in X-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5150.00	---	50.67	150	H	0	10.20	54.00	3.33
5150.00	57.23	---	150	H	0	10.20	74.00	16.77
High Channel: 5240MHz								
5350.00	54.16	---	100	V	315	10.60	74.00	19.84
5350.00	---	46.29	100	V	315	10.60	54.00	7.71

802.11n-HT40 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in X-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5190MHz								
5150.00	---	53.97	200	H	166	10.20	54.00	0.03
5150.00	59.72	---	200	H	166	10.20	74.00	14.28
High Channel: 5230MHz								
5350.00	53.87	---	100	V	308	10.60	74.00	20.13
5350.00	---	46.38	100	V	308	10.60	54.00	7.62

Restricted Bands Emissions Test (5725-5850MHz Band):

Note:

1. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
2. Corrected Amplitude = Corrected Factor + Reading
3. Margin = Limit - Corrected. Amplitude

802.11a Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in X-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5650.00	57.37	---	150	H	344	11.50	68.20	10.83
5700.00	57.37	---	150	H	0	11.70	105.20	47.83
5720.00	59.76	---	150	H	0	11.70	110.80	51.04
5725.00	63.71	---	150	H	192	11.80	122.20	58.49
High Channel: 5825MHz								
5850.00	60.75	---	150	H	358	12.80	122.20	61.45
5855.00	57.53	---	150	H	167	12.80	110.80	53.27
5875.00	58.42	---	150	H	0	12.80	105.20	46.78
5925.00	57.38	---	150	H	305	12.80	68.20	10.82

802.11n-HT20 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in X-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5650.00	57.32	---	150	H	174	11.50	68.20	10.88
5700.00	58.22	---	150	H	72	11.70	105.20	46.98
5720.00	61.56	---	150	H	160	11.70	110.80	49.24
5725.00	64.66	---	150	H	358	11.80	122.20	57.54
High Channel: 5825MHz								
5850.00	61.18	---	150	H	349	12.80	122.20	61.02
5855.00	60.92	---	150	H	0	12.80	110.80	49.88
5875.00	57.47	---	150	H	181	12.80	105.20	47.73
5925.00	58.05	---	150	H	0	12.80	68.20	10.15

802.11n-HT40 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in X-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5190MHz								
5650.00	56.98	---	150	H	358	11.50	68.20	11.22
5700.00	58.37	---	150	H	194	11.70	105.20	46.83
5720.00	67.93	---	150	H	353	11.70	110.80	42.87
5725.00	64.87	---	150	H	180	11.80	122.20	57.33
High Channel: 5230MHz								
5850.00	57.67	---	150	H	24	12.80	122.20	64.53
5855.00	58.09	---	150	H	358	12.80	110.80	52.71
5875.00	56.64	---	150	H	0	12.80	105.20	48.56
5925.00	58.31	---	150	H	266	12.80	68.20	9.89

FCC §15.407(a) & §15.407(e)–EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	23.5~25.1 °C
Relative Humidity:	49~50 %
ATM Pressure:	101.2~101.3 kPa

The testing was performed by Stone Zhang from 2020-01-20 to 2020-02-21.

Test Result: Compliant

5150-5250 MHz:

Test mode	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
802.11a	5180	29.058	17.555
	5200	29.900	17.315
	5240	29.960	17.315
802.11n-HT20	5180	24.048	18.196
	5200	25.391	18.196
	5240	25.852	18.196
802.11n-HT40	5190	73.547	37.034
	5230	73.677	36.713


5750-5850 MHz:

Test mode	Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
802.11a	5745	16.513	17.395	≥0.5
	5785	16.513	17.395	≥0.5
	5825	16.513	17.555	≥0.5
802.11n-HT20	5745	17.796	18.116	≥0.5
	5785	17.796	18.196	≥0.5
	5825	17.796	18.517	≥0.5
802.11n-HT40	5755	36.393	36.713	≥0.5
	5795	36.513	37.034	≥0.5


Note: No transmitted signal in the 99% bandwidth extends into the U-NII-2A and U-NII-2C band.

26 Bandwidth
5150-5250 MHz Band:


802.11a mode, 5180MHz




802.11a mode, 5200MHz




802.11a mode, 5240MHz




802.11n-HT20 mode, 5180MHz




802.11n-HT20 mode, 5200MHz




802.11n-HT20 mode, 5240MHz



802.11n-HT40 mode, 5190MHz




802.11n-HT40 mode, 5230MHz




6 Bandwidth
5725-5850 MHz Band:


802.11a mode, 5745MHz




802.11a mode, 5785MHz




802.11a mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz



802.11n-HT40 mode, 5755MHz




802.11n-HT40 mode, 5795MHz




**99% Occupied Bandwidth
5150-5250 MHz Band:**


802.11a mode, 5180MHz




802.11a mode, 5200MHz




802.11a mode, 5240MHz




802.11n-HT20 mode, 5180MHz




802.11n-HT20 mode, 5200MHz




802.11n-HT20 mode, 5240MHz



802.11n-HT40 mode, 5190MHz




802.11n-HT40 mode, 5230MHz




5725-5850 MHz Band:


802.11a mode, 5745MHz




802.11a mode, 5785MHz




802.11a mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz



802.11n-HT40 mode, 5755MHz



802.11n-HT40 mode, 5795MHz



FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

According to §15.407(a)(1)


(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to §15.407(a) (3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24.2~25.3 °C
Relative Humidity:	49~50 %
ATM Pressure:	101.3~101.5 kPa

The testing was performed by Stone Zhang from 2020-01-14 to 2020-01-15.

Test Mode: Transmitting

Test Mode: Transmitting

Test mode	Band	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)	Limit	Result
802.11a	5150-5250 MHz	Low	5180	14.26	24	PASS
		Middle	5200	13.54	24	PASS
		High	5240	14.37	24	PASS
	5725-5850 MHz	Low	5745	13.94	30	PASS
		Middle	5785	14.82	30	PASS
		High	5825	13.67	30	PASS
802.11n-HT20	5150-5250 MHz	Low	5180	15.00	24	PASS
		Middle	5200	15.31	24	PASS
		High	5240	15.24	24	PASS
	5725-5850 MHz	Low	5745	15.00	30	PASS
		Middle	5785	15.13	30	PASS
		High	5825	15.24	30	PASS
802.11n-HT40	5150-5250 MHz	Low	5190	15.72	24	PASS
		High	5230	15.84	24	PASS
	5725-5850 MHz	Low	5755	15.05	30	PASS
		High	5795	15.00	30	PASS

Note: The maximum antenna gain is 0.0dBi.

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY

Applicable Standard

According to §15.407(a)(1)

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to §15.407(a) (3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

The measurements are base on FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices section F: Maximum power spectral density (PPSD)

Test Data

Environmental Conditions

Temperature:	22.5 °C
Relative Humidity:	52 %
ATM Pressure:	101.3 kPa

The testing was performed by Stone Zhang on 2020-01-15.

Test Mode: Transmitting

5150MHz-5250MHz:

Mode	Channel	Frequency (MHz)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
802.11a	Low	5180	4.70	11	PASS
	Middle	5200	4.65	11	PASS
	High	5240	4.58	11	PASS
802.11n-HT20	Low	5180	4.13	11	PASS
	Middle	5200	4.24	11	PASS
	High	5240	4.62	11	PASS
802.11n-HT40	Low	5190	1.64	11	PASS
	High	5230	1.61	11	PASS


5725MHz-5850MHz:

Mode	Channel	Frequency (MHz)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
802.11a	Low	5745	2.30	30	PASS
	Middle	5785	2.19	30	PASS
	High	5825	2.04	30	PASS
802.11n-HT20	Low	5745	2.22	30	PASS
	Middle	5785	2.51	30	PASS
	High	5825	2.61	30	PASS
802.11n-HT40	Low	5755	-0.54	30	PASS
	High	5795	0.22	30	PASS


Note:
The maximum antenna gain is 0.0dBi.

5150MHz-5250MHz:


802.11a mode, Power spectral density-5180MHz




802.11a mode, Power spectral density-5200MHz




802.11a mode, Power spectral density-5240MHz




802.11n-HT20 mode, Power spectral density-5180MHz




802.11n-HT20 mode, Power spectral density-5200MHz




802.11n-HT20 mode, Power spectral density-5240MHz



802.11n-HT40 mode, Power spectral density-5190MHz




802.11n-HT40 mode, Power spectral density-5230MHz




5725MHz-5850MHz:


802.11a mode, Power spectral density-5745MHz




802.11a mode, Power spectral density-5785MHz




802.11a mode, Power spectral density-5825MHz




802.11n-HT20 mode, Power spectral density-5745MHz




802.11n-HT20 mode, Power spectral density-5785MHz




802.11n-HT20 mode, Power spectral density-5825MHz



802.11n-HT40 mode, Power spectral density-5755MHz



802.11n-HT40 mode, Power spectral density-5795MHz



***** END OF REPORT *****