

RF Exposure Report

Report No.: MFBDas-WTW-P20090564A R1

FCC ID: 2ACTO-7922DMC

Test Model: XGS 116w (with MC7411)

Received Date: Mar. 12, 2022

Date of Evaluation: Jul. 28, 2022

Issued Date: Sep. 29, 2022

Applicant: Sophos Ltd.

Address: The Pentagon, Abingdon Science Park, Abingdon, OX14 3YP United Kingdom

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration /

Designation Number: 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power.....	6

Release Control Record

Issue No.	Description	Date Issued
MFBDAS-WTW-P20090564A	Original release	Aug. 12, 2022
MFBDAS-WTW-P20090564A R1	Added simultaneous operation mode	Sep. 29, 2022

1 Certificate of Conformity

Product: Network appliance

Brand: SOPHOS

Test Model: XGS 116w (with MC7411)

Sample Status: Production Unit

Applicant: Sophos Ltd.

Date of Evaluation: Jul. 28, 2022

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** Sep, 29, 2022
Pettie Chen / Senior Specialist

Approved by : Jeremy Lin , **Date:** Sep, 29, 2022
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

WWAN-Optional (WWAN module: Brand: Sierra / Model: MC7411 / FCC ID: N7NMC74B)

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA/LTE Band 2	1850~1910	24	1.56	20	0.072	1.000
WCDMA/LTE Band 4	1710~1755	24	1.62	20	0.073	1.000
WCDMA/LTE Band 5	824~849	24.3	3.2	20	0.112	0.549
LTE Band 7	2500~2570	23.8	0.86	20	0.058	1.000
LTE Band 12	699~716	24	1.49	20	0.070	0.466
LTE Band 13	777~787	24	1.66	20	0.073	0.518
LTE Band 14	788~798	24	2.98	20	0.099	0.525
LTE Band 25	1850~1915	24	1.92	20	0.078	1.000
LTE Band 26	814~849	24	3.2	20	0.104	0.543
LTE Band 41	2496~2690	23.8	0.86	20	0.058	1.000
LTE Band 42	3400~3600	23.8	0.45	20	0.053	1.000
LTE Band 43	3600~3800	23.8	0.45	20	0.053	1.000
LTE Band 48	3550~3700	23.8	0.45	20	0.053	1.000
LTE Band 66	1710~1780	24	1.6	20	0.072	1.000
LTE Band 71	663~698	24	1.37	20	0.069	0.442

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

WLAN-1 for on Mainboard, 1 for Optional (WLAN Module: Brand: Sophos / Module: 7922DMC / FCC ID: 2ACTO-7922DMC)

Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	1TX	21.26	3.90	20	0.065	1
	2TX	22.63	6.91	20	0.179	1
5180-5240	1TX	21.55	3.70	20	0.067	1
	2TX	24.17	6.71	20	0.244	1
5745-5825	1TX	22.32	4.40	20	0.093	1
	2TX	23.53	7.41	20	0.247	1

Note:

2412-2462MHz Directional gain = 3.9dBi + 10log(2) = 6.91dBi

5180-5240MHz Directional gain = 3.7dBi + 10log(2) = 6.71dBi

5745-5825MHz Directional gain = 4.4dBi + 10log(2) = 7.41dBi

* 2.4GHz & 5GHz technology cannot transmit at same time.

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4G + WWAN = 0.179 / 1 + 0.112/0.549 = 0.383

WLAN 5G + WWAN = 0.247 / 1 + 0.112/0.549 = 0.451

WLAN 2.4G + WLAN 2.4G = 0.179 / 1 + 0.179 / 1 = 0.358

WLAN 5G + WLAN 5G = 0.247 / 1 + 0.247 / 1 = 0.494

*For WLAN power density data, please refer to report no.: SA170731C02.

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---