

17

97

This device complies with part 15 of the FCC Rules.
 Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference, and
 (2) this device must accept any interference received, including interference that may cause undesired operation.

Material

(124) Gloss Clear Polyester PM 200

Face material Topcoated thermal transfer printable clear polyester film.

Face substance 50 microns

Adhesive Special permanent pressure sensitive acrylic adhesive. Minimum application temperature 10°C

Liner White glassine release liner

Liner substance 56 microns

Service temperature -40°C to +150°C


Chemical resistance Resistant to water, mild acids, salt and alkalis, petroleum based greases, oils and aliphatic solvents

Shelf life 2 years when stored at 21°C | 50% RH

Approvals UL (MH16635)

Notes

1. Arial Font - 2.5mm

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS		FINISH:		PART NUMBER ART0059		REVISION 1.0	
TOLERANCES: LINEAR: ±0.1 ANGULAR: ±0.25° HOLE POSN: ±0.05mm				CCS 		CCS Ltd, Victory House, Vision Park Chivers Way, Histon, Cambridge, CB24 9ZR, UK	
DRAWN MHL		SIGNATURE		DATE		TITLE:	
CHK'D				06/03/2018		FCC Statement Label	
MATERIAL:				DWG NO.		A4	
				ART0059 Iss 1.0			
				SCALE:1:1		SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 CCS Ltd. ANY REPRODUCTION IN
 PART OR AS A WHOLE WITHOUT THE
 WRITTEN PERMISSION OF CCS Ltd IS
 PROHIBITED.