

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	KREAFUNK APS
<b>Address</b>	:	Klamsagervej 35 A, st.8230 Åbyhøj, Denmark
<b>Equipment under Test</b>	:	Wireless Speaker
<b>Model No.</b>	:	aGO MINI
<b>Trade Mark</b>	:	KREAFUNK
<b>FCC ID</b>	:	2ACVC-AGOMINI
<b>Manufacturer</b>	:	CASUN TECHNOLOGIES CO., LTD
<b>Address</b>	:	4th Floor, Building C, Third Industrial Zone, Hourui Street, Xixiang, Bao'an District, Shenzhen

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add.:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,  
Dongguan City, Guangdong Province, China, 523808

**Tel.:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

### Table of Contents

Test report declares.....	3
1. General Information .....	5
1.1. Description of equipment .....	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC.....	5

## Test Report Declare

<b>Applicant</b>	:	KREAFUNK APS
<b>Address</b>	:	Klamsagervej 35 A, st.8230 Åbyhøj, Denmark
<b>Equipment under Test</b>	:	Wireless Speaker
<b>Model No.</b>	:	aGO MINI
<b>Trade mark</b>	:	KREAFUNK
<b>Manufacturer</b>	:	CASUN TECHNOLOGIES CO., LTD
<b>Address</b>	:	4th Floor, Building C, Third Industrial Zone, Hourui Street, Xixiang, Bao'an District, Shenzhen

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R22031115-2E11		
<b>Date of Receipt:</b>	Apr. 21, 2022	<b>Date of Test:</b>	Apr. 21, 2022 ~ May 30, 2022

**Prepared By:**

*Sam Li*

**Sam Li/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

## Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	May 31, 2022	

## 1. General Information

### 1.1. Description of equipment

EUT* Name	: Wireless Speaker
Model Number	: aGO MINI
EUT function description	: Please reference user manual of this device
Power Supply	: DC 5V by external AC Adapter or DC 3.7V built-in battery
Radio Specification	: Bluetooth V5.0
Operation Frequency	: 2402 MHz - 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Gain	: 0 dBi
Sample Type	: Series production
Sample Number	: N/A

Note: EUT is the abbreviation of equipment under test.

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

**BT Manufacturing Tolerance**

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-2	-1	0
Tolerance ±(dB)	1	1	1
π/4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-2	-1	0
Tolerance ±(dB)	1	1	1
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1	0	0
Tolerance ±(dB)	1	1	1

**BLE Manufacturing Tolerance**

GFSK_1M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-2	-1	-1
Tolerance ±(dB)	1	1	1
GFSK_2M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-2	-1	0
Tolerance ±(dB)	1	1	1

**Estimation Result**

Worse case is as below: [2480 MHz, 1 dBm, 1.26 mW) output power]

$(1.26/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.40 < 3.0$  for 1-g SAR

Then SAR evaluation is not required

**END OF REPORT**