

RF EXPOSURE REPORT

FOR

| | | |
|-----------------------------|---|--|
| Applicant | : | KREAFUNK APS |
| Address | : | Klamsagervej 35 A, st.8230 Åbyhøj, Denmark |
| Equipment under Test | : | Wireless Headphone with Active Noise Cancellation |
| Model No. | : | aHEAD II |
| Trade Mark | : | KREAFUNK |
| FCC ID | : | 2ACVC-AHEADII |
| Manufacturer | : | Shen Zhen Lighkeep Co., Ltd. |
| Address | : | 3&4 Floor, No.19 Plant, Baotong South Road, Xikeng Community, Yuanshan Street, Longgang District, Shenzhen |

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

| | |
|--|---|
| Test report declares..... | 3 |
| 1. General Information | 5 |
| 1.1. Description of equipment | 5 |
| 1.2. Assess laboratory..... | 5 |
| 2. RF Exposure evaluation for FCC..... | 5 |

Test Report Declare

| | | |
|-----------------------------|---|--|
| Applicant | : | KREAFUNK APS |
| Address | : | Klamsagervej 35 A, st.8230 Åbyhøj, Denmark |
| Equipment under Test | : | Wireless Headphone with Active Noise Cancellation |
| Model No. | : | aHEAD II |
| Trade mark | : | KREAFUNK |
| Manufacturer | : | Shen Zhen Lighkeep Co., Ltd. |
| Address | : | 3&4 Floor, No.19 Plant, Baotong South Road, Xikeng Community, Yuanshan Street, Longgang District, Shenzhen |

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

| | | | |
|-------------------------|---------------------|----------------------|-------------------------------|
| Report No: | DDT-R21120820-22E09 | | |
| Date of Receipt: | Dec. 29, 2021 | Date of Test: | Dec. 29, 2021 ~ Feb. 10, 2022 |

Prepared By:

Sam Li
Sam Li/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

| Rev. | Revisions | Issue Date | Revised By |
|------|---------------|---------------|------------|
| --- | Initial issue | Feb. 10, 2022 | |
| | | | |

1. General Information

1.1. Description of equipment

| | |
|--------------------------|--|
| EUT* Name | : Wireless Headphone with Active Noise Cancellation |
| Model Number | : aHEAD II |
| EUT function description | : Please reference user manual of this device |
| Power Supply | : DC 5V by an external adapter or a built-in 3.7V lithium battery. |
| Radio Specification | : Bluetooth V5.0 |
| Operation Frequency | : 2402 MHz - 2480 MHz |
| Modulation | : GFSK, $\pi/4$ -DQPSK, 8DPSK |
| Data Rate | : 1 Mbps, 2 Mbps, 3 Mbps |
| Antenna Gain | : 1.24 dBi |
| Sample Type | : Series production |
| Serial Number | : N/A |

Note: EUT is the abbreviation of equipment under test.

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

BT Manufacturing Tolerance

| GFSK (Peak) | | | |
|-----------------|-----------|------------|------------|
| Channel | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm) | 8 | 8.5 | 8.5 |
| Tolerance ±(dB) | 1 | 1 | 1 |
| π/4DQPSK (Peak) | | | |
| Channel | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm) | 8 | 8.5 | 8.5 |
| Tolerance ±(dB) | 1 | 1 | 1 |
| 8DPSK (Peak) | | | |
| Channel | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm) | 8 | 8.5 | 8.5 |
| Tolerance ±(dB) | 1 | 1 | 1 |

BLE Manufacturing Tolerance

| GFSK (Peak) | | | |
|-----------------|-----------|------------|------------|
| Channel | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm) | 6 | 7 | 7 |
| Tolerance ±(dB) | 1 | 1 | 1 |

Estimation Result

Worse case is as below: [2480 MHz, 9.5 dBm, 8.91 mW] output power]

$(8.91/5) \cdot [\sqrt{2.480(\text{GHz})}] = 2.81 < 3.0$ for 1-g SAR

Then SAR evaluation is not required

END OF REPORT