## mophie LLC

2019.7.13To: Federal Communications Commission7435 Oakland Mills Road

Columbia, MD

## FCC ID:2ACWB-STANDA

## To Whom It May Concern:

This letter is to ascertain that mophie LLC, Product mophie wireless charging stand, Model: MC-WRLS-STAND, has been the units used for conducting FCC compliance testing, and it meets KDB 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) 6 conditions.

5(b) 6 conditions.	
1	Power transfer frequency is less that 1 MHz
	YES; the device operated in the frequency range from 110.5-205KHz.
2	Output power from each primary coil is less than or equal to 15 watts.
	YES; the maximum output power of the primary coil is 10W.
	The transfer system includes only single primary and secondary coils. This includes
3	charging systems that may have multiple primary coils and clients that are able to
	detect and allow coupling only between individual pairs of coils.
	YES; the transfer system includes only single primary and secondary coils.
4	Client device is placed directly in contact with the transmitter.
	YES; Client device is placed directly in contact with the transmitter.
5	Mobile exposure conditions only (portable exposure conditions are not covered by
	this exclusion).
	No.
	The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the
6	top surface from all simultaneous transmitting coils are demonstrated to be less than
	50% of the MPE limit.
	YES; The EUT field strength levels are 50% x MPE limts.

<Signature>
Name: Hank

Hark (en

Title: Safety Engineer Company: mophie LLC