

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: **2ACWIELSFS502**

EUT Specification

EUT	LED TV
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	22.02dBm for 802.11b 22.51dBm for 802.11g 22.62dBm for 802.11n(H20) 21.76dBm for 802.11n(H40)
Antenna gain (Max)	2dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Operating Mode	Test Channel	Output Peak power (dBm)	Output Peak power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	1	19.92	98.175	2	1.585	0.030957	1
	6	20.59	114.551	2	1.585	0.036121	1
	11	22.02	159.221	2	1.585	0.050206	1
802.11g	1	20.49	111.944	2	1.585	0.035299	1
	6	21.13	129.718	2	1.585	0.040903	1
	11	22.51	178.238	2	1.585	0.056203	1
802.11n (H20)	1	20.77	119.399	2	1.585	0.037649	1
	6	21.43	138.995	2	1.585	0.043829	1
	11	22.62	182.810	2	1.585	0.057645	1
802.11n (H40)	3	20.58	114.288	2	1.585	0.036038	1
	6	21.05	127.350	2	1.585	0.040157	1
	9	21.76	149.968	2	1.585	0.047289	1

Signature:



Print: Sam Lv

Title: Manager

Company: DONGGUAN EMTEK CO., LTD.

Address: No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

Date: 2014-10-14