

FCC 47 CFR MPE REPORT

Shenyang Tongfang Multimedia Technology Co., Limited

LED TV

Model Number: WD32FBE1001

Additional Model: WD32HBB101, WD32FE2120, ELEFW328,

ELST3216H, ELEFW328B, ELEFT328, 8502809, 1129265,

WD32*****,EL*****, maybe followed by character

FCC ID: 2ACWIELST3216

Prepared for:	Shenyang Tongfang Multimedia Technology Co., Limited
	No.10 Nanping East Road HunNan New District, Shenyang, LiaoNing
	Province, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1901066
Date of Test:	Jan. 03~22, 2019
Date of Report:	Jan. 22, 2019



Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result

3.1 Antenna 0

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	9.66	9.25	10±2	1.21	1.32
	2437	9.63	9.18	10±2	1.21	1.32
	2462	9.68	9.29	10±2	1.21	1.32
IEEE 802.11g	2412	5.90	3.89	6±2	1.21	1.32
	2437	5.63	3.66	6±2	1.21	1.32
	2462	5.43	3.49	5±2	1.21	1.32
IEEE 802.11n HT20	2412	5.18	3.30	5±2	1.21	1.32
	2437	5.52	3.57	6±2	1.21	1.32
	2462	5.46	3.52	5±2	1.21	1.32
IEEE 802.11n HT40	2422	3.36	2.17	3±2	1.21	1.32
	2437	3.22	2.10	3±2	1.21	1.32
	2452	3.14	2.06	3±2	1.21	1.32

3.2 Antenna 1

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	9.78	9.51	10±2	1.21	1.32
	2437	9.86	9.68	10±2	1.21	1.32
	2462	8.71	7.43	9±2	1.21	1.32
IEEE 802.11g	2412	5.55	3.59	6±2	1.21	1.32
	2437	5.91	3.90	6±2	1.21	1.32
	2462	5.63	3.66	6±2	1.21	1.32
IEEE 802.11n HT20	2412	4.93	3.11	5±2	1.21	1.32
	2437	5.62	3.65	6±2	1.21	1.32
	2462	5.37	3.44	5±2	1.21	1.32
IEEE 802.11n HT40	2422	2.80	1.91	3±2	1.21	1.32
	2437	2.39	1.73	2±2	1.21	1.32
	2452	3.69	2.34	4±2	1.21	1.32

4、Calculated Result and Limit

4.1 Antenna 0

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	12	1.21	1.32	0.00417	1	Compiles
IEEE 802.11g	8	1.21	1.32	0.00166	1	Compiles
IEEE 802.11n HT20	8	1.21	1.32	0.00166	1	Compiles
IEEE 802.11n HT40	5	1.21	1.32	0.00083	1	Compiles

4.2 Antenna 1

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	12	1.21	1.32	0.00417	1	Compiles
IEEE 802.11g	8	1.21	1.32	0.00166	1	Compiles
IEEE 802.11n HT20	8	1.21	1.32	0.00166	1	Compiles
IEEE 802.11n HT40	6	1.21	1.32	0.00105	1	Compiles

4.3 Antenna 0+1

Mode	Power Density (S) (mW/cm ²) Antenna 0	Power Density (S) (mW/cm ²) Antenna 1	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
IEEE 802.11n HT20	0.00166	0.00166	0.00332	1	Compiles
IEEE 802.11n HT40	0.00083	0.00105	0.00188	1	Compiles