

FCC RF EXPOSURE REPORT

Shenyang Tongfang Multimedia Technology Co., Limited

LED TV

Model Number: SE40FYP1T

Additional Model: LE-40GY15T, LE-40GY15T1, LE-40GY15-T3, SE40FYT,

ELSFW401, EW40XXXXXXXXXX, DWM40XXXXXXXXXXXX,

SEXXXXXXXXXX,ELXXXXXXXXXX, LE-40GXXXXXXXXXX,

LE40GXXXXXXXXXXXX

FCC ID: 2ACWISE40FYP1T

Prepared for : Shenyang Tongfang Multimedia Technology Co., Limited
No. 10 Nanping East Road HunNan New District Shenyang,
LiaoNing Province P.R. China

Prepared By :EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City,GuangDong,
China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1601035

Date of Test : January 20~ January 27, 2016

Date of Report : January 28, 2016



Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

Mode	Frequency (MHz)	output power (dBm)	output power (mW)	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
					(dBi)	(Linear)			
IEEE 802.11b	2412	11.73	14.89	11±1	2	1.59	0.00500	1	Compiles
	2442	11.66	14.66	11±1	2	1.59	0.00500	1	Compiles
	2472	10.71	11.78	11±1	2	1.59	0.00500	1	Compiles
IEEE 802.11g	2412	10.07	10.16	10±1	2	1.59	0.00397	1	Compiles
	2442	9.89	9.75	10±1	2	1.59	0.00397	1	Compiles
	2472	9.64	9.20	10±1	2	1.59	0.00397	1	Compiles
IEEE 802.11n HT20	2412	9.15	8.22	9±1	2	1.59	0.00315	1	Compiles
	2442	9.17	8.26	9±1	2	1.59	0.00315	1	Compiles
	2472	9.39	8.69	9±1	2	1.59	0.00315	1	Compiles
IEEE 802.11n HT40	2422	7.84	6.08	7±1	2	1.59	0.00199	1	Compiles
	2442	7.33	5.41	7±1	2	1.59	0.00199	1	Compiles
	2462	6.74	4.72	7±1	2	1.59	0.00199	1	Compiles