

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	LED TV
<b>FCC ID</b>	2ACWITC50CX400
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	13.50dBm for 802.11b; 12.62dBm for 802.11g; 12.55dBm for 802.11n(HT20); 12.08dBm for 802.11n(HT40);
<b>Antenna gain (Max)</b>	2.0dBi ( for per antenna port Max) 5.01dBi for MIMO(Ant1+Ant2 Directional Gain)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

**Applicable Standard:**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J. Section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m Normally can be maintained between the user and the device.

**Limits for Maximum Permissible Exposure(MPE)**

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>0.3-3.0</b>	<b>614</b>	<b>1.63</b>	<b>(100)*</b>	<b>6</b>
<b>3.0-30</b>	<b>1842/f</b>	<b>4.89/f</b>	<b>(900/f)*</b>	<b>6</b>
<b>30-300</b>	<b>61.4</b>	<b>0.163</b>	<b>1.0</b>	<b>6</b>
<b>300-1500</b>	<b>--</b>	<b>--</b>	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	<b>--</b>	<b>--</b>	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>0.3-1.34</b>	<b>614</b>	<b>1.63</b>	<b>(100)*</b>	<b>30</b>
<b>1.34-30</b>	<b>824/f</b>	<b>2.19/f</b>	<b>(180/f)*</b>	<b>30</b>
<b>30-300</b>	<b>27.5</b>	<b>0.073</b>	<b>0.2</b>	<b>30</b>
<b>300-1500</b>	<b>--</b>	<b>--</b>	<b>F/1500</b>	<b>30</b>
<b>1500-100000</b>	<b>--</b>	<b>--</b>	<b>1</b>	<b>30</b>

**Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>,  $P_{out}$ =output power to antenna in Mw

$G$ = gain of antenna in linear scale,  $\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Max power Result:

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)			Limit (dBm)	Verdict
			Ant1	Ant2	Sum		
802.11b	1	2412	11.04	10.02	--	30	PASS
	6	2437	12.69	11.72	--	30	PASS
	11	2462	13.15	12.03	--	30	PASS
802.11g	1	2412	10.24	8.72	--	30	PASS
	6	2437	11.24	9.41	--	30	PASS
	11	2462	12.69	10.62	--	30	PASS
802.11n (HT20)	1	2412	8.42	7.53	11.01	28	PASS
	6	2437	9.04	8.46	11.77	28	PASS
	11	2462	9.23	8.79	12.03	28	PASS
802.11n (HT40)	3	2422	7.26	7.84	10.57	28	PASS
	6	2437	8.42	8.63	11.54	28	PASS
	9	2452	9.04	8.83	11.95	28	PASS

Antenna 1:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	1	11±1	12	15.849	2	1.585	0.004997	1
	6	13±1	14	25.119	2	1.585	0.007920	1
	11	12±1	13	19.953	2	1.585	0.006291	1
802.11g	1	10±1	11	12.59	2	1.585	0.003969	1
	6	11±1	12	15.85	2	1.585	0.004997	1
	11	13±1	14	25.12	2	1.585	0.007920	1
802.11n (HT20)	1	8±1	9	7.94	2	1.585	0.002505	1
	6	9±1	10	10.00	2	1.585	0.003153	1
	11	9±1	10	10.00	2	1.585	0.003153	1
802.11n (HT40)	3	7±1	8	6.31	2	1.585	0.001989	1
	6	8±1	9	7.94	2	1.585	0.002505	1
	9	9±1	10	10.00	2	1.585	0.003153	1

## Antenna 2:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	1	10±1	11	12.589	2	1.585	0.003969	1
	6	12±1	13	19.953	2	1.585	0.006291	1
	11	12±1	13	19.953	2	1.585	0.006291	1
802.11g	1	9±1	10	10.00	2	1.585	0.003153	1
	6	9±1	10	10.00	2	1.585	0.003153	1
	11	11±1	12	15.85	2	1.585	0.004997	1
802.11n (HT20)	1	8±1	9	7.94	2	1.585	0.002505	1
	6	8±1	9	7.94	2	1.585	0.002505	1
	11	9±1	10	10.00	2	1.585	0.003153	1
802.11n (HT40)	3	8±1	9	7.94	2	1.585	0.002505	1
	6	9±1	10	10.00	2	1.585	0.003153	1
	9	9±1	10	10.00	2	1.585	0.003153	1

## MPE Result:

Operation Mode	Channel Number	Channel Frequency (MHz)	Power density at 20cm (mW/cm <sup>2</sup> )			Power density Limits (mW/cm <sup>2</sup> )	Verdict
			Ant1	Ant2	Sum		
802.11b	1	2412	0.004997	0.003969	--	1	PASS
	6	2437	0.007920	0.006291	--	1	PASS
	11	2462	0.006291	0.006291	--	1	PASS
802.11g	1	2412	0.003969	0.003153	--	1	PASS
	6	2437	0.004997	0.003153	--	1	PASS
	11	2462	0.007920	0.004997	--	1	PASS
802.11n (HT20)	1	2412	0.002505	0.002505	0.005010	1	PASS
	6	2437	0.003153	0.002505	0.005658	1	PASS
	11	2462	0.003153	0.003153	0.006306	1	PASS
802.11n (HT40)	3	2422	0.001989	0.002505	0.004494	1	PASS
	6	2437	0.002505	0.003153	0.005658	1	PASS
	9	2452	0.003153	0.003153	0.006306	1	PASS