

FCC 47 CFR MPE REPORT

Shenyang Tongfang Multimedia Technology Co.,Limited

LED TV

Model Number: WD32HBB101

FCC ID: 2ACWIWD32HBB10

Prepared for:	Shenyang Tongfang Multimedia Technology Co.,Limited
	No. 10 Nanping East Road HunNan New District Shenyang,
	LiaoNing, Province P. R. China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1804013
Date of Test:	Apr. 14, 2018
Date of Report:	Apr. 16, 2018

Maximum Permissible Exposure

1、 Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、 Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、 Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、 MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	17.45	55.590	17±1	2	1.58
	2437	17.19	52.360	17±1	2	1.58
	2462	16.97	49.774	16±1	2	1.58
IEEE 802.11g	2412	11.53	14.223	11±1	2	1.58
	2437	12.19	16.558	12±1	2	1.58
	2462	11.39	13.772	11±1	2	1.58
IEEE 802.11n HT20	2412	11.11	12.912	11±1	2	1.58
	2437	11.80	15.136	11±1	2	1.58
	2462	11.34	13.614	11±1	2	1.58
IEEE 802.11n HT40	2422	9.88	9.727	9±1	2	1.58
	2437	10.76	11.912	10±1	2	1.58
	2452	9.88	9.727	9±1	2	1.58

4、 Calculated Result and Limit

4.Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	18	2	1.58	0.01989	1	Compiles
IEEE 802.11g	13	2	1.58	0.00629	1	Compiles
IEEE 802.11n HT20	12	2	1.58	0.00500	1	Compiles
IEEE 802.11n HT40	11	2	1.58	0.00397	1	Compiles