

FCC 47 CFR MPE REPORT

Shenyang Tongfang Multimedia Technology Co.,Limited

LED TV

Model Number: WE50UE4008

Additional Model: 1574939, WD*****, EL*****,WE*****

(maybe followed by 9 character, * can be A-Z, 0-9 or “-“ or blank)

FCC ID: 2ACWIWE50UB44

Prepared for:	Shenyang Tongfang Multimedia Technology Co.,Limited
	No. 10 Nanping East Road HunNan New District Shenyang,
	LiaoNing, Province P. R. China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1810107
Date of Test:	Oct. 25~Nov. 01, 2018
Date of Report:	Nov. 01, 2018



Maximum Permissible Exposure

1、 Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、 Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、 Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、 MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result

3.1 Antenna 0

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	14.76	29.92	15±2	1.21	1.32
	2437	14.61	28.91	15±2	1.21	1.32
	2462	14.69	29.44	15±2	1.21	1.32
IEEE 802.11g	2412	9.79	9.53	10±2	1.21	1.32
	2437	10.22	10.52	10±2	1.21	1.32
	2462	10.40	10.97	10±2	1.21	1.32
IEEE 802.11n HT20	2412	10.77	11.94	11±2	1.21	1.32
	2437	10.48	11.17	10±2	1.21	1.32
	2462	10.07	10.16	10±2	1.21	1.32
IEEE 802.11n HT40	2422	7.82	6.05	8±2	1.21	1.32
	2437	8.59	7.23	9±2	1.21	1.32
	2452	10.26	10.62	10±2	1.21	1.32

3.2 Antenna 1

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	14.81	30.27	15±2	1.21	PASS
	2437	14.92	31.05	15±2	1.21	PASS
	2462	14.42	27.67	14±2	1.21	PASS
IEEE 802.11g	2412	11.02	12.65	11±2	1.21	PASS
	2437	9.91	9.80	10±2	1.21	PASS
	2462	10.21	10.50	10±2	1.21	PASS
IEEE 802.11n HT20	2412	10.93	12.39	11±2	1.21	PASS
	2437	10.19	10.45	10±2	1.21	PASS
	2462	10.37	10.89	10±2	1.21	PASS
IEEE 802.11n HT40	2422	7.18	5.22	7±2	1.21	PASS
	2437	7.68	5.86	8±2	1.21	PASS
	2452	7.33	5.41	7±2	1.21	PASS

4、 Calculated Result and Limit

4.1 Antenna 0

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	17	1.21	1.32	0.01317	1	Compiles
IEEE 802.11g	12	1.21	1.32	0.00417	1	Compiles
IEEE 802.11n HT20	13	1.21	1.32	0.00524	1	Compiles
IEEE 802.11n HT40	12	1.21	1.32	0.00417	1	Compiles

4.2 Antenna 1

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	17	1.21	1.32	0.01317	1	Compiles
IEEE 802.11g	13	1.21	1.32	0.00524	1	Compiles
IEEE 802.11n HT20	13	1.21	1.32	0.00524	1	Compiles
IEEE 802.11n HT40	10	1.21	1.32	0.00263	1	Compiles

4.3 Antenna 0+1

Mode	Power Density (S) (mW/cm ²) Antenna 0	Power Density (S) (mW/cm ²) Antenna 1	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
IEEE 802.11n HT20	0.00524	0.00524	0.01048	1	Compiles
IEEE 802.11n HT40	0.00417	0.00263	0.00680	1	Compiles