

APPLICATION CERTIFICATION FCC Part 15C  
On Behalf of  
TIMSEN INTERNATIONAL LIMITED

Turntable  
Model No.: CR6023A-XX  
("X" can be replaced by letter from "A" to "Z" or blank)

FCC ID: 2ACX8CR6023A

Prepared for : TIMSEN INTERNATIONAL LIMITED.  
Address : 5F, No. 447, Tianhebei Road, Tianhe District,  
Guangzhou, Guangdong Province, China  
Prepared by : ACCURATE TECHNOLOGY CO., LTD  
Address : F1, Bldg. A, Chan Yuan New Material Port, Keyuan  
Rd. Science & Industry Park, Nan Shan, Shenzhen,  
Guangdong P.R. China

Tel: (0755) 26503290

Fax: (0755) 26503396

Report No. : ATE20170147  
Date of Test : Feb. 16, 2017--Feb. 27, 2017  
Date of Report : Feb. 28, 2017

## TABLE OF CONTENTS

Description	Page
Test Report Certification	
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. Description of Device (EUT).....	5
1.2. Accessory and Auxiliary Equipment .....	6
1.3. Description of Test Facility .....	6
1.4. Measurement Uncertainty .....	6
<b>2. MEASURING DEVICE AND TEST EQUIPMENT .....</b>	<b>7</b>
<b>3. OPERATION OF EUT DURING TESTING .....</b>	<b>8</b>
3.1. Operating Mode .....	8
3.2. Configuration and peripherals .....	8
<b>4. TEST PROCEDURES AND RESULTS .....</b>	<b>9</b>
<b>5. 20DB BANDWIDTH TEST.....</b>	<b>10</b>
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(1).....	10
5.3. EUT Configuration on Measurement .....	10
5.4. Operating Condition of EUT .....	10
5.5. Test Procedure .....	10
5.6. Test Result .....	11
<b>6. CARRIER FREQUENCY SEPARATION TEST.....</b>	<b>17</b>
6.1. Block Diagram of Test Setup.....	17
6.2. The Requirement For Section 15.247(a)(1).....	17
6.3. EUT Configuration on Measurement .....	17
6.4. Operating Condition of EUT .....	17
6.5. Test Procedure .....	18
6.6. Test Result .....	18
<b>7. NUMBER OF HOPPING FREQUENCY TEST .....</b>	<b>24</b>
7.1. Block Diagram of Test Setup.....	24
7.2. The Requirement For Section 15.247(a)(1)(iii).....	24
7.3. EUT Configuration on Measurement .....	24
7.4. Operating Condition of EUT .....	24
7.5. Test Procedure .....	24
7.6. Test Result .....	25
<b>8. DWELL TIME TEST .....</b>	<b>27</b>
8.1. Block Diagram of Test Setup.....	27
8.2. The Requirement For Section 15.247(a)(1)(iii).....	27
8.3. EUT Configuration on Measurement .....	27
8.4. Operating Condition of EUT .....	27
8.5. Test Procedure .....	27
8.6. Test Result .....	28
<b>9. MAXIMUM PEAK OUTPUT POWER TEST .....</b>	<b>43</b>
9.1. Block Diagram of Test Setup.....	43
9.2. The Requirement For Section 15.247(b)(1).....	43
9.3. EUT Configuration on Measurement .....	43
9.4. Operating Condition of EUT .....	43

9.5.	Test Procedure .....	43
9.6.	Test Result .....	44
<b>10.</b>	<b>RADIATED EMISSION TEST .....</b>	<b>50</b>
10.1.	Block Diagram of Test Setup.....	50
10.2.	The Limit For Section 15.247(d) .....	51
10.3.	Restricted bands of operation .....	52
10.4.	Configuration of EUT on Measurement .....	52
10.5.	Test Procedure .....	53
10.6.	The Field Strength of Radiation Emission Measurement Results .....	53
<b>11.</b>	<b>BAND EDGE COMPLIANCE TEST .....</b>	<b>66</b>
11.1.	Block Diagram of Test Setup.....	66
11.2.	The Requirement For Section 15.247(d) .....	66
11.3.	EUT Configuration on Measurement .....	66
11.4.	Operating Condition of EUT .....	66
11.5.	Test Procedure .....	67
11.6.	Test Result .....	67
<b>12.</b>	<b>AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..</b>	<b>90</b>
12.1.	Block Diagram of Test Setup.....	90
12.2.	Power Line Conducted Emission Measurement Limits.....	90
12.3.	Configuration of EUT on Measurement .....	90
12.4.	Operating Condition of EUT .....	90
12.5.	Test Procedure .....	91
12.6.	Power Line Conducted Emission Measurement Results .....	91
<b>13.</b>	<b>ANTENNA REQUIREMENT.....</b>	<b>95</b>
13.1.	The Requirement .....	95
13.2.	Antenna Construction .....	95

## Test Report Certification

Applicant : TIMSEN INTERNATIONAL LIMITED  
Manufacturer : TIMSEN INTERNATIONAL LIMITED  
EUT Description : Turntable  
(A) MODEL NO.: CR6023A-XX  
(B) TRADE NAME.: CROSLEY  
(C) Adapter Input Voltage: AC 120V/60Hz

Measurement Procedure Used:

### FCC Rules and Regulations Part 15 Subpart C Section 15.247:2016 ANSI C63.10: 2013

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Feb. 16, 2017--Feb. 27, 2017  
Date of Report: Feb. 28, 2017

Prepared by :   
( Tim.zhang, Engineer)

Approved & Authorized Signer :   
(Sean Liu, Manager)

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

EUT	:	Turntable
Model Number	:	CR6023A-XX (Note: XX represents the color, the main test model is CR6023A-NA)
Bluetooth version	:	BT 3.0+EDR
Frequency Range	:	2402MHz-2480MHz
Number of Channels	:	79
Antenna Gain(Max)	:	2dBi
Antenna type	:	PCB Antenna
Trade Name	:	CROSLEY
Adapter Input Voltage	:	AC 120V/60Hz
Adapter information	:	Model: RHD35-0900400 Input: AC 120V/60Hz 7W Output: DC 9V; 0.4A
Modulation mode	:	GFSK, $\pi/4$ DQPSK, 8DPSK
Applicant	:	TIMSEN INTERNATIONAL LIMITED
Address	:	5F, No. 447, Tianhebei Road, Tianhe District, Guangzhou, Guangdong Province, China.
Manufacturer	:	TIMSEN INTERNATIONAL LIMITED
Address	:	5F, No. 447, Tianhebei Road, Tianhe District, Guangzhou, Guangdong Province, China.
Date of sample received	:	Feb. 16, 2017
Date of Test	:	Feb. 16, 2017--Feb. 27, 2017

## 1.2. Accessory and Auxiliary Equipment

N/A

## 1.3. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC  
The Registration Number is 752051

Listed by Industry Canada  
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee  
for Laboratories  
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD  
Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

## 1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2  
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2  
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2  
(Above 1GHz)

## 2. MEASURING DEVICE AND TEST EQUIPMENT

**Table 1: List of Test and Measurement Equipment**

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 07, 2017	Jan. 06, 2018
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 07, 2017	Jan. 06, 2018
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 07, 2017	Jan. 06, 2018
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 07, 2017	Jan. 06, 2018
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 13, 2017	Jan. 12, 2018
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 13, 2017	Jan. 12, 2018
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 13, 2017	Jan. 12, 2018
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 13, 2017	Jan. 12, 2018
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 07, 2017	Jan. 06, 2018
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 07, 2017	Jan. 06, 2018
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 07, 2017	Jan. 06, 2018
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 07, 2017	Jan. 06, 2018

### 3. OPERATION OF EUT DURING TESTING

#### 3.1. Operating Mode

The mode is used: Transmitting mode


Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

#### 3.2. Configuration and peripherals






#### 4. TEST PROCEDURES AND RESULTS

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
Section 15.207	Conducted Emission Test	Compliant
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

## 5. 20DB BANDWIDTH TEST

### 5.1. Block Diagram of Test Setup



(EUT: Turntable)

### 5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### 5.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

### 5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


### 5.6. Test Result

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	$\Pi/4$ -DQPSK 20dB Bandwidth (MHz)	8DPSK 20dB Bandwidth (MHz)	Result
Low	2402	0.860	1.272	1.254	Pass
Middle	2441	0.808	1.266	1.260	Pass
High	2480	0.856	1.260	1.266	Pass

The spectrum analyzer plots are attached as below.


GFSK Mode

Low channel




Date: 27.FEB.2017 16:10:33

Middle channel



Date: 27.FEB.2017 15:59:41


### High channel



Date: 27.FEB.2017 15:58:46


### Π/4-DQPSK Mode

### Low channel




Date: 27.FEB.2017 16:11:22

### Middle channel



Date: 27.FEB.2017 16:13:45


### High channel



Date: 27.FEB.2017 16:14:12


8DPSK Mode

Low channel




Date: 27.FEB.2017 16:24:37

Middle channel



Date: 27.FEB.2017 16:25:37

### High channel



Date: 27.FEB.2017 16:26:36



## 6. CARRIER FREQUENCY SEPARATION TEST

### 6.1. Block Diagram of Test Setup



(EUT: Turntable)

### 6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

## 6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 2MHz.

6.5.3. Set the adjacent channel of the EUT Maxhold another trace.

6.5.4. Measurement the channel separation

## 6.6. Test Result

### GFSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.008	25KHz or 20dB bandwidth	PASS
	2403			
Middle	2440	1.004	25KHz or 20dB bandwidth	PASS
	2441			
High	2479	1.008	25KHz or 20dB bandwidth	PASS
	2480			

### Π/4-DQPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.008	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.008	25KHz or 2/3*20dB bandwidth	PASS
	2480			


### 8DPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.008	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.008	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2480			

The spectrum analyzer plots are attached as below.


GFSK Mode

Low channel




Date: 27.FEB.2017 17:26:32

Middle channel




Date: 27.FEB.2017 17:30:56

### High channel




### Π/4-DQPSK Mode

### Low channel




### Middle channel



Date: 27.FEB.2017 17:35:16


### High channel



Date: 27.FEB.2017 17:33:58


## 8DPSK Mode

### Low channel




Date: 27.FEB.2017 17:42:07

### Middle channel



Date: 27.FEB.2017 17:44:01

### High channel



Date: 27.FEB.2017 17:45:17

## 7. NUMBER OF HOPPING FREQUENCY TEST

### 7.1. Block Diagram of Test Setup



(EUT: Turntable)

### 7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

### 7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.


7.5.3. Max hold, view and count how many channel in the band.



### 7.6. Test Result


Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	≥ 15

The spectrum analyzer plots are attached as below.




Date: 27.FEB.2017 16:39:36

### Number of hopping channels( $\Pi/4$ -DQPSK)



Date: 27.FEB.2017 17:09:36


### Number of hopping channels(8DPSK)



Date: 27.FEB.2017 17:23:02

## 8. DWELL TIME TEST

### 8.1. Block Diagram of Test Setup



(EUT: Turntable)

### 8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

### 8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

8.5.4.Repeat above procedures until all frequency measured were complete.

## 8.6.Test Result

### GFSK Mode

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.410	131.20	400
	2441	0.405	129.60	400
	2480	0.405	129.60	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2402	1.695	271.20	400
	2441	1.695	271.20	400
	2480	1.695	271.20	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2402	2.970	316.80	400
	2441	2.970	316.80	400
	2480	2.970	316.80	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

### $\Pi/4$ -DQPSK


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.430	137.60	400
	2441	0.430	137.60	400
	2480	0.430	137.60	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2402	1.690	270.40	400
	2441	1.670	267.20	400
	2480	1.690	270.40	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2402	2.970	316.80	400
	2441	2.976	317.44	400
	2480	2.976	317.44	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

## 8DPSK Mode

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.425	136.00	400
	2441	0.430	137.60	400
	2480	0.425	136.00	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2402	1.720	275.20	400
	2441	1.700	272.00	400
	2480	1.700	272.00	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2402	2.970	316.80	400
	2441	2.970	316.80	400
	2480	2.970	316.80	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				


The spectrum analyzer plots are attached as below.

## GFSK Mode




Date: 27.FEB.2017 14:57:14

### DH1 Middle channel




Date: 27.FEB.2017 14:47:27

### DH1 High channel




Date: 27.FEB.2017 14:48:13

### DH3 Low channel




Date: 27.FEB.2017 13:54:40

### DH3 Middle channel




Date: 27.FEB.2017 14:42:51

### DH3 High channel



Date: 27.FEB.2017 14:45:13


### DH5 Low channel



Date: 27.FEB.2017 14:54:55




### DH5 Middle channel



Date: 27.FEB.2017 14:53:19


### DH5 High channel



Date: 27.FEB.2017 14:52:10


Π/4-DQPSK

2DH1 Low channel




Date: 27.FEB.2017 15:00:19

2DH1 Middle channel




Date: 27.FEB.2017 15:01:29

### 2DH1 High channel




Date: 27.FEB.2017 15:02:11

### 2DH3 Low channel




Date: 27.FEB.2017 15:13:58

### 2DH3 Middle channel




Date: 27.FEB.2017 15:16:17

### 2DH3 High channel




Date: 27.FEB.2017 15:17:59

### 2DH5 Low channel




Date: 27.FEB.2017 13:47:54

### 2DH5 Middle channel



Date: 27.FEB.2017 13:40:07


### 2DH5 High channel



Date: 27.FEB.2017 13:46:46


### 8DPSK Mode

### 3DH1 Low channel




Date: 27.FEB.2017 15:20:17

### 3DH1 Middle channel




Date: 27.FEB.2017 15:21:20

### 3DH1 High channel




Date: 27.FEB.2017 15:22:01

### 3DH3 Low channel



Date: 27.FEB.2017 15:25:35


### 3DH3 Middle channel



Date: 27.FEB.2017 15:26:10




### 3DH3 High channel




Date: 27.FEB.2017 15:26:45

### 3DH5 Low channel




Date: 27.FEB.2017 13:37:19

### 3DH5 Middle channel



Date: 27.FEB.2017 13:40:33


### 3DH5 High channel



Date: 27.FEB.2017 13:45:31

## 9. MAXIMUM PEAK OUTPUT POWER TEST

### 9.1. Block Diagram of Test Setup



(EUT: Turntable)

### 9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

### 9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz for GFSK mode

9.5.3. Set RBW of spectrum analyzer to 3MHz and VBW to 3MHz for other mode

9.5.4. Measurement the maximum peak output power.

## 9.6. Test Result

### GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	4.66/0.0029	30 / 1.0
Middle	2441	4.80/0.0030	30 / 1.0
High	2480	5.04/0.0032	30 / 1.0

### Π/4-DQPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	5.22/0.0033	21 / 0.125
Middle	2441	4.93/0.0031	21 / 0.125
High	2480	5.20/0.0033	21 / 0.125


### 8DPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	4.35/0.0027	21 / 0.125
Middle	2441	4.58/0.0029	21 / 0.125
High	2480	4.75/0.0030	21 / 0.125

The spectrum analyzer plots are attached as below.


## GFSK Mode

### Low channel




Date: 27.FEB.2017 15:30:53

### Middle channel



Date: 27.FEB.2017 15:33:14


### High channel



Date: 27.FEB.2017 15:33:46


### Π/4-DQPSK Mode

### Low channel




Date: 27.FEB.2017 15:35:35

## Middle channel



Date: 27.FEB.2017 15:36:40


## High channel



Date: 27.FEB.2017 15:37:08


8DPSK Mode

Low channel



Date: 27.FEB.2017 15:39:56


Middle channel



Date: 27.FEB.2017 15:40:48



### High channel




Date: 27.FEB.2017 15:41:06

## 10. RADIATED EMISSION TEST


### 10.1. Block Diagram of Test Setup

#### 10.1.1. Block diagram of connection between the EUT and peripherals




#### 10.1.2. Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30-1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



## 10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

### 10.3.Restricted bands of operation

#### 10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

<sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510

<sup>2</sup>Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 10.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

## 10.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground (Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground (Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

## 10.6. The Field Strength of Radiation Emission Measurement Results

**Note: 1. We tested GFSK mode,  $\pi/4$ -DQPSK Mode & 8DPSK mode and recorded the worst case data (GFSK mode) for all test mode.**

**2. The test frequency is from 9KHz to 25GHz, The radiation emission from 9KHz-30MHz and 18-25GHz are not reported, because the levels are too low against the limit.**

Below 1GHz



**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING1 #332  
Standard: FCC Class B 3M Radiated  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 25 C / 55 %  
EUT: Turntable  
Mode: TX 2402MHz  
Model: CR6023A-NA  
Manufacturer: TIMSEN

Polarization: Horizontal  
Power Source: AC 120V/60Hz  
Date: 17/02/23/  
Time: 9/52/56  
Engineer Signature: DING  
Distance: 3m

Note: Report NO.:ATE20170147




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	172.5975	44.20	-20.57	23.63	43.50	-19.87	QP			
2	222.2806	43.45	-18.37	25.08	46.00	-20.92	QP			
3	251.3676	49.05	-18.05	31.00	46.00	-15.00	QP			
4	266.8394	45.65	-17.18	28.47	46.00	-17.53	QP			
5	340.0473	43.60	-14.25	29.35	46.00	-16.65	QP			
6	385.8981	41.51	-13.19	28.32	46.00	-17.68	QP			

Job No.: DING1 #331  
 Standard: FCC Class B 3M Radiated  
 Test item: Radiation Test  
 Temp.( C)/Hum.(%) 25 C / 55 %  
 EUT: Turntable  
 Mode: TX 2402MHz  
 Model: CR6023A-NA  
 Manufacturer: TIMSEN

Polarization: Vertical  
 Power Source: AC 120V/60Hz  
 Date: 17/02/23/  
 Time: 9/51/43  
 Engineer Signature: DING  
 Distance: 3m

Note: Report NO.:ATE20170147



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.7760	45.48	-22.36	23.12	43.50	-20.38	QP			
2	172.5975	47.92	-20.57	27.35	43.50	-16.15	QP			
3	222.2806	45.30	-18.37	26.93	46.00	-19.07	QP			
4	251.3676	48.33	-18.05	30.28	46.00	-15.72	QP			
5	266.8394	45.91	-17.18	28.73	46.00	-17.27	QP			
6	369.9658	39.71	-13.35	26.36	46.00	-19.64	QP			



**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: DING1 #333  
Standard: FCC Class B 3M Radiated  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 25 C / 55 %  
EUT: Turntable  
Mode: TX 2441MHz  
Model: CR6023A-NA  
Manufacturer: TIMSEN

Polarization: Horizontal  
Power Source: AC 120V/60Hz  
Date: 17/02/23/  
Time: 9/53/22  
Engineer Signature: DING  
Distance: 3m

Note: Report NO.:ATE20170147




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	172.5975	43.11	-20.57	22.54	43.50	-20.96	QP			
2	222.2806	43.74	-18.37	25.37	46.00	-20.63	QP			
3	259.4433	45.96	-17.57	28.39	46.00	-17.61	QP			
4	275.4123	45.24	-16.88	28.36	46.00	-17.64	QP			
5	326.0079	42.63	-14.85	27.78	46.00	-18.22	QP			
6	369.9658	44.25	-13.35	30.90	46.00	-15.10	QP			



Job No.: DING1 #334	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 17/02/23/
Temp.( C)/Hum.(%) 25 C / 55 %	Time: 9/54/47
EUT: Turntable	Engineer Signature: DING
Mode: TX 2441MHz	Distance: 3m
Model: CR6023A-NA	
Manufacturer: TIMSEN	

Note: Report NO.:ATE20170147




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.7760	45.42	-22.36	23.06	43.50	-20.44	QP			
2	172.5975	46.04	-20.57	25.47	43.50	-18.03	QP			
3	222.2806	44.33	-18.37	25.96	46.00	-20.04	QP			
4	251.3676	47.15	-18.05	29.10	46.00	-16.90	QP			
5	266.8394	44.02	-17.18	26.84	46.00	-19.16	QP			
6	354.6911	38.88	-13.64	25.24	46.00	-20.76	QP			

Job No.: DING1 #336  
 Standard: FCC Class B 3M Radiated  
 Test item: Radiation Test  
 Temp.( C)/Hum.(%) 25 C / 55 %  
 EUT: Turntable  
 Mode: TX 2480MHz  
 Model: CR6023A-NA  
 Manufacturer: TIMSEN

Polarization: Horizontal  
 Power Source: AC 120V/60Hz  
 Date: 17/02/23/  
 Time: 9/55/15  
 Engineer Signature: DING  
 Distance: 3m

Note: Report NO.:ATE20170147




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	207.1967	40.63	-18.47	22.16	43.50	-21.34	QP			
2	222.2806	42.85	-18.37	24.48	46.00	-21.52	QP			
3	235.9621	39.66	-18.23	21.43	46.00	-24.57	QP			
4	326.0079	42.64	-14.85	27.79	46.00	-18.21	QP			
5	369.9658	40.10	-13.35	26.75	46.00	-19.25	QP			
6	385.8981	40.57	-13.19	27.38	46.00	-18.62	QP			

Job No.: DING1 #335  
Standard: FCC Class B 3M Radiated  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 25 C / 55 %  
EUT: Turntable  
Mode: TX 2480MHz  
Model: CR6023A-NA  
Manufacturer: TIMSEN

Polarization: Vertical  
Power Source: AC 120V/60Hz  
Date: 17/02/23/  
Time: 9/54/52  
Engineer Signature: DING  
Distance: 3m

Note: Report NO.:ATE20170147



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	172.5975	46.04	-20.57	25.47	43.50	-18.03	QP			
2	189.1075	41.82	-19.49	22.33	43.50	-21.17	QP			
3	222.2806	43.33	-18.37	24.96	46.00	-21.04	QP			
4	251.3676	45.15	-18.05	27.10	46.00	-18.90	QP			
5	293.3933	41.82	-16.01	25.81	46.00	-20.19	QP			
6	369.9658	39.63	-13.35	26.28	46.00	-19.72	QP			

## Above 1GHz


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ding1 #355	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 17/02/25/
Temp.( C)/Hum.(%) 25 C / 55 %	Time: 8/51/06
EUT: Turntable	Engineer Signature: DING
Mode: TX 2402MHz	Distance: 3m
Model: CR6023A-NA	
Manufacturer: TIMSEN	

Note: Report NO.:ATE20170147



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.019	104.85	-5.98	98.87			peak			
2	4804.057	56.41	3.15	59.56	74.00	-14.44	peak			
3	4804.057	46.20	3.15	49.35	54.00	-4.65	AVG			

Job No.: ding1 #356

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: Turntable

Mode: TX 2402MHz

Model: CR6023A-NA

Manufacturer: TIMSEN

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 17/02/25/

Time: 8/54/29

Engineer Signature: DING

Distance: 3m

Note: Report NO.:ATE20170147



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.019	99.94	-5.98	93.96			peak			
2	4804.057	55.42	3.15	58.57	74.00	-15.43	peak			
3	4804.057	45.20	3.15	48.35	54.00	-5.65	AVG			

Job No.: ding1 #358

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: Turntable

Mode: TX 2441MHz

Model: CR6023A-NA

Manufacturer: TIMSEN

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 17/02/25/

Time: 9/00/30

Engineer Signature: DING

Distance: 3m

Note: Report NO.:ATE20170147




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.021	104.40	-5.72	98.68			peak			
2	4882.042	57.13	3.53	60.66	54.00	6.66	peak			
3	4882.042	46.32	3.67	49.99	54.00	-4.01	AVG			

Job No.: ding1 #357  
 Standard: FCC Class B 3M Radiated  
 Test item: Radiation Test  
 Temp.( C)/Hum.(%) 25 C / 55 %  
 EUT: Turntable  
 Mode: TX 2441MHz  
 Model: CR6023A-NA  
 Manufacturer: TIMSEN

Polarization: Vertical  
 Power Source: AC 120V/60Hz  
 Date: 17/02/25/  
 Time: 8/57/32  
 Engineer Signature: DING  
 Distance: 3m

Note: Report NO.:ATE20170147



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.021	101.84	-5.72	96.12			peak			
2	4882.042	54.96	3.67	58.63	74.00	-15.37	peak			
3	4882.042	44.51	3.67	48.18	54.00	-5.82	AVG			

Job No.: ding1 #359

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: Turntable

Mode: TX 2480MHz

Model: CR6023A-NA

Manufacturer: TIMSEN

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 17/02/25/

Time: 9/03/40

Engineer Signature: DING

Distance: 3m

Note: Report NO.:ATE20170147



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.034	104.72	-5.55	99.17			peak			
2	4960.068	56.52	4.54	61.06	74.00	-12.94	peak			
3	4960.068	46.23	4.54	50.77	54.00	-3.23	QP			





**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ding1 #360	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 17/02/25/
Temp.( C)/Hum.(%) 25 C / 55 %	Time: 9/07/43
EUT: Turntable	Engineer Signature: DING
Mode: TX 2480MHz	Distance: 3m
Model: CR6023A-NA	
Manufacturer: TIMSEN	

Note: Report NO.:ATE20170147



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.034	101.45	-5.55	95.90			peak			
2	4960.068	53.82	4.54	58.36	74.00	-15.64	peak			
3	4960.068	44.23	4.54	48.77	54.00	-5.23	AVG			