

RF EXPOSURE EVALUATION REPORT

ACCORDING TO: FCC 47 CFR part 1, §1.1307, §1.1310

FOR:

Siklu Communication Ltd.

**Terminal unit of point-to-multipoint high
BW system operating in 57-66 GHz**

Model: MH-T260-CNN-N-MWB

FCC ID: 2ACYESK-MH60TG-A4

IC:12353A-MH60TGA4

This report is in conformity with ISO/ IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested.
This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.

Table of contents

1	Applicant information.....	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details.....	3
5	Tests summary.....	4
6	EUT description.....	5
6.1	General information.....	5
6.2	Transmitter characteristics	5
7	RF Exposure Evaluation.....	6
7.1	Maximum Permissive Exposure	6
7.2	MPE calculation	6
7.3	Test results of RF exposure evaluation.....	7
8	APPENDIX A Test laboratory description.....	8
9	APPENDIX B Specification references.....	8
10	APPENDIX C Abbreviations and acronyms	9

1 Applicant information

Client name: Siklu Communication Ltd.
Address: 43 Hasivim street, Petach-Tikva 49517, Israel
Telephone: +972 3921 4015
Fax: +972 3921 4162
E-mail: baruch@siklu.com
Contact name: Mr. Baruch Schwarz

2 Equipment under test attributes

Product name: Terminal unit of point-to-multipoint high BW system operating in 57-66 GHz
Product type: Transceiver
Model(s): MH-T260-CNN-N-MWB
Brand name: MultiHaul™
Serial number: FB06444487
Hardware version: A1
Software release: 1.1.1
Receipt date 24-May-21

3 Manufacturer information

Manufacturer name: Siklu Communication Ltd.
Address: 43 Hasivim street, Petach-Tikva 49517, Israel
Telephone: +972 3921 4015
Fax: +972 3921 4162
E-Mail: baruch@siklu.com
Contact name: Mr. Baruch Schwarz

4 Test details

Project ID: 42910
Location: Hermon Laboratories Ltd. Harakevet Industrial Zone, Binyamina 30500, Israel
Test started: 24-May-21
Test completed: 07-Jun-21
Test specification(s): FCC 47 CFR part 1, §1.1307, §1.1310

5 Tests summary

Test	Status
FCC Section 1.1310, RF exposure evaluation	Pass

This report is based on the test report SIKRAD_FCC.42910 issued by Hermon Laboratories.

The test results relate only to the items tested.

	Name and Title	Date	Signature
Reviewed by:	Mrs. M. Cherniavsky, certification engineer	December 13, 2021	
Approved by:	Mr. S. Samokha, Technical Manager, EMC and Radio	December 20, 2021	



6 EUT description

6.1 General information

The EUT is the Terminal Unit, model MH-T260-CNN-N-MWB. The unit operates in 57-66 GHz regulated V-band. It communicates to the MH-N366-CCP-PoE-MWB TG Distribution node using the TG protocol, acting as an end point in a fully meshed MultiHahul TG topology.

6.2 Transmitter characteristics

Type of equipment			
V	Stand-alone (Equipment with or without its own control provisions)		
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)		
	Plug-in card (Equipment intended for a variety of host systems)		
Intended use	Condition of use		
V fixed	Always at a distance more than 2 m from all people		
mobile	Always at a distance more than 20 cm from all people		
portable	May operate at a distance closer than 20 cm to human body		
Assigned frequency range	57.0 GHz – 66.0 GHz		
Operating frequency range	58320 -64800 MHz		
Test frequencies	58320 MHz, 62640 MHz, 64800 MHz		
Maximum rated output power	EIRP		
			41.30 dBm
Is transmitter output power variable?	V	No	
		continuous variable	
	Yes	stepped variable with stepsize	
		minimum RF power	
		maximum RF power	
Antenna connection			
unique coupling	standard connector	V	Integral
			with temporary RF connector
			without temporary RF connector
Antenna/s technical characteristics			
Type	Manufacturer	Model number	Gain
Patch antenna array	Siklu	PCB267	24
Transmitter 99% power bandwidth, MHz	Transmitter aggregate data rate/s, Mbps		Type of modulation
2135.1	385		16QAM
2082.2	4620		16QAM
Type of multiplexing	TDD		
Transmitter power source			
	Nominal rated voltage		Battery type
V DC	Nominal rated voltage	48 V via POE	
	Voltage range		
AC mains	Nominal rated voltage	120 V	Frequency
			60 Hz
Common power source for transmitter and receiver		V	yes
			no



HERMON LABORATORIES

7 RF Exposure Evaluation

7.1 Maximum Permissive Exposure

7.1.1 General

According to FCC CFR 47 §1.1310 the criteria listed in the Table 7.1.1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in CFR 47 §1.1307 (b).

Table 7.1.1 Limits for Maximum Permissible Exposure (MPE)

Frequency range, MHz	Electric field strength, V/m	Magnetic field strength, A/m	Power density, mW/cm ²	Average time, minutes
(A) Limits for Occupational / Control Exposures				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5.0	<6
(B) Limits for General Population / Uncontrolled Exposures				
0.3-3.0	614	1.63	*(100)	<30
3.0-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

f - frequency in MHz; * - Plane-wave equivalent power density

7.2 MPE calculation

The calculation was made in accordance with ANSI C95.1 standard and FCC OET Bulletin 65 for fixed device. The applicable exposure environment is General Population/Uncontrolled.

According to Friis transmission formula $P_d = P_T / 4\pi r^2$, where

P_d - power density in mW/cm²

$P_T = P_{out} \times G$ - highest Effective Isotropic Radiated Power (EIRP) in mW

P_{out} - highest output power to antenna in mW

G - gain of antenna in linear scale

r - distance to the centre of radiation of the antenna



HERMON LABORATORIES

7.3 Test results of RF exposure evaluation

The calculation was done to confirm required safe distance for fixed device.

Limit for power density for general population/uncontrolled exposure is $P_d = 1 \text{ mW/cm}^2$ for 1500 -100000 MHz frequency range

The minimum safe distance "r" for general population/uncontrolled exposure, where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{PT / (Px4\pi)} = \sqrt{13489 / 12.56} = 32.77 \text{ cm} \approx 33 \text{ cm.}$$

The minimum safe distance "r" for occupational exposure, where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{PT / (Px4\pi)} = \sqrt{13489 / 5 \times 12.56} = 15 \text{ cm}$$

The information note about safe distance shall be provided in the User Manual.

8 APPENDIX A Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, Radio, Safety, Environmental and Telecommunication testing facility.

Hermon Laboratories is recognized and accredited by the Federal Communications Commission (USA) for relevant parts of Code of Federal Regulations 47 (CFR 47), Test Firm Registration Number is 927748, Designation Number is IL1001; Recognized by Innovation, Science and Economic Development Canada for wireless and terminal testing (ISED), ISED #2186A, CAB identifier is IL1001; Certified by VCCI, Japan (the registration numbers for OATS are R-10808 for RE measurements below 1 GHz, G-20112 for RE measurements above 1 GHz, R-11082 for anechoic chamber for RE measurements below 1 GHz, G-10869 for RE measurements above 1 GHz, C-10845 for conducted emissions site and T-11606 for conducted emissions at telecommunication ports).

The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing, environmental simulation and calibration (for exact scope please refer to Certificate No. 839.01, 839.03 and 839.04).

Address: P.O. Box 23, Binyamina 3055001, Israel.
Telephone: +972 4628 8001
Fax: +972 4628 8277
e-mail: mail@hermonlabs.com
website: www.hermonlabs.com

Person for contact: Mr. Michael Nikishin, EMC&Radio group manager

9 APPENDIX B Specification references

FCC 47CFR part 1: 2020	Practice and Procedure; Subpart I—Procedures Implementing the National Environmental Policy Act of 1969
ANSI C95.1™-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
IEEE Std C95.1™-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
OET Bulletin 65:1997	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

10 APPENDIX C Abbreviations and acronyms

cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
EIRP	equivalent isotropically radiated power
EUT	equipment under test
F	frequency
G	antenna gain
GHz	gigahertz
HL	Hermon laboratories
m	meter
MHz	megahertz
min	minute
mW	milliwatt
NA	not applicable
RF	radio frequency
Rx	receive
s	second
Tx	transmit
W	watt

END OF REPORT

11