

Test Report

FCC ID:2ACYP-YN900II

Date of issue: Mar. 14, 2018

Report Number:	MTi180314E048
Sample Description:	Pro LED Video Light
Model(s):	YN900 II
Applicant:	SHENZHEN YONGNUO PHOTOGRAPHIC EQUIPMENT CO., LTD.
Address:	Building A, Shenfubao modern optics factory, Kengzi Street, Pingshan District, Shenzhen
Date of Test:	Mar. 06, 2018 to Mar. 14, 2018

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>

Table of Contents

1. GENERAL INFORMATION	5
1.1. DESCRIPTION OF EUT	5
1.2. OPERATION CHANNEL LIST	5
1.3. TEST CHANNEL LIST	6
1.4. ANCILLARY EQUIPMENT LIST	6
1.5. DESCRIPTION OF SUPPORT UNITS	6
2. SUMMARY OF TEST RESULTS	7
3. TEST FACILITIES AND ACCREDITATIONS	8
3.1. TEST LABORATORY	8
3.2. ENVIRONMENTAL CONDITIONS	8
3.3. MEASUREMENT UNCERTAINTY	8
3.4. TEST SOFTWARE	8
4. EQUIPMENT LIST	9
5. TEST RESULT	10
5.1. ANTENNA REQUIREMENT	10
5.1.1 <i>Standard requirement</i>	10
5.1.2 <i>EUT Antenna</i>	10
5.2. PEAK OUTPUT POWER TEST	11
5.2.1 <i>Limit</i>	11
5.2.2 <i>Test setup</i>	11
5.2.3 <i>Test procedure</i>	11
5.2.4 <i>EUT operation condition</i>	11
5.2.5 <i>Test results</i>	11
5.3. CONDUCTED EMISSION	14
5.3.1 <i>Limits</i>	14
5.3.2 <i>Test setup</i>	14
5.3.3 <i>Test procedure</i>	15
5.3.4 <i>Test results</i>	15
5.4. RADIATED SPURIOUS EMISSION	18
5.4.1 <i>Limits</i>	18
5.4.2 <i>Test setup</i>	19
5.4.3 <i>Test procedure</i>	20
5.4.4 <i>Test results</i>	21
5.4.4.1 <i>Radiation emission</i>	21
5.4.4.2 <i>Bandedge-radiated</i>	25
5.5. POWER SPECTRAL DENSITY TEST	26
5.5.1 <i>Limit</i>	26
5.5.2 <i>Test procedure</i>	26
5.5.3 <i>Test setup</i>	26
5.5.4 <i>EUT operation conditions</i>	26
5.5.5 <i>Test results</i>	27
5.6. 6DB BANDWIDTH	29
5.6.1 <i>Limit</i>	29
5.6.2 <i>TEST PROCEDURE</i>	29
5.6.3 <i>TEST SETUP</i>	29
5.6.4 <i>EUT operation conditions</i>	29
5.6.5 <i>Test Result</i>	29
5.7. CONDUCTED SPURIOUS EMISSION	32
5.7.1 <i>Limits</i>	32
5.7.2 <i>Test setup</i>	32
5.7.3 <i>Test procedure</i>	32

5.7.4 EUT operation conditions32

5.7.5 Test Result32

EUT TEST PHOTO..... 35

PRODUCT INFORMATION

Applicant's name: SHENZHEN YONGNUO PHOTOGRAPHIC EQUIPMENT CO., LTD.

Address: Building A, Shenfubao modern optics factory, Kengzi Street, Pingshan District, Shenzhen

Manufacture's Name: Shenzhen Yongnuo photographic equipment Co., Ltd Dalang plant

Address: 4/F&5/F East Building 2, Donglongxing Technology Park, East Huaning Road, Dalang Street, Longhua District, Shenzhen, Guangdong. P.R. China

Product name: Pro LED Video Light

Trademark: YONGNUO

Model name: YN900 II

Standards: FCC Part 15.247

Test Procedure: ANSI C63.10:2013

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Amy Lu

Amy Lu

Mar. 14, 2018

Reviewed by:

Blue Zheng

Blue Zheng

Mar. 14, 2018

Approved by:

Smith Chen

Smith Chen

Mar. 14, 2018

1. General Information

1.1. Description of EUT

Equipment	Pro LED Video Light	
Trade Name	YONGNUO	
Model Name	YN900 II	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Pro LED Video Light	
	Operation Frequency:	BLE: 2402-2480MHz
	Modulation Type:	GFSK
	Bit Rate of Transmitter	1Mbps
	Number Of Channel	40
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	BLE: -2.472dBm (Max.)
	Antenna Type:	PCB Antenna
	Antenna Gain (dBi)	0dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 1.	
Power supply	DC 19V from DC power	
Connecting I/O Port(s)	Please refer to the User's Manual	
Hardware Version	V1.0	
Software Version	V1.0	
Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.2. Operation channel list

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474

7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

1.3. Test channel list

Channel	Channel	Frequency (MHz)
Low	00	2402
Middle	19	2440
High	39	2480

1.4. Ancillary equipment list

Equipment	Model	S/N	Manufacturer	Certificate type
DC Power	QJ3020E	009510	/	/

1.5. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
/	/	/	/	/	
/	/	/	/	/	

Note:

(1)The support equipment was authorized by Declaration of Confirmation.

(2)For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2. Summary of Test Results

Test procedures according to the technical standards:

No.	Standard Section	Test Item	Result	Remark
1	15.207	Conducted Emission	Pass	
2	15.247 (a)(2)	6dB Bandwidth	Pass	
3	15.247 (b)	Peak Output Power	Pass	
4	15.247 (c)	Radiated Spurious Emission	Pass	
5	15.247 (d)	Power Spectral Density	Pass	
6	15.205	Band Edge Emission	Pass	
7	15.203	Antenna Requirement	Pass	

3. Test Facilities and Accreditations

3.1. Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China
FCC Registration No.:	448573

3.2. Environmental conditions

Temperature:	20°C~30°C
Humidity	30%~70%
Atmospheric pressure	98kPa~101kPa

3.3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$ where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3.4. Test software

Software Name	Manufacturer	Model	Version
RF Test System	Farad	LZ-RF	Lz_Rf 3A3

4. Equipment list

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E001	Spectrum Analyzer	Agilent	E4407B	MY41441082	2017/09/18	2018/09/17
MTI-E002	CMU 200 universal radio communication tester	Rohde&schwarz	CMU 200	114587	2017/09/18	2018/09/17
MTI-E004	EMI Test Receiver	Rohde&schwarz	ESPI	1000314	2017/09/18	2018/09/17
MTI-E006	Broadband antenna	schwarabeck	VULB9163	872	2017/09/18	2018/09/17
MTI-E007	Horn antenna	schwarabeck	BBHA9120D	1201	2017/09/18	2018/09/17
MTI-E014	amplifier	America	8447D	3113A06150	2017/09/18	2018/09/17
MTI-E015	Conduction Immunity Signal Generator	Schloder	CDG6000	126A1343/2015	2017/09/18	2018/09/17
MTI-E016	Coupled decoupling network	Schloder	CDA M2/M3	A2210332/2015	2017/09/18	2018/09/17
MTI-E032	Comprehensive test instrument	Rohde&schwarz	CMW500	124192	2017/04/13	2018/04/12
MTI-E034	amplifier	Agilent	8449B	3008A02400	2017/08/22	2018/08/21
MTI-E040	Spectrum analyzer	Agilent	N9020A	MY49100060	2018/03/04	2019/03/04
MTI-E041	Signal generator	Agilent	N5182A	MY49060455	2018/02/22	2019/02/22
MTI-E042	Analog signal generator	Agilent	E4421B	GB40051240	2018/02/22	2019/02/22
MTI-E043	Power probe	Dare Instruments	RPR3006W	16I00054SN016	2018/02/28	2019/02/28
MTI-E047	10dB attenuator	Mini-Circuits	UNAT-10+	15542	2017/05/23	2018/05/23
MTI-E049	spectrum analyzer	Rohde&schwarz	FSP-38	100019	2017/09/18	2018/09/17
MTI-E050	PSG Signal generator	Agilent	E8257D	MY46520873	2017/04/24	2018/04/23
MTI-E051	Active Loop Antenna 9kHz - 30MHz	Schwarzbeek	FMZB 1519 B	00044	2018//2/26	2019/02/25
MTI-E052	18-40GHz amplifier	Chengdu step Micro Technology	ZLNA-18-40G-21	1608001	2017/09/18	2018/09/17
MTI-E053	15-40G Antenna	Schwarzbeek	BBHA9170	BBHA9170582	2017/09/18	2018/09/17
Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).						

5. Test Result

5.1. Antenna requirement

5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT Antenna

The EUT antenna is integrated antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2. Peak output power test

5.2.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.2.2 Test setup



5.2.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
 RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)
 RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.2.4 EUT operation condition

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.2.5 Test results


EUT :	Pro LED Video Light	Model Name :	YN900 II
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 19V from DC power

TX BLE mode


Test Channe	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
CH01	2402	-2.472	30
CH20	2440	-3.099	30
CH40	2480	-3.856	30

///


2402MHz



2440MHz



2480MHz



5.3. Conducted emission

5.3.1 Limits


FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note

(1)The tighter limit applies at the band edges.

(2)The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.3.2 Test setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

5.3.3 Test procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item –EUT Test Photos.


5.3.4 Test results

EUT:	Pro LED Video Light	Model Name. :	YN900 II
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 19V from DC power	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.4282	46.18	0.02	46.20	57.29	-11.09	QP	
2		0.4282	31.67	0.02	31.69	47.29	-15.60	AVG	
3		0.7632	37.21	0.02	37.23	56.00	-18.77	QP	
4		0.7632	18.84	0.02	18.86	46.00	-27.14	AVG	
5		1.2047	36.93	0.02	36.95	56.00	-19.05	QP	
6		1.2047	21.97	0.02	21.99	46.00	-24.01	AVG	
7		2.1304	35.01	0.02	35.03	56.00	-20.97	QP	
8		2.1304	21.40	0.02	21.42	46.00	-24.58	AVG	
9		3.0977	33.52	0.04	33.56	56.00	-22.44	QP	
10		3.0977	21.97	0.04	22.01	46.00	-23.99	AVG	
11		17.2070	34.52	0.09	34.61	60.00	-25.39	QP	
12		17.2070	27.38	0.09	27.47	50.00	-22.53	AVG	

EUT:	Pro LED Video Light	Model Name. :	YN900 II
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 19V from DC power	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.4391	46.85	0.02	46.87	57.08	-10.21	QP	
2		0.4391	35.44	0.02	35.46	47.08	-11.62	AVG	
3		0.5172	40.38	0.02	40.40	56.00	-15.60	QP	
4		0.5172	27.23	0.02	27.25	46.00	-18.75	AVG	
5		1.2944	38.32	0.02	38.34	56.00	-17.66	QP	
6		1.2944	24.73	0.02	24.75	46.00	-21.25	AVG	
7		2.1969	36.72	0.02	36.74	56.00	-19.26	QP	
8		2.1969	23.73	0.02	23.75	46.00	-22.25	AVG	
9		3.0901	35.74	0.04	35.78	56.00	-20.22	QP	
10		3.0901	24.20	0.04	24.24	46.00	-21.76	AVG	
11		6.5859	33.28	0.08	33.36	60.00	-26.64	QP	
12		6.5859	25.15	0.08	25.23	50.00	-24.77	AVG	

5.4 Radiated spurious emission

5.4.1 Limits


Frequency (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.4.2 Test setup


Radiated emission test-up frequency below 30MHz



Radiated emission test-up frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



5.4.3 Test procedure

- a. EUT operating conditions. The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.
- b. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- c. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter shield area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- g. For the actual test configuration, please refer to the related Item –EUT Test photos.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.4.4 Test results

5.4.4.1 Radiation emission

Below 30MHz

EUT:	Pro LED Video Light	Model Name:	YN900 II
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage:	DC 19V from DC power
Test Mode:	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.


Between 30MHz – 1GHz:

EUT :	Pro LED Video Light	Model Name. :	YN900 II
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	H
Test Voltage :	DC 19V from DC power	Test Mode :	TX Mode



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		63.7588	39.25	-12.12	27.10	40.00	-12.87	QP		
2	*	95.7622	47.31	-12.14	35.10	43.50	-8.33	QP		
3		111.7380	46.56	-11.73	34.80	43.50	-8.67	QP		
4		159.7844	45.20	-14.06	31.10	43.50	-12.36	QP		
5		191.7450	45.47	-12.99	32.40	43.50	-11.02	QP		
6		545.1826	39.54	-5.20	34.30	46.00	-11.66	QP		

EUT :	Pro LED Video Light	Model Name. :	YN900 II
Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	V
Test Voltage :	DC 19V from DC power	Test Mode :	TX Mode



1G-25GHz
GFSK

Normal Voltage

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (2402 MHz)							
H	4803.82	52.68	-3.08	49.6	74	-24.4	Peak
H	4803.96	51.87	-6.41	45.46	74	-28.54	Peak
H	7205.97	52.08	-3.51	48.57	74	-25.43	Peak
H	7206.57	53.37	-2.40	50.97	74	-23.03	Peak
H	9608.50	51.18	0.17	51.35	74	-22.65	Peak
H	9608.74	51.55	1.47	53.02	74	-20.98	Peak
V	4804.22	50.81	-2.24	48.57	74	-25.43	Peak
V	4803.88	45.81	-3.55	42.26	74	-31.74	Peak
V	7206.66	49.22	-2.36	46.86	74	-27.14	Peak
V	7206.13	50.95	-1.39	49.56	74	-24.44	Peak
V	9608.01	50.93	1.91	52.84	74	-21.16	Peak
V	9607.80	49.83	2.74	52.57	74	-21.43	Peak
Mid Channel (2440 MHz)							
H	4880.35	49.58	-2.73	46.85	74	-27.15	Peak
H	4880.86	51.23	-3.61	47.62	74	-26.38	Peak
H	7319.94	51.98	0.53	52.51	74	-21.49	Peak
H	7320.61	49.47	2.02	51.49	74	-22.51	Peak
H	9759.76	47.97	2.53	50.5	74	-23.5	Peak
H	9760.28	48.27	2.14	50.41	74	-23.59	Peak
V	2480.62	46.43	-2.84	43.59	74	-30.41	Peak
V	2480.40	49.07	-4.95	44.12	74	-29.88	Peak
V	7319.77	49.80	-2.90	46.9	74	-27.1	Peak
V	7319.88	49.63	-1.81	47.82	74	-26.18	Peak
V	9760.72	52.55	0.80	53.35	74	-20.65	Peak
V	9759.98	46.67	2.72	49.39	74	-24.61	Peak
High Channel (2480 MHz)							
H	4960.40	51.67	-2.75	48.92	74	-25.08	Peak
H	4960.39	50.88	-5.07	45.81	74	-28.19	Peak
H	7440.17	51.68	-3.71	47.97	74	-26.03	Peak
H	7440.33	52.28	0.66	52.94	74	-21.06	Peak
H	9919.83	50.35	1.45	51.8	74	-22.2	Peak
H	9920.11	51.24	1.86	53.1	74	-20.9	Peak
V	4960.01	50.80	-2.16	48.64	74	-25.36	Peak
V	4959.92	45.70	-1.99	43.71	74	-30.29	Peak
V	7440.34	48.47	0.28	48.75	74	-25.25	Peak
V	7439.66	50.07	2.31	52.38	74	-21.62	Peak
V	9920.72	50.49	2.82	53.31	74	-20.69	Peak
V	9920.10	50.36	2.94	53.3	74	-20.7	Peak

Note1 : Absolute Level = Reading Level+ Factor, Margin= Absolute Level- Limit, Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Note2 :The peak value is less than the AV value, AV value is not required Factor added by measurement software automatically.

5.4.4.2 Bandedge-radiated

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
BLE							
2385.730	62.07	-10.42	51.65	74	-22.35	peak	Vertical
2400.000	59.62	-10.31	49.31	74	-24.69	peak	Vertical
2386.960	52.25	-9.55	42.70	74	-31.30	peak	Horizontal
2400.000	54.54	-9.43	45.11	74	-28.89	peak	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
BLE							
2483.500	55.71	-9.73	45.98	74	-28.02	peak	Vertical
2491.200	54.24	-9.67	44.57	74	-29.43	peak	Vertical
2483.500	56.88	-8.66	48.22	74	-25.78	peak	Horizontal
2488.500	54.13	-8.61	45.52	74	-28.48	peak	Horizontal

Note1 : Absolute Level = Reading Level+ Factor, Margin= Absolute Level- Limit, Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Note2 :The peak value is less than the AV value, AV value is not required Factor added by measurement software automatically.

5.5 Power spectral density test

5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5

5.5.2 Test procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.3 Test setup




5.5.4 EUT operation conditions



The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing

5.5.5 Test results

EUT :	Pro LED Video Light	Model Name :	YN900 II
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 19V from DC power
Test Mode :	TX Mode /CH00, CH19, CH39		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2402 MHz	-16.757	8	PASS
2440 MHz	-16.645	8	PASS
2480 MHz	-17.668	8	PASS





5.6 6dB bandwidth


5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5

5.6.2 TEST PROCEDURE

1. Set RBW= 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 TEST SETUP




5.6.4 EUT operation conditions


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing

5.6.5 Test Result

EUT :	Pro LED Video Light	Model Name :	YN900 II
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 19V from DC power
Test Mode :	TX Mode /CH00, CH19, CH39		

Channel	Frequency (MHz)	6dB bandwidth (KHz)	Limit (kHz)	Result
Low	2402	699.3	500	Pass
Middle	2440	716.6	500	Pass
High	2480	697.0	500	Pass





5.7 Conducted spurious emission

5.7.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.7.2 Test setup



5.7.3 Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

5.7.4 EUT operation conditions


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing

5.7.5 Test Result


EUT :	Pro LED Video Light	Model Name :	YN900 II
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 19V from DC power

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
BLE mode			
Left-band	37.91	20	Pass
Right-band	46.18	20	Pass

BLE: Band Edge, Left Side



BLE: Band Edge, Right Side




EUT TEST PHOTO

Radiated emission – below 1GHz



Radiated emission – above 1GHz



Conducted emission



---END OF REPORT---