

FCC/IC - TEST REPORT

Report Number : **68.760.14.215.01** Date of Issue: August 5, 2014

Model : See Page 4

Product Type : LED Interactive Multi-Touch Display

Applicant : SHENZHEN Hitevision Technology Co., Ltd.

Address : 1th-3th floor and 6th floor No.1 Building 1th floor No.2 Building,
1th floor No.4 Building, HongHui Industrial Park, Liu Xian No.2
Road, Xin An District, Shenzhen

Production Facility : SHENZHEN Hitevision Technology Co., Ltd.

Address : 1th-3th floor and 6th floor No.1 Building 1th floor No.2 Building,
1th floor No.4 Building, HongHui Industrial Park, Liu Xian No.2
Road, Xin An District, Shenzhen

Test Result : **Positive** **Negative**

Total pages including
 Appendices : 17

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.



1 Table of Contents

1 Table of Contents	2
2 Details about the Test Laboratory	3
3 Description of the Equipment Under Test	4
4 Summary of Test Standards	5
5 Summary of Test Results.....	6
6 General Remarks.....	7
7 Systems test configuration.....	8
8 Technical Requirement.....	9
8.1 Conducted Emission Test.....	9
8.2 Radiated Emission Test 30MHz – 1000MHz	13
8.3 Radiated Emission Test 1GHz – 6GHz.....	15

2 Details about the Test Laboratory

Details about the Test Laboratory

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2, Nanshan District,
Shenzhen City, 518052,
P. R. China

Telephone: 86 755 8828 6998
Fax: 86 755 8828 5299

Test Site 2

Company name: Shenzhen CTL Testing Technology Co., Ltd
Floor 1-A, Baisha Technology Park, No.3011, Shahehexi Road, Nanshan District,
Shenzhen, China 518055

FCC Registration
No: 970318

Telephone: 86 755 8948 6194

3 Description of the Equipment Under Test

Product:	LED Interactive Multi-Touch Display
Model no.:	65GT-X 、EPR8AX0065 、QIT1X65 、TWB-N65 、TWB-NB65 、TWB-N65X 、TWB-NB65X 、OTS-65VX 、OTS-65V2 、OTS-65X 、P-65 、X-65 、P-65X 、TID-65 、TID-65X 、Avtek TouchScreen 65P 、Avtek TouchScreen 65X 、65GT 、65GT-X (standard) 、65GT-X (deluxe) 、65GT(standard) 、65GT(deluxe) 、CCS-TS-650X-CA 、HD-I65XXE 、WS-Z65XX 、WS-Z65AX 、WB-E65X 、WB-L65X 、WB-N65X 、WB-K65X 、WB-Z65X 、TT-6514X ("X" represent 0-9 random numbers or A-Z random letters)
FCC ID:	2ACYT-06965
IC ID:	NIL
Brand Name:	Hitevision
Options and accessories:	1KHz Color Bar and the program of "H"
Rating:	100-240VAC~50/60Hz, Max 4.5A
Description of the EUT:	Class B Equipment

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart B 10-1-13 Edition	Unintentional Radiators
ICES-003 Issue 5 August 2012	Information Technology Equipment (ITE) – Limits and methods of measurement



5 Summary of Test Results

Emission Tests				
FCC Part 15 Subpart B 10-1-13 Edition/ICES-003 Issue 5				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
Conducted Emission on AC 150kHz to 30MHz	9	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Emission 30MHz to 1000MHz	13	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Emission 1GHz to 6GHz	15	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

6 General Remarks

Remarks

The model 65GT-X(Non-intelligent) and other models are identical except the model name, so all the EMC requirements were applied on 65GT-X(Non-intelligent) and other models are deemed to fulfill the relevant EMC requirements without further testing.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: Jane 13, 2014


Testing Start Date: Jane 16, 2014

Testing End Date: August 5, 2014

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:

Prepared by:



John Zhi
EMC Project Manager

Alan Xiong
EMC Project Engineer

7 Systems test configuration

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Configuration List:

TEST MODE	DESCRIPTION	REMARK
TC1	VGA In	Connect to Notebook
TC2	HDMI In	Connect to Notebook
TC3	USB In	Connect to U-Disk
TC4	Audio & Video In	Connect to DVD Player
TC5	Audio & Video Out	Connect to Display
TC6	YPbPr In	Connect to DVD Player

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
PC	DELL	INSPIRON 3420	---

Auxiliary Cable List and Details:

CABLE DESCRIPTION	LENGTH (M)	SHIELDED/ UNSHIELDED	WITH CORE/ WITHOUT CORE
HDMI Cable	1.6	Shielded	Without Core
AV Cable	1.65	Unshielded	Without Core
VGA Cable	1.6	Shielded	Without Core
WAN Cable	1.5	Unshielded	Without Core

The EUT has been tested under two frequencies of input voltage (50Hz, 60Hz) and Six operational models (VGA In, HDMI In, USB In, AV In, AV Out and YPbPr In), the worst test result are listed in the report.

8 Technical Requirement

8.1 Conducted Emission Test

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Limit


According to §15.107, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : LED Interactive Multi-Touch Display
 M/N : 65GT-X
 Operating Condition : VGA In
 Test Specification : Line
 Comment : AC 120V/60Hz



MEASUREMENT RESULT: "071428_fin"

7/14/2014 21:57

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.200000	51.00	11.3	64	12.6	QP	L1	GND
0.265000	42.30	11.1	61	19.0	QP	L1	GND
0.990000	34.90	10.5	56	21.1	QP	L1	GND
1.185000	34.30	10.4	56	21.7	QP	L1	GND
2.110000	35.60	10.4	56	20.4	QP	L1	GND
3.765000	33.10	10.4	56	22.9	QP	L1	GND


MEASUREMENT RESULT: "071428_fin2"

7/14/2014 21:57

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.195000	46.70	11.5	54	7.1	AV	L1	GND
0.265000	38.50	11.1	51	12.8	AV	L1	GND
0.330000	33.60	10.9	50	15.9	AV	L1	GND
0.460000	28.10	10.6	47	18.6	AV	L1	GND
0.990000	27.00	10.5	46	19.0	AV	L1	GND
1.185000	27.20	10.4	46	18.8	AV	L1	GND

Conducted Emission

Product Type : LED Interactive Multi-Touch Display
 M/N : 65GT-X
 Operating Condition : VGA In
 Test Specification : Neutral
 Comment : AC 120V/60Hz



MEASUREMENT RESULT: "071429_fin"

7/14/2014 22:00

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.200000	51.00	11.3	64	12.6	QP	N	GND
0.265000	42.70	11.1	61	18.6	QP	N	GND
1.190000	34.30	10.4	56	21.7	QP	N	GND
2.110000	35.10	10.4	56	20.9	QP	N	GND
2.635000	33.90	10.4	56	22.1	QP	N	GND
3.760000	34.90	10.4	56	21.1	QP	N	GND

MEASUREMENT RESULT: "071429_fin2"

7/14/2014 22:00


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.200000	47.50	11.3	54	6.1	AV	N	GND
0.265000	38.50	11.1	51	12.8	AV	N	GND
0.330000	33.50	10.9	50	16.0	AV	N	GND
0.460000	27.60	10.6	47	19.1	AV	N	GND
0.640000	25.60	10.4	46	20.4	AV	N	GND
8.190000	31.20	10.6	50	18.8	AV	N	GND

Test Equipment List**Conducted emission test**

Equipment	Manufacturer	Model No.	Serial No.	Cal. due. date
EMI Test Receiver	R&S	ESCI	100687	2014.11.21
Teo Line Single Phase Module	R&S	ENV216	8128247	2014.11.21
10dB attenuator	SCHWARZCECK	VTSD 9561F	836	2014.11.21

8.2 Radiated Emission Test 30MHz – 1000MHz

Product Type : LED Interactive Multi-Touch Display
 M/N : 65GT-X
 Operating Condition : VGA In
 Ant. Polarity : Vertical
 Comment : 30-1000MHz




MEASUREMENT RESULT: "HH071812_red"

7/18/2014 14:45

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
53.280000	33.40	15.7	40.0	6.6	---	100.0	0.00	VERTICAL
57.160000	35.50	15.1	40.0	4.5	---	100.0	0.00	VERTICAL
117.300000	38.40	15.1	43.5	5.1	QP	100.0	0.00	VERTICAL
134.760000	38.50	12.7	43.5	5.0	QP	100.0	0.00	VERTICAL
270.560000	40.50	17.8	46.0	5.5	---	100.0	0.00	VERTICAL
625.580000	38.00	26.1	46.0	8.0	---	100.0	0.00	VERTICAL

Radiated Emission Test 30MHz – 1000MHz

Product Type : LED Interactive Multi-Touch Display
 M/N : 65GT-X
 Operating Condition : VGA In
 Ant. Polarity : Horizontal
 Comment : 30-1000MHz




MEASUREMENT RESULT: "HH071811_red"

7/18/2014 14:43

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
55.220000	32.00	15.6	40.0	8.0	---	100.0	0.00	HORIZONTAL
86.260000	31.90	14.8	40.0	8.1	---	100.0	0.00	HORIZONTAL
121.180000	40.50	14.5	43.5	3.0	---	300.0	0.00	HORIZONTAL
173.560000	36.90	13.4	43.5	6.6	---	100.0	0.00	HORIZONTAL
270.560000	40.60	17.8	46.0	5.4	---	100.0	0.00	HORIZONTAL
608.120000	40.90	26.0	46.0	5.1	---	100.0	0.00	HORIZONTAL

8.3 Radiated Emission Test 1GHz – 6GHz

Product Type : LED Interactive Multi-Touch Display
 M/N : 65GT-X
 Operating Condition : VGA In
 Ant. Polarity : Vertical
 Comment : 1GHz-6GHz



MEASUREMENT RESULT: "0805 11_red"

8/5/2014 10:03

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
5710.000000	46.50	3.4	74.0	27.5	---	100.0	0.00	VERTICAL


MEASUREMENT RESULT: "0805 11_red2"

8/5/2014 10:03

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
3260.000000	28.00	-6.1	54.0	26.0	---	100.0	0.00	VERTICAL
4420.000000	30.40	-2.9	54.0	23.6	---	100.0	0.00	VERTICAL
5530.000000	35.70	3.9	54.0	18.3	---	100.0	0.00	VERTICAL

Radiated Emission Test 1GHz – 6GHz

Product Type : LED Interactive Multi-Touch Display
 M/N : 65GT-X
 Operating Condition : VGA In
 Ant. Polarity : Horizontal
 Comment : 1GHz-6GHz



MEASUREMENT RESULT: "0805 12_red"

8/5/2014 10:06

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
5490.000000	46.80	3.8	74.0	27.2	---	100.0	0.00	HORIZONTAL

MEASUREMENT RESULT: "0805 12_red2"

8/5/2014 10:06

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
3250.000000	28.10	-6.2	54.0	25.9	---	100.0	0.00	HORIZONTAL
4330.000000	30.50	-3.2	54.0	23.5	---	100.0	0.00	HORIZONTAL
5610.000000	35.80	3.7	54.0	18.2	---	100.0	0.00	HORIZONTAL

Test Equipment List

Radiated Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	R&S	ESCI	100687	2014.11.21
EMI Test Receiver	R&S	ESPI	100097	2014.11.21
TRILOG Broadband Test-Antenna	Sunol Sciences Corp.	JB1	9163-324	2014.11.21
Horn Antenna	Sunol Sciences Corp.	DRH-118	0499	2014.11.21
EMI Test Receiver	R&S	ESCI	100687	2014.11.21