

Report No.: SZEM150700425802

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 114

FCC REPORT

Application No: SZEM1507004258CR

Applicant: SHENZHEN Hitevision Technology Co., Ltd.

Manufacturer: Newline Interactive Inc.

Factory: SHENZHEN Hitevision Technology Co., Ltd.

Product Name: Collaboration Touch Screen

Model No.(EUT): X7

Add Model No.: X7-x, X7-xx, X7-xxx (x = 0-9, a-z or A-Z)

FCC ID: 2ACYTBHHX7-000

Standards: 47 CFR Part 15, Subpart C (2014)

Date of Receipt: 2015-07-20

Date of Test: 2015-08-27 to 2015-09-02

Date of Issue: 2015-09-07

Test Result: PASS *

. * In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM150700425802

Page: 2 of 114

2 Version

Revision Record									
Version	Version Chapter Date Modifier Remark								
00		2015-09-07		Original					

Authorized for issue by:		
	Eric Fu	2015-09-02
Tested By	(Eric Fu) /Project Engineer	Date
	Heely Wen.	2015-09-07
Prepared By	(Hedy Wen) /Clerk	Date
	Chros Thong	2015-09-07
Checked By	(Chris Zhong) /Reviewer	Date



Report No.: SZEM150700425802

Page: 3 of 114

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2009	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2009	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2009	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

Remark:

Model No.: X7, X7-x, X7-xx, X7-xxx (x =0-9, a-z or A-Z)

Only the model X7 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, only different on outlook silkprint, color and model number.



Report No.: SZEM150700425802

Page: 4 of 114

4 Contents

			Page
1	COV	'ER PAGE	1
2	VER	SION	2
3	TES	T SUMMARY	3
4	CON	ITENTS	4
5	GEN	IERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT	5
	5.3	TEST ENVIRONMENT AND MODE	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	
	5.7	DEVIATION FROM STANDARDS	_
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	
6	TES	T RESULTS AND MEASUREMENT DATA	12
	6.1	ANTENNA REQUIREMENT	12
	6.2	CONDUCTED EMISSIONS	13
	6.3	CONDUCTED PEAK OUTPUT POWER	17
	6.4	6DB OCCUPY BANDWIDTH	
	6.5	Power Spectral Density	
	6.6	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.7	RF CONDUCTED SPURIOUS EMISSIONS	
	6.8	RADIATED SPURIOUS EMISSIONS	
	6.8.1		
	6.8.2		
	6.9	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PHO	TOGRAPHS - EUT TEST SETUP	113
	7.1	CONDUCTED EMISSION	113
	7.2	RADIATED EMISSION	
	7.3	RADIATED SPURIOUS EMISSION	114
8	PHO	TOGRAPHS - EUT CONSTRUCTIONAL DETAILS	114



Report No.: SZEM150700425802

Page: 5 of 114

5 General Information

5.1 Client Information

Applicant:	SHENZHEN Hitevision Technology Co., Ltd.			
Address of Applicant:	No. 8, Qinglan 1st Road, Pingshan, Shenzhen, Guangdong 518118, P. R. China.			
Manufacturer:	Newline Interactive Inc.			
Address of Manufacturer:	101 East Park Blvd. Suite 807 Plano, TX 75074, USA			
Factory:	SHENZHEN Hitevision Technology Co., Ltd.			
Address of Factory:	No. 8, Qinglan 1st Road, Pingshan, Shenzhen, Guangdong 518118, P. R. China.			

5.2 General Description of EUT

Draduat Name	Callaboration Touch Corean
Product Name:	Collaboration Touch Screen
Model No.:	X7
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
	IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n(HT20): 11 Channels
	IEEE 802.11n(HT40): 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)
	IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Sample Type:	Fixed production
Test Power Grade:	11B: 40; 11G: 45; 11N: 45 (manufacturer declare)
Antenna Gain:	3dBi
Power Supply:	Input voltage: AC100-240V 50/60Hz Max 4.5A
	DC 3V (1.5V*2 Size "AAA" battery) for remote control



Report No.: SZEM150700425802

Page: 6 of 114

Operation Frequency each of channel(802.11b/g/n HT20)												
Channel	Fr	equency	Channe	I Frequency	Channel	Fre	quency	Chan	nel	Frequency		
1	24	112MHz	4	2427MHz	7	244	2442MHz)	2457MHz		
2	24	117MHz	5	2432MHz	8	244	2447MHz		47MHz 11			2462MHz
3	24	122MHz	6	2437MHz	9	245	2452MHz					
Operation F	requ	ency each	of channe	el(802.11n HT40)							
Channel Frequency			ency	Channel	Frequen	су	Chan	nel	ſ	requency		
1		2422	ИНz	4	2437MF	lz	7			2452MHz		
2		2427	MHz	5	5 2442MHz							
3 2432MHz				6	2447MF	lz						

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz



Report No.: SZEM150700425802

Page: 7 of 114

5.3 Test Environment and Mode

Operating Environment:	Operating Environment:							
Temperature:	24.0 °C							
Humidity:	52 % RH							
Atmospheric Pressure:	1010 mbar							
Test mode:								
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.							

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM150700425802

Page: 8 of 114

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM150700425802

Page: 9 of 114

5.10Equipment List

	Conducted Emission								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)			
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-05-13	2016-05-13			
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2014-10-24	2015-10-24			
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-13	2016-05-13			
4	8 Line ISN	Fischer Custom Communications Inc.	FCC- TLISN-T8- 02	SEL0162	2015-08-30	2016-08-30			
5	4 Line ISN	Fischer Custom Communications Inc.	FCC- TLISN-T4- 02	SEL0163	2015-08-30	2016-08-30			
6	2 Line ISN	Fischer Custom Communications Inc.	FCC- TLISN-T2- 02	SEL0164	2015-08-30	2016-08-30			
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-13	2016-05-13			
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-13	2016-05-13			
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24			
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24	2015-10-24			
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13			





Report No.: SZEM150700425802

Page: 10 of 114

RE in Chamber								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)		
1	3m Semi- Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-05-13	2016-05-13		
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	2016-09-16		
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A		
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-10-24	2015-10-24		
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2014-10-24	2015-10-24		
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-11-24	2015-11-24		
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-13	2016-05-13		
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2014-10-24	2015-10-24		
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-13	2016-05-13		
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-13	2016-05-13		
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-13	2016-05-13		
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13		
13	Band filter	Amindeon	82346	SEL0094	2015-05-13	2016-05-13		
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13		
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24		
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24	2015-10-24		
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-13	2016-05-13		
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2014-10-24	2015-10-24		
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-05-13	2016-05-13		



Report No.: SZEM150700425802

Page: 11 of 114

	RF connected test						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)	
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24	
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2014-10-24	2015-10-24	
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2014-10-24	2015-10-24	
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13	
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13	
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13	
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25	
8	Band filter	amideon	82346	SEL0094	2015-05-13	2016-05-13	
9	POWER METER	R&S	NRVS	SEL0144	2014-10-24	2015-10-24	
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-04-25	2016-04-25	
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2014-10-24	2015-10-24	



Report No.: SZEM150700425802

Page: 12 of 114

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard 47 CFR Part 15C Section 15.203 /247(c) requirement:


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3dBi.



Report No.: SZEM150700425802

Page: 13 of 114


6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207				
Test Method:	ANSI C63.10: 2009				
Test Frequency Range:	150kHz to 30MHz				
Limit:	Limit (dBuV)				
	Frequency range (MHz)	Quasi-peak	Average		
	0.15-0.5	66 to 56*	56 to 46*		
	0.5-5	56	46		
	5-30	60	50		
	* Decreases with the logarithm	n of the frequency.		•	
Test Procedure:	 The mains terminal disturb room. The EUT was connected 	Ç			
	Impedance Stabilization Network) which provides a $50\Omega/50\mu H + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.				
	 The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 				
	5) In order to find the maximum emission, the relative positions equipment and all of the interface cables must be changed according ANSI C63.10: 2009 on conducted measurement.				



Report No.: SZEM150700425802

Page: 14 of 114





Report No.: SZEM150700425802


Page: 15 of 114

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:



Site : Shielding Room

Condition : 47 CFR PART15C AV CE LINE

Job No. : 4258CR Test Mode : TX+charge


	Freq		LISN Factor					Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17215	0.02	9.82	39.74	49.59	54.86	-5.27	Peak
2	0.26866	0.01	9.84	31.94	41.79	51.16	-9.37	Peak
3	0.59478	0.02	9.87	31.75	41.64	46.00	-4.36	Peak
4	0.94809	0.02	9.89	28.97	38.88	46.00	-7.12	Peak
5	2.144	0.02	9.96	31.97	41.96	46.00	-4.04	Peak
6	15.388	0.02	10.17	29.28	39.47	50.00	-10.53	Peak



Report No.: SZEM150700425802

Page: 16 of 114

Neutral Line:



Site : Shielding Room

Condition : 47 CFR PART15C AV CE NEUTRAL

Job No. : 4258CR Test Mode : TX+charge

	Freq		LISN Factor					Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.20505	0.02	9.85	36.07	45.93	53.40	-7.47	Peak
2	0.46367	0.01	9.88	31.64	41.52	46.63	-5.10	Peak
3	0.94809	0.02	10.01	32.12	42.15	46.00	-3.85	Peak
4	1.980	0.02	10.12	31.14	41.27	46.00	-4.73	Peak
5	3.528	0.02	10.13	29.39	39.54	46.00	-6.46	Peak
6	14.364	0.01	10.21	28.49	38.71	50.00	-11.29	Peak

Notes:

- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM150700425802

Page: 17 of 114

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)		
Test Method:	ANSI C63.10 2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane		
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Test Instruments:	Refer to section 5.10 for details.		
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.		
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).		
Limit:	30dBm		
Test Results:	Pass		



Report No.: SZEM150700425802

Page: 18 of 114

Measurement Data

	000 441	-1-	
	802.11b mo	ae	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	17.67	30.00	Pass
Middle	17.55	30.00	Pass
Highest	17.49	30.00	Pass
	802.11g mo	de	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	18.93	30.00	Pass
Middle	19.12	30.00	Pass
Highest	19.07	30.00	Pass
	802.11n(HT20)	mode	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	18.98	30.00	Pass
Middle	19.23	30.00	Pass
Highest	19.20	30.00	Pass
	802.11n(HT40)	mode	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	18.21	30.00	Pass
Middle	18.18	30.00	Pass
Highest	18.17	30.00	Pass
	•		



Report No.: SZEM150700425802

Page: 19 of 114

Test plot as follows:

Test mode: 802.11b Test channel: Lowest



Test mode: 802.11b Test channel: Middle







Report No.: SZEM150700425802

Page: 20 of 114

Test mode: 802.11b Test channel: Highest



Test mode:	802.11g	Test channel:	Lowest
	00=g		






Report No.: SZEM150700425802

Page: 21 of 114

Test mode: 802.11g Test channel: Middle



Test mode: 802.11g Test channel: Highest






Report No.: SZEM150700425802

Page: 22 of 114

Test mode: 802.11n(HT20) Test channel: Lowest



Test mode: 802.11n(HT20) Test channel: Middle






Report No.: SZEM150700425802

Page: 23 of 114

Test mode: 802.11n(HT20) Test channel: Highest



Test mode:	802.11n(HT40)	Test channel:	Lowest







Report No.: SZEM150700425802

Page: 24 of 114

Test mode: 802.11n(HT40) Test channel: Middle



Test mode:	802.11n(HT40)	Test channel:	Highest
	00=:::(:::(:::)		g






Report No.: SZEM150700425802

Page: 25 of 114

6.4 6dB Occupy Bandwidth





Report No.: SZEM150700425802

Page: 26 of 114

Measurement Data

Weasurement Data							
	802.11b mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	10.110	≥500	Pass				
Middle	10.140	≥500	Pass				
Highest	10.140	≥500	Pass				
	802.11g mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	16.650	≥500	Pass				
Middle	16.620	≥500	Pass				
Highest	16.620	≥500	Pass				
	802.11n(HT20) mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	17.880	≥500	Pass				
Middle	17.880	≥500	Pass				
Highest	17.940	≥500	Pass				
	802.11n(HT40)mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	36.600	≥500	Pass				
Middle	36.540	≥500	Pass				
Highest	36.540	≥500	Pass				




Report No.: SZEM150700425802


Page: 27 of 114

Test plot as follows:

Test mode: 802.11b Test channel: Lowest



Test mode: 802.11b Test channel: Middle







Report No.: SZEM150700425802

Page: 28 of 114

Test mode: 802.11b Test channel: Highest



Test mode: 802.11g Test channel: Lowest







Report No.: SZEM150700425802

Page: 29 of 114

Test mode: 802.11g Test channel: Middle



Test mode: 802.11g Test channel: Highest









Report No.: SZEM150700425802

Page: 30 of 114

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: SZEM150700425802

Page: 31 of 114

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: SZEM150700425802

Page: 32 of 114

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: SZEM150700425802

Page: 33 of 114

6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)		
Test Method:	ANSI C63.10 2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane		
	Remark:		
	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Test Instruments:	Refer to section 5.10 for details.		
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.		
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).		
Limit:	≤8.00dBm/3kHz		
Test Results:	Pass		



Report No.: SZEM150700425802

Page: 34 of 114

Measurement Data

	802.11b mode					
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result			
Lowest	-16.10	≤8.00	Pass			
Middle	-16.05	≤8.00	Pass			
Highest	-16.16	≤8.00	Pass			
	802.11g mode					
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result			
Lowest	-18.15	≤8.00	Pass			
Middle	-18.00	≤8.00	Pass			
Highest	-18.10	≤8.00	Pass			
	802.11n(HT20) mode)				
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result			
Lowest	-17.78	≤8.00	Pass			
Middle	-17.29	≤8.00	Pass			
Highest	-17.47	≤8.00	Pass			
	802.11n(HT40) mode)				
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result			
Lowest	-18.77	≤8.00	Pass			
Middle	-18.22	≤8.00	Pass			
Highest	-17.87	≤8.00	Pass			




Report No.: SZEM150700425802

Page: 35 of 114

Test plot as follows:

Test mode: 802.11b Test channel: Lowest











Report No.: SZEM150700425802

Page: 36 of 114

Test mode: 802.11b Test channel: Highest











Report No.: SZEM150700425802

Page: 37 of 114

Test mode: 802.11g Test channel: Middle











Report No.: SZEM150700425802

Page: 38 of 114

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: SZEM150700425802

Page: 39 of 114

Test mode: 802.11n(HT20) Test channel: Highest



Test mode: 802.11n(HT40) Test channel: Lowest









Report No.: SZEM150700425802

Page: 40 of 114

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: SZEM150700425802

Page: 41 of 114

6.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2009
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass




Report No.: SZEM150700425802


Page: 42 of 114

Test plot as follows:

Test mode: 802.11b Test channel: Lowest











Report No.: SZEM150700425802

Page: 43 of 114

Test mode: 802.11g Test channel: Lowest











Report No.: SZEM150700425802

Page: 44 of 114

Test mode: 802.11n(HT20) Test channel: Lowest



Test mode: 802.11n(HT20) Test channel: Highest







Report No.: SZEM150700425802

Page: 45 of 114

Test mode: 802.11n(HT40) Test channel: Lowest









Report No.: SZEM150700425802

Page: 46 of 114

6.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2009
Test Setup:	Spectrum Analyzer Non-Conducted Table Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass





Report No.: SZEM150700425802

Page: 47 of 114

Test plot as follows:


Test mode: 802.11b Test channel: Lowest








Report No.: SZEM150700425802 Page: 48 of 114









Report No.: SZEM150700425802

Page: 49 of 114











Report No.: SZEM150700425802

Page: 50 of 114

Test mode: 802.11b Test channel: Middle









Report No.: SZEM150700425802

Page: 51 of 114









Report No.: SZEM150700425802

Page: 52 of 114









Report No.: SZEM150700425802

Page: 53 of 114

Test mode: 802.11b Test channel: Highest









Report No.: SZEM150700425802











Report No.: SZEM150700425802

Page: 55 of 114









Report No.: SZEM150700425802

Page: 56 of 114

Test mode: 802.11g Test channel: Lowest









Report No.: SZEM150700425802

Page: 57 of 114









Report No.: SZEM150700425802

Page: 58 of 114









Report No.: SZEM150700425802

Page: 59 of 114

Test mode: 802.11g Test channel: Middle












Report No.: SZEM150700425802 Page: 60 of 114








Report No.: SZEM150700425802









Report No.: SZEM150700425802

Page: 62 of 114


Test mode: 802.11g Test channel: Highest








Report No.: SZEM150700425802









Report No.: SZEM150700425802

Page: 64 of 114









Report No.: SZEM150700425802

Page: 65 of 114


Test mode: 802.11n(HT20) Test channel: Lowest









Report No.: SZEM150700425802 Page: 66 of 114








Report No.: SZEM150700425802









Report No.: SZEM150700425802

Page: 68 of 114


Test mode: 802.11n(HT20) Test channel: Middle








Report No.: SZEM150700425802 Page: 69 of 114











Report No.: SZEM150700425802











Report No.: SZEM150700425802

Page: 71 of 114

Test mode: 802.11n(HT20) Test channel: Highest









Report No.: SZEM150700425802

Page: 72 of 114









Report No.: SZEM150700425802











Report No.: SZEM150700425802

Page: 74 of 114

Test mode: 802.11n(HT40) Test channel: Lowest









Report No.: SZEM150700425802

Page: 75 of 114









Report No.: SZEM150700425802

Page: 76 of 114









Report No.: SZEM150700425802

Page: 77 of 114

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: SZEM150700425802

Page: 78 of 114









Report No.: SZEM150700425802

Stop 8 GHz





200 MHz/

Start 6 GHz







Report No.: SZEM150700425802

Page: 80 of 114


Test mode: 802.11n(HT40) Test channel: Highest








Report No.: SZEM150700425802 Page: 81 of 114









Report No.: SZEM150700425802

Page: 82 of 114





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM150700425802

Page: 83 of 114

6.8 Radiated Spurious Emissions


Test Requirement:	47 CFR Part 15C Section	n 15.209 and 15.2	05								
Test Method:	ANSI C63.10 2009										
Test Site:	Measurement Distance:	3m (Semi-Anecho	ic Chamber)								
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark						
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak						
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average						
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak						
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak						
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average						
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak						
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak						
	Above 1GHz	Peak	1MHz	3MHz	Peak						
	Above IGHZ	Peak	1MHz	10Hz	Average						
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)						
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300						
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30						
	1.705MHz-30MHz	30	-	-	30						
	30MHz-88MHz	100	40.0	Quasi-peak	3						
	88MHz-216MHz	150	43.5	Quasi-peak	3						
	216MHz-960MHz	200	46.0	Quasi-peak	3						
	960MHz-1GHz	500	54.0	Quasi-peak	3						
	Above 1GHz	500	54.0	Average	3						
	emissions is 20di applicable to the	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.									



Report No.: SZEM150700425802

Page: 84 of 114

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average



Report No.: SZEM150700425802

Page: 85 of 114

	method as specified and then reported in a data sheet.
g.	Test the EUT in the lowest channel ,the middle channel ,the Highest channel
h.	Repeat above procedures until all frequencies measured was complete.
est Tra	nsmitting with all kind of modulations, data rates.
Tra	insmitting mode.
Tra	ansmitting mode.
of	rough Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 2.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
	r below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at vest channel is the worst case.
On	ly the worst case is recorded in the report.
Re	fer to section 5.10 for details.
Pa	ss
	h. est Tra Tra Tra Thi of 802 Foi low On




Report No.: SZEM150700425802

Page: 86 of 114

6.8.1 Radiated emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting	Vertical



Condition: 47 CFR PART 15B 10m Vertical

Job No. : 4258CR


Test Mode: a


	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	44.90	6.80	12.02	32.65	39.57	25.74	29.50	-3.76
2!	58.00	7.00	11.84	32.66	38.25	24.43	29.50	-5.07
3	104.17	7.22	9.87	32.65	37.80	22.24	33.00	-10.76
4	122.40	7.31	11.45	32.63	40.20	26.33	33.00	-6.67
5	207.12	7.64	9.98	32.59	40.32	25.35	33.00	-7.65
6!	446.41	8.42	16.52	32.56	38.52	30.90	35.60	-4.70



Report No.: SZEM150700425802

Page: 87 of 114





Condition: 47 CFR PART 15B 10m Horizontal

Job No. : 4258CR

Test Mode: a

	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	46.02	6.82	11.98	32.65	30.08	16.23	29.50	-13.27
2	127.66	7.34	11.76	32.63	32.16	18.63	33.00	-14.37
3	148.96	7.45	13.12	32.62	29.73	17.68	33.00	-15.32
4	259.23	7.90	11.85	32.56	35.06	22.25	35.60	-13.35
5	446.41	8.42	16.52	32.56	33.82	26.20	35.60	-9.40
6 pp	744.87	9.20	21.70	32.49	32.65	31.06	35.60	-4.54



Report No.: SZEM150700425802

Page: 88 of 114

6.8.2 Transmitter emission above 1GHz

Test mode:	802	.11b	Test ch	annel:	Lowest	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3892.524	6.75	33.31	38.91	46.68	47.83	74.00	-26.17	Vertical
4824.000	6.46	34.72	39.24	47.75	49.69	74.00	-24.31	Vertical
5964.939	8.03	36.23	39.19	48.02	53.09	74.00	-20.91	Vertical
7236.000	8.96	35.60	39.06	47.45	52.95	74.00	-21.05	Vertical
9648.000	9.97	37.45	37.91	41.96	51.47	74.00	-22.53	Vertical
11757.650	10.50	38.46	38.59	43.32	53.69	74.00	-20.31	Vertical
3548.251	6.94	32.94	38.76	48.07	49.19	74.00	-24.81	Horizontal
4824.000	6.46	34.72	39.24	48.97	50.91	74.00	-23.09	Horizontal
5913.378	7.95	36.13	39.19	47.95	52.84	74.00	-21.16	Horizontal
7236.000	8.96	35.60	39.06	48.09	53.59	74.00	-20.41	Horizontal
9648.000	9.97	37.45	37.91	42.19	51.70	74.00	-22.30	Horizontal
11656.010	10.46	38.36	38.54	42.32	52.60	74.00	-21.40	Horizontal

Test mode:	802	.11b	Test ch	annel:	Middle	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3548.251	6.94	32.94	38.76	48.07	49.19	74.00	-24.81	Vertical
4874.000	6.57	34.77	39.26	48.09	50.17	74.00	-23.83	Vertical
5913.378	7.95	36.13	39.19	47.95	52.84	74.00	-21.16	Vertical
7311.000	9.06	35.52	39.06	47.42	52.94	74.00	-21.06	Vertical
9748.000	9.91	37.76	37.85	41.88	51.70	74.00	-22.30	Vertical
11656.010	10.46	38.36	38.54	42.32	52.60	74.00	-21.40	Vertical
3631.354	6.89	33.02	38.80	48.44	49.55	74.00	-24.45	Horizontal
4874.000	6.57	34.77	39.26	48.92	51.00	74.00	-23.00	Horizontal
5913.378	7.95	36.13	39.19	47.85	52.74	74.00	-21.26	Horizontal
7311.000	9.06	35.52	39.06	47.11	52.63	74.00	-21.37	Horizontal
9648.000	9.97	37.45	37.91	42.23	51.74	74.00	-22.26	Horizontal
11422.280	10.37	38.17	38.43	43.30	53.41	74.00	-20.59	Horizontal



Report No.: SZEM150700425802

Page: 89 of 114

Test mode:	802	.11b	Test ch	annel:	Highest	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3548.251	6.94	32.94	38.76	48.07	49.19	74.00	-24.81	Vertical
4924.000	6.68	34.82	39.28	48.71	50.93	74.00	-23.07	Vertical
5913.378	7.95	36.13	39.19	47.95	52.84	74.00	-21.16	Vertical
7386.000	9.16	35.44	39.05	46.40	51.95	74.00	-22.05	Vertical
9848.000	9.85	38.06	37.79	42.16	52.28	74.00	-21.72	Vertical
11488.580	10.39	38.22	38.46	43.19	53.34	74.00	-20.66	Vertical
3641.878	6.89	33.03	38.80	47.62	48.74	74.00	-25.26	Horizontal
4924.000	6.68	34.82	39.28	48.69	50.91	74.00	-23.09	Horizontal
5913.378	7.95	36.13	39.19	47.95	52.84	74.00	-21.16	Horizontal
7386.000	9.16	35.44	39.05	47.39	52.94	74.00	-21.06	Horizontal
9848.000	9.85	38.06	37.79	42.16	52.28	74.00	-21.72	Horizontal
11389.270	10.37	38.15	38.41	42.97	53.08	74.00	-20.92	Horizontal

Test mode:	8	02.11g	Test channel:		Lowest	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Factor	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3652.432	6.88	33.04	38.81	48.32	49.43	74.00	-24.57	Vertical
4824.000	6.46	34.72	39.24	49.93	51.87	74.00	-22.13	Vertical
5913.378	7.95	36.13	39.19	47.85	52.74	74.00	-21.26	Vertical
7236.000	8.96	35.60	39.06	46.40	51.90	74.00	-22.10	Vertical
9648.000	9.97	37.45	37.91	42.18	51.69	74.00	-22.31	Vertical
11128.630	10.31	1 38.11	38.29	42.83	52.96	74.00	-21.04	Vertical
3814.467	6.79	33.18	38.88	48.30	49.39	74.00	-24.61	Horizontal
4824.000	6.46	34.72	39.24	49.31	51.25	74.00	-22.75	Horizontal
5913.378	7.95	36.13	39.19	48.95	53.84	74.00	-20.16	Horizontal
7236.000	8.96	35.60	39.06	47.46	52.96	74.00	-21.04	Horizontal
9648.000	9.97	37.45	37.91	42.61	52.12	74.00	-21.88	Horizontal
11488.580	10.39	38.22	38.46	43.19	53.34	74.00	-20.66	Horizontal



Report No.: SZEM150700425802

Page: 90 of 114

Test mode:	802	.11g	Test ch	annel:	Middle	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3417.246	7.13	32.80	38.70	48.97	50.20	74.00	-23.80	Vertical
4874.000	6.57	34.77	39.26	48.83	50.91	74.00	-23.09	Vertical
6016.949	8.08	36.28	39.18	47.08	52.26	74.00	-21.74	Vertical
7311.000	9.06	35.52	39.06	44.22	49.74	74.00	-24.26	Vertical
9748.000	9.91	37.76	37.85	42.46	52.28	74.00	-21.72	Vertical
11389.270	10.37	38.15	38.41	42.97	53.08	74.00	-20.92	Vertical
3903.804	6.74	33.33	38.91	48.03	49.19	74.00	-24.81	Horizontal
4874.000	6.57	34.77	39.26	48.09	50.17	74.00	-23.83	Horizontal
6087.002	8.06	36.20	39.17	47.44	52.53	74.00	-21.47	Horizontal
7311.000	9.06	35.52	39.06	46.92	52.44	74.00	-21.56	Horizontal
9748.000	9.91	37.76	37.85	41.88	51.70	74.00	-22.30	Horizontal
11757.650	10.50	38.46	38.59	42.24	52.61	74.00	-21.39	Horizontal

Test mode:	802	.11g	Test ch	annel:	Highest	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3417.246	7.13	32.80	38.70	48.97	50.20	74.00	-23.80	Vertical
4924.000	6.68	34.82	39.28	47.95	50.17	74.00	-23.83	Vertical
6016.949	8.08	36.28	39.18	47.08	52.26	74.00	-21.74	Vertical
7386.000	9.16	35.44	39.05	44.64	50.19	74.00	-23.81	Vertical
9848.000	9.85	38.06	37.79	42.07	52.19	74.00	-21.81	Vertical
11488.580	10.39	38.22	38.46	43.19	53.34	74.00	-20.66	Vertical
3748.808	6.83	33.11	38.85	47.95	49.04	74.00	-24.96	Horizontal
4924.000	6.68	34.82	39.28	48.71	50.93	74.00	-23.07	Horizontal
5811.590	7.79	35.93	39.20	47.97	52.49	74.00	-21.51	Horizontal
7386.000	9.16	35.44	39.05	47.81	53.36	74.00	-20.64	Horizontal
9848.000	9.85	38.06	37.79	42.16	52.28	74.00	-21.72	Horizontal
10873.950	10.21	37.99	38.16	42.91	52.95	74.00	-21.05	Horizontal



Report No.: SZEM150700425802

Page: 91 of 114

Test mode:		802.	.11n(HT20)	Test cha	annel:	Lowest	Remark	:	Peak
Frequency (MHz)	Cab Los (dB	s	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3748.808	6.8	3	33.11	38.85	47.95	49.04	74.00	-24.96	Vertical
4824.000	6.4	6	34.72	39.24	48.94	50.88	74.00	-23.12	Vertical
6087.002	8.0	6	36.20	39.17	47.44	52.53	74.00	-21.47	Vertical
7236.000	8.9	6	35.60	39.06	44.69	50.19	74.00	-23.81	Vertical
9648.000	9.9	7	37.45	37.91	42.77	52.28	74.00	-21.72	Vertical
11656.010	10.4	16	38.36	38.54	43.13	53.41	74.00	-20.59	Vertical
3457.032	7.0	5	32.84	38.72	48.37	49.54	74.00	-24.46	Horizontal
4824.000	6.4	6	34.72	39.24	49.06	51.00	74.00	-23.00	Horizontal
6087.002	8.0	6	36.20	39.17	47.33	52.42	74.00	-21.58	Horizontal
7236.000	8.9	6	35.60	39.06	44.27	49.77	74.00	-24.23	Horizontal
9648.000	9.9	7	37.45	37.91	42.23	51.74	74.00	-22.26	Horizontal
11422.280	10.3	37	38.17	38.43	43.30	53.41	74.00	-20.59	Horizontal

Test mode:	802	.11n(HT20)	Test ch	annel:	Middle	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3626.104	6.90	33.02	38.80	46.49	47.61	74.00	-26.39	Vertical
4874.000	6.57	34.77	39.26	47.62	49.70	74.00	-24.30	Vertical
6034.386	8.07	36.26	39.18	47.20	52.35	74.00	-21.65	Vertical
7311.000	9.06	35.52	39.06	41.61	47.13	74.00	-26.87	Vertical
9748.000	9.91	37.76	37.85	40.16	49.98	74.00	-24.02	Vertical
11723.670	10.49	38.43	38.57	43.61	53.96	74.00	-20.04	Vertical
3412.305	7.14	32.79	38.70	47.83	49.06	74.00	-24.94	Horizontal
4874.000	6.57	34.77	39.26	49.20	51.28	74.00	-22.72	Horizontal
5879.252	7.89	36.07	39.20	48.18	52.94	74.00	-21.06	Horizontal
7311.000	9.06	35.52	39.06	46.30	51.82	74.00	-22.18	Horizontal
9748.000	9.91	37.76	37.85	41.87	51.69	74.00	-22.31	Horizontal
11521.870	10.40	38.24	38.48	42.95	53.11	74.00	-20.89	Horizontal



Report No.: SZEM150700425802

Page: 92 of 114

Test mode:	802	.11n(HT20)	Test ch	annel:	Highest	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3477.098	7.01	32.87	38.73	48.03	49.18	74.00	-24.82	Vertical
4924.000	6.68	34.82	39.28	48.16	50.38	74.00	-23.62	Vertical
6034.386	8.07	36.26	39.18	47.45	52.60	74.00	-21.40	Vertical
7386.000	9.16	35.44	39.05	47.82	53.37	74.00	-20.63	Vertical
9848.000	9.85	38.06	37.79	41.65	51.77	74.00	-22.23	Vertical
11740.650	10.50	38.44	38.58	41.74	52.10	74.00	-21.90	Vertical
3631.354	6.89	33.02	38.80	47.95	49.06	74.00	-24.94	Horizontal
4924.000	6.68	34.82	39.28	48.88	51.10	74.00	-22.90	Horizontal
5870.752	7.88	36.05	39.20	48.37	53.10	74.00	-20.90	Horizontal
7386.000	9.16	35.44	39.05	47.13	52.68	74.00	-21.32	Horizontal
9648.000	9.97	37.45	37.91	42.07	51.58	74.00	-22.42	Horizontal
11538.550	10.41	38.25	38.48	42.11	52.29	74.00	-21.71	Horizontal

Test mode:	80	02.11n(HT40)	Test ch	annel:	Lowest	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3300.615	7.35	32.52	38.65	47.35	48.57	74.00	-25.43	Vertical
4844.000	6.51	34.74	39.25	47.38	49.38	74.00	-24.62	Vertical
5896.291	7.92	36.10	39.19	48.71	53.54	74.00	-20.46	Vertical
7266.000	9.00	35.57	39.06	46.62	52.13	74.00	-21.87	Vertical
9688.000	9.94	37.57	37.88	41.11	50.74	74.00	-23.26	Vertical
11389.270	10.37	38.15	38.41	41.35	51.46	74.00	-22.54	Vertical
3903.804	6.74	33.33	38.91	47.76	48.92	74.00	-25.08	Horizontal
4844.000	6.51	34.74	39.25	48.46	50.46	74.00	-23.54	Horizontal
6016.949	8.08	36.28	39.18	47.31	52.49	74.00	-21.51	Horizontal
7266.000	9.00	35.57	39.06	43.86	49.37	74.00	-24.63	Horizontal
9688.000	9.94	37.57	37.88	42.10	51.73	74.00	-22.27	Horizontal
10842.530	10.19	37.96	38.14	43.50	53.51	74.00	-20.49	Horizontal



Report No.: SZEM150700425802

Page: 93 of 114

Test mode:	802	.11n(HT40)	Test ch	annel:	Middle	Remark	:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3610.398	6.90	33.01	38.79	48.61	49.73	74.00	-24.27	Vertical
4874.000	6.57	34.77	39.26	49.46	51.54	74.00	-22.46	Vertical
5736.401	7.67	35.76	39.21	49.52	53.74	74.00	-20.26	Vertical
7311.000	9.06	35.52	39.06	47.39	52.91	74.00	-21.09	Vertical
9748.000	9.91	37.76	37.85	41.84	51.66	74.00	-22.34	Vertical
11723.670	10.49	38.43	38.57	42.24	52.59	74.00	-21.41	Vertical
3631.354	6.89	33.02	38.80	45.22	46.33	74.00	-27.67	Horizontal
4874.000	6.57	34.77	39.26	48.22	50.30	74.00	-23.70	Horizontal
5999.562	8.08	36.30	39.18	46.79	51.99	74.00	-22.01	Horizontal
7311.000	9.06	35.52	39.06	46.93	52.45	74.00	-21.55	Horizontal
9748.000	9.91	37.76	37.85	42.45	52.27	74.00	-21.73	Horizontal
11860.170	10.55	38.56	38.64	43.40	53.87	74.00	-20.13	Horizontal

Test mode: 802.		302.11n(HT40) Test ch	annel:	Highest Remark:		:	Peak
Frequency (MHz)	Cable Loss (dB)	Factor	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3636.612	6.89	33.03	38.80	48.54	49.66	74.00	-24.34	Vertical
4904.000	6.64	34.81	39.27	47.93	50.11	74.00	-23.89	Vertical
6025.661	8.07	36.27	39.18	47.26	52.42	74.00	-21.58	Vertical
7356.000	9.12	35.47	39.05	46.46	52.00	74.00	-22.00	Vertical
9808.000	9.88	37.94	37.81	42.10	52.11	74.00	-21.89	Vertical
11356.360	10.36	38.14	38.40	42.97	53.07	74.00	-20.93	Vertical
3574.015	6.93	32.97	38.77	48.16	49.29	74.00	-24.71	Horizontal
4904.000	6.64	34.81	39.27	49.26	51.44	74.00	-22.56	Horizontal
5939.103	7.99	36.18	39.19	47.69	52.67	74.00	-21.33	Horizontal
7356.000	9.12	35.47	39.05	46.71	52.25	74.00	-21.75	Horizontal
9808.000	9.88	37.94	37.81	42.63	52.64	74.00	-21.36	Horizontal
11438.810	10.38	38.18	38.44	42.83	52.95	74.00	-21.05	Horizontal



Report No.: SZEM150700425802

Page: 94 of 114

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- (3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM150700425802

Page: 95 of 114

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10 2009	ANSI C63.10 2009							
Test Site:	Measurement Distance: 3n	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Limit:	Frequency	Limit (dBuV/m @3m)	Remark						
	30MHz-88MHz	40.0	Quasi-peak Value						
	88MHz-216MHz	43.5	Quasi-peak Value						
	216MHz-960MHz	46.0	Quasi-peak Value						
	960MHz-1GHz	54.0	Quasi-peak Value						
	Above 1GHz	54.0	Average Value						
	Above IGHZ	74.0	Peak Value						
Test Setup:			<u> </u>						






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: SZEM150700425802

Page: 96 of 114

Test Procedure:	a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.					
	b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.					
	c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.					
	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.					
	e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.					
	f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel					
	g. Test the EUT in the lowest channel, the Highest channel					
	h. Repeat above procedures until all frequencies measured was complete.					
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.					
	Transmitting mode.					
Final Test Mode:	Transmitting mode.					
	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).					
	Only the worst case is recorded in the report.					
Instruments Used:	Refer to section 5.10 for details.					
Test Results:	Pass					




Report No.: SZEM150700425802

Page: 97 of 114

Test plot as follows:

Test mode: 802.11b Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2412 Band edge B


Ant Preamp Limit 0ver Read Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 2390.00 4.90 38.46 46.64 45.43 74.00 -28.57 32.35 4.93 32.41 38.46 77.99 76.87 2 pp 2411.91 74.00



Report No.: SZEM150700425802

Page: 98 of 114

Test mode: 802.11b Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2412 Band edge B


Ant Preamp Limit Read Loss Factor Factor Level Level Line Limit MHz dB dB/m dΒ dBuV dBuV/m dBuV/m dB 4.90 38.46 49.05 47.84 74.00 -26.16 2390.00 32.35 4.93 32.41 38.46 77.58 76.46 2 pp 2411.91 74.00



Report No.: SZEM150700425802

Page: 99 of 114

Test mode: 802.11b Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2462 Band edge B

Ant Preamp Limit 0ver Read Loss Factor Factor Level Level Line Limit dΒ MHz dB dB/m dBuV dBuV/m dBuV/m dB 5.00 79.20 78.17 74.00 2461.61 32.43 38.46 4.17 2483.50 5.03 32.44 38.47 45.58 44.58 74.00 -29.42






Report No.: SZEM150700425802

Page: 100 of 114

Test mode: 802.11b Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2462 Band edge B


Ant Preamp Limit 0ver Read Loss Factor Factor Level Level Line Limit MHz dB dB/m dΒ dBuV dBuV/m dBuV/m dB 5.00 38.46 76.23 75.20 74.00 2461.81 32.43 1.20 2483.50 5.03 32.44 38.47 45.84 44.84 74.00 -29.16



Report No.: SZEM150700425802

Page: 101 of 114

Test mode: 802.11g Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2412 Band edge G


Ant Preamp Limit Read Loss Factor Factor Level Level Line Limit MHz dB dB/m dΒ dBuV dBuV/m dBuV/m dB 4.90 38.46 46.33 45.12 74.00 -28.88 2390.00 32.35 4.93 32.42 38.46 77.71 76.60 74.00 2 pp 2413.81



Report No.: SZEM150700425802

Page: 102 of 114

Test mode: 802.11g Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2412 Band edge G


Ant Preamp Limit 0ver Read Loss Factor Factor Level Level Line Limit MHz dB dB/m dΒ dBuV dBuV/m dBuV/m dB 4.90 38.46 46.18 44.97 74.00 -29.03 2390.00 32.35 4.94 32.42 38.46 77.82 76.72 74.00 2 pp 2415.03



Report No.: SZEM150700425802

Page: 103 of 114

Test mode: 802.11g Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2462 Band edge G


Ant Preamp Limit Read Loss Factor Factor Level Level Line Limit MHz dB dB/m dΒ dBuV dBuV/m dBuV/m dB 38.46 78.92 77.88 74.00 4.99 2456.25 32.43 3.88 2483.50 5.03 32.44 38.47 45.54 44.54 74.00 -29.46



Report No.: SZEM150700425802

Page: 104 of 114

Test mode: 802.11g Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2462 Band edge G


Ant Preamp Limit 0ver Read Loss Factor Factor Level Level Line Limit MHz dB dB/m dΒ dBuV dBuV/m dBuV/m dB 76.47 75.43 74.00 4.99 2456.29 32.43 38.46 1.43 2483.50 5.03 32.44 38.47 44.95 43.95 74.00 -30.05



Report No.: SZEM150700425802

Page: 105 of 114

Test mode: 802.11n(HT20) Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2412 Band edge N20


Ant Preamp Read Limit Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 46.58 45.37 4.90 38.46 2390.00 32.35 74.00 -28.63 4.94 32.42 38.46 77.65 76.55 2 pp 2416.50 74.00



Report No.: SZEM150700425802

Page: 106 of 114

Test mode: 802.11n(HT20) Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2412 Band edge N20


Ant Preamp Read Limit Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 4.90 38.46 46.93 45.72 74.00 -28.28 2390.00 32.35 4.94 32.42 38.46 77.77 76.67 2 pp 2416.38 74.00



Report No.: SZEM150700425802

Page: 107 of 114

Test mode: 802.11n(HT20) Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2462 Band edge N20


Ant Preamp Read Limit 0ver Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 38.46 78.50 77.46 74.00 4.99 2457.39 32.43 2483.50 5.03 32.44 38.47 45.01 44.01 74.00 -29.99



Report No.: SZEM150700425802

Page: 108 of 114

Test mode: 802.11n(HT20) Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2462 Band edge N20


Ant Preamp Read Limit Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 4.99 79.39 78.35 74.00 2457.34 32.43 38.46 4.35 2483.50 5.03 32.44 38.47 45.45 44.45 74.00 -29.55



Report No.: SZEM150700425802

Page: 109 of 114

Test mode: 802.11n(HT40) Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2422 Band edge N40

Ant Preamp Read Limit Loss Factor Factor Level Level Line Limit dΒ MHz dB dB/m dBuV dBuV/m dBuV/m dB 4.90 38.46 48.03 46.82 74.00 -27.18 2390.00 32.35 4.93 32.42 38.46 77.31 76.20 74.00 2 pp 2414.65






Report No.: SZEM150700425802

Page: 110 of 114

Test mode: 802.11n(HT40) Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2422 Band edge N40


Ant Preamp Read Limit Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 4.90 38.46 46.09 44.88 74.00 -29.12 2390.00 32.35 4.95 32.42 38.46 77.39 76.30 74.00 2 pp 2425.19



Report No.: SZEM150700425802

Page: 111 of 114

Test mode: 802.11n(HT40) Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 4258CR

Mode: : 2452 Band edge N40


Ant Preamp Read Limit Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 4.98 38.46 77.34 76.29 74.00 2444.54 32.43 2.29 2483.50 5.03 32.44 38.47 44.58 43.58 74.00 -30.42



Report No.: SZEM150700425802

Page: 112 of 114

Test mode: 802.11n(HT40) Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4258CR

Mode: : 2452 Band edge N40

Ant Preamp Read Limit Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 4.99 38.46 78.20 77.16 74.00 2455.18 32.43 3.16 2483.50 5.03 32.44 38.47 44.68 43.68 74.00 -30.32

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor




Report No.: SZEM150700425802

Page: 113 of 114


7 Photographs - EUT Test Setup

Test model No.: X7

7.1 Conducted Emission



7.2 Radiated Emission






Report No.: SZEM150700425802

Page: 114 of 114

7.3 Radiated Spurious Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1507004258CR.