

RF EXPOSURE EVALUATION

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

FCC ID	2ACZO-USR-G805
EUT	4G Wireless Router
Frequency band (Operating)	☐ BT: 2.402GHz ~ 2.480GH ☒ WLAN: 2.412GHz ~ 2.462GHz ☐ RLAN: 5.180GHz ~ 5.240GHz ☐ RLAN: 5.260GHz ~ 5.320GHz ☐ RLAN: 5.500GHz ~ 5.700GHz ☐ RLAN: 5.745GHz ~ 5.825GHz ☒ Others: FDD Band 2: 1850.7 MHz – 1909.3 MHz FDD Band 4: 1710.7 MHz – 1754.3 MHz FDD Band 5: 824.7 MHz – 848.3 MHz FDD Band 7: 2502.5 MHz – 2567.5 MHz FDD Band 12: 699.7 MHz – 715.3 MHz FDD Band 13: 779.5 MHz – 784.5 MHz FDD Band 25: 1850.7 MHz – 1914.3 MHz FDD Band 26: 814.7 MHz – 848.3 MHz TDD Band 38: 2572.5 MHz – 2617.5 MHz TDD Band 41: 2498.5 MHz – 2687.5 MHz FDD Band 66: 1710.7 MHz-1779.3 MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm2) ☒ General Population/Uncontrolled exposure (S=1mW/cm2)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	Wi-Fi 2.4G: 5.32dBi FDD Band 2: 5.09dBi FDD Band 4: 5.04dBi

Shenzhen Anbotech Compliance Laboratory Limited

	FDD Band 5: 2.79dBi FDD Band 7: 3.91dBi FDD Band 12: 2.75dBi FDD Band 13: 3.72dBi FDD Band 25: 5.09dBi FDD Band 26: 2.79dBi TDD Band 38: 4.05dBi TDD Band 41: 4.4dBi FDD Band 66: 5.04dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Shenzhen Anbotek Compliance Laboratory Limited

Address: Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park,
Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Tel:(86)0755-26066440 Email:service@anbotek.com



Hotline
400-003-0500
www.anbotek.com

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in Mw

G = gain of antenna in linear scale

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Max. Conducted Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)
	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm ²)	
WiFi 2.4G	13.77	13.77 ±1	14.77	5.32	0.0203	1
LTE Band 2	24.92	24 ±1	25.00	5.09	0.2032	1
LTE Band 4	23.74	22.5 ±1	23.50	5.04	0.1422	1
LTE Band 5	24.18	23.5 ±1	24.50	2.79	0.1066	0.5498
LTE Band 7	23.53	23.5 ±1	24.50	3.91	0.1380	1
LTE Band 12	24.79	24 ±1	25.00	2.75	0.1186	0.4664
LTE Band 13	24.94	24 ±1	25.00	3.72	0.1482	0.5196
LTE Band 25	23.65	23 ±1	23.50	5.09	0.1439	1
LTE Band 26	24.17	23.5 ±1	24.50	2.79	0.1066	0.5431
LTE Band 38	23.61	23 ±1	24.00	4.05	0.1270	1
LTE Band 41	23.83	23 ±1	24.00	4.4	0.1377	1
LTE Band 66	23.78	23 ±1	24.00	5.04	0.1596	1

The Maximum simultaneous transmission for WiFi 2.4G+LTE Band13:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= S_{WLAN} / S_{limit-2.4} + S_{LTE B2} / S_{limit-LTE}$$

$$= 0.0203 / 1 + 0.1482 / 0.5196$$

$$= 0.3055$$

$$< 1.0$$

Result: No Standalone SAR test is required.

Shenzhen Anbotek Compliance Laboratory Limited

