

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-229-RWD-040
Reception No. : 2207002388
Applicant : C&A Marketing Inc.
Address : 114 Tived Lane East, Edison, New Jersey, 08837, United States
Manufacturer : C&A Marketing Inc.
Address : 114 Tived Lane East, Edison, New Jersey, 08837, United States
Type of Equipment : HP Sprocket Panorama Printer
FCC ID. : 2AD2W-HPISPPAN
Model Name : HPISPPAN
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 35 pages (including this page)
Date of Incoming : August 08, 2022
Date of issue : September 27, 2022

SUMMARY


The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.





Tested by
 Joon-Woo, Kim / Assistant Manager
 ONETECH Corp.

Reviewed by
 Tae-Ho, Kim / General Manager
 ONETECH Corp.

Approved by
 Ki-Hong, Nam / General Manager
 ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY.....	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY.....	6
2.6 TEST FACILITY.....	6
3. GENERAL INFORMATION.....	7
3.1 PRODUCT DESCRIPTION.....	7
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	7
4. EUT MODIFICATIONS.....	7
5. SYSTEM TEST CONFIGURATION	8
5.1 JUSTIFICATION.....	8
5.2 PERIPHERAL EQUIPMENT	8
5.3 MODE OF OPERATION DURING THE TEST	8
5.4 CONFIGURATION OF TEST SYSTEM.....	10
5.5 ANTENNA REQUIREMENT	10
6. PRELIMINARY TEST	10
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	10
6.2 GENERAL RADIATED EMISSIONS TESTS	10
7. MINIMUM 6 DB BANDWIDTH	11
7.1 OPERATING ENVIRONMENT	11
7.2 TEST SET-UP	11
7.3 TEST DATE	11
7.4 TEST DATA FOR 1 MBPS	12
8. MAXIMUM PEAK OUTPUT POWER.....	14
8.1 OPERATING ENVIRONMENT	14
8.2 TEST SET-UP	14
8.3 TEST DATE	14
8.4 TEST DATA FOR 1 MBPS	15
9. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND.....	17

9.1 OPERATING ENVIRONMENT	17
9.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	17
9.3 TEST SET-UP FOR RADIATED MEASUREMENT.....	17
9.4 TEST DATE	17
9.5 TEST DATA FOR CONDUCTED EMISSION	18
9.5.1 TEST DATA FOR 1 MBPS.....	18
9.6 TEST DATA FOR RADIATED EMISSION.....	23
9.6.1 Radiated Emission which fall in the Restricted Band.....	23
9.6.2 Spurious & Harmonic Radiated Emission.....	24
10. PEAK POWER SPECTRAL DENSITY	25
10.1 OPERATING ENVIRONMENT	25
10.2 TEST SET-UP	25
10.3 TEST DATE	25
10.4 TEST DATA FOR 1 MBPS	26
11. RADIATED EMISSION TEST	28
11.1 OPERATING ENVIRONMENT	28
11.2 TEST SET-UP	28
11.3 TEST DATE	29
11.4 TEST DATA FOR 30 MHz ~ 1 000 MHz	30
11.5 TEST DATA FOR BELOW 30 MHz	31
11.6 TEST DATA FOR ABOVE 1 GHz	31
12. CONDUCTED EMISSION TEST.....	32
12.1 OPERATING ENVIRONMENT	32
12.2 TEST SET-UP	32
12.3 TEST DATE	32
12.4 TEST DATA.....	33
13. LIST OF TEST EQUIPMENT	35

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-229-RWD-040	September 27, 2022	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : C&A Marketing Inc.

Address : 114 Tived Lane East, Edison, New Jersey, 08837, United States

Contact Person : Chaim, Piekarski / Chief Executive Officer

Telephone No. : +8482442000

FCC ID : 2AD2W-HPISPPAN

Model Name : HPISPPAN

Brand Name : hp

Serial Number : N/A

Date : September 27, 2022

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	HP Sprocket Panorama Printer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2020
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (2)	Minimum 6 dB Bandwidth	Met the Limit / PASS
15.247 (b) (3)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.247 (e)	Peak Power Spectral Density	Met the Limit / PASS
15.209	Radiated Emission Limits	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2020. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The C&A Marketing Inc., Model HPISPPAN (referred to as the EUT in this report) is a HP Sprocket Panorama Printer. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	HP Sprocket Panorama Printer		
Temperature Range	5 °C ~ 40 °C		
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz	
	Bluetooth	2 402 MHz ~ 2 480 MHz	
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps	
	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps	
RF OUTPUT POWER	Bluetooth LE	-1.38 dBm	
	Bluetooth	1 Mbps	2.48 dBm
		2 Mbps	1.06 dBm
		3 Mbps	1.52 dBm
ANTENNA TYPE	Chip Antenna		
ANTENNA GAIN	1.80 dBi		
List of each Osc. or crystal Freq. (Freq. $\geq$ 1 MHz)	24 MHz		

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	HP500 V1.0	N/A
SUB Board	N/A	N/A	N/A
Speaker	N/A	N/A	N/A
Battery	EVE Energy Co., Ltd	P0866A	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
HPISPPAN	C&A Marketing Inc.	HP Sprocket Panorama Printer (EUT)	-
N/A	HP	Notebook PC	EUT
PA-1061-0	LITE-ON TECHNOLOGY CORPORATION	AC Adaptor	Notebook PC

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at 2 402 MHz, 2 440 MHz, and 2 480 MHz to get a maximum emission levels from the EUT. The EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XY” axis, but the worst data was recorded in this report.

-. Frequency / Channel Operations

Channel	Frequency
0	2 402
19	2 440
39	2 480


-. Duty Cycle

Mode	Tx On Time [ms]	Tx Off Time [ms]	Duty Cycle [%]	Correction Factor [dB]
Bluetooth LE [1 Mbps]	0.388 5	0.622 2	62.44	2.05

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : 10 * Log(1 / (Duty Cycle / 100))

-. Test Plot



5.4 Configuration of Test System

Line Conducted Test: The EUT was connected to LISN. All supporting equipment's were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2020 to determine the worse operating conditions.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2020 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Charging Mode	X

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X


7. MINIMUM 6 dB BANDWIDTH

7.1 Operating environment

Temperature : 25.3 °C
Relative humidity : 53.1 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.




7.3 Test Date


August 09, 2022 ~ August 22, 2022

7.4 Test data for 1 Mbps


CHANNEL	FREQUENCY(MHz)	MEASURED VALUE (kHz)	LIMIT (kHz)	MARGIN (kHz)
Low	2 402.00	729.30	500.00	229.30
Middle	2 440.00	729.30	500.00	229.30
High	2 480.00	729.30	500.00	229.30

Remark. Margin = Measured Value - Limit





Middle Channel



High Channel

8. MAXIMUM PEAK OUTPUT POWER


8.1 Operating environment

Temperature : 25.3 °C
Relative humidity : 53.1 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to $\geq$ DTS Bandwidth, the video bandwidth is set to 3 times the resolution bandwidth.



8.3 Test Date


August 09, 2022 ~ August 22, 2022


8.4 Test data for 1 Mbps

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	-1.55	30.00	31.55
MIDDLE	2 440.00	-1.38	30.00	31.38
HIGH	2 480.00	-1.82	30.00	31.82

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)





Middle Channel



High Channel


9. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND

9.1 Operating environment

Temperature : 25.3 °C
Relative humidity : 53.1 % R.H.

9.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, the video bandwidth is set to 3 times the resolution bandwidth and peak detection was used.



9.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m semi anechoic chamber. The EUT was placed on turntable approximately 1.5 m above the ground plane.


The frequency spectrum from 30 MHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.


9.4 Test Date


August 09, 2022 ~ August 22, 2022

9.5 Test data for conducted emission


9.5.1 Test data for 1 Mbps









Low Channel




Low Channel





High Channel



High Channel

9.6 Test data for radiated emission

9.6.1 Radiated Emission which fall in the Restricted Band

9.6.1.1 Test data for 1 Mbps

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Measurement distance : 3 m
- . Duty Cycle : 62.44 %
- . Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Gain	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel										
2 377.874	54.10	Peak	H	27.40	6.87	44.90	-	43.47	74.00	30.53
2 377.966	44.43	Average	H	27.40	6.87	44.90	2.05	35.85	54.00	18.15
2 389.455	55.51	Peak	V	27.40	6.87	44.90	-	44.88	74.00	29.12
2 378.058	45.92	Average	V	27.40	6.87	44.90	2.05	37.34	54.00	16.66
Test Data for High Channel										
2 498.252	53.68	Peak	H	27.50	6.98	44.90	-	43.26	74.00	30.74
2 483.626	42.05	Average	H	27.50	6.98	44.90	2.05	33.68	54.00	20.32
2 488.302	53.81	Peak	V	27.50	6.98	44.90	-	43.39	74.00	30.61
2 483.746	42.4	Average	V	27.50	6.98	44.90	2.05	34.03	54.00	19.97

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Total Level (dBμV/m)

Total Level = Reading + Antenna Factor + Cable Loss – AMP Gain + Duty Factor

9.6.2 Spurious & Harmonic Radiated Emission

9.6.2.1 Test data for 1 Mbps

- Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,
1 MHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 62.44 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Gain	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel										
4 804.00	49.16	Peak	H	31.30	9.96	44.70	-	45.72	74.00	28.28
4 804.00	38.13	Average	H	31.30	9.96	44.70	2.05	36.74	54.00	17.26
4 804.00	48.81	Peak	V	31.30	9.96	44.70	-	45.37	74.00	28.63
4 804.00	38.14	Average	V	31.30	9.96	44.70	2.05	36.75	54.00	17.25
Test Data for Middle Channel										
4 880.00	49.44	Peak	H	31.30	9.96	44.70	-	46.00	74.00	28.00
4 880.00	38.13	Average	H	31.30	9.96	44.70	2.05	36.74	54.00	17.26
4 880.00	48.87	Peak	V	31.30	9.96	44.70	-	45.43	74.00	28.57
4 880.00	38.25	Average	V	31.30	9.96	44.70	2.05	36.86	54.00	17.14
Test Data for High Channel										
4 960.00	49.10	Peak	H	31.40	9.96	44.70	-	45.76	74.00	28.24
4 960.00	38.24	Average	H	31.40	9.96	44.70	2.05	36.95	54.00	17.05
4 960.00	49.68	Peak	V	31.40	9.96	44.70	-	46.34	74.00	27.66
4 960.00	38.12	Average	V	31.40	9.96	44.70	2.05	36.83	54.00	17.17

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{AMP Gain} + \text{Duty Factor}$$

10. PEAK POWER SPECTRAL DENSITY


10.1 Operating environment

Temperature : 25.3 °C
Relative humidity : 53.1 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$, the video bandwidth is set to 3 times the resolution bandwidth.



10.3 Test Date

August 09, 2022 ~ August 22, 2022


10.4 Test data for 1 Mbps


-. Test Result : Pass

-. Operating Condition : Continuous transmitting mode


CHANNEL	FREQUENCY(MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
Low	2 402.00	-20.12	8.00	28.12
Middle	2 440.00	-20.03	8.00	28.03
High	2 480.00	-19.69	8.00	27.69

Remark. Margin = Limit – Measured value





Middle Channel



High Channel

11. RADIATED EMISSION TEST

11.1 Operating environment

Temperature : 25.3 °C
Relative humidity : 53.1 % R.H.


11.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.


The frequency spectrum from 30 MHz to 26.5 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

- Test Configuration


1. Below 30 MHz



2. 30 MHz - 1 GHz



3. Above 1 GHz



11.3 Test Date

August 09, 2022 ~ August 22, 2022


11.4 Test data for 30 MHz ~ 1 000 MHz

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : HP Sprocket Panorama Printer

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	[dBuV]	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	81.410	34.1	13.4	2.6	33.1	17.0	40.0	23.0	200	2
2	138.640	34.8	19.3	3.4	33.0	24.5	43.5	19.0	200	20
3	209.450	48.6	15.7	4.3	33.0	35.6	43.5	7.9	100	358
4	265.710	38.7	18.6	4.8	32.9	29.2	46.0	16.8	100	337
5	408.300	34.2	21.6	6.0	32.9	28.9	46.0	17.1	100	0
6	840.911	27.7	27.3	8.7	33.0	30.7	46.0	15.3	200	211
----- Vertical -----										
7	44.550	43.2	15.3	1.9	33.1	27.3	40.0	12.7	100	338
8	99.840	39.6	15.4	2.9	33.1	24.8	43.5	18.7	100	359
9	138.640	37.4	19.3	3.4	33.0	27.1	43.5	16.4	100	359
10	210.420	49.8	15.7	4.3	33.0	36.8	43.5	6.7	100	359
11	359.800	35.7	20.3	5.6	33.0	28.6	46.0	17.4	100	358
12	800.172	32.5	27.1	8.5	33.0	35.1	46.0	10.9	100	352

11.5 Test data for Below 30 MHz

- . Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- . Frequency range : 9 kHz ~ 30 MHz
- . Measurement distance : 3 m
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

11.6 Test data for above 1 GHz

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Frequency range : 1 GHz ~ 26.5 GHz
- . Measurement distance : 3 m
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

12. CONDUCTED EMISSION TEST

12.1 Operating environment

Temperature : 25.3 °C
Relative humidity : 53.1 % R.H.

12.2 Test set-up


The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a 50 Ω / 50 μ H + 5 Ω Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.

12.3 Test Date

August 09, 2022 ~ August 22, 2022


12.4 Test data

- . Resolution bandwidth : 9 kHz
- . Frequency range : 0.15 MHz ~ 30 MHz
- . Tested Line : HOT LINE



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.19100	32.9	----	10.0	42.9	----	64.0	----	21.1	----	H (QP)
2	0.50600	22.0	----	10.0	32.0	----	56.0	----	24.0	----	H (QP)
3	0.65700	19.6	----	10.0	29.6	----	56.0	----	26.4	----	H (QP)
4	2.10000	15.8	----	10.1	25.9	----	56.0	----	30.1	----	H (QP)
5	21.16000	16.7	----	10.5	27.2	----	60.0	----	32.8	----	H (QP)
6	25.87000	19.3	----	10.6	29.9	----	60.0	----	30.1	----	H (QP)
7	0.19100	----	28.5	10.0	----	38.5	----	54.0	----	15.5	H (CAV)
8	0.50600	----	18.9	10.0	----	28.9	----	46.0	----	17.1	H (CAV)
9	0.65700	----	12.2	10.0	----	22.2	----	46.0	----	23.8	H (CAV)
10	2.10000	----	9.4	10.1	----	19.5	----	46.0	----	26.5	H (CAV)
11	21.16000	----	9.7	10.5	----	20.2	----	50.0	----	29.8	H (CAV)
12	25.87000	----	13.5	10.6	----	24.1	----	50.0	----	25.9	H (CAV)

-. Tested Line : NEUTRAL LINE



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15200	37.4	----	10.0	47.4	----	65.9	----	18.5	----	N (QP)
2	0.20900	33.2	----	10.0	43.2	----	63.2	----	20.0	----	N (QP)
3	0.51200	21.0	----	10.0	31.0	----	56.0	----	25.0	----	N (QP)
4	2.08400	18.2	----	10.1	28.3	----	56.0	----	27.7	----	N (QP)
5	21.16000	15.6	----	10.5	26.1	----	60.0	----	33.9	----	N (QP)
6	25.87000	18.5	----	10.6	29.1	----	60.0	----	30.9	----	N (QP)
7	0.15200	----	28.5	10.0	----	38.5	----	55.9	----	17.4	N (CAV)
8	0.20900	----	30.4	10.0	----	40.4	----	53.2	----	12.8	N (CAV)
9	0.51200	----	16.7	10.0	----	26.7	----	46.0	----	19.3	N (CAV)
10	2.08400	----	10.8	10.1	----	20.9	----	46.0	----	25.1	N (CAV)
11	21.16000	----	9.1	10.5	----	19.6	----	50.0	----	30.4	N (CAV)
12	25.87000	----	14.0	10.6	----	24.6	----	50.0	----	25.4	N (CAV)

Remark: Margin (dB) = Limit – Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.

13. LIST OF TEST EQUIPMENT

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
FSV40-N	Rohde & Schwarz	Signal Analyzer	102196	Apr. 11, 2022 (1Y)
TC-3000C	TESCOM	BUETOOTH TESTER	3000C000634	Jan. 17, 2022 (1Y)
152610	KRYTAR	Directional Coupler	214012	Jun. 21, 2022 (1Y)
HPF 3GHz	Rohde & Schwarz	High Pass Filter (1-3 GHz)	N/A	Jan. 18, 2022 (1Y)
ESR	Rohde & Schwarz	EMI Test Receiver	101470	Oct. 18, 2021 (1Y)
310N	Sonoma Instrument	Pre-Amplifier	312544	Mar. 15, 2022 (1Y)
SCU18	Rohde & Schwarz	Pre-Amplifier	102266	Jul. 12, 2022 (1Y)
FMZB 1513	Schwarzbeck	Loop Antenna	1513-235	Mar. 24, 2022 (2Y)
HLP-2008	TDK	Hybrid Antenna	131313	Fed. 21, 2022 (2Y)
BBHA9120D	Schwarzbeck	Horn Antenna	295	Mar. 02, 2022 (1Y)
ESCI	Rohde & Schwarz	EMI TEST RECEIVER	101012	Oct. 20, 2021 (1Y)
NSLK8128	Schwarzbeck	V - LISN (4*32/50A)	8128216	Mar. 14, 2022 (1Y)
NSLK8121	Schwarzbeck	V - LISN	804	Oct. 19, 2021 (1Y)
ESH3-Z2	Rohde & Schwarz	PULSE LIMITER	100655	Mar. 14, 2022 (1Y)
DT3000-3t	Innco System	Turn Table	DT3000/093	N/A
MA-4000XPET	Innco System	Antenna Master	MA4000/509	N/A