





RF Exposure Evaluation Report

FCC ID : 2AD37JIKMW115K

Equipment : Full-Size Wireless Keyboard

Brand Name : j5create

Model Name : JIKMW115-K

Applicant : KAIJET TECHNOLOGY INTERNATIONAL CORPORATION

8F., No.109, Zhongcheng Rd., Tucheng Dist.,

New Taipei City 236, Taiwan, R.O.C.

Manufacturer : Magic Control Technology Corporation

10F., No.123, Zhongcheng Rd., Tucheng Dist.,

New Taipei City 236, Taiwan R.O.C.

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Jul. 26, 2021, and testing was started from Sep. 29, 2021 and completed on Sep. 29, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 5
FAX: 886-3-327-0973 Issued Date : Oct. 10

FCC ID: 2AD37JIKMW115K



Table of Contents

1.	Gene	eral Descriptioneral Description	. 4			
	1.1.	EUT General Information Testing Location Information	4			
2.	RF Exposure Evaluation					
	2.1.	Applicable Standard	5			
		SAR evaluation				

Photographs of EUT V01

TEL: 886-3-327-3456 FAX: 886-3-327-0973

Report Template No.: HE1-A3 Ver4.0

FCC ID: 2AD37JIKMW115K

Page Number : 2 of 5

Issued Date : Oct. 18, 2021

Report Version : 01



History of This Test Report

Report No.	Version	Description	Issued Date
FA172603-03AA	01	Initial issue of report	Oct. 18, 2021

Reviewed by: Sam Tsai Report Producer: Jenny Yang

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Oct. 18, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 01 FCC ID: 2AD37JIKMW115K



1. General Description

1.1. EUT General Information

	RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type	
2.4GHz WLAN	2400-2483.5	2412-2462	GFSK	

1.2. Testing Location Information

Tes	Test Lab. : Sporton International Inc. Hsinhua Laboratory					
\boxtimes	Hsinhua	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)				
	(TAF: 3785)	TEL: 886-3-327-3456	FAX: 886-3-327-0973			
	ith FCC.					
	Wen 33rd.St.	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)				
	(TAF: 3785)	TEL: 886-3-318-0787	FAX: 886-3-318-0287			
	Test site Designation No. TW0008 with FCC.					

TEL: 886-3-327-3456 Page Number : 4 of 5
FAX: 886-3-327-0973 Issued Date : Oct. 18, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 01 FCC ID: 2AD37JIKMW115K



2. RF Exposure Evaluation

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]•

 $[\sqrt{f}_{(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power	Tolerance	Tune-up Max. Power		Test Distance	Frequency	Exclusion
(dBm)	(dB)	(dBm)	(mW)	(mm)	(GHz)	Thresholds
-17.97	0.5	-17.47	0.02	5	2.40385	0.01

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is 0.01 < 3, RF exposure evaluation is not required.

——THE END——

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Oct. 18, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 01 FCC ID: 2AD37JIKMW115K