




FCC RADIO TEST REPORT

Applicant	: Kaijet Technology International Corporation
Address	: 8F., No. 109, Zhongcheng Road, Tucheng Dist., New Taipei City, Taiwan R.O.C
Equipment	: Qi2 3-in-1 Magnetic Foldable Wireless Charging Station
	JUPW3415, JUPW3415YPZ (All model provide with main wireless charging stand product; Y can be blank, A to Z represent different appearance colour; P can be blank, with or without for marketing purpose only; Z can be blank, A to Z, a to z, 0-9 represent non-power related accessory(s) included in box)
Model No.	: different appearance colour; P can be blank, with or without for marketing purpose only; Z can be blank, A to Z, a to z, 0-9 represent non-power related accessory(s) included in box)
Trademark	: j5create
FCC ID	: 2AD37JUPW3415

I HEREBY CERTIFY THAT:

The sample was received on Jun. 14, 2024 and the test items were conducted during Jul. 03, 2024~Aug. 01, 2024 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:



Leevin Li / Supervisor



Contents

1. Report of Measurements and Examinations	4
1.1 List of Measurements and Examinations	4
2. Test Configuration of Equipment under Test	5
2.1 Feature of Equipment under Test.....	5
2.2 Description of the test mode	6
2.3 Description of Test System.....	8
2.4 General Information of Test.....	9
2.5 Measurement Uncertainty	9
3. Test Equipment and Ancillaries Used for Tests.....	10
4. Antenna Requirements.....	11
4.1 Standard Applicable	11
4.2 Antenna Construction.....	11
4.3 Result	11
5. Test of Conducted Emission.....	12
5.1 Test Limit	12
5.2 Test Procedures	12
5.3 Typical Test Setup	13
5.4 Test Result and Data.....	14
6. Test of Radiated Emission	16
6.1 Test Limit	16
6.2 Test Procedures	17
6.3 Typical Test Setup	18
6.4 Test Result and Data	19
7. 20dB Bandwidth.....	25
7.1 Test Limit	25
7.2 Test Procedures	25
7.3 Typical Test Setup	25
7.4 Test Result and Data	26



History of this test report

- Original.
- Additional attachment as following record:



1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC CFR Title 47 Part 15 Subpart C Section 15.209

FCC Rule	Description of Test	Result
§ 15.203	. Antenna Requirement	Pass
§ 15.207(a)	. Conducted Emission	Pass
§ 15.209(a)	. Radiated Emission	Pass
§ 15.215	20dB Bandwidth	Pass

Note: Deviations Yes No

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Product	Qi2 3-in-1 Magnetic Foldable Wireless Charging Station	
Model No.	JUPW3415, JUPW3415YPZ (All model provide with main wireless charging stand product; Y can be blank, A to Z represent different appearance colour; P can be blank, with or without for marketing purpose only; Z can be blank, A to Z, a to z, 0-9 represent non-power related accessory(s) included in box)a to z, 0-9 represent non-power related accessory(s) included in box)	
Model Discrepancy	See explanation of model designation JUPW3415YPZ. Model JUPW3415 is the representative for final test.	
Frequency Range	Output Wireless 1	Magnetic wireless charging: 360KHz
	Output Wireless 2	Wireless charging for earphone: 111~205KHz
	Output Wireless 3	Wireless charging for watch: 325KHz
Antenna Type	Coil Antenna	
Modulation Type	Output Wireless 1: FSK Output Wireless 2: ASK Output Wireless 3: ASK	
Input	5.0V~3.0A,9.0V~3.0A (27.0W Max)	
Magnetic wireless charging	5.0W,7.5W,10.0W,15.0W(Max)	
Wireless charging for earphone	5.0W(Max)	
Wireless charging for watch	Compatible with Apple® Watch®: Series 9/ Ultra 2/Ultra/8/7/SE/6/5/4/3/2/1	
Operating Temperature	-10°C~+40°C	

Note: For more details, please refer to the User's manual of the EUT.



2.2 Description of the test mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The EUT was tested under the following modes, the worst mode was recorded in this report.

For Conducted Emission	
Pre-tested Mode:	Description
Mode 1	Wireless Charging for Wireless 1(Standby mode) +Wireless 2(Standby mode)+ Wireless 3(Standby mode) for 120V
Mode 2	Wireless Charging for Wireless 1(15W for Wireless Load, Operating @360KHz) +Wireless 2(5W for Wireless Load, Operating @111~205KHz) +Wireless 3(5W for Apple watch 6, Operating @325KHz) for 120V
Mode 3	Wireless Charging for Wireless 1(15W for Wireless Load, Operating @360KHz) +Wireless 2(5W for Wireless Load, Operating @111~205KHz) +Wireless 3(5W for Apple watch 6, Operating @325KHz) for 240V
Worst test Mode	Description
Mode 2	Wireless Charging for Wireless 1(15W for Wireless Load, Operating @360KHz) +Wireless 2(5W for Wireless Load, Operating @111~205KHz) +Wireless 3(5W for Apple watch 6, Operating @325KHz) for 120V
For Radiated Emission	
Pre-tested Mode:	Description
Mode 1	Wireless Charging for Wireless 1(Standby mode) +Wireless 2(Standby mode)+ Wireless 3(Standby mode)
Mode 2	Wireless Charging for Wireless 1(15W for Wireless Load, Operating @360KHz) +Wireless 2(5W for Wireless Load, Operating @111~205KHz) +Wireless 3(5W for Apple watch 6, Operating @325KHz)
Worst test Mode For Radiated Emission (9KHz-30MHz)	
Mode 2	Wireless Charging for Wireless 1(15W for Wireless Load, Operating @360KHz) +Wireless 2(5W for Wireless Load, Operating @111~205KHz) +Wireless 3(5W for Apple watch 6, Operating @325KHz)
Worst test Mode For Radiated Emission (30MHz-1GHz)	
Mode 2	Wireless Charging for Wireless 1(15W for Wireless Load, Operating @360KHz) +Wireless 2(5W for Wireless Load, Operating @111~205KHz) +Wireless 3(5W for Apple watch 6, Operating @325KHz)

Note:

a: While charging, client devices were between 20% to 50% state of charge.

b: The EUT Have three coils, the specific location is shown below:






2.3 Description of Test System

Product	Manufacturer	Model No.	S/N	Power Cord
1 Adapter	XIAOMI	HA832	N/A	N/A
2 Wireless Load 1	YBZ	N/A	N/A	N/A
3 Wireless Load 2	YBZ	N/A	N/A	N/A
4 Apple watch	Apple	Apple watch 6	GY6F512JQ1RN	N/A

Connection Diagram



Signal Cable Type	Quantity	Signal cable Description
A	Type-C Cable	1m Shielding



2.4 General Information of Test

Test Site	Cerpass Technology Corporation(Cerpass Laboratory) Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 9 kHz to 40,000MHz
Test Distance:	9KHz~30MHz: radiated emission from antenna to EUT is 3 M. 30MHz~1GHz: radiated emission from antenna to EUT is 3 M.

Test Item	Test Site	Test period	Environmental Conditions	Tested By
Radiated Emissions	3M01-DG	2024/07/03~2024/07/31	23~26°C / 54~58%	Amos Zhang
AC Power Line Conducted Emission	CON01-DG	2024/08/01	25°C / 59%	Amos Zhang

2.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2).

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±2.52dB
Radiated Spurious Emission(9KHz~30MHz)	±4.10dB
Radiated Spurious Emission(30MHz~1GHz)	±4.51dB
Radiated Spurious Emission(1GHz~18GHz)	±5.49dB



3. Test Equipment and Ancillaries Used for Tests

AC Power Line Conducted Emission					
Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100564	2024/01/03	2025/01/02
LISN	SCHWARZBECK	NSLK 8127	8127749	2023/08/03	2024/08/02
LISN	R&S	ENV216	100024	2024/01/03	2025/01/02
ISN	SCHWARZBECK	T8 CAT6	173	2023/08/03	2024/08/02
Pulse Limiter with 10dB Attenuation	SCHWARZBECK	VTSD 9561-F	9561-F106	2024/01/03	2025/01/02
Cable	Aoda	RG214	Cable-06	2024/01/03	2025/01/02
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2023/08/03	2024/08/02
Software	AUDIX	E3	Version: 8.14806b	N/A	N/A

Radiated Emissions					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Test Receiver	R&S	ESCI	100565	2023/08/03	2024/08/02
Amplifier	EMCI	EMC330	980082	2024/01/03	2025/01/02
Loop Antenna	R&S	HFH2-Z2	100150	2024/01/03	2026/01/02
Bilog Antenna	Sunol Science	JB1	A072414-3	2023/06/18	2025/06/17
Preamplifier	Agilent	8449B	3008A02342	2023/08/03	2024/08/02
Preamplifier	COM-POWER	PA-840	711885	2024/01/03	2025/01/02
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2024/01/03	2026/01/02
Standard Gain Horn Antenna	TRC	HA-2640	18050	2024/01/03	2026/01/02
Standard Gain Horn Antenna	TRC	HA-1726	18051	2024/01/03	2026/01/02
FSQ Signal Analyzer	R&S	FSQ40	200012	2024/01/03	2025/01/02
Cable	EMCI	EM104-NMS M-8.5M	Cable-03	2023/08/03	2024/08/02
Cable	Jiuzhoubona	T-SMA	SMA48AL-7000	2023/08/03	2024/08/02
Cable	CH-CoDesigh	CCXA40-2.92 -2.92-1M	21071954	2023/08/03	2024/08/02
Cable	CH-CoDesigh	CCX40-2.92M -2.92M-9M	21070892	2023/08/03	2024/08/02
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2023/08/03	2024/08/02



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 Antenna Construction

The antenna is Coil Antenna, and the antenna connector is de-signed with permanent attachment and on consideration of replacement. Please see the EUT photo for details.

4.3 Result

The EUT antenna is Loop Antenna. It complies with the standard requirement.



5. Test of Conducted Emission

5.1 Test Limit

According to §15.207: For all the consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

Remark: (1)*Decreases with the logarithm of the frequency.


(2)The lower limit shall apply at the transition frequency.

5.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.





5.3 Typical Test Setup





5.4 Test Result and Data







6. Test of Radiated Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by According to §15.209(a), for a intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following valuses:

Radiated Emission Limit (9KHz~1000MHz)

FREQUENCIES(MHz)	FIELD STRENGTH(microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dB_uV/m)=20log Emission Level(uV/m)




6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 1/3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.




6.3 Typical Test Setup

Below 30MHz Test Setup




30M - 1GHz Test Setup





6.4 Test Result and Data


For 9KHz~30MHz



Note: Level = Reading + Factor

Margin = Level – Limit


Factor= Antenna Factor + Cable Loss - Amplifier Factor



Note: Level = Reading + Factor

Margin = Level – Limit


Factor= Antenna Factor + Cable Loss - Amplifier Factor



Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor




Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor




For 30MHz~1GHz





Test Mode :	Mode 2	Pol/Phase :	Horizontal
Power :	AC 120V/60Hz		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dB _{uV})	Level (dB _{uV/m})	Limit (dB _{uV/m})	Margin (dB)	Detector	P/F
1	82.38	-15.95	54.27	38.32	40.00	-1.68	QP	P
2	144.46	-10.25	48.91	38.66	43.50	-4.84	QP	P
3	173.56	-11.21	50.18	38.97	43.50	-4.53	QP	P
4	200.72	-10.64	47.74	37.10	43.50	-6.40	QP	P
5	257.95	-10.48	47.72	37.24	46.00	-8.76	Peak	P
6	359.80	-7.44	41.50	34.06	46.00	-11.94	Peak	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



7. 20dB Bandwidth


7.1 Test Limit

None: for reporting purposes only.

7.2 Test Procedures

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.215, must be designed to ensure that 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates is contained within the frequency band designated in the rule section under which the equipment is operated.

7.3 Typical Test Setup






7.4 Test Result and Data


Wireless 1 (15W for Wireless Load, Operating @360KHz)

Frequency (kHz)	20 dB bandwidth (kHz)
360KHz	0.048




Wireless 2 (5W for Wireless Load, Operating @ 111~205KHz)

Frequency (kHz)	20 dB bandwidth (kHz)
121.124KHz	0.050





Wireless 3 (5W for Apple watch 6, Operating @325KHz)



----- End of the report -----