

## RF EXPOSURE EVALUATION

### EUT Specification

|                                   |   |
|-----------------------------------|---|
| <b>EUT</b>                        | SOUNDBAR  |
| <b>Frequency band (Operating)</b> | <input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz<br><input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz<br><input checked="" type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz) |
| <b>Device category</b>            | <input type="checkbox"/> Portable (<20cm separation)<br><input checked="" type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others ____   |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/> Single antenna<br><input type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input type="checkbox"/> Tx/Rx diversity                                |
| <b>Max. output power</b>          | 0.733 dBm (1.184mW)   |
| <b>Antenna gain</b>               | 0 dBi   |
| <b>Evaluation applied</b>         | <input checked="" type="checkbox"/> MPE Evaluation<br><input type="checkbox"/> SAR Evaluation   |

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range(MHz)   | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| <b>(A) Limits for Occupational/Control Exposures</b>         |                              |                              |                                    |              |
| 300-1500   | --                           | --                           | F/300                              | 6            |
| 1500-100000  | --                           | --                           | 5                                  | 6            |
| <b>(B) Limits for General Population/Uncontrol Exposures</b> |                              |                              |                                    |              |
| 300-1500   | --                           | --                           | F/1500                             | 6            |
| 1500-100000  | --                           | --                           | 1                                  | 30           |

## Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

| Channel          | Gain | Channel Frequency (MHz) | Max Output power (dBm) | Tolerance | Max Tune-UP power (mW) | Power density at 20cm (mW/ cm <sup>2</sup> ) | Power density Limits (mW/cm <sup>2</sup> ) |
|------------------|------|-------------------------|------------------------|-----------|------------------------|--|--|
| <b>GFSK</b>      |      |                         |                        |           |                        |  |  |
| Low              | 0    | 2402                    | 0.549                  | ±0.5      | 1.273                  | 2.258E-04                                    | 1  |
| Middle           | 0    | 2441                    | 0.636                  | ±0.5      | 1.299                  | 2.304E-04                                    | 1  |
| High             | 0    | 2480                    | 0.405                  | ±0.5      | 1.232                  | 2.184E-04                                    | 1  |
| <b>π/4-DQPSK</b> |      |                         |                        |           |                        |  |  |
| Low              | 0    | 2402                    | 0.525                  | ±0.5      | 1.266                  | 2.244E-04                                    | 1  |
| Middle           | 0    | 2441                    | -0.756                 | ±0.5      | 0.943                  | 1.671E-04                                    | 1  |
| High             | 0    | 2480                    | -0.892                 | ±0.5      | 0.914                  | 1.619E-04                                    | 1  |
| <b>8DPSK</b>     |      |                         |                        |           |                        |  |  |
| Low              | 0    | 2402                    | 0.572                  | ±0.5      | 1.280                  | 2.270E-04                                    | 1  |
| Middle           | 0    | 2441                    | 0.733                  | ±0.5      | 1.328                  | 2.355E-04                                    | 1  |
| High             | 0    | 2480                    | 0.488                  | ±0.5      | 1.255                  | 2.226E-04                                    | 1  |