



REPORT No. : SZ15010124S01

# RF EXPOSURE EVALUATION REPORT

APPLICANT : SHENZHEN KEWEITAI ENTERPRISE  
DEVELOPMENT CO., LTD

PRODUCT NAME : T460 UAV HD VIDEO TRANSMITTER

MODEL NAME : T460

TRADE NAME : ALLTECH

BRAND NAME : ALLTECH

FCC ID : 2AD5L-T460

STANDARD(S) : 47CFR 2.1091  
KDB 447498 D01 General RF Exposure  
Guidance v06

ISSUE DATE : 2016-07-29



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB GROUP**

FL1-3, Building A, FeiYang Science Park, No 8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Http://www.morlab.com

Fax: 86-755-36698525  
E-mail: service@morlab.cn



# DIRECTORY

**TEST REPORT DECLARATION..... 3**

**1. TECHNICAL INFORMATION ..... 4**

1.1. IDENTIFICATION OF APPLICANT ..... 4

1.2. IDENTIFICATION OF MANUFACTURER ..... 4

1.3. EQUIPMENT UNDER TEST (EUT)..... 4

1.3.1. PHOTOGRAPHS OF THE EUT..... 5

1.3.2. IDENTIFICATION OF ALL USED EUT..... 6

1.4. APPLIED REFERENCE DOCUMENTS..... 6

**2. DEVICE CATEGORY AND RF EXPOSURE LIMIT ..... 7**

**3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER ..... 8**

**4. RF EXPOSURE EVALUATION..... 9**

**ANNEX C GENERAL INFORMATION..... 10**

Change History		
Issue	Date	Reason for change
1.0	2016-07-29	First edition

**TEST REPORT DECLARATION**

Applicant	SHENZHEN KEWEITAI ENTERPRISE DEVELOPMENT CO., LTD
Applicant Address	2F,BUILDING C3, Hengfeng Industrial Area, Baoan District, Shenzhen, 518126 P.R.C
Manufacturer	SHENZHEN KEWEITAI ENTERPRISE DEVELOPMENT CO., LTD
Manufacturer Address	2F,BUILDING C3, Hengfeng Industrial Area, Baoan District, Shenzhen, 518126 P.R.C
Product Name	T460 UAV HD VIDEO TRANSMITTER
Model Name	T460
Brand Name	ALLTECH
HW Version	V2
SW Version	V1.5
Test Standards	47CFR 2.1091; KDB 447498 D01 General RF Exposure Guidance v06
Issue Date	2016-07-29
SAR Evaluation	Not Required

Tested by : Chen Shengkui  
Chen Shengkui

Reviewed by : Liu Jun  
Liu Jun

Approved by : Zeng Dexin  
Zeng Dexin



## 1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

### 1.1. Identification of Applicant

Company Name:	SHENZHEN KEWEITAI ENTERPRISE DEVELOPMENT CO., LTD
Address:	2F,BUILDING C3, Hengfeng Industrial Area, Baoan District, Shenzhen, 518126 P.R.C

### 1.2. Identification of Manufacturer

Company Name:	SHENZHEN KEWEITAI ENTERPRISE DEVELOPMENT CO., LTD
Address:	2F,BUILDING C3, Hengfeng Industrial Area, Baoan District, Shenzhen, 518126 P.R.C

### 1.3. Equipment Under Test (EUT)

Model Name:	T460
Trade Name:	ALLTECH
Brand Name:	ALLTECH
Hardware Version:	V2
Software Version:	V1.5
Frequency Bands:	2420MHz-2440MHz
Modulation Mode:	COFDM
Antenna type:	Dedicated Antenna
Antenna Gain:	5dBi

### 1.3.1. Photographs of the EUT

#### 1. EUT front view



#### 2. EUT rear view





### 1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	V2	V1.5

### 1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	<b>47 CFR§2.1091</b>	Radiofrequency Radiation Exposure Evaluation: mobile devices
2	<b>KDB 447498 D01v06</b>	General RF Exposure Guidance



## 2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, this device is a T460 UAV HD video Transmitter. Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

### Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

### GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density



### 3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

#### 1. 2.4G Conducted Peak Output Power

Band	Channel	Frequency (MHz)	Output Power(dBm)		
			1.5MHz BW	4MHz BW	8MHz BW
WiFi 2.4G	1	2412	20.83	20.89	20.83
	6	2437	21.13	21.18	21.16
	11	2462	20.98	20.99	20.91



## 4. RF EXPOSURE EVALUATION

### Standalone transmission MPE evaluation

Bands	Frequency (MHz)	Antenna Gain (dBi)	Conducted Power (dBm)	Time-averaging EIRP (mW)	Power density (mW/cm <sup>2</sup> )	Limit for MPE (mW/cm <sup>2</sup> )
2430	2430	5	21.18	414.95	0.08	1.0

Note:

1. MPE calculation method

$$\text{Power Density} = \text{EIRP}/4\pi R^2$$

Where:  $\text{EIRP} = P \cdot G$

P = Peak out power

G = Antenna gain

R = Separation distance (20cm)



## ANNEX C GENERAL INFORMATION

### 1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

\*\*\*\*\* END OF REPORT \*\*\*\*\*