



REPORT No. : SZ16060065E02

# FCC TEST REPORT

**APPLICANT** : XIAMEN RONGTA TECHNOLOGY CO., LTD.

**PRODUCT NAME** : Thermal Receipt Printer

**MODEL NAME** : RP326-USE, RP325-L, RP325-U, RP325-USE,  
RP326-L, RP326-U, RP326-US, RP327-L,  
RP327-US, RP327-USE

**TRADE NAME** : Rongta

**BRAND NAME** : Rongta

**FCC ID** : 2AD6G-RP326-USE

**STANDARD(S)** : 47 CFR Part 15 Subpart B

**TEST DATE** : 2016-06-15 to 2016-09-05

**ISSUE DATE** : 2016-09-07

**SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.**



NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB GROUP**

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Http://www.morlab.cn

Fax: 86-755-36698525  
E-mail: service@morlab.cn



## DIRECTORY

<b>1. TECHNICAL INFORMATION</b>	<b>5</b>
1.1. APPLICANT INFORMATION	5
1.2. EQUIPMENT UNDER TEST (EUT) DESCRIPTION	5
<b>2. TEST RESULTS</b>	<b>6</b>
2.1. APPLIED REFERENCE DOCUMENTS	6
<b>3. TEST CONDITIONS SETTING</b>	<b>7</b>
3.1. TEST MODE	7
3.2. TEST SETUP AND EQUIPMENTS LIST	8
3.2.1. CONDUCTED EMISSION	8
3.2.2. RADIATED EMISSION	9
<b>4. 47 CFR PART 15B REQUIREMENTS</b>	<b>10</b>
4.1. CONDUCTED EMISSION	10
4.1.1. REQUIREMENT	10
4.1.2. TEST DESCRIPTION	10
4.1.3. TEST RESULT	10
4.2. RADIATED EMISSION	13
4.2.1. REQUIREMENT	13
4.2.2. TEST DESCRIPTION	13
4.2.3. FREQUENCY RANGE OF MEASUREMENT	14
4.2.4. TEST RESULT	14
<b>ANNEX A PHOTOGRAPHS OF TEST SETUP</b>	<b>17</b>
<b>ANNEX B TEST UNCERTAINTY</b>	<b>19</b>
<b>ANNEX C TESTING LABORATORY INFORMATION</b>	<b>20</b>



REPORT No. : SZ16060065E02

- 1. IDENTIFICATION OF THE RESPONSIBLE TESTING LABORATORY .....20
- 2. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION.....20
- 3. ACCREDITATION CERTIFICATE .....20
- 4. TEST ENVIRONMENT CONDITIONS .....20

**Change History**

Issue	Date	Reason for change
1.0	2016-09-07	First edition



### Test Report Declaration

Applicant	XIAMEN RONGTA TECHNOLOGY CO., LTD.
Applicant Address	3F-1/E Building, No.195 Gaoqishe, Gaodian Village, Dianqian Street Office, Huli District, Xiamen City
Manufacturer	XIAMEN RONGTA TECHNOLOGY CO., LTD.
Manufacturer Address	3F-1/E Building, No.195 Gaoqishe, Gaodian Village, Dianqian Street Office, Huli District, Xiamen City
Product Name	Thermal Receipt Printer
Model Name	RP326-USE, RP325-L, RP325-U, RP325-USE, RP326-L, RP326-U, RP326-US, RP327-L, RP327-US, RP327-USE
Brand Name	Rongta
HW Version	N/A
SW Version	N/A
Test Standards	47 CFR Part 15 Subpart B
Test Result	PASS

Tested by : Wang Dalong  
Wang Dalong (Test Engineer)

Reviewed by : Xiao Xiong  
Xiao Xiong (EMC Manager)

Approved by : Zeng Dexin  
Zeng Dexin (Technology Manager)



# 1. Technical Information

Note: Provided by applicant

## 1.1. Applicant Information

Company: XIAMEN RONGTA TECHNOLOGY CO., LTD.  
Address: 3F-1/E Building, No.195 Gaoqishe, Gaodian Village, Dianqian Street Office,  
Huli District, Xiamen City

## 1.2. Equipment under Test (EUT) Description

<b>EUT Type:</b>	Thermal Receipt Printer
<b>Serial No:</b>	(N/A, marked #1 by test site)
<b>Hardware Version:</b>	N/A
<b>Software Version:</b>	N/A

<b>Ancillary Equipment:</b>	<b>AC Adapter (Charger for Battery)</b>	
	Brand Name:	DAJING
	Model No.:	ADP-60E4
	Serial No.:	(N/A, marked #1 by test site)
	Rated Input:	~ 100-240V, 50/60Hz, 1.5 A
	Rated Output:	= 24V, 2.5 A

### NOTE:

1. The EUT is a Thermal Receipt Printer. The EUT is equipped with a serial, an USB port, an Ethernet port, a cash drawer and a power port.
2. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.



## 2. Test Results

### 2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15(September 02, 2016 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Result
1	15.107	Conducted Emission	2016.09.02	PASS
2	15.109	Radiated Emission	2016.09.02	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.



### 3. Test Conditions Setting


#### 3.1. Test Mode

1	<b>The first test mode(Serial)</b> The EUT configuration of the emission tests is EUT + Adapter + PC. During the measurement, the EUT was connected with an Adapter and kept charging by the Adapter, the EUT was connected with PC via the serial, the EUT was working normally as an intentional device.
2	<b>The second test mode(USB)</b> The EUT configuration of the emission tests is EUT + Adapter + PC. During the measurement, the EUT was connected with an Adapter and kept charging by the Adapter, the EUT was connected with PC via the USB port, the EUT was working normally as an intentional device.
3	<b>The third test mode (Ethernet port)</b> The EUT configuration of the emission tests is EUT + Adapter + PC. During the measurement, the EUT was connected with an Adapter and kept charging by the Adapter, the EUT was connected with PC via the Ethernet port, the EUT was working normally as an intentional device.
4	<b>The fourth test mode (Cash Drawer)</b> The EUT configuration of the emission tests is EUT + Adapter + PC. During the measurement, the EUT was connected with an Adapter and kept charging by the Adapter, the EUT was connected with PC via the Cash Drawer port, the EUT was working normally as an intentional device.
<b>NOTE: All test modes are performed, only the worst case(USB)is recorded in this report.</b>	

## 3.2. Test Setup and Equipments List

### 3.2.1. Conducted Emission

#### A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides  $50\Omega/50\mu\text{H}$  of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.


#### B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
Receiver	Narda	PMM 9060	001WX11001	2015.11.26	2016.11.25
Receiver	Narda	PMM 9010	595WX11007	2016.01.13	2017.01.12
LISN	Schwarzbeck	NSLK 8127	812744	2016.01.13	2017.01.12
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	2016.01.13	2017.01.12
PC	lenovo	ThinkPadT430i	N/A	N/A	N/A



### 3.2.2. Radiated Emission

#### A. Test Setup:



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna: In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) is used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

#### B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
MXE EMIR Receiver	Agilent	N9038A	MY54130016	2016.01.13	2017.01.12
Semi-Anechoic Chamber	Changning	9m*6m*6m	N/A	2016.01.13	2017.01.12
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2016.01.13	2017.01.12
PC	lenovo	ThinkPad T430i	N/A	N/A	N/A



## 4. 47 CFR Part 15B Requirements

### 4.1. Conducted Emission

#### 4.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.


#### 4.1.2. Test Description

See section 3.2.1 of this report.


#### 4.1.3. Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

##### A. Test Plot and Suspicious Points:



NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.15	56.91	31.98	66.00	56.00	Line	PASS
2	0.695	36.16	23.90	56.00	46.00		PASS
3	8.665	36.09	32.50	60.00	50.00		PASS
4	9.68	39.33	31.97	60.00	50.00		PASS
5	10.485	36.26	30.81	60.00	50.00		PASS
6	13.46	35.70	27.65	60.00	50.00		PASS



NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.15	48.58	25.18	66.00	56.00	Neutral	PASS
2	2.115	34.98	27.33	56.00	46.00		PASS
3	8.755	37.87	30.46	60.00	50.00		PASS
4	9.745	38.79	28.81	60.00	50.00		PASS
5	10.495	33.37	25.21	60.00	50.00		PASS
6	13.475	36.13	26.91	60.00	50.00		PASS

**Test Result: PASS**



## 4.2. Radiated Emission

### 4.2.1. Requirement

According to FCC section 15.109(a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength Limitation at 3m Measurement Dist	
	( $\mu\text{V/m}$ )	( $\text{dB}\mu\text{V/m}$ )
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in  $\text{dB}\mu\text{V/m}$  is calculated by  $20\log$  Emission Level( $\mu\text{V/m}$ ).
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $L_{d1} = L_{d2} * (d_2/d_1)^2$ .

Example:

F.S Limit at 30m distance is  $30\mu\text{V/m}$ , then F.S Limitation at 3m distance is adjusted as

$$L_{d1} = L_1 = 30\mu\text{V/m} * (10)^2 = 100 * 30\mu\text{V/m}$$

### 4.2.2. Test Description

See section 3.2.2 of this report.



### 4.2.3. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705 .....	30.
1.705-108 .....	1000.
108-500 .....	2000.
500-1000 .....	5000.
Above 1000 .....	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

The highest frequency of the internal sources of the EUT is less than 108MHz, the measurement shall only be made up to 1G.


### 4.2.4. Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.

#### A. Test Plots and Suspicious Points:



(Plot A: 30MHz –1GHz, Test Antenna Vertical)

No.	Fre. MHz	Pk dB $\mu$ V/m	QP dB $\mu$ V/m	AV dB $\mu$ V/m	Limit-PK dB $\mu$ V/m	Limit-QP dB $\mu$ V/m	Limit-AV dB $\mu$ V/m	ANT	Verdict
1	43.580	N.A.	29.24	N.A.	N.A.	40.00	N.A.	V	PASS
2	138.640	N.A.	30.28	N.A.	N.A.	43.50	N.A.	V	PASS
3	268.620	N.A.	41.16	N.A.	N.A.	46.00	N.A.	V	PASS
4	450.010	N.A.	39.04	N.A.	N.A.	46.00	N.A.	V	PASS
5	497.540	N.A.	38.30	N.A.	N.A.	46.00	N.A.	V	PASS
6	798.240	N.A.	26.06	N.A.	N.A.	46.00	N.A.	V	PASS




No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	55.220	N.A.	18.71	N.A.	N.A.	40.00	N.A.	H	PASS
2	104.690	N.A.	28.50	N.A.	N.A.	43.50	N.A.	H	PASS
3	228.850	N.A.	33.97	N.A.	N.A.	46.00	N.A.	H	PASS
4	268.620	N.A.	43.85	N.A.	N.A.	46.00	N.A.	H	PASS
5	438.370	N.A.	33.82	N.A.	N.A.	46.00	N.A.	H	PASS
6	800.180	N.A.	28.38	N.A.	N.A.	46.00	N.A.	H	PASS

**Test Result: PASS**



## Annex A Photographs of Test Setup

### 1. Conducted emission main's port front view




### 2. Conducted emission main's port side view





3. Radiated emission (30MHz-1GHz)





## **Annex B Test Uncertainty**

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	$\pm 1.8\text{dB}$
Uncertainty of Radiated Emission:	$\pm 3.1\text{dB}$



## Annex C Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Accreditation Certificate

Accredited Testing Laboratory: The FCC registration number is 695796.  
(Shenzhen Morlab Communications Technology Co., Ltd.)

### 4. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

\*\*\*\*\* END OF REPORT \*\*\*\*\*