

## RF exposure Estimation

### 1. Introduction

Product Description	Remote Control
Model Name	CX-35, CX-20, CX-22, CX-36, CX-37, CX-23, CX-24, CX-91, CX-92, CX-93
RF Transmission Frequency:	2420MHz-2465MHz
FCC ID	2AD6LGC0324352

### 2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right]$$

$$[\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>25</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### 3. Calculation method

According to the follow transmitter output power (Pt) formula:

$$P_t = (E \times d)^2 / (30 \times g_t)$$

Pt=transmitter output power in watts

gt=numeric gain of the transmitting antenna (unitless)

E=electric field strength in V/m

d=measurement distance in meters (m)

$$E_{\max} = 92.37 \text{ dBuV/m} = 0.042 \text{ V/m}, d = 3 \text{ m}, g_t = 2$$

$$P_t = (E \times d)^2 / (30 \times g_t) = 0.00105 \text{ W} = 1.05 \text{ mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (1.05 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.465} (\text{GHz})] = 0.33 < 3.0 \text{ for 1-g SAR}$$

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch


Reviewed by:



John Zhi/ EMC Project Manager

Date: 2016-06-30

Prepared By:



Alan Xiong/EMC Project Engineer

Date: 2016-06-30