

# Test Report

Verified code: 653833

Report No.: E202309059135-01-9

Customer: Kräemer Automotive Systems GmbH

Address: Obere Wässere 6-8 72764 Reutlingen Germany

Sample Name: Bentley Infotainment System(BIS)

Sample Model: KR-BIS

Receive Sample Date: Sep.22,2023

Test Date: Nov.28,2023 ~ May.10,2024

Reference Document: 47 CFR, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices

Test Result: Pass

Prepared by: Chen Xiaocong  
Chen Xiaocong

Reviewed by: Wu Haoting  
Wu Haoting

Approved by: Xiao Liang  
Xiao Liang

GRG METROLOGY & TEST GROUP CO., LTD.

Issued Date: 2024-07-24

GRG METROLOGY & TEST GROUP CO., LTD.

Address: No.163,Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China  
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



## Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. This testing report is only for scientific research, teaching, internal quality control, etc.

——Blank space below this page——

## TABLE OF CONTENTS

1.	GENERAL DESCRIPTION OF EUT.....	5
1.1	APPLICANT.....	5
1.2	MANUFACTURER.....	5
1.3	FACTORY .....	5
1.4	BASIC DESCRIPTION OF EQUIPMENT UNDER TEST .....	5
2.	LABORATORY.....	7
2.1	LABORATORY.....	7
2.2	ACCREDITATIONS .....	7
3.	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE .....	8
4.	CALCULATION METHOD .....	9
5.	ESTIMATION RESULT .....	10
5.1	MEASUREMENT RESULTS .....	10
6.	CONCLUSION.....	11

—Blank space below this page—

**REPORT ISSUED HISTORY**

<b>Report Version</b>	<b>Report No.</b>	<b>Description</b>	<b>Compile Date</b>
1.0	E202309059135-01-9	Original Issue	2024-05-23

—Blank space below this page—

## 1. GENERAL DESCRIPTION OF EUT

### 1.1 APPLICANT

Name: Kräemer Automotive Systems GmbH  
Address: Obere Wässere 6-8 72764 Reutlingen Germany

### 1.2 MANUFACTURER

Name: Kräemer Automotive Systems GmbH  
Address: Obere Wässere 6-8 72764 Reutlingen Germany

### 1.3 FACTORY

Name : Huizhou Foryou General Electronics Co., Ltd.  
Address : No.2 District A, Foryou Industry Park, No. 1 North Shangxia Road, Dongjiang Hi tech Industry Park, 516005 Huizhou city, Guangdong Province, China(PROC)

### 1.4 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Equipment: Bentley Infotainment System(BIS)  
Model No.: KR-BIS  
Trade Mark: BENTLEY  
FCC ID: 2AD6S-KRBIS  
Power supply: DC 12V, 15A  
Frequency Band: 5180MHz-5240MHz & 5745MHz~5825MHz for IEEE 802.11a/n HT20/ac VHT20;  
5190MHz-5230MHz & 5755MHz~5795MHz for IEEE 802.11n HT40/ac VHT40;  
5210MHz & 5775MHz for IEEE 802.11ac VHT80  
2402MHz - 2480MHz for Bluetooth LE with 1M  
2402MHz - 2480MHz for Bluetooth GFSK, Pi/4DQPSK, 8DPSK  
Bluetooth LE for 1Mbps:4.32dBm  
Bluetooth for GFSK:4.10dBm  
Bluetooth for Pi/4DQPSK:6.21dBm  
Bluetooth for 8DPSK:6.65dBm  
U-NII-1:  
9.28dBm for IEEE 802.11a  
8.93dBm for IEEE 802.11n HT20  
Transmit Power: 9.31dBm for IEEE 802.11acVHT20  
9.54dBm for IEEE 802.11n HT40  
9.31dBm for IEEE 802.11acVHT40  
8.25dBm for IEEE 802.11ac VHT80  
U-NII-3:  
9.08dBm for IEEE 802.11a  
8.06dBm for IEEE 802.11n HT20  
7.97dBm for IEEE 802.11acVHT20

8.46dBm for IEEE 802.11n HT40  
8.28dBm for IEEE 802.11acVHT40  
8.15dBm for IEEE 802.11ac VHT80

Modulation type: GFSK for Bluetooth LE, GFSK&Pi/4DQPSK&8DPSK for Bluetooth,  
OFDM for IEEE 802.11a/n/ac mode

Bluetooth LE:  
Antenna 1: 2.47dBi gain (Max)

Bluetooth:  
Antenna 1: 2.47dBi gain (Max)

Antenna Specification: 5G WIFI: 5150MHz – 5250MHz  
Antenna 2: 2.58dBi gain (Max)  
5G WIFI: 5725MHz – 5850MHz  
Antenna 2: 3.66dBi gain (Max)

Temperature Range: -20 °C ~ 60 °C

Hardware Version: V0.1

Software Version: V00.00.01

Sample No: E202309059135-01-0001, E202309059135-01-0003

Note: The EUT antenna gain is provided by the applicant. This report is made solely on the basis of such data and/or information. We accept no responsibility for the authenticity and completeness of the above data and information and the validity of the results and/or conclusions.

—Blank space below this page—

## 2. LABORATORY

### 2.1 LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of GRG METROLOGY & TEST GROUP CO., LTD.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District  
Shenzhen, 518110, People's Republic of China.

P.C.: 518110

Tel : 0755-61180008

Fax: 0755-61180008

### 2.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to GB/T 27025(ISO/IEC 17025:2017)

**USA** A2LA(Certificate #2861.01)

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

**Canada** ISED (Company Number: 24897, CAB identifier:CN0069)

**USA** FCC (Registration Number: 759402, Designation Number:CN1198)

Copies of granted accreditation certificates are available for downloading from our web site,

<http://www.grgtest.com>

—Blank space below this page—

### 3. LIMITS FOR GENERAL POPULATION/UNCONTROLLEDEXPOSURE

#### General

According to the KDB 447498 D04 Interim General RF Exposure Guidance v01, General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table 4.1 to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE 4.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
$f_L$ MHz		$f_H$ MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$
1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$
30	–	300	1.6 m	–	159 mm	$3.83 R^2$
300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2f$
1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2R^2$

Subscripts L and H are low and high;  $\lambda$  is wavelength.  
From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

For mobile devices that are not exempt per Table 4.1 at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than  $ERP_{20\text{cm}}$  in Formula (4.1).

Formula (4.1):

$$P_{\text{th}} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$



#### 4. CALCULATION METHOD

Predication of MPE limit at a given distance

$EIRP(dBm) = \text{Maximum Tune-up Output power (dBm)} + \text{Maximum antenna gain(dBi)}$

$ERP(dBm) = EIRP(dBm) - 2.15$

R=minimum distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance,  $d=20\text{cm}$ , as well as the maximum gain of the used as following information, the RF power ERP can be obtained.

**Table 1 Antenna Specification**

Mode	Antenna type	Internal Identification	Maximum antenna gain
Bluetooth LE	Ceramics antenna	Antenna 1	2.47dBi
Bluetooth	Ceramics antenna	Antenna 1	2.47dBi
5GHz WiFi U-NII-1	Ceramics antenna	Antenna 2	2.58dBi
5GHz WiFi U-NII-3	Ceramics antenna	Antenna 2	3.66dBi

**Table 2 Transmit Power**

Mode	Maximum Output Power (dBm)	Maximum Tune-up Output power (dBm)
Bluetooth LE	4.32	$4.00 \pm 1.00$
Bluetooth DH5	4.10	$4.00 \pm 1.00$
Bluetooth 2DH5	6.21	$6.00 \pm 1.00$
Bluetooth 3DH5	6.65	$6.00 \pm 1.00$
5GHz WiFi U-NII-1	802.11a	$9.00 \pm 1.00$
	802.11n HT20	$9.00 \pm 1.00$
	802.11ac VHT20	$9.00 \pm 1.00$
	802.11n HT40	$9.00 \pm 1.00$
	802.11ac VHT40	$9.00 \pm 1.00$
	802.11ac VHT80	$9.00 \pm 1.00$
5GHz WiFi U-NII-3	802.11a	$8.50 \pm 1.00$
	802.11n HT20	$8.50 \pm 1.00$
	802.11ac VHT20	$8.50 \pm 1.00$
	802.11n HT40	$8.50 \pm 1.00$
	802.11ac VHT40	$8.50 \pm 1.00$
	802.11ac VHT80	$8.50 \pm 1.00$

## 5. ESTIMATION RESULT

### 5.1 MEASUREMENT RESULTS

#### STANDALONE MPE

Mode	Frequency (MHz)	Maximum Tune-up Output power (dBm)	Antenna Gain (dBi)	Maximum Tune-up EIRP (dBm)	ERP (dBm)	Maximum Tune-up ERP (W)	Threshold ERP(W)
BLE 1M	2402- 2480	5.00	2.47	7.47	5.32	0.00340	0.768
BT DH5	2402- 2480	5.00	2.47	7.47	5.32	0.00340	0.768
BT DH5	2402- 2480	7.00	2.47	9.47	7.32	0.00540	0.768
BT DH5	2402- 2480	7.00	2.47	9.47	7.32	0.00540	0.768
5GHz WiFi U-NII-1	5150-5250	10.00	2.58	12.58	10.43	0.01104	0.768
5GHz WiFi U-NII-3	5725-5850	9.50	3.66	13.16	11.01	0.01262	0.768

#### Remark:

1. RF Exposure use distance is 20cm from manufacturer declaration of user manual.
2. Threshold  $ERP(W) = 19.2R^2(W) = 19.2 * 0.2^2(W) = 0.768(W)$ .
3. The BLE and BT do not support simultaneous transmission, the BLE and WiFi do not support simultaneous transmission, the BT and WiFi do not support simultaneous transmission.
4.  $ERP(dBm) = EIRP(dBm) - 2.15$

—Blank space below this page—

## 6. CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- End of Report -----