

RF Exposure Report				
(C2PC (Class II Permissive Change)				

Report No.: SA180829C14A

FCC ID: 2AD8UAHBB01

Test Model: AHBB

Received Date: Jan. 30, 2019

Test Date: Mar. 04 ~ Mar. 05, 2019 and Apr. 25 ~ May 03, 2019

Issued Date: May 13, 2019

Applicant: Nokia Solutions and Networks, OY

Address: 2000 W. Lucent Lane, Naperville, IL 60563, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003 Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specification, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Relea	se Control Record	3			
1	I Certificate of Conformity				
2	RF Exposure	5			
2.1 2.2 2.3 2.4	Limits for Maximum Permissible Exposure (MPE) MPE Calculation Formula Classification Antenna Gain	5 5			
3	Calculation Result of Maximum Tune up Power	6			
4	Brief Summary of results	6			



Release Control Record

Issue No.	Description	Date Issued
SA180829C14A	Original release	May 13, 2019

1 Certificate of Conformity

Product:	AirScale Micro Remote Radio Head		
Brand:	Nokia		
Test Model:	AHBB		
Sample Status:	Engineering sample		
Applicant:	Nokia Solutions and Networks, OY		
Test Date:	Mar. 04 ~ Mar. 05, 2019 and Apr. 25 ~ May 03, 2019		
Standards:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01 General RF Exposure Guidance v06		
	IEEE C95.1		

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :	Celine	Ch-u	, Date:	May 13, 2019	
	Celine Chou / Senio	or Specialist			

Approved by :

eu

Date: May 13, 2019

Bruce Chen / Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)			Power Density (mW/cm2)	Average Time (minutes)				
(A)Limits For Occupational / Control Exposures								
300-1500			F/300	6				
1500-100,000	1500-100,000		5	6				
(B)Limits For General Population / Uncontrolled Exposure								
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout^{*}G) / (4^{*}pi^{*}r^{2})$

where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

For General Population

The antenna of this product, under normal use condition, is at least 292cm away from the body of the user. So, this device is classified as **fixed device**.

For Occupational Population

The antenna of this product, under normal use condition, is at least 131cm away from the body of the user. So, this device is classified as **fixed device**.



2.4 Antenna Gain

Model Name	AABA
Sales Item	474230A
Antenna Spec.	Calculation based on the gain of this example Nokia antenna is a maximum of 7dBi \pm 1dBi.
Antenna Model	NA
Antenna Gain	8dBi

3 Calculation Result of Maximum Tune up Power

For General Population

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
LTE Band 13	748.5-753.5	55.10	57.25	292	0.495	0.499
LTE Band 13 NB-IOT Guard Band	751	49.42	51.57	292	0.134	0.500
LTE Band 13 NB-IOT In-Band	751	50.00	52.15	292	0.153	0.500

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For Occupational Population

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
LTE Band 13	748.5-753.5	55.10	57.25	131	2.462	2.495
LTE Band 13 NB-IOT Guard Band	751	49.42	51.57	131	0.666	2.503
LTE Band 13 NB-IOT In-Band	751	50.00	52.15	131	0.761	2.503

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

4 Brief Summary of results

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(cm)		
Configuration	Occupational	General Population	
LTE Band 13	131	292	
LTE Band 13 NB-IOT Guard Band	131	292	
LTE Band 13 NB-IOT In-Band	131	292	

---END---