

**EXHIBIT 4: FCC ID LABEL SAMPLE AND LOCATION INFORMATION**

**SECTION 2.1033(c) (11) also SECTION 2.925 (a) (1)**

**A photograph or drawing of the equipment identification plate or label showing the information to be placed thereon.**

**Response:**

The drawing of the equipment identification labels to be placed on the **Nokia AWEUC/D 5G AirScale 24 GHz mmWave Radio, FCC ID: 2AD8UASMR24FA3UB** are below. A drawing showing label location and drawings of the equipment identification label is attached.

# FCC Label Drawings for Nokia AWEUC 5G AirScale 24 GHz mmWave Radio, FCC ID: 2AD8UASMR24FA3UB - AWEUC Base Unit

1	2	3	4																								
<p><b>NOTES:</b>  <b>CHARACTERISTICS (UNLESS OTHERWISE SPECIFIED):</b>            1. PARTS MUST BE CLEAN AND FREE OF SCRATCHES, BLEMISHES AND IMPERFECTIONS.            2. PACKAGING DESIGN MUST BE APPROVED BY NOKIA BEFORE PROCEEDING WITH PRODUCTION RUN OF PARTS.            3. SAMPLE PARTS MUST BE APPROVED BY NOKIA BEFORE PROCEEDING WITH PRODUCTION RUN.            4. A REFERENCE DIMENSION (X.XX) IS A DIMENSION WITHOUT TOLERANCE AND IS USED FOR INFORMATION PURPOSES ONLY.            5. ALL DIMENSIONS SHOWN ACROSS A CENTERLINE SHALL BE CENTRALIZED WITHIN ONE HALF THEIR TOTAL TOLERANCE.            6. A CRITICAL DIMENSION IS DENOTED WITH A BOX-X SYMBOL X.            7. ALL DIMENSIONS SHOWN ARE IN MILLIMETERS. UNLESS OTHERWISE SPECIFIED            TOLERANCES FOR DIMENSIONS SHOWN ON DRAWING ARE AS FOLLOWS: ZERO (X) OR ONE PLACE (X.X) +/-0.3, TWO PLACE (X.XX) +/-0.13.            8. MATERIAL: NOKIA CODE 836517A            9. ARTWORK TO BE FURNISHED BY NOKIA. INK TO BE UV RESISTANT.            10. LABELS MUST SATISFY UL CATEGORY PGDQ2 AND UL969, LABELS ARE INTENDED FOR OUTDOOR USE AND MUST BE CAPABLE OF WITHSTANDING THE FOLLOWING ENVIRONMENTAL CONDITIONS; OPERATING TEMPERATURE RANGE: -40° C TO +85° C, STORAGE TEMPERATURE RANGE: -40° C TO +105° C, SALT FOG PER GR-487-CORE, ISSUE 2. SECTION 3.34 AND WIND DRIVEN RAIN PER TELCORDIA GR-487-CORE. PARTS MUST BE SUITABLE FOR USE ON ALUMINUM, POLYESTER PAINT, AND ACRYLONITRILE BUTADIENE STYRENE (ABS) PLASTIC TO THE ENVIRONMENTAL CONDITIONS DEFINED ABOVE. PARTS SHOULD BE SUITABLE FOR OTHER SUBSTRATES AND TEMPERATURES AS REQUIRED BY THE INDIVIDUAL UL PGDQ2 FILE THAT IS APPLICABLE.            11. FLAMMABILITY RATING: ALL MATERIALS MUST HAVE A RATING OF UL 94V-2 OR HIGHER            12. NOKIA PART CODE, PART REVISION (SEE DRAWING FOR CODE AND REVISION), MANUFACTURE DATE CODE (WK/YR), AND VENDOR ID MUST BE PERMANENTLY AND LEGIBLY MARKED ON RELEASE LINER. REVISION LABELED MUST REFLECT CURRENT COMPONENT REVISION AT TIME OF MANUFACTURE. CHARACTERS MUST BE 2.0MM TO 4.0MM HIGH.            13. EXCEPTIONS: NO CHANGE SHALL BE ALLOWED ON PRODUCTION MATERIAL REGARDLESS OF WHETHER SUCH CHANGE AFFECTS REQUIREMENTS SPECIFIED, WITHOUT PRIOR WRITTEN APPROVAL BY NOKIA.            14. THE RECOGNIZED COMPANY'S FULL TRADE NAME OR TRADEMARK, FACTORY IDENTIFICATION, AND LABEL DESIGNATION SHALL BE MARKED ON EACH LABEL PACKAGE, ROLL CORE, OR RELEASE LINER OF THE LABEL.            15. THE SUPPLIER MUST HAVE A CURRENT UL FILE NUMBER UNDER THE FOLLOWING CATEGORIES: PGDQ2 (MARKING AND LABELING SYSTEMS)            16. 1D LINEAR BARCODES: CODE TYPE CODE128 WITH DATA IDENTIFIERS ENCODED. DATA STRUCTURE ISO 15418.            X-DIMENSION: 0.21 mm (600dpi ONLY). HEIGHT OF CODE: 4 mm            17. 2D DATA MATRIX: CODE TYPE DATA MATRIX ECC200. MATRIX GRID 36x36. DATA STRUCTURE ISO 15434            X-DIMENSION: 0.26 mm (600dpi ONLY). EXTERNAL SIZE OF CODE: 9.1x9.1mm            18. FONT: ALL FONTS SHALL BE ARIAL NARROW 4.5pt UNLESS OTHERWISE NOTED            19. INK COLOR: BLACK UNLESS OTHERWISE NOTED</p>																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>REV</th> <th>ZONE</th> <th>DESCRIPTION</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>ALL</td> <td>INITIAL RELEASE</td> <td>7/8/2020</td> </tr> <tr> <td>B</td> <td>D3</td> <td>ADDED TUV MARK, ADDED TRIAL TEXT, CORRECTED INPUT VOLT</td> <td>8/28/2020</td> </tr> <tr> <td>C</td> <td>D3</td> <td>ADDED FCC ID &amp; PART 15 TEXT</td> <td>10/22/2020</td> </tr> </tbody> </table>				REV	ZONE	DESCRIPTION	DATE	A	ALL	INITIAL RELEASE	7/8/2020	B	D3	ADDED TUV MARK, ADDED TRIAL TEXT, CORRECTED INPUT VOLT	8/28/2020	C	D3	ADDED FCC ID & PART 15 TEXT	10/22/2020								
REV	ZONE	DESCRIPTION	DATE																								
A	ALL	INITIAL RELEASE	7/8/2020																								
B	D3	ADDED TUV MARK, ADDED TRIAL TEXT, CORRECTED INPUT VOLT	8/28/2020																								
C	D3	ADDED FCC ID & PART 15 TEXT	10/22/2020																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Material : NOKIA 836517A</td> <td colspan="2">Tolerance 1:</td> </tr> <tr> <td colspan="2">Finish :</td> <td colspan="2">Tolerance 2:</td> </tr> <tr> <td>Item code</td> <td>836476</td> <td>Item ver</td> <td>C</td> </tr> <tr> <td>Drawing code</td> <td>P544025</td> <td>Drawing ver</td> <td>02</td> </tr> <tr> <td colspan="2">Title</td> <td colspan="2">NOKIA</td> </tr> <tr> <td colspan="2">AWEUC PRODUCT LABEL</td> <td colspan="2">NOKIA</td> </tr> </table>				Material : NOKIA 836517A		Tolerance 1:		Finish :		Tolerance 2:		Item code	836476	Item ver	C	Drawing code	P544025	Drawing ver	02	Title		NOKIA		AWEUC PRODUCT LABEL		NOKIA	
Material : NOKIA 836517A		Tolerance 1:																									
Finish :		Tolerance 2:																									
Item code	836476	Item ver	C																								
Drawing code	P544025	Drawing ver	02																								
Title		NOKIA																									
AWEUC PRODUCT LABEL		NOKIA																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>DES</td> <td>STEVENS</td> <td>200708</td> <td>MASS:</td> <td>0.0 g</td> </tr> <tr> <td>PREP</td> <td>STEVENS</td> <td>200708</td> <td>Volume:</td> <td>cm³</td> </tr> <tr> <td>CHK</td> <td>WARYCH</td> <td>200708</td> <td>Scale(s):</td> <td>1:1</td> </tr> <tr> <td>APP</td> <td>WARYCH</td> <td>200708</td> <td>Sheet(s):</td> <td>1 / 2</td> </tr> </table>				DES	STEVENS	200708	MASS:	0.0 g	PREP	STEVENS	200708	Volume:	cm³	CHK	WARYCH	200708	Scale(s):	1:1	APP	WARYCH	200708	Sheet(s):	1 / 2				
DES	STEVENS	200708	MASS:	0.0 g																							
PREP	STEVENS	200708	Volume:	cm³																							
CHK	WARYCH	200708	Scale(s):	1:1																							
APP	WARYCH	200708	Sheet(s):	1 / 2																							

**FCC Label Drawings for Nokia AWEUD 5G AirScale 24 GHz mmWave Radio,  
FCC ID: 2AD8UASMR24FA3UB - AWEUD Base Unit**

1
3
4

**NOTES:**  
 CHARACTERISTICS (UNLESS OTHERWISE SPECIFIED):  
 1. PARTS MUST BE CLEAN AND FREE OF SCRATCHES, BLEMISHES AND IMPERFECTIONS.  
 2. PACKAGING DESIGN MUST BE APPROVED BY NOKIA BEFORE PROCEEDING WITH PRODUCTION RUN OF PARTS.  
 3. SAMPLE PARTS MUST BE APPROVED BY NOKIA BEFORE PROCEEDING WITH PRODUCTION RUN.  
 4. A REFERENCE DIMENSION (X.XX) IS A DIMENSION WITHOUT TOLERANCE AND IS USED FOR INFORMATION PURPOSES ONLY.  
 5. ALL DIMENSIONS SHOWN ACROSS A CENTERLINE SHALL BE CENTRALIZED WITHIN ONE HALF THEIR TOTAL TOLERANCE.  
 6. A CRITICAL DIMENSION IS DENOTED WITH A BOX-X SYMBOL X.  
 7. ALL DIMENSIONS SHOWN ARE IN MILLIMETERS. UNLESS OTHERWISE SPECIFIED  
 TOLERANCES FOR DIMENSIONS SHOWN ON DRAWING ARE AS FOLLOWS: ZERO (X) OR ONE PLACE (X.X) +/-0.3, TWO PLACE (X.XX) +/-0.13.  
 8. MATERIAL: NOKIA CODE 836517A  
 9. ARTWORK TO BE FURNISHED BY NOKIA. INK TO BE UV RESISTANT.  
 10. LABELS MUST SATISFY UL CATEGORY PGDQ2 AND UL969. LABELS ARE INTENDED FOR OUTDOOR USE AND MUST BE CAPABLE OF WITHSTANDING THE FOLLOWING ENVIRONMENTAL CONDITIONS; OPERATING TEMPERATURE RANGE: -40° C TO +85° C, STORAGE TEMPERATURE RANGE: -40° C TO +105° C, SALT FOG PER GR-487-CORE, ISSUE 2. SECTION 3.34 AND WIND DRIVEN RAIN PER TELCORDIA GR-487-CORE. PARTS MUST BE SUITABLE FOR USE ON ALUMINUM, POLYESTER PAINT, AND ACRYLONITRILE BUTADIENE STYRENE (ABS) PLASTIC TO THE ENVIRONMENTAL CONDITIONS DEFINED ABOVE. PARTS SHOULD BE SUITABLE FOR OTHER SUBSTRATES AND TEMPERATURES AS REQUIRED BY THE INDIVIDUAL UL PGDQ2 FILE THAT IS APPLICABLE.  
 11. FLAMMABILITY RATING: ALL MATERIALS MUST HAVE A RATING OF UL 94V-2 OR HIGHER  
 12. NOKIA PART CODE, PART REVISION (SEE DRAWING FOR CODE AND REVISION), MANUFACTURE DATE CODE (WK/YR), AND VENDOR ID MUST BE PERMANENTLY AND LEGIBLY MARKED ON RELEASE LINER. REVISION LABELED MUST REFLECT CURRENT COMPONENT REVISION AT TIME OF MANUFACTURE. CHARACTERS MUST BE 2.0MM TO 4.0MM HIGH.  
 13. EXCEPTIONS: NO CHANGE SHALL BE ALLOWED ON PRODUCTION MATERIAL REGARDLESS OF WHETHER SUCH CHANGE AFFECTS REQUIREMENTS SPECIFIED, WITHOUT PRIOR WRITTEN APPROVAL BY NOKIA.  
 14. THE RECOGNIZED COMPANY'S FULL TRADE NAME OR TRADEMARK, FACTORY IDENTIFICATION, AND LABEL DESIGNATION SHALL BE MARKED ON EACH LABEL PACKAGE, ROLL CORE, OR RELEASE LINER OF THE LABEL.  
 15. THE SUPPLIER MUST HAVE A CURRENT UL FILE NUMBER UNDER THE FOLLOWING CATEGORIES: PDGQ2 (MARKING AND LABELING SYSTEMS)  
 16. 1D LINEAR BARCODES: CODE TYPE CODE128 WITH DATA IDENTIFIERS ENCODED. DATA STRUCTURE ISO 15418.  
     X-DIMENSION: 0.21 mm (600dpi ONLY). HEIGHT OF CODE: 4 mm  
 17. 2D DATA MATRIX: CODE TYPE DATA MATRIX ECC200. MATRIX GRID 36x36. DATA STRUCTURE ISO 15434  
     X-DIMENSION: 0.26 mm (600dpi ONLY). EXTERNAL SIZE OF CODE: 9.1x9.1mm  
 18. FONT: ALL FONTS SHALL BE ARIAL NARROW 4.5pt UNLESS OTHERWISE NOTED  
 19. INK COLOR: BLACK UNLESS OTHERWISE NOTED

The diagram shows a rectangular product label with the following features and callouts:

- Top Left:** "DYNAMICALLY PRINTED BARCODE (1P) SEE NOTE 16" pointing to a 1D barcode.
- Top Center:** "DYNAMICALLY PRINTED (1P) ARIAL NARROW 5pt" pointing to the top text area.
- Top Right:** "DYNAMICALLY PRINTED (S) ARIAL NARROW 5pt" pointing to the top right text area.
- Right Side:** "DYNAMICALLY PRINTED BARCODE (1S) - SEE NOTE 16" pointing to a 1D barcode on the right edge.
- Bottom Right:** "DYNAMICALLY PRINTED 2D BARCODE CONTENTS: 1S,1P,18V,2P,1V,10D,4L SEE NOTE 17" pointing to a 2D Data Matrix code.
- Bottom Center:** "DYNAMICALLY PRINTED 1V & 10D" pointing to the bottom center text area.
- Bottom Left:** "DYNAMICALLY PRINTED 2P" pointing to the bottom left text area.
- Bottom:** "DYNAMICALLY PRINTED MANUFACTURING LOCATION" pointing to the bottom text area.
- Left Side:** "ARIAL NARROW BOLD 4.5pt" pointing to the bold text "NOKIA".
- Left Side:** "ARIAL NARROW 5.5pt" pointing to the text "Nokia Solutions and Networks Oy".
- Left Side:** "ARIAL NARROW 4.5pt" pointing to the text "Made in 2000x".
- Center:** "125±0.5" indicating the width of the label.
- Right Side:** "23±0.5" indicating the height of the label.
- Text on Label:**
  - Top left: "AirScale ASMR mmWave Radio", "Model: AWEUD (DC version)", "WIFI 7", "40.5-57 VDC", "MAX EIRP 55 dBm", "11.5A MAX", "ENCLOSURE IP68", "NOKIA", "Nokia Solutions and Networks Oy", "Karunkari 7 FH-02810 Lapco Finland".
  - Top center: "(1P) P/N: 47516BAJCCX".
  - Center: "(S) S/N: 0000000000000000", "(18V) NOKIA ISO C/N: LENOX", "(2P) Rev: 00x", "(1V) Man Loc: 0000", "(10D) Man Date: YYYW".
  - Bottom right: "FCC ID: 2A0145A8M2F4S0UR", "CLASS 1 LASER PRODUCT", and various safety icons.

REVISION HISTORY			
REV	ZONE	DESCRIPTION	DATE
A	ALL	INITIAL RELEASE	7/8/2020
B	D3	ADDED TUV MARK, ADDED TRIAL TEXT	8/28/2020
C	D3	ADDED FCC ID & PART 15	10/22/2020

Material : NOKIA 836517A

Finish :

Item code : **836477**

Drawing code : **P544026**

Title : **AWEUD PRODUCT LABEL**

Tolerance 1:

Tolerance 2:

Item ver : **C**

Drawing ver : **02**

DES	STEVENS	200708	MASS:	0.0 g
PREP	STEVENS	200708	Volume:	cm³
CHK	WARYCH	200708	Scale(s):	1:1
APP	WARYCH	200708		

Sheet(s):

1 / 2

Dimension

In mm

MDI : 11533284 1.8 ASMR-PRODUCT-LABEL
DRW: 11563637 1.1 AWEUD-PRODUCT-LABEL
Creo Parametric 4.0
Size:

**FCC Label Drawings for Nokia FA3UB 5G AirScale 24 GHz mmWave Extension Module,  
FCC ID: 2AD8UASMR24FA3UB – FA3UB Extension Unit**

1	2	3	4
---	---	---	---

**NOTES:**  
**CHARACTERISTICS (UNLESS OTHERWISE SPECIFIED):**  
1. PARTS MUST BE CLEAN AND FREE OF SCRATCHES, BLEMISHES AND IMPERFECTIONS.  
2. PACKAGING DESIGN MUST BE APPROVED BY NOKIA BEFORE PROCEEDING WITH PRODUCTION RUN OF PARTS.  
3. SAMPLE PARTS MUST BE APPROVED BY NOKIA BEFORE PROCEEDING WITH PRODUCTION RUN.  
4. A REFERENCE DIMENSION (X.XX) IS A DIMENSION WITHOUT TOLERANCE AND IS USED FOR INFORMATION PURPOSES ONLY.  
5. ALL DIMENSIONS SHOWN ACROSS A CENTERLINE SHALL BE CENTRALIZED WITHIN ONE HALF THEIR TOTAL TOLERANCE.  
6. A CRITICAL DIMENSION IS DENOTED WITH A BOX-X SYMBOL X.  
7. ALL DIMENSIONS SHOWN ARE IN MILLIMETERS, UNLESS OTHERWISE SPECIFIED  
TOLERANCES FOR DIMENSIONS SHOWN ON DRAWING ARE AS FOLLOWS: ZERO (X) OR ONE PLACE (X.X) +/-0.3, TWO PLACE (X.XX) +/-0.13.  
8. MATERIAL: NOKIA CODE 836518A  
9. ARTWORK TO BE FURNISHED BY NOKIA. INK TO BE UV RESISTANT.  
10. LABELS MUST SATISFY UL CATEGORY PGDQ2 AND UL969, LABELS ARE INTENDED FOR OUTDOOR USE AND MUST BE CAPABLE OF WITHSTANDING THE FOLLOWING ENVIRONMENTAL CONDITIONS; OPERATING TEMPERATURE RANGE: -40° C TO +85° C, STORAGE TEMPERATURE RANGE: -40° C TO +105° C, SALT FOG PER GR-487-CORE, ISSUE 2. SECTION 3.34 AND WIND DRIVEN RAIN PER TELCORDIA GR-487-CORE. PARTS MUST BE SUITABLE FOR USE ON ALUMINUM, POLYESTER PAINT, AND ACRYLONITRILE BUTADIENE STYRENE (ABS) PLASTIC TO THE ENVIRONMENTAL CONDITIONS DEFINED ABOVE. PARTS SHOULD BE SUITABLE FOR OTHER SUBSTRATES AND TEMPERATURES AS REQUIRED BY THE INDIVIDUAL UL PGDQ2 FILE THAT IS APPLICABLE.  
11. FLAMMABILITY RATING: ALL MATERIALS MUST HAVE A RATING OF UL 94V-2 OR HIGHER  
12. NOKIA PART CODE, PART REVISION (SEE DRAWING FOR CODE AND REVISION), MANUFACTURE DATE CODE (WK/YR), AND VENDOR ID MUST BE PERMANENTLY AND LEGIBLY MARKED ON RELEASE LINER. REVISION LABELED MUST REFLECT CURRENT COMPONENT REVISION AT TIME OF MANUFACTURE. CHARACTERS MUST BE 2.0MM TO 4.0MM HIGH.  
13. EXCEPTIONS: NO CHANGE SHALL BE ALLOWED ON PRODUCTION MATERIAL REGARDLESS OF WHETHER SUCH CHANGE AFFECTS REQUIREMENTS SPECIFIED, WITHOUT PRIOR WRITTEN APPROVAL BY NOKIA.  
14. THE RECOGNIZED COMPANY'S FULL TRADE NAME OR TRADEMARK, FACTORY IDENTIFICATION, AND LABEL DESIGNATION SHALL BE MARKED ON EACH LABEL PACKAGE, ROLL CORE, OR RELEASE LINER OF THE LABEL.  
15. THE SUPPLIER MUST HAVE A CURRENT UL FILE NUMBER UNDER THE FOLLOWING CATEGORIES: PGDQ2 (MARKING AND LABELING SYSTEMS)  
16. 1D LINEAR BARCODES: CODE TYPE CODE128 WITH DATA IDENTIFIERS ENCODED. DATA STRUCTURE ISO 15418. X-DIMENSION: 0.21 mm (600dpi ONLY). HEIGHT OF CODE: 4 mm  
17. 2D DATA MATRIX: CODE TYPE DATA MATRIX ECC200. MATRIX GRID 36x36. DATA STRUCTURE ISO 15434 X-DIMENSION: 0.26 mm (600dpi ONLY). EXTERNAL SIZE OF CODE: 9.1x9.1mm  
18. FONT: ALL FONTS SHALL BE ARIAL NARROW 4.5pt UNLESS OTHERWISE NOTED  
19. INK COLOR: BLACK UNLESS OTHERWISE NOTED

The drawing shows a rectangular label with a width of 125±0.5 mm and a height of 19±0.5 mm. It includes various text elements and barcodes with the following callouts:

- DYNAMICALLY PRINTED (1P) ARIAL NARROW 5pt**: Points to the 1P P/N: 475048A-XXXX.
- DYNAMICALLY PRINTED (S) ARIAL NARROW 5pt**: Points to the (S) S/N: xxxxxxxxxxxx.
- DYNAMICALLY PRINTED BARCODE (1P) SEE NOTE 16**: Points to the 1D linear barcode.
- DYNAMICALLY PRINTED BARCODE (1S) - SEE NOTE 16**: Points to the 1D linear barcode.
- DYNAMICALLY PRINTED 2D BARCODE CONTENTS: 1S,1P,18V,2P,1V,10D,4L SEE NOTE 17**: Points to the 2D data matrix barcode.
- ARIAL NARROW BOLD 4.5pt**: Points to the text "AirSolve mmH Radio Model: FA3UB".
- ARIAL NARROW 5.5pt**: Points to the text "Nokia Solutions and Networks Oy".
- DYNAMICALLY PRINTED 1V & 10D**: Points to the (1V) Man Loc: xxxx and (10D) Man Date: YYYYMM.
- DYNAMICALLY PRINTED MANUFACTURING LOCATION**: Points to the (18V) NOKIA ISO CEN LEMOK.
- DYNAMICALLY PRINTED 2P**: Points to the (2P) Rnc: xxxx.

REVISION HISTORY			
REV	ZONE	DESCRIPTION	DATE
00	ALL	INITIAL RELEASE	7/21/2020
01	D3	ADDED TUV MARK	8/28/2020
02	D3	ADDED FCC ID & PART 15	10/22/2020

Material : NOKIA 836518A		Tolerance 1:	
Finish :		Tolerance 2:	
Item code	Item ver	DES	STEVENS
<b>836509</b>	<b>C</b>	PREP	STEVENS
		CHK	WARYCH
		APP	WARYCH
Drawing code	Drawing ver	200721	200721
<b>P545914</b>	<b>02</b>	200721	200721
		200721	200721
Title		Dimension	
<b>FA3UB PRODUCT LABEL</b>		<b>NOKIA</b>	
		Sheet(s): 1 / 2	

MDL: 11533918 1.7 FA3UA-EXT-MOD-LABEL	DRW: 11563635 1.1 FA3UB-PRODUCT-LABEL	Geo Parametric 4.0	Size: A4
---------------------------------------	---------------------------------------	--------------------	----------

**Equipment Identification Label Location (Equipment Left Side):**



**AWEUC/D Base Unit**



**FA3UB Extension Module**

**Label Location**