

Exhibit 3 FCC REQUIRED INFORMATION

The following information is presented in the content and format requested by FCC:

Section 2.1033 (c)(1):

The full name and mailing address of the manufacturer of the device and the applicant for certification

Manufacturer: **NOKIA SOLUTIONS AND NETWORKS OY
KARAKAARI 7, FI-02610 ESPOO
FINLAND**

Applicant: **Nokia Solutions and Networks, OY
2000 Lucent Lane
Naperville, IL, 60563
Attention: Lee Klinkenberg
Phone: 224-221-7580
email: lee.klinkenberg@nokia.com**

Section 2.1033(c)(5): IC Identifier: **2AD8UAWHQ01**

Section 2.1033(c)(7): Type or types of emission:

The Nokia **AWHQU AirScale Micro 4T4R n48 40W CBRS 20W** is capable of amplifying transmission involving the following types of emissions:

BW (MHz)	Emissions Designation
10	8M87F9W
20	18M9F9W
10	8M55W7W
20	18M2W7W
30	27M9W7W
40	37M8W7W
80	77M8W7W

Section 2.1033(c)(8): Frequency range, Transmit / Receive:

Blocks	Transmit Range (MHz)	Receive Range (MHz)	Bandwidth (MHz)
B48/n48	3550 - 3700	3550 - 3700	150

Section 2.1033(c)(9): Range of operating power values or specific operating power levels, and description of any means provided for variation of operating power.

Response:

The AWHQU AirScale Micro 4T4R n48 40W CBRS 20W is capable operating from 21.0 dBm to 37.0 dBm/port in 0.1 dB steps.

Section 2.1033(c)(10): Maximum power rating as defined in the applicable part (s) of the rules.

Response:

The maximum average power output of the AWHQU AirScale Micro 4T4R n48 40W CBRS 20W at the Antenna connection is summarized in the following table:

Operation Mode	Max Power per Port	Total Max Power	Modulation
4T4R	5 W	20.0 W	LTE/NR