


FCC RF Exposure Report

FCC ID : 2AD8UFTHF01
Equipment : Single Band UE Relay
Model No. : FTHF
Brand Name : Nokia
Applicant : Nokia Solutions and Networks, OY
Address : 1455 W Shure Drive Arlington Heights, Illinois
United States 60004
Standard : 47 CFR FCC Part 2.1091
Received Date : Jul. 27, 2016
Tested Date : Aug. 10 ~ Aug. 12, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:


Gary Chang / Manager



Table of Contents

| | | |
|----------|---|----------|
| 1 | MPE EVALUATION OF MOBILE DEVICES | 4 |
| 1.1 | LIMITS | 4 |
| 1.2 | MPE EVALUATION FORMULA | 4 |
| 1.3 | MPE EVALUATION RESULTS | 5 |
| 1.4 | SEPERATION DISTANCE BOUNDARY LIMITS..... | 5 |
| 2 | TEST LABORATORY INFORMATION | 6 |

Release Record

| Report No. | Version | Description | Issued Date |
|------------|---------|---------------|---------------|
| FA672702 | Rev. 01 | Initial issue | Sep. 19, 2016 |

1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 21 cm or more from persons.

1.1 LIMITS

Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Power Density (mW /cm ²) | Averaging Time (minutes) |
|-----------------------|--------------------------------------|--------------------------|
| 300~1500 | F/300 | 6 |
| 1500~100000 | 5 | 6 |

Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Power Density (mW /cm ²) | Averaging Time (minutes) |
|-----------------------|--------------------------------------|--------------------------|
| 300~1500 | F/1500 | 30 |
| 1500~100000 | 1 | 30 |

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

1.3 MPE EVALUATION RESULTS

For General Population/Uncontrolled Exposure

| Mode | Frequency Range (MHz) | Maximum Conducted Power (dBm) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limits (mW/cm ²) |
|-------------|-----------------------|-------------------------------|--------------------|---------------|-------------------------------------|------------------------------|
| LTE Band 41 | 2630.0 | 22.94 | 11 | 21 | 0.447 | 1 |
| | 2655.0 | 24.01 | 11 | 21 | 0.572 | 1 |
| | 2680.0 | 23.84 | 11 | 21 | 0.550 | 1 |

1.4 SEPERATION DISTANCE BOUNDARY LIMITS

| Mode | Frequency Range (MHz) | Maximum Conducted Power (dBm) | Antenna Gain (dBi) | General Population /Uncontrolled Exposure | | Occupational/Controlled Exposure | |
|-------------|-----------------------|-------------------------------|--------------------|---|------------------------------|----------------------------------|------------------------------|
| | | | | Distance (cm) | Limits (mW/cm ²) | Distance (cm) | Limits (mW/cm ²) |
| LTE Band 41 | 2630.0 | 22.94 | 11 | 14.041 | 1 | 6.279 | 5 |
| | 2655.0 | 24.01 | 11 | 15.882 | 1 | 7.102 | 5 |
| | 2680.0 | 23.84 | 11 | 15.574 | 1 | 6.965 | 5 |

2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==