

## RF Exposure Report

**Report No.:** SA160802E01B

**FCC ID:** 2AD8UFW2CA01

**Test Model:** FW2CA

**Received Date:** Aug. 02, 2016

**Test Date:** Oct. 11, 2016

**Issued Date:** Sep. 25, 2017

**Applicant:** Nokia Solutions and Networks

**Address:** 1455 West Shure Drive, Arlington Heights, IL 60004, USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits for Maximum Permissible Exposure (MPE) .....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
2.4 Antenna Gain .....	6
2.5 Calculation Result .....	7
<b>3 Brief Summary of results</b> .....	<b>8</b>

### Release Control Record

Issue No.	Description	Date Issued
SA160802E01B	Original release.	Sep. 25, 2017

## 1 Certificate of Conformity

**Product:** Mini Macro Outdoor Pico BTS

**Brand:** Nokia

**Test Model:** FW2CA

**Sample Status:** MASS-PRODUCTION

**Applicant:** Nokia Solutions and Networks

**Test Date:** Oct. 11, 2016

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

FCC Part 1 (Section 1.1310)

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**




**Date:**

Sep. 25, 2017

Claire Kuan / Specialist

**Approved by :**



**Date:**

Sep. 25, 2017

May Chen / Manager

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 304cm away from the body of the user. So, this device is classified as **fixed device** and installations by professional service personnel.

## 2.4 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Antenna Spec.						
Set	Antenna Condition	Brand	Model	Antenna Type	Gain(dBi)	Frequency (MHz)
1	LTE 1	Alpha Wireless	AW3439	PANEL Type	12.5	LTE B26 806-896
	LTE 2	Alpha Wireless	AW3439	PANEL Type	12.5	LTE B26 806-896
2	LTE 1	Alpha Wireless	AW3176	Omni Type	6	LTE B26 790-890
	LTE 2	Alpha Wireless	AW3176	Omni Type	6	LTE B26 790-890
3	LTE 1	Alpha Wireless	AW3543	Omni Type	4.5	LTE B26 806-896
	LTE 2	Alpha Wireless	AW3543	Omni Type	4.5	LTE B26 806-896

## 2.5 Calculation Result

All test data was copied from the original test report (Report No.: SA160802E01)

### For General Population

#### LTE:

Operating Frequency (MHz)	Max. ERP Power (dBm)	Max. EIRP Power (dBm)	Max. EIRP Power (mW)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
865.1~ 866.5 (LTE B26)	56.10	58.25	667632.1	304	0.57488	0.5772

Note: Limit of Power Density = F/1500

#### Bluetooth module (FCC ID: 2AD8UNBTM01):

Operating Frequency (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2402-2480	9.099	1.45	304	0.00001	1

### For Occupational

#### LTE:

Operating Frequency (MHz)	Max. ERP Power (dBm)	Max. EIRP Power (dBm)	Max. EIRP Power (mW)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
865.1~ 866.5 (LTE B26)	56.10	58.25	667632.1	136	2.87242	2.886

Note: Limit of Power Density = F/300

#### Bluetooth module (FCC ID: 2AD8UNBTM01):

Operating Frequency (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2402-2480	9.099	1.45	136	0.00005	5

### Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

#### For General Population

$$\text{LTE} + \text{Bluetooth} = 0.57488 / 0.5772 + 0.00001 / 1 = 0.996$$

Therefore the maximum calculations of above situations are less than the "1" limit.

#### For Occupational

$$\text{LTE} + \text{Bluetooth} = 2.87242 / 2.886 + 0.00005 / 5 = 0.995$$

Therefore the maximum calculations of above situations are less than the "1" limit.

### 3 Brief Summary of results

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(m)	
	Occupational	General Population
LTE Band 26 + Bluetooth	1.36	3.04

--- END ---