

RF Exposure Report

C2PC (Class II Permissive Change)

Report No.: SA170123E07A

FCC ID: 2AD8UFW2PADPM01

Test Model: FW2PADPM01

Received Date: Jan. 15, 2019

Test Date: Feb. 23 ~ Feb. 25, 2019, Apr. 29 ~ May 02, 2019 and Jul. 30 ~ Jul. 31, 2019

Issued Date: Aug. 01, 2019

Applicant: Nokia Solutions and Networks, OY

Address: 2000 W. Lucent Lane, City: Naperville, Illinois, United States, 60563

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /
Designation Number:** 788550 / TW0003

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
2.5 Calculation Result	6
3 Brief Summary of results	6

Release Control Record

Issue No.	Description	Date Issued
SA170123E07A	Original release.	Aug. 01, 2019

1 Certificate of Conformity

Product: Nokia FW2P LTE module

Brand: Nokia

Test Model: FW2PADPM01

Test Sample S/N: EB160810030

Hardware Version: A101

Sample Status: MASS-PRODUCTION

Applicant: Nokia Solutions and Networks, OY

Test Date: Feb. 23 ~ Feb. 25, 2019, Apr. 29 ~ May 02, 2019 and Jul. 30 ~ Jul. 31, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 GENERAL RF EXPOSURE GUIDANCE V06

IEEE STD C95.1

FCC Part 1 (Section 1.1310)

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen, **Date:** Aug. 01, 2019
Pettie Chen / Senior Specialist

Approved by : Bruce Chen, **Date:** Aug. 01, 2019
Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.
So, this device is classified as fixed device and installations by professional service personnel.

2.4 Antenna Gain

LTE Band 13

Antenna Spec.

Gain(dBi)	Frequency (MHz)
6	746~787

2.5 Calculation Result

Calculation for Maximum EIRP

For General Population

LTE Band 13 module (FCC ID: 2AD8UFW2PADPM01)

Frequency Band (MHz)	Max ERP Power (dBm)	Max EIRP Power (dBm)	Max EIRP Power (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
LTE Band 13 (256QAM)	30.03	32.18	1651.962	20	0.329	0.5
Guard Band 751.0MHz	31.75	33.90	2454.709	20	0.488	0.5
In Band 751.0MHz	31.36	33.51	2243.882	20	0.446	0.5

EIRP Power= ERP Power+2.15dBi

For Occupational Population

LTE Band 13 module (FCC ID: 2AD8UFW2PADPM01)

Frequency Band (MHz)	Max ERP Power (dBm)	Max EIRP Power (dBm)	EIRP Power (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
LTE Band 13 (256QAM)	30.03	32.18	1651.962	20	0.329	2.50
Guard Band 751.0MHz	31.75	33.90	2454.709	20	0.488	2.50
In Band 751.0MHz	31.36	33.51	2243.882	20	0.446	2.50

EIRP Power= ERP Power+2.15dBi

3 Brief Summary of results

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(m)	
	Occupational	General Population
LTE Band 13 (Guard Band/In Band)	0.2	0.2

Note: Compliance Boundaries apply to Guard Band/In Band NB-IoT configuration.

--- END ---