

RF Exposure Report

Report No.: SA160815E05A

FCC ID: 2AD8UFW2RADPM01

Test Model: FW2RADPM01

Received Date: Aug. 15, 2016

Test Date: Nov. 04, 2016

Issued Date: Nov. 25, 2016

Applicant: Nokia Solutions and Networks

Address: 1455 West Shure Drive, Arlington Heights, IL 60004, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.1 MPE Calculation Formula	5
2.2 Classification	5
2.3 Antenna Gain	6
2.4 Calculation Result of Maximum Conducted Power	7
3 Brief Summary of results	7

Release Control Record

Issue No.	Description	Date Issued
SA160815E05A	Original release.	Nov. 25, 2016

1 Certificate of Conformity

Product: Nokia FW2R LTE module

Brand: Nokia

Test Model: FW2RADPM01

Hardware Version: 95.1659T00 X36

Sample Status: MASS-PRODUCTION

Applicant: Nokia Solutions and Networks

Test Date: Nov. 04, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

FCC Part 1 (Section 1.1310)

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Midoli Peng , **Date:** Nov. 25, 2016
Midoli Peng / Specialist

Approved by : May Chen , **Date:** Nov. 25, 2016
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

2 F = Frequency in MHz

2.1 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.2 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **fixed device** and installations by professional service personnel.

2.3 Antenna Gain

1. The antennas provided to the EUT, please refer to the following table:

Antenna spec.					
Antenna No	Brand	Model	Antenna Type	Gain(dBi)	Frequency range (MHz)
1	Nokia	NA	Loop (LAA#4(Main))	5.24	5150 ~ 5250, 5725 ~ 5825
2	Nokia	NA	Loop (LAA#2(DIV))	8.26	5150 ~ 5250, 5725 ~ 5825

Cable Spec.						
Antenna No	Brand	Model	Connector Type	Cable Loss(dB)	Cable Length (mm)	Note
1	NA	NA	Right angle MMCX Plug	peak gain included	263	This cable will be equipped with Loop(LAA#4) antenna
2	NA	NA	Right angle MMCX Plug	peak gain included	263	This cable will be equipped with Loop(LAA#2) antenna

2. Directional gain(composite gain) :

Directional Gain.	
Frequency range (MHz)	Max Gain(dBi)
5150 ~ 5250, 5725 ~ 5825	7.66

Note:

1. Directional gain calculation is based on FCC document KDB662911

$$\text{Directional gain} = \text{GANT MAX} + 10 \log(\text{NANT/NSS}) \text{ dBi,}$$

where

NSS = the number of independent spatial streams of data ;

GANT MAX is.the gain of the antenna having the highest gain (in dBi).

2. Two directional gain values are calculated, directional gain values based on actual measurement data.

2.4 Calculation Result of Maximum Conducted Power

For General Population

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240	581.477	7.66	20	0.67493	1
5745-5825	582.879	7.66	20	0.67656	1

Note: Directional gain = 7.66dBi

For Occupational Population

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240	581.477	7.66	20	0.67493	5
5745-5825	582.879	7.66	20	0.67656	5

Note: Directional gain = 7.66dBi

3 Brief Summary of results

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(m)	
	Occupational	General Population
5GHz LAA	0.20	0.20

--- END ---